

```
// BootRunner.cs
using System.Collections;
using Sy.Core;
using UnityEngine;
using UnityEngine.SceneManagement;
using Logger = Sy.Core.Logger;
namespace Sy.P01.Boot
{
    public static class SceneIds
    {
        public const string Boot = "S00_Boot";
        public const string Main = "S01_Main";
    }
    /// <summary>
    /// S00_Boot      Mock → →      T001a
    ///      Boot      UI T001b  Boot      =
    /// </summary>
    public sealed class BootRunner : MonoBehaviour
    {
        IEnumerator Start()
        {
            BootServices.RegisterAll();
            var sequence = new BootSequence(SwitchToMain);
            if (!sequence.RunAll())
            {
                Logger.Error("BOOT", "boot sequence failed - stay on S00_Boot");
                yield break;
            }
            yield return null;
        }
        bool SwitchToMain()
        {
            StartCoroutine(LoadMainRoutine());
            return true;
        }
        IEnumerator LoadMainRoutine()
        {
            var op = SceneManager.LoadSceneAsync(SceneIds.Main, LoadSceneMode.Single);
            while (op != null && !op.isDone) yield return null;
        }
    }
}

// BootSequence.cs
using System;
using System.Collections.Generic;
using Sy.Core;
using Sy.Platform;
namespace Sy.P01.Boot
{
    /// <summary>
```

```

/// Boot      T001
/// ①Logger→② →③Config→④Save→⑤ILocale→⑥Ads.Preload→⑦      [BOOT] n/7
/// ⑦      Play  =SceneManager.LoadSceneAsync Editor dry-run=EditorSceneManager.OpenScene
/// X006      SY MOCK
/// &lt;/summary&gt;
public sealed class BootSequence
{
    public const int TotalSteps = 7;
    readonly Func&lt;bool&gt; _switchScene;
    readonly List&lt;string&gt; _lines = new();
    public BootSequence(Func&lt;bool&gt; switchScene)
    {
        _switchScene = switchScene;
    }
    public IReadOnlyList&lt;string&gt; Lines =&gt; _lines;
    public bool RunAll()
    {
        bool ok = true;
        ok &= Run(1, "Logger", LoggerStep);
        ok &= Run(2, "Time", TimeStep);
        ok &= Run(3, "Config", ConfigStep);
        ok &= Run(4, "Save", SaveStep);
        ok &= Run(5, "ILocale", LocaleStep);
        ok &= Run(6, "Ads.Preload", AdsStep);
        ok &= Run(7, "SwitchMain", () =&gt; _switchScene != null && _switchScene());
        return ok;
    }
    bool Run(int n, string name, Func&lt;bool&gt; step)
    {
        bool result;
        try
        {
            result = step();
        }
        catch (Exception e)
        {
            Logger.Error("BOOT", $"step {n} {name} exception: {e.Message}");
            result = false;
        }
        string line = $"[BOOT] {n}/{TotalSteps} {name} {(result ? "ok" : "FAIL")}";
        _lines.Add(line);
        Logger.Info("BOOT", line);
        return result;
    }
    static bool LoggerStep() =&gt; true; //      JS sink platform T001c
    static bool TimeStep()
    {
        var time = ServiceLocator.Get&lt;ITimeService&gt;();
        return time.ServerNowMs() &gt; 0 && !time.TimeCheated();
    }
}

```

```

        static bool ConfigStep()
        {
            var config = ServiceLocator.Get<IConfigService>();
            var update = config.CheckUpdate("mock://manifest");
            return update.NewVersion != null; // mock= X009 manifest
        }
        static bool SaveStep()
        {
            var save = ServiceLocator.Get<ISaveService>();
            save.Save("boot_probe", "{}");
            return !string.IsNullOrEmpty(save.Load("boot_probe"));
        }
        static bool LocaleStep()
        {
            var locale = ServiceLocator.Get<ILocaleService>();
            return !string.IsNullOrEmpty(locale.GetFontSet().NormalFont); // +
        }
        static bool AdsStep()
        {
            ServiceLocator.Get<IAdsService>().Preload("boot_warmup");
            return true;
        }
    }
}

// BootServices.cs
using System;
using System.Collections.Generic;
using System.Threading.Tasks;
using Sy.Core;
using Sy.Platform;
using UnityEngine;
using Logger = Sy.Core.Logger;
namespace Sy.P01.Boot
{
    /// <summary>
    /// Mock SY MOCK X006 Mock X002a AppID touristappid
    /// T001c WX/TT Channel Editor Boot
    /// </summary>
    public static class BootServices
    {
        public static void RegisterAll()
        {
            if (ServiceLocator.TryGet<ITimeService>(out _)) return; //
            ServiceLocator.Register<ITimeService>(new MockTimeService());
            ServiceLocator.Register<IConfigService>(new MockConfigService());
            ServiceLocator.Register<ISaveService>(new MockSaveService());
            ServiceLocator.Register<ILocaleService>(new MockLocaleService());
            // T021c-ii: launch-query seam (null = organic open; the platform
            // suite swaps this registration when its channel face lands T001c).
            ServiceLocator.Register<ILaunchInfo>(new MockLaunchInfo());
        }
    }
}

```

```

        // T011: the shared AdCapPolicy is registered BEFORE the ads service so the
        // revive pre-check (HasCategoryBudget) and ShowRewarded consumption read the
        // same $ category counters (P02 boot paradigm; p01_revive 6/day). The
        // ad service is the shared-package mock (red lines + lifecycle events) -
        // the old local MockAdsService ignored caps entirely.
        var adCap = new AdCapPolicy();
        ServiceLocator.Register(adCap);
        ServiceLocator.Register<IAdsService>(new Sy.Platform.MockAdsService(adCap));
        Logger.Info("BOOT", "mock services registered (SY MOCK)");
    }
}

public sealed class MockTimeService : ITimeService
{
    public TimeSource Source => TimeSource.Mock;
    public long ClientNowMs() => DateTimeOffset.UtcNow.ToUnixTimeMilliseconds();
    /// <summary>SY MOCK X006 TCB serverTime→HTTPS Date → T001b </summary>
    public long ServerNowMs() => ClientNowMs();
    public bool TimeCheated() => Math.Abs(ServerNowMs() - ClientNowMs()) > 120_000;
}

public sealed class MockConfigService : IConfigService
{
    public T GetTable<T>(string tableId) where T : class
        => throw new KeyNotFoundException("mock config table not loaded: " + tableId);
    public bool TryGetTable<T>(string tableId, out T table) where T : class
    {
        table = null;
        return false;
    }
    public ConfigUpdateResult CheckUpdate(string manifestUrl)
        => new ConfigUpdateResult(false, "mock-0.0.1");
    public void SwapPolicy(ConfigSwapPolicy policy) { }
    public string PinConfigVersion(string scope) => "mock-0.0.1";
}

public sealed class MockSaveService : ISaveService
{
    const string Prefix = "sy_save_";
    public void Save(string slot, string payloadJson) => PlayerPrefs.SetString(Prefix + slot, payloadJson);
    public string Load(string slot) => PlayerPrefs.GetString(Prefix + slot, string.Empty);
    /// <summary>X006 T001b v1→v2 </summary>
    public SyncResult CloudSync() => new SyncResult(false, null);
}

public sealed class MockLocaleService : ILocaleService
{
    public void SetLang(string lang) { }
    /// <summary>T035 i18n slice 1: resolves through the shipped cfg_i18n
    /// table (P01Configs.I18n); a missing key falls back to the raw key
    /// and warns (the T001b contract, now wired - AboutPanel keeps its own
    /// zero-service resolver for the headless gate face). Format args
    /// apply only when the caller actually passes them.</summary>
    public string GetText(string key, params string[] args)

```

```

    {
        var table = Sy.P01.Newbie.P01Configs.I18n;
        if (table != null && table.entries != null)
        {
            foreach (var e in table.entries)
            {
                if (e != null && e.key == key && e.value != key)
                {
                    return args != null && args.Length > 0 ? string.Format(e.value, args) : e.value;
                }
            }
        }
        Logger.Warn("LOCALE", "missing i18n key (fallback): " + key);
        return key;
    }

    public FontSet GetFontSet()
        => new FontSet("P01FontCJK", "P01FontCJK", "P01FontCJK"); // T035: bundled CJK subset (device-safe chain)
}

public sealed class MockLaunchInfo : ILaunchInfo
{
    /// <summary>SY MOCK Editor/      query=      T001c suite </summary>
    public LaunchQuery GetLaunchQuery() => null;
}

}

// MainUI.cs
using UnityEngine;
using UnityEngine.SceneManagement;
namespace Sy.P01.Newbie
{
    public static class NewbieSceneIds
    {
        public const string Main = "S01_Main";
        public const string Battle = "S01_Battle";
    }

    /// <summary>S01      →S01_Battle M5      —
    /// X027 art wiring: swaps the scene's solid Bg block for the generated scene
    /// painting and shows the hero showcase when the art keys resolve.
    /// T017 slice 3: hosts the DayLauncher (day/night loop day beat) on this scene
    /// root - AddComponent pattern keeps the scene YAML untouched.
    /// T018 slice 3: hosts the TalentLauncher AFTER the DayLauncher so the talent
    /// entry button renders above the day panel (later sibling order).</summary>
    public sealed class MainUI : MonoBehaviour
    {
        public void StartNight()
        {
            SceneManager.LoadScene(NewbieSceneIds.Battle);
        }

        void Awake()
        {
            Application.targetFrameRate = 30;
        }
    }
}

```

```
Sy.Core.MainArtInjector.Apply(transform, "P01_scene_01", "P01_unit_01");
if (GetComponent<DayLauncher>() == null)
    gameObject.AddComponent<DayLauncher>();
if (GetComponent<TalentLauncher>() == null)
    gameObject.AddComponent<TalentLauncher>();
// T045: compliance about entry - self-hosting programmatic panel
// (P06 T024 pattern, zero scene-YAML drift), after the talent
// host so the disclosure overlay renders above the day panel.
if (GetComponent<AboutPanel>() == null)
    gameObject.AddComponent<AboutPanel>();
// T033 slice A: first-launch privacy gate - hosted LAST so the
// privacy overlay renders above every menu face on first launch
// (deny = cannot-enter hint state, agree = local persisted bit;
// the X279 self-hosting pattern, zero scene-YAML drift).
if (GetComponent<PrivacyPanel>() == null)
    gameObject.AddComponent<PrivacyPanel>();
// T035: scene-serialized Text objects still reference the builtin
// font (zero CJK glyphs -& tofu on device); sweep them to the
// bundled subset at boot. Scene YAML untouched (zero drift), the
// swap is idempotent and play-mode only.
foreach (var txt in UnityEngine.Object.FindObjectsByType<UnityEngine.UI.Text>(
    UnityEngine.FindObjectsInactive.Include, UnityEngine.FindObjectsSortMode.None))
{
    if (txt.font != null && txt.font.name == "LegacyRuntime.ttf")
        txt.font = Sy.P01.UiFont.Resolve();
}
}
}

// AssemblyInfo.cs
using System.Runtime.CompilerServices;
// T011: editor gates (Sy.P01.Editor) stage lethal moments through
// BattleSim.ForceHeroHpForTests; gameplay assemblies never see the internals.
[assembly: InternalsVisibleTo("Sy.P01.Editor")]
// UiFont.cs
using System;
using Sy.Core;
using UnityEngine;
namespace Sy.P01
{
    /// <summary>;
    /// T035 font chain: resolve the UI font through the locale FontSet instead
    /// of hardcoding the engine built-in font.
    /// Why: LegacyRuntime.ttf carries no CJK glyphs and WebGL/WeChat builds
    /// have no OS font fallback, so every Chinese label would render blank
    /// on device (editor stays green via OS fallback - a false-comfort mask,
    /// the U184 portfolio-wide disease). The bundled subset asset P01FontCJK.ttf
    /// (Noto Sans SC OFL, subset to this game's own character census, 232KB,
    /// FontGate missing=0) covers the whole UI vocabulary; X027 law: missing
    /// asset falls back to the built-in font + one warning, never breaks a
```

```
/// build or gate. P02 FateGate U184 pattern replicated verbatim.
/// </summary>
public static class UIFont
{
    const string Fallback = "LegacyRuntime.ttf";
    static bool _warned;
    public static Font Resolve()
    {
        string name = null;
        try
        {
            if (ServiceLocator.TryGet<ILocaleService>(out var locale))
                name = locale.GetFontSet().NormalFont;
        }
        catch (Exception) { name = null; }
        if (!string.IsNullOrEmpty(name) && name != Fallback)
        {
            var font = Resources.Load<Font>("Fonts/" + name);
            if (font != null) return font;
            if (!_warned)
            {
                Sy.Core.Logger.Warn("UIFONT", "font asset missing, fallback LegacyRuntime: " + name);
                _warned = true;
            }
        }
        return Resources.GetBuiltinResource<Font>(Fallback);
    }
}

// UiText.cs
using System;
using Sy.Core;
namespace Sy.P01
{
    /// </summary>
    /// T035 i18n slice 2: the shared UI text resolver (the UIFont kin). The
    /// canonical ILocaleService.GetText seam runs first (play mode - the
    /// registered service owns localization when the platform suite swaps
    /// one in at T001c); the zero-service cfg_i18n table resolver runs
    /// second so edit-mode gates drive real renders without Boot
    /// (FriendBoardCheck F7 builds this panel headless). One semantics
    /// everywhere (T001b contract): a missing key falls back to the raw key
    /// (the service face warns), format args apply only when the caller
    /// passes them, so brace-bearing values never Format-crash on zero-arg
    /// calls. The migration queue (BattleView -& DayView -& ...) keys its
    /// labels through this seam batch by batch; the shipped table copy is
    /// the only place CJK lives.
    /// </summary>
    public static class UiText
    {

```

```

    public static string Get(string key, params string[] args)
    {
        bool hasArgs = args != null && args.Length > 0;
        try
        {
            if (ServiceLocator.TryGet<ILocaleService>(out var locale))
                return locale.GetText(key, args);
        }
        catch (Exception) { /* fall through to the zero-service face */ }
        // Edit-mode/gate face: resolve the shipped table directly (the
        // AboutPanel.TryText kin; value == key counts as missing).
        string value = key;
        var table = Newbie.P01Configs.I18n;
        if (table != null && table.entries != null)
        {
            foreach (var e in table.entries)
            {
                if (e != null && e.key == key && e.value != key) { value = e.value; break; }
            }
        }
        return hasArgs ? string.Format(value, args) : value;
    }
}

// AboutPanel.cs
using System;
using UnityEngine;
using UnityEngine.UI;
namespace Sy.P01.Newbie
{
    /// <summary>
    /// T045 compliance surface - the about/disclosure face on the main menu
    /// (the P06 T024 AboutPanel pattern). Every disclosure line is composed
    /// FROM the live law tables (cfg_rune rerollFace pool, cfg_ad_point
    /// global cap) so the published numbers can never drift from the
    /// enforced ones - the same construction guarantee the P02 odds panel
    /// uses. Programmatic UGUI, zero scene-YAML drift; the strings resolve
    /// through the shipped cfg_i18n table (raw-key fallback). The composer
    /// layer is pure static the headless gate asserts without rendering.
    /// </summary>
    public sealed class AboutPanel : MonoBehaviour
    {
        public const string KeyAboutButton = "about_button";
        public const string KeyPanelTitle = "about_title";
        public const string KeyAigcLine = "about_aigc_line";
        public const string KeyOddsLine = "about_odds_line";
        public const string KeyAdCapLine = "about_adcap_line";
        public const string KeyAgeLine = "about_age_line";
        public const string KeyCloseLabel = "about_close";
        /// Draw width of the bell_reroll re-draw (3 of the six-rune pool,

```

```
/// BattleSim.DrawRerollFaces law) - kept beside the composer so the
/// disclosure and the engine read one constant.
public const int RerollDrawWidth = 3;
static readonly Color LanternAmber = new Color(0.85f, 0.62f, 0.25f);
static readonly Color PaperWhite = new Color(0.95f, 0.91f, 0.84f);
static readonly Color InkBrown = new Color(0.24f, 0.20f, 0.18f);
static readonly Color NightDim = new Color(0.09f, 0.07f, 0.13f, 0.92f);
// —— composer layer (pure static, gate-facing) ——
/// Strings resolver over the shipped cfg_i18n table (the ILocaleService
/// semantics: a missing key falls back to the raw key and warns).
public static bool TryText(string key, out string value)
{
    value = key;
    var table = P01Configs.I18n;
    if (table == null || table.entries == null) return false;
    foreach (var e in table.entries)
    {
        if (e != null && e.key == key) { value = e.value; return e.value != key; }
    }
    return false;
}
public static string Text(string key)
{
    string value;
    return TryText(key, out value) ? value : key;
}
/// AIGC explicit disclosure: art and audio assets in this game are
/// AI-assisted (platform AI-generated-content labeling rule; the
/// implicit platform-side declaration stays an admin item).
public static string AigcLine()
{
    return Text(KeyAigcLine);
}
/// Random-draw disclosure. The published numbers are formatted
/// straight out of the live rerollFace pool (cfg_rune) and the draw
/// width law, so the shown face and the enforced law are the same
/// object - a hot-tuned pool re-renders the disclosure with zero
/// extra wiring. Uniform draw, no rarity tiers, no paid draws.
public static string OddsLine()
{
    int pool = NewbieConfig.RerollFaces.Length;
    int draw = Math.Min(RerollDrawWidth, pool);
    int pct = (int)Math.Round(draw * 100.0 / Math.Max(1, pool));
    return string.Format(Text(KeyOddsLine), pool, draw, pct);
}
/// Ad-cap disclosure: the global daily ceiling formatted out of the
/// live ad-point law (voluntary views only - no forced ad).
public static string AdCapLine()
{
    var law = P01Configs.AdPoint;
```

```
int cap = law != null ? law.globalCapDaily : 0;
return string.Format(Text(KeyAdCapLine), cap);
}
/// Age-rating disclosure (micro-horror folk theme: 12+).
public static string AgeLine()
{
    return Text(KeyAgeLine);
}
// —— view layer ——
RectTransform _overlay;
void Start()
{
    var canvas = FindObjectOfType<Canvas>();
    if (canvas == null) return; // headless gate: nothing to host on
    Initialize(canvas);
}
void Initialize(Canvas canvas)
{
    // persistent entry button, bottom-right of the main menu
    var entryGo = new GameObject("AboutEntry", typeof(RectTransform), typeof(Image), typeof(Button));
    entryGo.transform.SetParent(canvas.transform, false);
    var entry = (RectTransform)entryGo.transform;
    entry.anchorMin = entry.anchorMax = new Vector2(1f, 0f);
    entry.anchoredPosition = new Vector2(-140f, 96f);
    entry.sizeDelta = new Vector2(150f, 64f);
    var entryImg = entryGo.GetComponent<Image>();
    entryImg.sprite = MakeSquareSpriteShared();
    entryImg.color = LanternAmber;
    var entryTxt = MakeText(entry, Text(KeyAboutButton), 34, Vector2.zero,
        TextAnchor.MiddleCenter, 150f, 64f);
    entryTxt.color = PaperWhite;
    entryTxt.raycastTarget = false;
    entryGo.GetComponent<Button>().onClick.AddListener(Open);
    // disclosure overlay (hidden until the entry opens it)
    _overlay = new GameObject("AboutOverlay", typeof(RectTransform), typeof(Image)).GetComponent<RectTransform>();
    _overlay.transform.SetParent(canvas.transform, false);
    _overlay.anchorMin = Vector2.zero;
    _overlay.anchorMax = Vector2.one;
    _overlay.offsetMin = _overlay.offsetMax = Vector2.zero;
    var dim = _overlay.GetComponent<Image>();
    dim.sprite = MakeSquareSpriteShared();
    dim.color = NightDim;
    var paper = MakeCard(_overlay, "AboutPaper", Vector2.zero, new Vector2(940, 1180),
        new Color(PaperWhite.r, PaperWhite.g, PaperWhite.b, 0.97f));
    MakeText(paper, Text(KeyPanelTitle), 64, new Vector2(0, 460),
        TextAnchor.MiddleCenter, 900, 110).color = InkBrown;
    MakeText(paper, AigcLine(), 36, new Vector2(0, 250),
        TextAnchor.MiddleCenter, 820, 120).color = InkBrown;
    MakeText(paper, OddsLine(), 34, new Vector2(0, 60),
        TextAnchor.MiddleCenter, 820, 190).color = InkBrown;
```

```

        MakeText(paper, AdCapLine(), 34, new Vector2(0, -130),
            TextAnchor.MiddleCenter, 820, 110).color = InkBrown;
        MakeText(paper, AgeLine(), 34, new Vector2(0, -250),
            TextAnchor.MiddleCenter, 820, 110).color = InkBrown;
        MakeButton(paper, Text(KeyCloseLabel), new Vector2(0, -440),
            new Vector2(420, 96), Close);
        _overlay.gameObject.SetActive(false);
    }
    public void Open()
    {
        if (_overlay != null) _overlay.gameObject.SetActive(true);
    }
    void Close()
    {
        if (_overlay != null) _overlay.gameObject.SetActive(false);
    }
    // —— tools (programmatic UGUI, zero scene YAML) ——
    static RectTransform MakeCard(RectTransform parent, string name, Vector2 pos, Vector2 size, Color color)
    {
        var go = new GameObject(name, typeof(RectTransform), typeof(Image));
        go.transform.SetParent(parent, false);
        var rt = (RectTransform)go.transform;
        rt.anchorMin = rt.anchorMax = new Vector2(0.5f, 0.5f);
        rt.anchoredPosition = pos;
        rt.sizeDelta = size;
        var img = go.GetComponent<Image>();
        img.sprite = MakeSquareSpriteShared();
        img.color = color;
        return rt;
    }
    static Text MakeText(RectTransform parent, string text, int size, Vector2 pos, TextAnchor anchor, float w, float h)
    {
        var go = new GameObject("Text", typeof(RectTransform), typeof(Text));
        go.transform.SetParent(parent, false);
        var rt = (RectTransform)go.transform;
        rt.anchorMin = rt.anchorMax = new Vector2(0.5f, 0.5f);
        rt.anchoredPosition = pos;
        rt.sizeDelta = new Vector2(w, h);
        var t = go.GetComponent<Text>();
        t.font = UIFont.Resolve(); // T035: FontSet-driven CJK chain
        t.text = text;
        t.fontSize = size;
        t.alignment = anchor;
        t.color = InkBrown;
        return t;
    }
    static void MakeButton(RectTransform parent, string label, Vector2 pos, Vector2 size, Action onClick)
    {
        var go = new GameObject("ActionButton", typeof(RectTransform), typeof(Image), typeof(Button));
        go.transform.SetParent(parent, false);

```

```

        var rt = (RectTransform)go.transform;
        rt.anchorMin = rt.anchorMax = new Vector2(0.5f, 0.5f);
        rt.anchoredPosition = pos;
        rt.sizeDelta = size;
        var img = go.GetComponent<Image>();
        img.sprite = MakeSquareSpriteShared();
        img.color = LanternAmber;
        var txt = MakeText(rt, label, 40, Vector2.zero, TextAnchor.MiddleCenter, size.x, size.y);
        txt.color = PaperWhite;
        txt.raycastTarget = false;
        go.GetComponent<Button>().onClick.AddListener(() => onClick());
    }
    static Sprite _sharedSquare;
    static Sprite MakeSquareSpriteShared()
    {
        if (_sharedSquare == null)
        {
            var tex = new Texture2D(8, 8, TextureFormat.RGBA32, false);
            var px = tex.GetPixels32();
            for (int i = 0; i < px.Length; i++) px[i] = new Color32(255, 255, 255, 255);
            tex.SetPixels32(px);
            tex.Apply(false, false);
            _sharedSquare = Sprite.Create(tex, new Rect(0, 0, 8, 8), new Vector2(0.5f, 0.5f), 8f);
        }
        return _sharedSquare;
    }
}

// AdPointFunnel.cs
using System.Collections.Generic;
using Sy.Platform;
namespace Sy.P01.Newbie
{
    /// <summary>
    /// T020 slice 2 - the cfg_ad_point consumer face: the P02 three-piece pattern
    /// (HasCategoryBudget pre-check -> category-gated consume -> evt_ad funnel
    /// telemetry) as pure functions over the shared AdCapPolicy, so the slice-3
    /// point UI wiring and the AdFunnelCheck gate stay thin call sites. Per-run
    /// caps stay sim-side (BattleSim counters, the revive T011 precedent); this
    /// face owns the day pools, the gain decay ladder, the P1-11 revive gate and
    /// the interstitial rules. Zero server (red line 12) - policy and table are
    /// both local; a missing table row reads as "no offer" (fail-loud callers
    /// surface the missing asset through P01Configs.Load's error log).
    /// </summary>
    public static class AdPointFunnel
    {
        /// <summary>Runtime ad point id: p01_-isolated namespace (revive T011
        /// precedent) - the ads service and evt_ad telemetry never see a bare id
        /// that could collide with the P02/P06/G namespaces.</summary>
        public static string AdPointId(string pointId) => "p01_" + pointId;
    }
}

```

```

/// <summary>Table row for a cfg point id (null = unknown id).</summary>
public static P01Configs.AdPointRow Row(string pointId)
{
    var table = P01Configs.AdPoint;
    if (table?.points == null) return null;
    foreach (var p in table.points)
        if (p.pointId == pointId) return p;
    return null;
}
/// <summary>Section-six pre-offer gate (P02 paradigm): true when the
/// point's p01_ category still has day budget. The global 12 cap is
/// enforced at consume; per-run caps are sim-side and owned by the host.</summary>
public static bool PrecheckBudget(string pointId, string dayKey, AdCapPolicy policy)
{
    var row = Row(pointId);
    if (row == null || row.type != "rewarded") return false;
    return policy.HasCategoryBudget(dayKey, AdCategories.CategoryOfPoint(AdPointId(pointId)));
}
/// <summary>T020 slice 3b-3i: prep-face offer decision, pure so AdFunnelCheck
/// K9 can pin the red line without a scene. Run 1 IS the tutorial run
/// (redline11 sibling): its pick face never shows an in-run ad offer, even
/// with a full budget; every later run rides the normal budget precheck.</summary>
public static bool PrepOfferLive(string pointId, int runCount, string dayKey, AdCapPolicy policy)
{
    if (runCount == 1) return false;
    return PrecheckBudget(pointId, dayKey, policy);
}
/// <summary>Category-gated consume (P02 paradigm): day pool first, then
/// the global 12 hard cap; both counters advance together. False = the
/// host tracks the funnel "blocked" state and never retries the ad.</summary>
public static bool TryConsume(string pointId, string dayKey, AdCapPolicy policy)
{
    var row = Row(pointId);
    if (row == null || row.type != "rewarded") return false;
    return policy.TryConsumeRewarded(dayKey, AdCategories.CategoryOfPoint(AdPointId(pointId)));
}
/// <summary>Gain decay face (task book L15): rescue-class points keep full
/// value on every watch (decay null, constant full); gain-class points walk
/// the ladder by same-day watch index (watch 1 = 1.0, 2 = 0.9, 3 = 0.8,
/// 4+ = 0.7). watchIdx is 1-based; a missing table reads as full value.</summary>
public static float GainMul(string pointId, int watchIdx)
{
    var row = Row(pointId);
    var ladder = P01Configs.AdPoint?.gainDecayLadder;
    if (row == null || ladder == null || ladder.Length == 0) return 1f;
    if (string.IsNullOrEmpty(row.decay)) return 1f;
    int idx = watchIdx &lt;= 1 ? 0
        : watchIdx &gt; ladder.Length ? ladder.Length - 1
        : watchIdx - 1;
    return ladder[idx];
}

```

```

    }
    /// <summary>Revive second-watch gate (red-team P1-11): the second revive
    /// offer only arms late (wave >= 12 OR run duration >= 240s) so a strong
    /// early run cannot farm the 6/day rescue pool. First watch is ungated.</summary>
    public static bool ReviveGateOk(int wave, float durationSec, bool secondWatch)
    {
        if (!secondWatch) return true;
        var gate = Row("revive").gate;
        if (gate == null) return true;
        return wave >= gate.waveGte || durationSec >= gate.orDurationSecGte;
    }
    /// <summary>Interstitial face: the first-5-runs exemption (L121 verbatim)
    /// gates before the shared policy's 180s cooldown consume.</summary>
    public static bool InterstitialAllowed(int runCount, string dayKey, float nowSec, AdCapPolicy policy)
    {
        var row = Row("interstitial");
        if (row == null) return false;
        int exempt = row.gate?.firstRunsExempt ?? 0;
        if (runCount < exempt) return false;
        return policy.TryConsumeInterstitial(dayKey, nowSec);
    }
    /// <summary>evt_ad funnel telemetry (P01 TrackRevive field precedent:
    /// state/pointId/wave/reason - the emitted pointId is the p01_-isolated
    /// runtime id). Slice-3 hosts pass their boot-registered (or launcher
    /// fallback) TelemetryService; states = offer/accept/ad_fail/decline/
    /// blocked/complete per the P02 funnel vocabulary.</summary>
    public static void Track(Sy.Telemetry.TelemetryService telemetry, string state,
        string pointId, int wave, string reason)
    {
        if (telemetry == null) return;
        var fields = new Dictionary<string, string>
        {
            { "state", state },
            { "pointId", AdPointId(pointId) },
        };
        if (wave >= 0) fields["wave"] = wave.ToString();
        if (reason != null) fields["reason"] = reason;
        telemetry.Track(Sy.Telemetry.EventIds.Ad, fields);
    }
}

// BattleLauncher.cs
using System.Collections.Generic;
using UnityEngine;
using UnityEngine.EventSystems;
namespace Sy.P01.Newbie
{
    /// <summary>
    /// S01_Battle      BattleSim+TutorialFlow+BattleView  Tick+
    /// Sy.Telemetry Editor =Debug sink T001e      +TCB

```

```

/// HUD                                6
/// &lt;/summary>
public sealed class BattleLauncher : MonoBehaviour
{
    BattleSim _sim;
    TutorialFlow _tutorial;
    BattleView _view;
    Sy.Telemetry.TelemetryService _telemetry;
    Sy.Social.ShareCard _reportSpec;      // T021b: the settle-face report card spec
    Sy.Social.ComposeResult _reportCard;  // T021b: the composed report card (png path)
    Sy.Platform.AdCapPolicy _adCap;      // T011: shared boot policy (or session fallback)
    bool _revivePairShown;               // T011: mirrors the offer pair visibility
    bool _pullbackPlayed;                // T012: camera beat is intro-only (Fighting re-entries from talisman/revive m
    bool _dragging;
    Vector2 _dragOrigin;
    int _lastWave = -1, _lastCoins = -1, _lastKills = -1, _lastHp = -1, _lastCountdown = -1;
    const string RevivePointId = "p01_revive"; // T011: $ point 1 (p01_-isolated namespace)
    // T020 slice 3b: settle_double site state - the bonus face anchors the
    // wave-reward settle face (60+40 per cfg_item); the funnel takes the bare
    // point id and derives the p01_ runtime id.
    const string SettleDoublePointId = "settle_double"; // T020: $ point 2 (settle coins x2)
    const string InterstitialPointId = "interstitial"; // T020: $ interstitial row (post_run)
    const string StartTalentPointId = "start_talent"; // T020: $ point 3 (prep pair, uiStyle prep_panel)
    const string WeaponTrialPointId = "weapon_trial"; // T020: $ point 4 (prep pair, uiStyle prep_panel)
    const string DyingShieldPointId = "dying_shield"; // T020: $ point 3 (death-face shield)
    const string SoullampPointId = "soul_lamp";       // T020: $ point 6 (boss-wave burn window)
    const string BellRerollPointId = "bell_reroll";   // T020: $ point 7 (smart-trigger re-draw)
    int _settleBonusFace;
    bool _settleDoubleLive;
    bool _prepTalentLive; // T020 slice 3b-3i: prep-pair liveness (per pause face, settled on watch)
    bool _prepTrialLive;
    bool _dyingShieldLive; // T020 slice 3b-2: shield offer holds the death run open
    bool _nightRunClosed; // T020 slice 3b-2: one close per run (the shield-open nav face may tap after a clos
    bool _lampLive;       // T020 slice 3b-3ii: boss-wave lamp offer liveness (settled on watch)
    bool _rerollLive;     // T020 slice 3b-3iii: bell_reroll offer liveness (settled on watch)
    void Awake()
    {
        Application.targetFrameRate = 30;
        var canvas = FindObjectOfType<Canvas>();
        // T019 slice 2: the local save face hydrates BEFORE the sim consumes the
        // run-count / codex faces (red line 12 - local file is the authority; a
        // missing file = honest fresh D1 + run 1).
        NewbieSession.HydrateFromSave();
        _sim = new BattleSim(seed: 20260916);
        _sim.SetRunCount(NewbieSession.RunCount);
        // T023 slice 2: rotate the battlefield for this night run (cycle_by_run
        // over the dayIndex-unlocked roster, cfg_map) and stamp the formal-spawn
        // modifiers onto the sim (single numeric truth, the SetRunCount precedent).
        MapService.SelectCurrent(NewbieSession.RunCount, NewbieSession.DayState.DayIndex);
        _sim.SetMapModifiers(MapService.CurrentSpeedMul,

```

```

        MapService.PaperEffigyTemplateId, MapService.CurrentPaperHpPct);
_sim.SetCodexCollected(NewbieSession.TalentState.CodexCollected.Count);
_view = gameObject.AddComponent<BattleView>();
_view.Initialize(canvas, _sim);
_telemetry = new Sy.Telemetry.TelemetryService();
_telemetry.AddSink(new TelemetryDebugSink());
// T021c-ii: point-card receive face - a share-card cold start carries
// the friend's build on the boot query's bd= token; it becomes THIS
// run's opening build (apply-by-replace, one-shot). Organic opens
// stay byte-identical: no launch face (headless) reads as absent.
BuildImport.CaptureFromPlatform();
var importedBuild = BuildImport.TryTakeBuild();
if (importedBuild != null && _sim.ApplyImportedBuild(importedBuild))
    _view.SetHint(UiText.Get("battle_import_hint"));
_tutorial = new TutorialFlow(
    _sim,
    hint => {
        Debug.Log("[HINT] " + hint);
        _view.SetHint(hint);
    },
    step => { _telemetry.Track(Sy.Telemetry.EventIds.NewbieStep,
        new Dictionary<string, string> { { "step", step.ToString() } });
_view.TalismanPickRequested += OnTalismanPickRequested;
_sim.StateChanged += OnStateChanged;
_sim.EnemyKilled += OnEnemyKilled; // $4.1
_sim.TalismanPicked += OnTalismanPicked; // V1.1
_sim.ChainEvolvedDone += OnChainEvolved; // →
// T012 slice 2: soul-bottle presentation beats ($0 T+4-10, sim-clock driven
// so the View and the Redline11Check probes share one timeline).
_sim.BottleLidHit += OnBottleLidHit;
_sim.BottleHeadPoke += OnBottleHeadPoke;
// T016 slice 3: boss enrage + capture-bottle show (shareable moment 3) -
// the rune-short window shows the "so close" hint, the executed capture
// plays the boss-into-bottle beat.
_sim.BossEnraged += OnBossEnraged;
_sim.BossCaptureMarked += OnBossCaptureMarked;
_sim.BossCaptured += OnBossCaptured;
// T011 revive traffic (p01_revive point, $ point 1, P02 rescue paradigm):
// the boot-registered AdCapPolicy is the same instance the suite's
// ShowRewarded consumes from, so the pre-check and the consumption stay
// consistent; without boot the fallback policy scopes the cap to this
// session (headless baselines never reach here - they drive the sim only).
if (!Sy.Core.ServiceLocator.TryGet<Sy.Platform.AdCapPolicy>(out _adCap))
    _adCap = new Sy.Platform.AdCapPolicy();
_sim.ReviveOffered += OnReviveOffered;
_sim.ReviveOfferExpired += OnReviveOfferExpired;
_sim.Revived += OnRevived;
_sim.DyingShielded += OnDyingShielded; // T020 slice 3b-2: the shield resume beat
_sim.LampOffered += OnLampOffered; // T020 slice 3b-3ii: the boss-wave lamp arm

```

```

_sim.RerollOffered += OnRerollOffered; // T020 slice 3b-3iii: the re-offer bell arm
_view.ReviveAcceptRequested += OnReviveAcceptRequested;
_view.ReviveDeclineRequested += OnReviveDeclineRequested;
_view.SettleDoubleRequested += OnSettleDoubleRequested; // T020 slice 3b
_view.ShareRequested += OnShareRequested; // T021b: report-card share
_view.FriendBoardRequested += OnFriendBoardRequested; // T022-iii: friend board
_view.PrepareTalentRequested += OnPrepareTalentRequested; // T020 slice 3b-3i
_view.PrepareTrialRequested += OnPrepareTrialRequested;
_view.DyingShieldRequested += OnDyingShieldRequested; // T020 slice 3b-2
_view.LampAcceptRequested += OnLampAcceptRequested; // T020 slice 3b-3ii
_view.RerollAcceptRequested += OnRerollAcceptRequested; // T020 slice 3b-3iii
_view.DeathNavBattleRequested += () => LeaveDeathFace(NewbieSceneIds.Battle);
_view.DeathNavHomeRequested += () => LeaveDeathFace(NewbieSceneIds.Main);
}
void Update()
{
    TickJoystickInput();
    _sim.Tick(Time.deltaTime);
    _view.SyncView(_sim);
    if (_sim.SoulBurstPending)
    {
        _view.PlaySoulBurst();
        _sim.ConsumeSoulBurst();
    }
    // T011: countdown label mirrors the sim's 3s window (int-change only).
    if (_sim.ReviveOfferActive && _revivePairShown)
    {
        int left = Mathf.CeilToInt(_sim.ReviveCountdownSeconds);
        if (left != _lastCountdown)
        {
            _lastCountdown = left;
            _view.SetReviveCountdown(left);
        }
    }
    if (_sim.Wave != _lastWave) { _lastWave = _sim.Wave; _view.SetWave(_lastWave); }
    if (_sim.Coins != _lastCoins) { _lastCoins = _sim.Coins; _view.SetCoins(_lastCoins); }
    if (_sim.Kills != _lastKills) { _lastKills = _sim.Kills; _view.SetKills(_lastKills); }
    if ((int)_sim.HeroHp != _lastHp) { _lastHp = (int)_sim.HeroHp; _view.SetHp(_lastHp); }
}
/// <summary> §10.2.2 = UI </summary>
void TickJoystickInput()
{
    if (Input.GetMouseButtonDown(0)
        && (EventSystem.current == null || !EventSystem.current.IsPointerOverGameObject()))
    {
        _dragging = true;
        _dragOrigin = Input.mousePosition;
    }
    if (Input.GetMouseButtonUp(0))
    {

```

```
        _dragging = false;
        _sim.SetMoveInput(0f, 0f);
        _view.HideJoystick();
    }
    if (!_dragging) return;
    var delta = (Vector2)Input.mousePosition - _dragOrigin;
    if (delta.magnitude > 12f)
    {
        _sim.SetMoveInput(delta.x, delta.y);
        _view.ShowJoystick(_dragOrigin, Input.mousePosition);
    }
    else
    {
        _sim.SetMoveInput(0f, 0f);
        _view.HideJoystick();
    }
}

void OnTalismanPickRequested(int index)
{
    _sim.PickTalisman(index);
}

void OnTalismanPicked(int index)
{
    _view.SetChain(_sim.ChainDisplay);
}

void OnChainEvolved()
{
    _view.SetChain(_sim.ChainDisplay);
}

void OnEnemyKilled(BattleSim.GhostInst g)
{
    _view.PlaySoulAbsorb(g.X, g.Y);
    // T012 slice 2: the FIRST kill is the §0 triple-feedback beat - count+1
    // (SetKills), soul fire (absorb above) and the break sfx all land together.
    if (_sim.Kills == 1) _view.PlayBreakSfx();
}

// T012 slice 2: §0 bottle beats - the lid "dong" and the head-poke wow moment.
void OnBottleLidHit(float simTime) => _view.PlayBottleLidBeat();
void OnBottleHeadPoke(float simTime) => _view.PlayBottleHeadPoke();
// T016 slice 3: enrage red-light beat + the capture-window faces. The capture
// itself executes sim-side on the same tick the gate opens, so a "ready" boss
// never shows the miss hint - BossCaptured fires right after the mark.
void OnBossEnraged(BattleSim.GhostInst g) => _view.PlayBossEnrageShow();
void OnBossCaptureMarked(BattleSim.GhostInst g)
{
    if (!_sim.IsBossCaptureReady(g))
        _view.ShowCaptureMissHint(g.CaptureRunes - _sim.TalismanPicks);
}

void OnBossCaptured(BattleSim.GhostInst g)
{

```

```
_view.PlayBossCaptureShow(g.X, g.Y);
// T019 slice 3: first-encounter capture registration - the capture
// GUARANTEES the codex entry (05 s9 suspender next to the week-chain
// belt); the live count re-stamps the battle's collection bonus on the
// same tick, the collect beat lands right after the capture show, and
// the guaranteed collect persists immediately (crash-safe collection).
if (NewbieSession.RegisterCodexCapture(g.TemplateId))
{
    _sim.SetCodexCollected(NewbieSession.TalentState.CodexCollected.Count);
    NewbieSession.WriteToSave();
    string label = LauncherTelemetry.CodexSpeciesLabel(g.TemplateId);
    _view.PlayCodexCollectBeat(label);
    LauncherTelemetry.TrackCodexCollect(_telemetry, label,
        NewbieSession.TalentState.CodexCollected.Count);
}
}
void OnStateChanged(BattleSim.BattleState state)
{
    switch (state)
    {
        case BattleSim.BattleState.Fighting:
            _view.HideIntro();
            // T012 slice 2: $0 T+1.5-3.0s camera beat rides the intro-to-street
            // handover (zoomed on the bearer, eases out as the swarm closes in).
            // Fighting re-entries (talisman resume / revive) never replay it.
            if (!_pullbackPlayed)
            {
                _pullbackPlayed = true;
                _view.PlayCameraPullback();
            }
            break;
        case BattleSim.BattleState.TalismanPause:
            _view.ShowTalismanPanel();
            MaybeShowPrepOffers(); // T020 slice 3b-3i: the pick face doubles as the prep face
            break;
        case BattleSim.BattleState.Won:
            // T017 slice 3: the won night closes the day loop - bottle ghosts
            // (=Kills headcount since X209) + coins feed tomorrow's day layer.
            // T018 slice 3: the same deposit completes the chain verb - the
            // auto-claimed codex grant lands on the settle as its own beat.
            // T019 slice 2: the settle grants the pending wave rewards as coins
            // (cfg_item waveRewardFace) on top of the in-run counter, then the
            // night's run closes and the whole session persists.
            int settleCoins = _sim.Coins + _sim.PendingRewardCoins;
            int runIdx = NewbieSession.RunCount; // T020: pre-increment 1-based run index (interstitial exempt
            NewbieSession.DepositNight(_sim.BottleGhosts, settleCoins);
            CloseNightRun();
            _view.ShowSettle(_sim.Kills, settleCoins);
            if (NewbieSession.LastChainDay &gt; 0)
                _view.SetSettleCodex(UiText.Get("battle_settle_codex_fmt",
```

```

        NewbieSession.LastChainDay.ToString(), NewbieSession.LastChainEnemyId,
        NewbieSession.LastChainCoins.ToString());
    // T020 slice 3b: settle_double offer ($ point 2, P02 T015-A2
    // paradigm) - the bonus face = the wave-reward settle face
    // (60+40); no budget, no dead-end button.
    _settleBonusFace = _sim.PendingRewardCoins;
    _settleDoubleLive = false;
    if (_settleBonusFace > 0
        && AdPointFunnel.PrecheckBudget(SettleDoublePointId,
        Sy.Platform.AdCapPolicy.TodayKey(), _adCap))
    {
        _settleDoubleLive = true;
        // The offer label shows what THIS watch grants - the decay
        // ladder rides the same-day watch index (pre-consume +1).
        int watchIdxNext = _adCap.UsedCategoryToday(Sy.Platform.AdCapPolicy.TodayKey(),
        Sy.Platform.AdCategories.CategoryOfPoint(AdPointFunnel.AdPointId(SettleDoublePointId))) + 1;
        _view.ShowSettleDoubleOffer(Mathf.RoundToInt(
        _settleBonusFace * AdPointFunnel.GainMul(SettleDoublePointId, watchIdxNext));
        AdPointFunnel.Track(_telemetry, "offer", SettleDoublePointId, _sim.Wave, "settle_coins");
    }
    // T020 slice 3b: post-run interstitial (uiStyle post_run; the
    // death face rework lands with dying_shield in the next slice).
    ComposeReportCard(); // T021b: report card + share offer (Won = the one legal ReadPixels stall poi
    MaybeFirePostRunInterstitial(runIdx);
    break;
case BattleSim.BattleState.Lost:
    // T024-ii: the BattleLost-face wave-fail emitter (04 Schema
    // section 5) - one honest beat per real lost run, through the
    // shared seam the marathon gate also drives.
    LauncherTelemetry.TrackWaveFail(_telemetry, MapService.CurrentMapId, _sim.Wave);
    // T011: the death settle. The sim evaluates the revive offer BEFORE
    // this event, so a live offer means the pair is (or was budget-
    // checked to be) up; no pair shown = final form right away.
    _view.ShowDeathSettle(_sim.Kills, _sim.Coins, _sim.Wave);
    if (!_revivePairShown)
    {
        // T020 slice 3b-2: terminal death face (no revive pair) - the
        // dying_shield offer is the weaker second-chance tier (1/run
        // sim-side + p01_shield 3/day pre-check, no dead-end button).
        // While the offer holds, the run stays open (an accept resumes
        // the battle) and the nav pair rides alongside so leaving is
        // still one tap - the nav route closes the run on exit.
        _dyingShieldLive = false;
        if (!_sim.DyingShieldUsed
            && AdPointFunnel.PrecheckBudget(DyingShieldPointId,
            Sy.Platform.AdCapPolicy.TodayKey(), _adCap))
        {
            var shieldRow = AdPointFunnel.Row(DyingShieldPointId);
            if (shieldRow != null)
            {

```

```

        _dyingShieldLive = true;
        _view.ShowDyingShieldOffer(shieldRow.invulnSec, shieldRow.healPct);
        AdPointFunnel.Track(_telemetry, "offer", DyingShieldPointId, _sim.Wave, "death_face");
    }
}
_view.ShowDeathNav();
if (!_dyingShieldLive)
{
    // No shield face to answer: close + the post-run interstitial
    // death face (the Won face landed with slice 3b-1).
    int closeRunIdx = NewbieSession.RunCount;    // pre-close 1st-of-day index (site exemption fa
    CloseNightRun();
    MaybeFirePostRunInterstitial(closeRunIdx);
}
}
break;
}
}
// —— T011 revive traffic (p01_revive, $ funnel point 1) ——
void OnReviveOffered(int wave, int reviveIndex)
{
    // $ pre-offer gate: with no p01_revive budget (6/day) left the offer is
    // silently skipped instead of showing a dead-end button (P02 paradigm).
    string day = Sy.Platform.AdCapPolicy.TodayKey();
    if (!_adCap.HasCategoryBudget(day, Sy.Platform.AdCategories.CategoryOfPoint(RevivePointId))) return;
    _revivePairShown = true;
    _lastCountdown = -1;
    _view.ShowReviveOffer();
    TrackRevive("offer", wave, reviveIndex, null);
}
async void OnReviveAcceptRequested()
{
    if (!_sim.ReviveOfferActive) return;
    // The tap commits the offer: freeze the 3s window while the ad runs so a
    // real-channel ad (which can outlast 3s) can never expire the offer the
    // player already accepted.
    _sim.HoldReviveOfferForAd();
    _view.HideReviveOffer();
    if (Sy.Core.ServiceLocator.TryGet<Sy.Platform.IAdsService>(out var ads))
    {
        // Channel ad path (mock in Editor): the suite consumes the shared
        // policy inside ShowRewarded; awaiting keeps the real-channel JS
        // callback flow free of main-thread blocking.
        var result = await ads.ShowRewarded(RevivePointId);
        if (!result.Completed)
        {
            _sim.DeclineRevive();
            _revivePairShown = false;
            ShowDeathNavAndCloseRun();
            TrackRevive("ad_fail", _sim.Wave, _sim.ReviveCount + 1, result.Reason);
        }
    }
}

```

```
        return;
    }
}
else
{
    // Degraded session (no boot): consume locally against the fallback cap.
    if (!_adCap.TryConsumeRewarded(Sy.Platform.AdCapPolicy.TodayKey(),
        Sy.Platform.AdCategories.CategoryOfPoint(RevivePointId)))
    {
        _sim.DeclineRevive();
        _revivePairShown = false;
        ShowDeathNavAndCloseRun();
        TrackRevive("ad_fail", _sim.Wave, _sim.ReviveCount + 1, "daily_cap");
        return;
    }
}
if (_sim.AcceptRevive())
    TrackRevive("complete", _sim.Wave, _sim.ReviveCount, null);
}
void OnReviveDeclineRequested()
{
    if (!_sim.ReviveOfferActive) return;
    _sim.DeclineRevive();
    _revivePairShown = false;
    ShowDeathNavAndCloseRun();
    TrackRevive("decline", _sim.Wave, _sim.ReviveCount + 1, null);
}
void OnReviveOfferExpired()
{
    _revivePairShown = false;
    _view.HideReviveOffer();
    ShowDeathNavAndCloseRun();
    TrackRevive("decline", _sim.Wave, _sim.ReviveCount + 1, "timeout");
}
// T019 slice 2: a terminal death closes the night run - the difficulty
// schedule counts attempts, not wins - and persists the session.
// T020 slice 3b-2: every death-path close fires the post-run interstitial
// on the death face (uiStyle post_run; the shield-held run fires it at
// the nav exit instead).
void ShowDeathNavAndCloseRun()
{
    _view.ShowDeathNav();
    int runIdx = NewbieSession.RunCount;    // pre-close index (site exemption face)
    CloseNightRun();
    MaybeFirePostRunInterstitial(runIdx);
}
void CloseNightRun()
{
    // T020 slice 3b-2: idempotent one-close guard - with the shield offer
    // holding the run open, a nav tap can arrive after an ad_fail close;
```

```
// a second increment would double-count the attempt face.
if (_nightRunClosed) return;
_nightRunClosed = true;
NewbieSession.RunCount++;
NewbieSession.WriteToSave();
}
// T020 slice 3b-2: the death nav routes through the host so an exit from
// the shield-held death face still closes the run (run-count + interstitial
// death face) before the scene swap; an already-closed run (revive declined,
// shield ad_fail) rides straight into the load.
void LeaveDeathFace(string sceneId)
{
    if (!_nightRunClosed)
    {
        int runIdx = NewbieSession.RunCount;
        CloseNightRun();
        MaybeFirePostRunInterstitial(runIdx);
    }
    UnityEngine.SceneManagement.SceneManager.LoadScene(sceneId);
}
// —— T020 slice 3b-2: dying_shield traffic ($ point 3) ——
async void OnDyingShieldRequested()
{
    if (!_dyingShieldLive) return;
    _dyingShieldLive = false;
    _view.HideDyingShieldOffer();
    string day = Sy.Platform.AdCapPolicy.TodayKey();
    if (Sy.Core.ServiceLocator.TryGet<Sy.Platform.IAdsService>(out var ads))
    {
        // Channel ad path (mock in Editor): the suite consumes the shared
        // policy inside ShowRewarded - the same instance _adCap holds in a
        // booted session (settle_double 3b-1 paradigm).
        var result = await ads.ShowRewarded(AdPointFunnel.AdPointId(DyingShieldPointId));
        if (!result.Completed)
        {
            AdPointFunnel.Track(_telemetry, "ad_fail", DyingShieldPointId, _sim.Wave, result.Reason);
            ShowDeathNavAndCloseRun();
            return;
        }
    }
    else if (!AdPointFunnel.TryConsume(DyingShieldPointId, day, _adCap))
    {
        // Degraded session (no boot): consume locally against the fallback
        // cap; a false here is the daily-cap blocked face (never retried).
        AdPointFunnel.Track(_telemetry, "blocked", DyingShieldPointId, _sim.Wave, "daily_cap");
        ShowDeathNavAndCloseRun();
        return;
    }
    // Nav-exit race guard: while the ad was in flight the death nav could
    // close the run and start the scene swap - never resume a closed run
}
```

```

    // (the destroyed-view continuation would crash on the resume beat).
    if (_nightRunClosed || _view == null) return;
    var row = AdPointFunnel.Row(DyingShieldPointId);
    if (!_sim.AcceptDyingShield(row != null ? row.invulnSec : 0f, row != null ? row.healPct : 0f))
    {
        // Sim-side refusal (shield already used / a live revive pair) - the
        // honest face is the closed nav, never a stuck open panel.
        AdPointFunnel.Track(_telemetry, "decline", DyingShieldPointId, _sim.Wave, "sim_refused");
        ShowDeathNavAndCloseRun();
        return;
    }
    AdPointFunnel.Track(_telemetry, "complete", DyingShieldPointId, _sim.Wave, null);
}

/// <summary>The shield resume beat (sim DyingShielded event): the death settle
/// folds away and the run resumes in place - the dodge window is the point.</summary>
void OnDyingShielded(int wave)
{
    _view.HideDeathSettle();
    _view.PlayDyingShieldFlash();
    _view.SetHint(UiText.Get("battle_shield_hint"));
}

// —— T020 slice 3b-3ii: soul_lamp traffic ($ point 6) ——
// The sim arms the offer at a director boss wave (1/run cap sim-side);
// this host owns the p01_lamp day pre-check (3/day), the decay-adjusted
// label and the evt_ad funnel. The grant lights the burn window with
// the ladder-scaled magnitudes (label = grant, the honest-face precedent).
// A wave that clears while a real-channel ad is in flight refuses the
// accept (sim_refused, logged) - the untouched 1/run cap re-arms at the
// next boss wave, so no watch is silently swallowed.
void OnLampOffered(int wave)
{
    if (!_sim.LampOfferActive) return;
    string day = Sy.Platform.AdCapPolicy.TodayKey();
    if (!AdPointFunnel.PrecheckBudget(SoulLampPointId, day, _adCap)) return;
    var row = AdPointFunnel.Row(SoulLampPointId);
    if (row == null) return;
    _lampLive = true;
    int watchIdxNext = _adCap.UsedCategoryToday(day,
        Sy.Platform.AdCategories.CategoryOfPoint(AdPointFunnel.AdPointId(SoulLampPointId))) + 1;
    _view.ShowLampOffer(LampFace(row, AdPointFunnel.GainMul(SoulLampPointId, watchIdxNext)));
    AdPointFunnel.Track(_telemetry, "offer", SoulLampPointId, wave, "boss_wave");
}

/// <summary>Decay-adjusted label face: what THIS watch grants (the same
/// ladder the grant applies - label and grant must never disagree).</summary>
static string LampFace(P01Configs.AdPointRow row, float mul)
{
    int dmgPct = Mathf.RoundToInt(row.dmgPct * mul * 100f);
    float soul = row.soulMul * mul;
    string soulFace = Mathf.Approximately(soul, Mathf.Round(soul))
        ? Mathf.RoundToInt(soul).ToString()

```

```
        : soul.ToString("F1");
    return UiText.Get("battle_lamp_offer_fmt", dmgPct.ToString(),
        Mathf.RoundToInt(row.durationSec).ToString(), soulFace);
}
async void OnLampAcceptRequested()
{
    if (!_lampLive) return;
    _lampLive = false;
    _view.HideLampOffer();
    string day = Sy.Platform.AdCapPolicy.TodayKey();
    if (Sy.Core.ServiceLocator.TryGet<Sy.Platform.IAdsService>(out var ads))
    {
        // Channel ad path (mock in Editor): the suite consumes the shared
        // policy inside ShowRewarded - the same instance _adCap holds.
        var result = await ads.ShowRewarded(AdPointFunnel.AdPointId(SoulLampPointId));
        if (!result.Completed)
        {
            _sim.DeclineLamp();
            AdPointFunnel.Track(_telemetry, "ad_fail", SoulLampPointId, _sim.Wave, result.Reason);
            return;
        }
    }
    else if (!AdPointFunnel.TryConsume(SoulLampPointId, day, _adCap))
    {
        // Degraded session (no boot): the daily-cap blocked face, never retried.
        _sim.DeclineLamp();
        AdPointFunnel.Track(_telemetry, "blocked", SoulLampPointId, _sim.Wave, "daily_cap");
        return;
    }
    // Gain ladder rides the same-day watch index (post-consume read-back,
    // the settle_double precedent); the burn magnitudes scale by it.
    int watchIdx = _adCap.UsedCategoryToday(day,
        Sy.Platform.AdCategories.CategoryOfPoint(AdPointFunnel.AdPointId(SoulLampPointId)));
    var row = AdPointFunnel.Row(SoulLampPointId);
    if (row == null) return;
    float mul = AdPointFunnel.GainMul(SoulLampPointId, watchIdx);
    if (_sim.AcceptLamp(row.dmgPct * mul, row.durationSec, row.soulMul * mul))
    {
        _view.PlayLampFlash();
        _view.SetHint(UiText.Get("battle_lamp_burn_hint_fmt",
            Mathf.RoundToInt(row.dmgPct * mul * 100f).ToString(),
            Mathf.RoundToInt(row.durationSec).ToString()));
        AdPointFunnel.Track(_telemetry, "complete", SoulLampPointId, _sim.Wave, null);
    }
    else
    {
        // Sim-side refusal (the wave ended while the ad was in flight) -
        // the honest face is no burn window, never a phantom grant.
        AdPointFunnel.Track(_telemetry, "decline", SoulLampPointId, _sim.Wave, "sim_refused");
    }
}
```

```
}
// —— T020 slice 3b-3iii: bell_reroll traffic ($ point 7) ——
// The sim arms the bell on a re-offer where the fixed trio duplicates the
// held build (smart trigger + 1/run cap sim-side); this host owns the
// p01_reroll day pre-check (3/day) and the evt_ad funnel. The draw pool
// is cfg_rune rerollFace (single numeric authority) - the gain ladder
// stays bookkeeping-only for this point (the row has no magnitudes to
// scale, faces are never decayed). A pick that lands while a real-channel
// ad is in flight refuses the accept (sim_refused, logged) - the untouched
// cap re-arms at the next qualifying pause, so no watch is silently
// swallowed.
void OnRerollOffered(int pauseIndex)
{
    if (!_sim.RerollOfferActive) return;
    string day = Sy.Platform.AdCapPolicy.TodayKey();
    if (!AdPointFunnel.PrecheckBudget(BellRerollPointId, day, _adCap)) return;
    if (AdPointFunnel.Row(BellRerollPointId) == null) return;
    _rerollLive = true;
    _view.ShowRerollOffer();
    AdPointFunnel.Track(_telemetry, "offer", BellRerollPointId, pauseIndex, "talisman_reoffer");
}
async void OnRerollAcceptRequested()
{
    if (!_rerollLive) return;
    _rerollLive = false;
    _view.HideRerollOffer();
    string day = Sy.Platform.AdCapPolicy.TodayKey();
    if (Sy.Core.ServiceLocator.TryGet<Sy.Platform.IAdsService>(out var ads))
    {
        // Channel ad path (mock in Editor): the suite consumes the shared
        // policy inside ShowRewarded - the same instance _adCap holds.
        var result = await ads.ShowRewarded(AdPointFunnel.AdPointId(BellRerollPointId));
        if (!result.Completed)
        {
            _sim.DeclineReroll();
            AdPointFunnel.Track(_telemetry, "ad_fail", BellRerollPointId, _sim.Wave, result.Reason);
            return;
        }
    }
    else if (!AdPointFunnel.TryConsume(BellRerollPointId, day, _adCap))
    {
        // Degraded session (no boot): the daily-cap blocked face, never retried.
        _sim.DeclineReroll();
        AdPointFunnel.Track(_telemetry, "blocked", BellRerollPointId, _sim.Wave, "daily_cap");
        return;
    }
    if (_sim.AcceptReroll())
    {
        _view.ApplyRerollFaces(_sim.OfferedFacesNow);
        _view.PlayRerollFlash();
    }
}
```

```

        _view.SetHint(UiText.Get("battle_reroll_hint"));
        AdPointFunnel.Track(_telemetry, "complete", BellRerollPointId, _sim.Wave, null);
    }
    else
    {
        // Sim-side refusal (the pause closed while the ad was in flight) -
        // the honest face is no re-draw, never a phantom draw.
        AdPointFunnel.Track(_telemetry, "decline", BellRerollPointId, _sim.Wave, "sim_refused");
    }
}

void OnRevived(int wave)
{
    _revivePairShown = false;
    _view.HideDeathSettle();
    _view.PlayReviveFlash();
    _view.SetHint(UiText.Get("battle_revive_hint"));
}

void TrackRevive(string state, int wave, int reviveIndex, string reason)
{
    var fields = new Dictionary<string, string>;
    {
        { "state", state },
        { "pointId", RevivePointId },
        { "wave", wave.ToString() },
        { "reviveIdx", reviveIndex.ToString() },
    };
    if (reason != null) fields["reason"] = reason;
    _telemetry.Track(Sy.Telemetry.EventIds.Ad, fields);
}

// —— T020 slice 3b: settle_double traffic ($ point 2) ——
async void OnSettleDoubleRequested()
{
    if (!_settleDoubleLive) return;
    _settleDoubleLive = false;
    _view.HideSettleDoubleOffer();
    string day = Sy.Platform.AdCapPolicy.TodayKey();
    if (Sy.Core.ServiceLocator.TryGet<Sy.Platform.IAdsService>(out var ads))
    {
        // Channel ad path (mock in Editor): the suite consumes the shared
        // policy inside ShowRewarded - the same instance _adCap holds in a
        // booted session, so the post-consume read-back stays truthful.
        var result = await ads.ShowRewarded(AdPointFunnel.AdPointId(SettleDoublePointId));
        if (!result.Completed)
        {
            AdPointFunnel.Track(_telemetry, "ad_fail", SettleDoublePointId, _sim.Wave, result.Reason);
            return;
        }
    }
    else if (!AdPointFunnel.TryConsume(SettleDoublePointId, day, _adCap))
    {

```

```

        // Degraded session (no boot): consume locally against the fallback
        // cap; a false here is the daily-cap blocked face (never retried).
        AdPointFunnel.Track(_telemetry, "blocked", SettleDoublePointId, _sim.Wave, "daily_cap");
        return;
    }
    // Gain ladder rides the same-day watch index - UsedCategoryToday
    // already counts this watch after the consume (watch 1 = 1.0 full).
    int watchIdx = _adCap.UsedCategoryToday(day,
        Sy.Platform.AdCategories.CategoryOfPoint(AdPointFunnel.AdPointId(SettleDoublePointId)));
    int bonus = Mathf.RoundToInt(_settleBonusFace * AdPointFunnel.GainMul(SettleDoublePointId, watchIdx));
    if (bonus > 0)
    {
        // The accepted bonus re-deposits the settle face - base + bonus IS
        // the x2 (the ad reward mints nothing else; wallet = economy truth).
        NewbieSession.WalletCoins += bonus;
        NewbieSession.WriteToSave(); // crash-safe (T019 pattern)
        _view.PlaySettleDoubleFlash(bonus);
    }
    AdPointFunnel.Track(_telemetry, "complete", SettleDoublePointId, _sim.Wave, null);
}
// —— T020 slice 3b-3i: prep pair traffic ($ points 3+4) ——
// The three-pick face doubles as the level-prep face (X228 probe: the
// pitch book has no standalone prep page). Run 1 IS the tutorial run -
// PrepOfferLive pins the zero-offer red line pure for AdFunnelCheck K9.
// Each watch grants the cfg coins face x the decay ladder into the
// shared wallet (settle_double precedent); nothing spends wallet coins
// mid-run, so the weapon_trial "next run" semantic holds without a
// second economy truth.
void MaybeShowPrepOffers()
{
    string day = Sy.Platform.AdCapPolicy.TodayKey();
    _prepTalentLive = AdPointFunnel.PrepOfferLive(StartTalentPointId, NewbieSession.RunCount, day, _adCap);
    _prepTrialLive = AdPointFunnel.PrepOfferLive(WeaponTrialPointId, NewbieSession.RunCount, day, _adCap);
    int talentCoins = 0, trialCoins = 0;
    if (_prepTalentLive)
    {
        talentCoins = PrepCoinsFace(StartTalentPointId, day);
        AdPointFunnel.Track(_telemetry, "offer", StartTalentPointId, _sim.Wave, "prep_talent");
    }
    if (_prepTrialLive)
    {
        trialCoins = PrepCoinsFace(WeaponTrialPointId, day);
        AdPointFunnel.Track(_telemetry, "offer", WeaponTrialPointId, _sim.Wave, "prep_trial");
    }
    _view.ShowPrepOffers(talentCoins, trialCoins);
}
/// <summary>Offer label face: what THIS watch grants - the cfg coins
/// magnitude x the decay ladder on the pre-consume watch index.</summary>
int PrepCoinsFace(string pointId, string day)
{

```

```
var row = AdPointFunnel.Row(pointId);
if (row == null) return 0;
int watchIdxNext = _adCap.UsedCategoryToday(day,
    Sy.Platform.AdCategories.CategoryOfPoint(AdPointFunnel.AdPointId(pointId))) + 1;
return Mathf.RoundToInt(row.coins * AdPointFunnel.GainMul(pointId, watchIdxNext));
}
async void OnPrepTalentRequested()
{
    if (!_prepTalentLive) return;
    _prepTalentLive = false;
    _view.HidePrepTalentOffer();
    await GrantPrepWatch(StartTalentPointId);
}
async void OnPrepTrialRequested()
{
    if (!_prepTrialLive) return;
    _prepTrialLive = false;
    _view.HidePrepTrialOffer();
    await GrantPrepWatch(WeaponTrialPointId);
}
async System.Threading.Tasks.Task GrantPrepWatch(string pointId)
{
    string day = Sy.Platform.AdCapPolicy.TodayKey();
    if (Sy.Core.ServiceLocator.TryGet<Sy.Platform.IAdsService>(out var ads))
    {
        // Channel ad path (mock in Editor): the suite consumes the shared
        // policy inside ShowRewarded - the same instance _adCap holds.
        var result = await ads.ShowRewarded(AdPointFunnel.AdPointId(pointId));
        if (!result.Completed)
        {
            AdPointFunnel.Track(_telemetry, "ad_fail", pointId, _sim.Wave, result.Reason);
            return;
        }
    }
    else if (!AdPointFunnel.TryConsume(pointId, day, _adCap))
    {
        // Degraded session (no boot): the daily-cap blocked face, never retried.
        AdPointFunnel.Track(_telemetry, "blocked", pointId, _sim.Wave, "daily_cap");
        return;
    }
    // Gain ladder rides the same-day watch index - UsedCategoryToday
    // already counts this watch after the consume (watch 1 = 1.0 full).
    int watchIdx = _adCap.UsedCategoryToday(day,
        Sy.Platform.AdCategories.CategoryOfPoint(AdPointFunnel.AdPointId(pointId)));
    var row = AdPointFunnel.Row(pointId);
    int bonus = row != null ? Mathf.RoundToInt(row.coins * AdPointFunnel.GainMul(pointId, watchIdx)) : 0;
    if (bonus > 0)
    {
        NewbieSession.WalletCoins += bonus;
        NewbieSession.WriteToSave(); // crash-safe (T019 pattern)
    }
}
```

```

        _view.PlayPrepCoinsFlash(bonus);
    }
    AdPointFunnel.Track(_telemetry, "complete", pointId, _sim.Wave, null);
}
// —— T020 slice 3b: post-run interstitial ($ interstitial row) ——
// <summary>uiStyle post_run (the Won settle face since 3b-1; the death face
// since 3b-2 fires at the terminal close - the shield-held run defers it
// to the nav exit). The site owns the first-5-runs exemption (L121) so the
// suite's cooldown consume never fires for exempt runs; the suite consumes
// the 180s cooldown + cap internally (Mock/Wx/Douyin parity - never a
// second consume here), the degraded session rides the funnel face.</summary>
void MaybeFirePostRunInterstitial(int runIdx)
{
    int exempt = AdPointFunnel.Row(InterstitialPointId)?.gate?.firstRunsExempt ?? 0;
    if (exempt > 0 && runIdx < exempt) return; // 5
    if (Sy.Core.ServiceLocator.TryGet<Sy.Platform.IAdsService>(out var ads))
        ads.ShowInterstitial(AdPointFunnel.AdPointId(InterstitialPointId));
    else
        AdPointFunnel.InterstitialAllowed(runIdx, Sy.Platform.AdCapPolicy.TodayKey(),
            Time.realtimeSinceStartup, _adCap);
}
// —— T021b: settle-face report-card share (red line 11 share moment) ——
// <summary>Won is the one legal ReadPixels stall point (P02 law): compose
// the T021a report card from the closing run's stats; only a clean card
// raises the share button (no card = no dead-end button, P02 paradigm).
// Teaching-run zero-popup red line holds: this is the post-run face.</summary>
void ComposeReportCard()
{
    _reportSpec = ReportCardSpecs.FromStats(NewbieSession.RunCount, _sim.Wave,
        _sim.Kills, _sim.BossCaptures, NewbieSession.TalentState.CodexCollected.Count);
    // T021c-i: ride the build snapshot in the share query (point-card
    // import payload; the receive side parses it back out - T021c-ii).
    // Unmapped picks export NO fragment (honest absence).
    string bd = BuildSnapshotCodec.ExportQuery(_sim.BuildPickIds);
    if (bd.Length > 0) _reportSpec.Query = _reportSpec.Query + "&" + bd;
    _reportCard = new Sy.Social.ShareCardService().Compose(_reportSpec);
    if (_reportCard != null && _reportCard.Ok) _view.ShowShareOffer();
}
void OnShareRequested()
{
    _view.HideShareOffer();
    // Full three-stage funnel (share_call -> share_ok -> share_return
    // over the local save face); a "" refusal is impossible for a
    // visible button - ComposeReportCard gated it on compose Ok.
    ShareService.CallShare(_reportSpec, _reportCard, _telemetry);
}
// T022-iii: the settle-face friend board entry - ranked rows come
// from the open-data face (mock = save-derived pseudo friends until
// T022-iv); one open = one evt_friend_board funnel beat (K-goal
// instrument: face=settle + the rank/kills the player saw).

```

```

        public SubscribeGrantRow[] subscribeGrants = new SubscribeGrantRow[0];    // T022-ii: one row per type
    }
    /// <summary>
    /// T022-ii: the one-shot subscribe grant ledger row (local save face, red
    /// line 12 - zero server). One row per subscribeId: the day-scoped request
    /// counter drives the 1-type/day anti-nuisance gate (an asked-but-denied
    /// day still burns it); grantedCount accumulates verified grants only.
    /// </summary>
    [Serializable]
    public class SubscribeGrantRow
    {
        public string subscribeId;
        public int lastRequestDay;    // DayState.DayIndex scope; a new day reopens the gate
        public int requestCount;    // asks fired on lastRequestDay
        public int grantedCount;    // verified grants (mock local face / slice-iv device)
    }
}
// ShareService.cs
using System.Collections.Generic;
namespace Sy.P01.Newbie
{
    /// <summary>
    /// T021b: the three-stage share funnel over the platform bridge. The share
    /// button never dead-ends: the host only raises it after a report card
    /// composed clean, so a visible tap always completes the funnel. The share
    /// return lands on the LOCAL save face (red line 12: zero server - the
    /// shared counter persists in the local slot exactly like every other
    /// out-of-run beat).
    /// share_call = the player tapped share (intent, before the bridge).
    /// share_ok = the platform share surface accepted the payload.
    /// share_return = control came back to this process; the local save
    /// write completes and the counter persists.
    /// </summary>
    public static class ShareService
    {
        public const string StageCall = "share_call";
        public const string StageOk = "share_ok";
        public const string StageReturn = "share_return";
        public static bool IsReady => true;
        /// <summary>One tap = the full funnel. Returns the last fired stage;
        /// "" = honest refusal (null/not-ok inputs, or no platform service) -
        /// the caller hides the button in exactly those states, so a visible
        /// button always completes the funnel (no dead ends).</summary>
        public static string CallShare(Sy.Social.ShareCard spec,
            Sy.Social.ComposeResult card,
            Sy.Telemetry.TelemetryService telemetry)
        {
            if (spec == null || card == null || !card.Ok) return "";
            if (!Sy.Core.ServiceLocator.TryGet<Sy.Platform.IPlatformService>(out var platform))
                return "";

```

```

        Track(telemetry, StageCall);
        platform.Share(new Sy.Platform.SharePayload
        {
            Title = spec.Title,
            ImageUrl = card.Path,
            Query = spec.Query,
        });
        Track(telemetry, StageOk);
        // The return beat: the platform sheet closes, control lands back
        // in this process, and the only state change is the local save
        // write (the share return IS a save face - no server round trip).
        NewbieSession.RecordShareReturn();
        Track(telemetry, StageReturn);
        return StageReturn;
    }
    static void Track(Sy.Telemetry.TelemetryService telemetry, string stage)
    {
        if (telemetry == null) return;
        telemetry.Track(Sy.Telemetry.EventIds.Share,
            new Dictionary<string, string> { { "stage", stage } });
    }
}

// SpatialHashGrid.cs
using System;
using System.Collections.Generic;
namespace Sy.P01.Newbie
{
    /// <summary>
    /// Uniform spatial hash grid for same-screen 300-500 enemy collision queries (T008:
    /// spatial hash grid + pure-math circle tests, no Physics2D). Cell size = 2 x contact
    /// range so any circle query spans at most a 3x3 cell block.
    /// Rebuilt from the live ghost list once per tick after movement, before the collision
    /// phases. Pooled per-cell lists keep the steady state allocation-free (T013 GC face).
    /// QueryCircle applies the exact squared-distance test after the cell gather, so its
    /// result set is identical to a linear scan - the tutorial Flow baseline holds.
    /// </summary>
    public sealed class SpatialHashGrid
    {
        readonly float _minX;
        readonly float _minY;
        readonly float _cellSize;
        readonly int _cols;
        readonly int _rows;
        readonly List<BattleSim.GhostInst>[] _cells;
        public SpatialHashGrid(float minX, float maxX, float minY, float maxY, float cellSize)
        {
            _minX = minX;
            _minY = minY;
            _cellSize = Math.Max(1f, cellSize);
        }
    }
}

```

```

        _cols = Math.Max(1, (int)Math.Ceiling((maxX - minX) / _cellSize));
        _rows = Math.Max(1, (int)Math.Ceiling((maxY - minY) / _cellSize));
        _cells = new List<BattleSim.GhostInst>[_cols * _rows];
        for (int i = 0; i < _cells.Length; i++) _cells[i] = new List<BattleSim.GhostInst>(16);
    }
    int ColOf(float x)
    {
        int c = (int)((x - _minX) / _cellSize);
        return c &lt; 0 ? 0 : (c &gt;= _cols ? _cols - 1 : c);
    }
    int RowOf(float y)
    {
        int r = (int)((y - _minY) / _cellSize);
        return r &lt; 0 ? 0 : (r &gt;= _rows ? _rows - 1 : r);
    }
    public void Clear()
    {
        for (int i = 0; i < _cells.Length; i++) _cells[i].Clear();
    }
    public void Insert(BattleSim.GhostInst g)
    {
        _cells[RowOf(g.Y) * _cols + ColOf(g.X)].Add(g);
    }
    /// <summary>O(n) rebuild from the live list; zero allocations after warmup.</summary>
    public void Rebuild(IReadOnlyList<BattleSim.GhostInst> ghosts)
    {
        Clear();
        for (int i = 0; i < ghosts.Count; i++) Insert(ghosts[i]);
    }
    /// <summary>Collects ghosts within radius of (x, y) into the caller-owned buffer.</summary>
    public void QueryCircle(float x, float y, float radius, List<BattleSim.GhostInst> buffer)
    {
        buffer.Clear();
        float r2 = radius * radius;
        int c0 = ColOf(x - radius), c1 = ColOf(x + radius);
        int r0 = RowOf(y - radius), r1 = RowOf(y + radius);
        for (int r = r0; r <= r1; r++)
        {
            int rowBase = r * _cols;
            for (int c = c0; c <= c1; c++)
            {
                var cell = _cells[rowBase + c];
                for (int i = 0; i < cell.Count; i++)
                {
                    var g = cell[i];
                    float dx = g.X - x, dy = g.Y - y;
                    if (dx * dx + dy * dy <= r2) buffer.Add(g);
                }
            }
        }
    }
}

```

```
    }
}
}
// SubscribeService.cs
using System;
using System.Collections.Generic;
namespace Sy.P01.Newbie
{
    /// <summary>Ask outcome for one subscribe request face call.</summary>
    public enum SubscribeOutcome
    {
        /// <summary>The player granted the one-shot subscribe request.</summary>
        Granted,
        /// <summary>The ask fired but was not granted (player denied / unverified
        /// device result) - the ask still counts against the daily cap.</summary>
        Denied,
        /// <summary>No ask ever reached the player (daily gate block, or the
        /// platform face refused pre-dialog) - zero events, zero ledger burn.</summary>
        NotAsked,
        /// <summary>The subscribeId is not in cfg_subscribe (fail loud, no
        /// fabricated asks - the data layer is the only type authority).</summary>
        UnknownType
    }
    /// <summary>
    /// T022-ii: the subscribe request face swap point (T001c paradigm). The
    /// local mock face is authoritative until the real account-side WX template
    /// ids arrive (U014); the armed-build WX face swaps in without touching
    /// callers. Zero shared-package changes by design (P02/P06 pending-review
    /// byte stability, X236 law).
    /// </summary>
    public interface ISubscribeFace
    {
        /// <summary>Fire the ask for one cfg_subscribe row. NotAsked = the face
        /// never asked (placeholder template ids refuse with zero device calls).
        /// onDeviceResult = the T022-iv-B result channel: an armed async face
        /// may deliver the verified device grant later (true) - the grant only
        /// ever lands through that callback, never the sync return. Faces
        /// without a device result (mock faces grant synchronously) never
        /// touch it.</summary>
        SubscribeOutcome Request(P01Configs.SubscribeRow row, Action<bool> onDeviceResult);
    }
    /// <summary>
    /// T022-ii: the one-shot subscribe request service, four cfg-driven faces
    /// (codex_new_ghost / endless_record / share_return / night_ready per D008).
    /// Red line 12: zero server - the grant ledger lives in the LOCAL save slot
    /// exactly like the share-return beat (the ask IS a save face). The
    /// anti-nuisance gate = 1 request per type per day (cfg requestCapPerDay,
    /// R38a-pinned); an asked-but-denied day still burns the gate.
    /// Funnel: evt_subscribe stage=request (the ask fired) then stage=granted
    /// (verified grant only). Gate-blocked and pre-dialog refusals fire zero
```

```

/// events (the player was never asked).
/// &lt;/summary&gt;
public static class SubscribeService
{
    public const string EventId = "evt_subscribe";
    public const string StageRequest = "request";
    public const string StageGranted = "granted";
    /// &lt;/summary&gt;Placeholder template-id prefix (cfg swap face): ids with
    /// this prefix are not real console ids and never reach the device.&lt;/summary&gt;
    public const string PlaceholderPrefix = "placeholder_tmpl_";
    // The four live cfg_subscribe ids (D008; stamina_full stays a reserved
    // object - no trigger source may be fabricated for it).
    public const string CodexNewGhost = "codex_new_ghost";
    public const string EndlessRecord = "endless_record";
    public const string ShareReturn = "share_return";
    public const string NightReady = "night_ready";
    static ISubscribeFace _faceOverride;
    /// &lt;/summary&gt;Editor/gate injection point; also the channel-suite seam
    /// for future platform wiring (MockLaunchInfo paradigm).&lt;/summary&gt;
    public static void SetFace(ISubscribeFace face) { _faceOverride = face; }
    /// &lt;/summary&gt;The active ask face: gate override first, then the channel
    /// default (armed WX builds swap the real face in, X129 law).&lt;/summary&gt;
    public static ISubscribeFace Face =&gt; _faceOverride ?? DefaultFaceFactory.Create();
    /// &lt;/summary&gt;One ask for one cfg_subscribe type. The full chain: type
    /// lookup -&gt; daily gate -&gt; face ask -&gt; ledger write (local save) -&gt;
    /// funnel events. Never dead-ends: every call returns a definite
    /// outcome and the caller can always surface it.&lt;/summary&gt;
    public static SubscribeOutcome Subscribe(string subscribeId,
        Sy.Telemetry.TelemetryService telemetry)
    {
        var row = FindRow(subscribeId);
        if (row == null) return SubscribeOutcome.UnknownType;
        int day = NewbieSession.DayState.DayIndex;
        int cap = row.requestCapPerDay &gt; 0 ? row.requestCapPerDay : 1;
        SubscribeGrantRow grant = null;
        for (int i = 0; i &lt; NewbieSession.SubscribeGrants.Count; i++)
        {
            var g = NewbieSession.SubscribeGrants[i];
            if (g != null &amp;&amp; g.subscribeId == subscribeId) { grant = g; break; }
        }
        if (grant != null &amp;&amp; grant.lastRequestDay == day &amp;&amp; grant.requestCount &gt;= cap)
            return SubscribeOutcome.NotAsked; // daily gate: silent block
        var outcome = Face.Request(row, granted =&gt; RecordDeviceGrant(row, granted, telemetry));
        if (outcome == SubscribeOutcome.NotAsked)
            return SubscribeOutcome.NotAsked; // pre-dialog refusal: no ledger burn
        Track(telemetry, StageRequest, row);
        if (grant == null)
        {
            grant = new SubscribeGrantRow { subscribeId = subscribeId };
            NewbieSession.SubscribeGrants.Add(grant);
        }
    }
}

```

```

    }
    if (grant.lastRequestDay != day)
    {
        grant.lastRequestDay = day;    // new day: the counter reopens
        grant.requestCount = 0;
    }
    grant.requestCount++;
    if (outcome == SubscribeOutcome.Granted) grant.grantedCount++;
    NewbieSession.WriteToSave();    // the ask beat is a save face (share-return law)
    if (outcome == SubscribeOutcome.Granted)
        Track(telemetry, StageGranted, row);
    return outcome;
}

// — The four request faces (cfg_subscribe trigger.source documents the
// may-ask moments: RegisterCodexCapture / BeginEndlessRun /
// RecordShareReturn / ChainRewardClaimed - the hosts call the face
// matching their beat when the ask-moment UI lands). —
public static SubscribeOutcome RequestCodexNewGhost(Sy.Telemetry.TelemetryService telemetry)
    => Subscribe(CodexNewGhost, telemetry);
public static SubscribeOutcome RequestEndlessRecord(Sy.Telemetry.TelemetryService telemetry)
    => Subscribe(EndlessRecord, telemetry);
public static SubscribeOutcome RequestShareReturn(Sy.Telemetry.TelemetryService telemetry)
    => Subscribe(ShareReturn, telemetry);
public static SubscribeOutcome RequestNightReady(Sy.Telemetry.TelemetryService telemetry)
    => Subscribe(NightReady, telemetry);

/// <summary>cfg row lookup or null (the data layer is the only type
/// authority - unknown ids fail loud, nothing is fabricated).</summary>
public static P01Configs.SubscribeRow FindRow(string subscribeId)
{
    var table = P01Configs.Subscribe;
    if (table == null || table.types == null) return null;
    foreach (var t in table.types)
        if (t != null && t.subscribeId == subscribeId) return t;
    return null;
}

/// <summary>T022-iv-B: the device result channel's grant landing (the
/// armed WX real-id era). The sync face returns Denied as the honest
/// pending outcome; this lands later, only on a verified device grant:
/// grantedCount bumps, the granted funnel event fires and the ledger
/// re-saves through the same local slot. A denied device result lands
/// nothing (the ask already burned as Denied on the sync path).</summary>
static void RecordDeviceGrant(P01Configs.SubscribeRow row, bool granted,
    Sy.Telemetry.TelemetryService telemetry)
{
    if (!granted) return;
    var grant = FindGrantRow(row.subscribeId);
    if (grant == null) return;    // nothing was ever asked - never fabricate
    grant.grantedCount++;
    NewbieSession.WriteToSave();
    Track(telemetry, StageGranted, row);
}

```

```

    }
    /// <summary>The ledger row for one subscribe id, or null (device-result
    /// grants only ever land on a row the ask beat already wrote).</summary>
    public static SubscribeGrantRow FindGrantRow(string subscribeId)
    {
        for (int i = 0; i < NewbieSession.SubscribeGrants.Count; i++)
        {
            var g = NewbieSession.SubscribeGrants[i];
            if (g != null && g.subscribeId == subscribeId) return g;
        }
        return null;
    }
    static void Track(Sy.Telemetry.TelemetryService telemetry, string stage,
        P01Configs.SubscribeRow row)
    {
        if (telemetry == null) return;
        telemetry.Track(EventId, new Dictionary<string, string>
        {
            { "stage", stage },
            { "subscribeId", row.subscribeId },
            { "category", row.@class },
        });
    }
}
/// <summary>
/// The local authoritative ask face (Mock law, T001c): simulates the player
/// granting the request. Editor, batchmode gates and SY MOCK builds run on
/// this face until the real account-side template ids arrive (U014).
/// </summary>
public sealed class MockSubscribeFace : ISubscribeFace
{
    public SubscribeOutcome Request(P01Configs.SubscribeRow row, Action<bool> onDeviceResult)
        => SubscribeOutcome.Granted; // sync local grant - no device result to deliver
}
/// <summary>Channel default resolution (X129 law: the WX DllImport surface
/// only exists on armed weixin builds; everything else = local face).</summary>
static class DefaultFaceFactory
{
#if SY_WECHAT
    public static ISubscribeFace Create() => new WxSubscribeFace();
#else
    public static ISubscribeFace Create() => new MockSubscribeFace();
#endif
}
}
// TalentLauncher.cs
using System.Collections.Generic;
using UnityEngine;
namespace Sy.P01.Newbie
{

```

```
/// &lt;summary&gt;
/// T018 slice 3: S01 out-of-run talent/codex host (pitch s3). Hosted by MainUI
/// at Awake AFTER the DayLauncher (AddComponent pattern - no scene YAML
/// churn; later sibling = the entry button renders above the day panel).
/// Owns the hub face of the talent tree: the pinned TalentSim session buys
/// points (wallet mirror deducts; the host reads SpendCoins back so the
/// session books stay authoritative - DaySim precedent), the branch/codex
/// panel displays the collection. The chain claim verb is NOT here: the
/// won-night settle auto-claims (NewbieSession.DepositNight), this panel
/// makes the grant visible. Funnel telemetry rides evt_talent_layer
/// (open/buy/deny/close + day).
/// T035 slice 6 (X2099): every visible label resolves through UiText -&gt;
/// cfg_i18n (the shipped table copy is the only place CJK lives).
/// &lt;/summary&gt;
public sealed class TalentLauncher : MonoBehaviour
{
    TalentSim _sim;
    TalentView _view;
    Sy.Telemetry.TelemetryService _telemetry;
    void Awake()
    {
        var canvas = FindObjectOfType<Canvas>();
        _sim = NewbieSession.TalentSimToday;
        _view = gameObject.AddComponent<TalentView>();
        _view.Initialize(canvas);
        _telemetry = new Sy.Telemetry.TelemetryService();
        _telemetry.AddSink(new TelemetryDebugSink());
        _view.OpenRequested += OnOpenRequested;
        _view.BuyRequested += OnBuyRequested;
        _view.CloseRequested += OnCloseRequested;
        _view.CodexPageRequested += OnCodexPageRequested;
        _view.TalentPageRequested += OnTalentPageRequested;
        _sim.PointBought += OnPointBought;
        _sim.BuyDenied += OnBuyDenied;
    }
    void OnOpenRequested()
    {
        RefreshPanel();
        Track("open");
    }
    void OnTalentPageRequested()
    {
        RefreshPanel();
        Track("page", "talent");
    }
    void OnCodexPageRequested()
    {
        RefreshCodexPanel();
        Track("page", "codex");
    }
}
```

```

void RefreshPanel()
{
    var branches = BuildBranchFaces();
    _view.ShowTalent(NewbieSession.TalentState.DayIndex, NewbieSession.WalletCoins,
        branches, _sim.NextPointCost(), ChainStatus(), NewbieSession.TalentState.WeekClaimed);
}
/// &summaryT019 slice 3: the codex page refresh - the roster from cfg_enemy
/// (row order = bookSlot order), lit per the session collection, the live
/// global bonus from CollectionBook (the panel never re-derives it).&summary
void RefreshCodexPanel()
{
    var faces = BuildCodexFaces();
    int count = NewbieSession.TalentState.CodexCollected.Count;
    var coll = P01Configs.Collection;
    int total = coll != null && coll.collection != null ? coll.collection.firstVersionCount : 10;
    _view.ShowCodex(NewbieSession.TalentState.DayIndex, NewbieSession.WalletCoins, faces,
        count, total, Newbie.CollectionBook.GlobalPctFor(count), ChainStatus());
}
TalentView.CodexSlotFace[] BuildCodexFaces()
{
    var enemy = P01Configs.Enemy;
    var rows = enemy != null && enemy.templates != null ? enemy.templates : null;
    var faces = new TalentView.CodexSlotFace[rows != null ? rows.Length : 0];
    for (int i = 0; i < faces.Length; i++)
    {
        var t = rows[i];
        faces[i] = new TalentView.CodexSlotFace
        {
            CodeName = t.codeName,
            NameCn = SpeciesNameCn(t.enemyId),
            Collected = NewbieSession.TalentState.CodexCollected.Contains(t.enemyId),
        };
    }
    return faces;
}
// T035 slice 6: the first-version CN display names moved to the loc table
// keyed by enemy id (talent_codex_&id); cfg_enemy carries nameKey loc ids
// and the nameKey face lands with the codex art batch (T026). Unknown ids
// keep the raw id (the TryGetValue-miss kin; a table miss returns the key).
static string SpeciesNameCn(string enemyId)
{
    string key = "talent_codex_" + enemyId;
    string name = UiText.Get(key);
    return name != key ? name : enemyId;
}
void OnBuyRequested(string branchId)
{
    var reason = _sim.BuyPoint(branchId);
    if (reason != TalentSim.BuyDenyReason.None) Track("deny", reason.ToString());
}

```

```
void OnPointBought(string branchId, int newPoints, int cost)
{
    // Host books stay authoritative: deduct the talent session's spend counter.
    NewbieSession.SpendFromTalent(_sim.SpendCoins);
    NewbieSession.WriteToSave(); // T019 slice 2: the buy persists immediately
    RefreshPanel();
    _view.PlayBuyFlash(BranchName(branchId));
    Track("buy", branchId);
}

void OnBuyDenied(TalentSim.BuyDenyReason reason)
{
    switch (reason)
    {
        case TalentSim.BuyDenyReason.BranchNotFound:
            _view.SetHint(UiText.Get("talent_deny_branch"));
            break;
        case TalentSim.BuyDenyReason.BranchFull:
            _view.SetHint(UiText.Get("talent_deny_full"));
            break;
        case TalentSim.BuyDenyReason.DailyCapReached:
            _view.SetHint(UiText.Get("talent_deny_cap"));
            break;
        case TalentSim.BuyDenyReason.NotEnoughCoins:
            _view.SetHint(UiText.Get("talent_deny_coins_fmt", _sim.NextPointCost().ToString()));
            break;
        default:
            _view.SetHint(UiText.Get("talent_deny_closed"));
            break;
    }
}

void OnCloseRequested()
{
    _view.Hide();
    Track("close");
}

TalentView.BranchFace[] BuildBranchFaces()
{
    var cfg = P01Configs.Talent;
    var rows = cfg != null && cfg.tree != null && cfg.tree.branches != null ? cfg.tree.branches : 0;
    var faces = new TalentView.BranchFace[rows != null ? rows.Length : 0];
    for (int i = 0; i < faces.Length; i++)
    {
        var b = rows[i];
        faces[i] = new TalentView.BranchFace
        {
            Id = b.branchId,
            Name = b.name,
            Points = NewbieSession.TalentState.PointsIn(b.branchId),
            Max = b.points,
            NextMilestoneDesc = NextMilestoneDesc(b),
        };
    }
}
```

```

        };
    }
    return faces;
}

static string NextMilestoneDesc(P01Configs.TalentBranchRow branch)
{
    if (branch.milestones == null || branch.milestones.Length == 0) return "";
    int pts = NewbieSession.TalentState.PointsIn(branch.branchId);
    for (int i = 0; i < branch.milestones.Length; i++)
        if (branch.milestones[i].atPoints > pts)
            return UiText.Get("talent_next_node_fmt", branch.milestones[i].atPoints.ToString(),
                               branch.milestones[i].desc);
    return UiText.Get("talent_branch_full");
}

string ChainStatus()
{
    var row = _sim.ChainDayToday();
    if (row == null || row.rewards == null)
    {
        int collected = NewbieSession.TalentState.CodexCollected.Count;
        return UiText.Get("talent_chain_done_fmt", collected.ToString());
    }
    return UiText.Get("talent_chain_active_fmt", row.dayIndex.ToString(), row.rewards.enemyId,
                     row.rewards.coins.ToString());
}

static string BranchName(string branchId)
{
    var cfg = P01Configs.Talent;
    var rows = cfg != null && cfg.tree != null && cfg.tree.branches != null ? cfg.tree.branches : null;
    if (rows == null) return branchId;
    for (int i = 0; i < rows.Length; i++)
        if (rows[i].branchId == branchId) return rows[i].name;
    return branchId;
}

void Track(string state, string detail = null)
{
    // T024-ii: delegated to the shared seam (LauncherTelemetry) so the
    // marathon gate rides the exact same field construction; zero
    // behavior change here - same fields, same id, same order.
    LauncherTelemetry.TrackTalent(_telemetry, state, detail, NewbieSession.TalentState.DayIndex);
}

sealed class TelemetryDebugSink : Sy.Telemetry.TelemetryService.ISink
{
    public void Write(string evtId, Dictionary<string, string> fields)
    {
        var sb = new System.Text.StringBuilder(evtId);
        foreach (var kv in fields) sb.Append(' ').Append(kv.Key).Append('=').Append(kv.Value);
        Debug.Log("[TELEMETRY] " + sb);
    }
}

```

```

    }
}
// TalentSim.cs
using System;
using System.Collections.Generic;
namespace Sy.P01.Newbie
{
    /// <summary>
    /// T018 slice 2b: the out-of-run talent session state machine (pure C#, zero
    /// rendering, zero rng, zero server - deterministic by construction, red line
    /// 12 safe). Two faces over cfg_talent:
    /// (a) the 30-point tree - buy ONE point per day (dailyBuyCap=1, the pace gate
    /// independent of coins) at the GLOBAL curve cost 55n+45 where n is the
    /// global point index (P1=100 -> P30=1695, total 26,925 <= the 30,000 no-ads
    /// D30 disposable = the 30-day closure); progression is linear inside a
    /// branch, no cross-branch gates (free orthogonal builds);
    /// (b) the seven-day codex chain - each session day D1-D7 the host reports won
    /// nights; one claim per day grants that day's codex ghost (slot = dayIndex,
    /// roster order) + chain coins 20..80 (total 350 <= the 1,075 economy buffer
    /// - a retention hook, never an income pillar).
    /// The wallet mirrors the host-injected coin snapshot; the host reads the spend
    /// and gain counters back and owns the authoritative books (DaySim precedent).
    /// BattleSim is untouched by construction, so the Flow baseline has zero drift
    /// surface. The talent/codex UI + session wiring land in slice 3.
    /// Authoring authority = Design/configs/P01/cfg_talent.json (05 s3 + s8).
    /// </summary>
    public sealed class TalentSim
    {
        public enum BuyDenyReason
        {
            None = 0,
            BranchNotFound,
            BranchFull,
            DailyCapReached,
            NotEnoughCoins
        }
        public enum ChainDenyReason
        {
            None = 0,
            NotInChainWindow,
            TaskIncomplete,
            AlreadyClaimed
        }
        readonly TalentState _state;
        readonly P01Configs.TalentTableFile _cfg;
        public TalentSim(TalentState state, P01Configs.TalentTableFile cfg, int coins)
        {
            _state = state ?? new TalentState();
            _cfg = cfg;
            WalletCoins = coins;
        }
    }
}

```

```

    }
    // Wallet mirror + host readback counters.
    public int WalletCoins { get; private set; }
    public int SpendCoins { get; private set; }
    public int ChainCoinsGained { get; private set; }
    P01Configs.TalentCostCurveBlock Curve
    {
        get { return _cfg != null && _cfg.tree != null ? _cfg.tree.costCurve : null; }
    }
    public event Action<string, int, int> PointBought;           // (branchId, newPointsInBranch, cost)
    public event Action<BuyDenyReason> BuyDenied;
    public event Action<int> NightWinReported;                 // (winsToday)
    public event Action<int, string, int, int> ChainRewardClaimed; // (dayIndex, enemyId, coins, codexSlot)
    public event Action<ChainDenyReason> ChainClaimDenied;
    /// <summary>Global curve cost of the next point: 55n+45 with n = global point
    /// index 1..30 (P1=100, P30=1695; R27 pins the recomputed sum 26,925).</summary>
    public int NextPointCost()
    {
        var curve = Curve;
        if (curve == null) return int.MaxValue;
        return curve.slopePerPoint * (_state.TotalPoints + 1) + curve.baseOffset;
    }
    /// <summary>Buy one point in a branch (linear in-branch progression: the next
    /// point is always current points + 1). Deny precedence: branch not found ->
    /// branch full -> daily cap -> not enough coins (checked in this order).</summary>
    public BuyDenyReason BuyPoint(string branchId)
    {
        _state.EnsureDay();
        var branch = FindBranch(branchId);
        if (branch == null) return DenyBuy(BuyDenyReason.BranchNotFound);
        int inBranch = _state.PointsIn(branchId);
        if (inBranch >= branch.points) return DenyBuy(BuyDenyReason.BranchFull);
        var curve = Curve;
        if (curve != null && _state.BuysToday >= curve.dailyBuyCap)
            return DenyBuy(BuyDenyReason.DailyCapReached);
        int cost = NextPointCost();
        if (WalletCoins < cost) return DenyBuy(BuyDenyReason.NotEnoughCoins);
        WalletCoins -= cost;
        SpendCoins += cost;
        _state.BuysToday++;
        _state.AddPoint(branchId);
        PointBought?.Invoke(branchId, inBranch + 1, cost);
        return BuyDenyReason.None;
    }
    /// <summary>Host reports a won night (the chain verb: win 1 night/day).</summary>
    public void ReportNightWin()
    {
        _state.EnsureDay();
        _state.NightWinsToday++;
        NightWinReported?.Invoke(_state.NightWinsToday);
    }

```

```

    }
    /// <summary>Today's chain row (null outside the D1-D7 window or table missing).</summary>
    public P01Configs.WeekChainDayRow ChainDayToday()
    {
        if (_cfg == null || _cfg.weekChain == null || _cfg.weekChain.days == null) return null;
        var days = _cfg.weekChain.days;
        int d = _state.DayIndex;
        for (int i = 0; i < days.Length; i++)
            if (days[i].dayIndex == d) return days[i];
        return null;
    }
    /// <summary>Claim today's chain reward once the day's win requirement holds:
    /// grants the codex ghost (slot = dayIndex, roster order) + chain coins into
    /// the wallet. Deny precedence: outside window -> already claimed -> task not
    /// complete yet.</summary>
    public ChainDenyReason ClaimChainDay()
    {
        _state.EnsureDay();
        var row = ChainDayToday();
        if (row == null) return DenyChain(ChainDenyReason.NotInChainWindow);
        int slot = _state.DayIndex - 1;
        if (slot >= 0 && slot < _state.WeekClaimed.Length && _state.WeekClaimed[slot])
            return DenyChain(ChainDenyReason.AlreadyClaimed);
        int need = row.require != null ? row.require.winNights : 1;
        if (_state.NightWinsToday < need) return DenyChain(ChainDenyReason.TaskIncomplete);
        if (slot >= 0 && slot < _state.WeekClaimed.Length) _state.WeekClaimed[slot] = true;
        int coins = row.rewards != null ? row.rewards.coins : 0;
        string enemyId = row.rewards != null ? row.rewards.enemyId : null;
        int codexSlot = row.rewards != null ? row.rewards.codexSlot : 0;
        WalletCoins += coins;
        ChainCoinsGained += coins;
        // T019 slice 3: dedupe against the capture suspender - a species the
        // player already capture-registered never double-counts when its chain
        // day arrives (belt + suspenders, one entry per species).
        if (!string.IsNullOrEmpty(enemyId) && !_state.CodexCollected.Contains(enemyId))
            _state.CodexCollected.Add(enemyId);
        ChainRewardClaimed?.Invoke(_state.DayIndex, enemyId, coins, codexSlot);
        return ChainDenyReason.None;
    }
    // — derived stat face: the host reads these when wiring the in-run effects
    // (BattleSim consumption lands with a later slice; nothing there changes now).
    P01Configs.TalentBranchRow FindBranch(string branchId)
    {
        if (_cfg == null || _cfg.tree == null || _cfg.tree.branches == null) return null;
        var branches = _cfg.tree.branches;
        for (int i = 0; i < branches.Length; i++)
            if (branches[i].branchId == branchId) return branches[i];
        return null;
    }
    P01Configs.TalentPerPointBlock PerPointOf(string branchId)

```

```

{
    var b = FindBranch(branchId);
    return b != null ? b.perPoint : null;
}
/// <summary>Aggregated per-point attack bonus (soul: +2%/pt, full +20%).</summary>
public float AtkPct
{
    get
    {
        var pp = PerPointOf("soul");
        return pp != null ? pp.atkPct * _state.SoulPoints : 0f;
    }
}
/// <summary>Multiplicative skill-CD multiplier (rune: 0.97^pts, ~26% full).</summary>
public double SkillCdMul
{
    get
    {
        var pp = PerPointOf("rune");
        return pp != null ? Math.Pow(1.0 + pp.cdPct, _state.RunePoints) : 1.0;
    }
}
/// <summary>Aggregated per-point HP bonus (body: +3%/pt, full +30%).</summary>
public float HpPct
{
    get
    {
        var pp = PerPointOf("body");
        return pp != null ? pp.hpPct * _state.BodyPoints : 0f;
    }
}
/// <summary>Milestone lookup: the branch milestone's effect-field value once
/// branch points reach atPoints (each field is unique per branch, so the
/// highest unlocked milestone carrying a non-zero value wins; 0 when none).</summary>
float Milestone(string branchId, Func<P01Configs.TalentMilestoneEffectBlock, float> field)
{
    var b = FindBranch(branchId);
    if (b == null || b.milestones == null) return 0f;
    int pts = _state.PointsIn(branchId);
    float v = 0f;
    for (int i = 0; i < b.milestones.Length; i++)
    {
        var m = b.milestones[i];
        if (m == null || m.effect == null || m.atPoints > pts) continue;
        float fv = field(m.effect);
        if (fv != 0f) v = fv;
    }
    return v;
}
public float KillSoulRegenPerSec { get { return Milestone("soul", e => e.killSoulRegenPerSec); } }

```

```

    public float SoulFireFamilyDmgPct { get { return Milestone("soul", e => e.soulFireFamilyDmgPct); } }
    public int InRunRerollCharges { get { return (int)Milestone("rune", e => e.inRunRerollCharges); } }
    public float EvolveThresholdPct { get { return Milestone("rune", e => e.evolveThresholdPct); } }
    public float MoveSpeedPct { get { return Milestone("body", e => e.moveSpeedPct); } }
    public int ReviveInvulnSec { get { return (int)Milestone("body", e => e.reviveInvulnSec); } }
    public int DeathShieldCharges { get { return (int)Milestone("body", e => e.deathShieldCharges); } }
    BuyDenyReason DenyBuy(BuyDenyReason reason)
    {
        BuyDenied?.Invoke(reason);
        return reason;
    }
    ChainDenyReason DenyChain(ChainDenyReason reason)
    {
        ChainClaimDenied?.Invoke(reason);
        return reason;
    }
}
}
// TalentState.cs
using System.Collections.Generic;
namespace Sy.P01.Newbie
{
    /// <summary>
    /// T018 slice 2b: cross-day persistent state for the out-of-run talent tree and
    /// the seven-day codex chain (pitch s3, 05 s3 + s8). Plain C# POCO, zero
    /// UnityEngine dependency, zero server (red line 12) - the host owns the instance
    /// and the local save face lands with T019, so nothing here serializes yet by
    /// design (DayState precedent).
    /// DayIndex is 1-based and shares the DayState domain (the player's session day).
    /// </summary>
    public sealed class TalentState
    {
        public int DayIndex = 1;
        // Branch points bought (soul/rune/body, 0..10 each per cfg branches[].points).
        public int SoulPoints;
        public int RunePoints;
        public int BodyPoints;
        // Daily buy cap latch (cfg costCurve.dailyBuyCap = 1; resets on day change).
        public int BuysToday;
        public int BuyDayIndex = 1;
        // Night-win counter for the week-chain requirement (win 1 night/day).
        public int NightWinsToday;
        public int WinsDayIndex = 1;
        // Week chain D1-D7 claim latch + the codex collection the chain grants.
        public bool[] WeekClaimed = new bool[7];
        public readonly List<string> CodexCollected = new List<string>();
        public int TotalPoints { get { return SoulPoints + RunePoints + BodyPoints; } }
        public int PointsIn(string branchId)
        {
            switch (branchId)

```

```

        {
            case "soul": return SoulPoints;
            case "rune": return RunePoints;
            case "body": return BodyPoints;
            default: return -1;
        }
    }

    public void AddPoint(string branchId)
    {
        switch (branchId)
        {
            case "soul": SoulPoints++; break;
            case "rune": RunePoints++; break;
            case "body": BodyPoints++; break;
        }
    }

    /// <summary>Day rollover: the host advances DayIndex directly; this syncs the
    /// per-day counters to the current day so caps reset on a new session day.</summary>
    public void EnsureDay()
    {
        if (BuyDayIndex != DayIndex) { BuysToday = 0; BuyDayIndex = DayIndex; }
        if (WinsDayIndex != DayIndex) { NightWinsToday = 0; WinsDayIndex = DayIndex; }
    }
}

// TalentView.cs
using System;
using System.Collections;
using System.Collections.Generic;
using UnityEngine;
using UnityEngine.UI;
namespace Sy.P01.Newbie
{
    /// <summary>
    /// T018 slice 3: the S01 out-of-run talent/codex panel (pitch s3). Pure
    /// programmatic UGUI mirroring the DayView factory style (no scene YAML
    /// churn, no art dependency - headless safe). Violet meta palette to read
    /// as "soul ledger" against the day panel's warm gold. Faces:
    /// - a corner entry button ("talent/codex") always visible in the hub,
    ///   rendered above the day panel (created later in MainUI.Awake order);
    /// - the panel: three branch rows (name/points/next cost + buy button,
    ///   next milestone desc from cfg), the seven codex slots D1-D7, today's
    ///   chain status line, wallet label and a close button;
    /// - T019 slice 3: a codex PAGE inside the same panel (corner switch) - the
    ///   10-species roster grid lighting per the collection + the live global
    ///   bonus progress line (the capture->codex->craft loop's visible face).
    /// The claim verb itself is NOT here: the deposit auto-claims at the won
    /// night's settle (zero-friction retention hook), this panel makes the
    /// collection and the next milestone visible (shareable collection face).
    /// Copy source: task book T018 (talent tree 30 pts / codex slots D1-D7 /

```

```
/// chain win-claim UI) + T019 (CollectionBook codex page) + cfg_talent
/// branches + weekChain days.
/// T035 slice 5 (X2095): every visible label resolves through UiText -&gt;
/// cfg_i18n (talent_* 16 keys; branch row {0}-{3}, codex progress {0}/{1}/{2},
/// day/wallet fmts), rendered byte-identical to the pre-migration literals,
/// so the source file carries zero CJK string literals (I18nLintCheck L4).
/// &lt;/summary&gt;
public sealed class TalentView : MonoBehaviour
{
    /// &lt;/summary&gt;One branch row's display face (built by the launcher from cfg + state).&lt;/summary&gt;
    public struct BranchFace
    {
        public string Id;
        public string Name;
        public string NextMilestoneDesc;
        public int Points;
        public int Max;
    }
    Canvas _canvas;
    Sprite _square;
    RectTransform _panel;
    Text _dayLabel, _walletText, _hintText, _chainText, _titleText, _codexProgressText, _codexBeltText;
    AudioSource _toneSource;
    readonly List<string> _branchIds = new();
    readonly List<Text> _slotTexts = new();
    readonly List<Text> _codexSlotTexts = new();
    // T019 slice 3: page sets inside the one talent/codex panel - the talent page
    // (branch rows + week-chain slots) and the codex page (10-species roster).
    readonly List<GameObject> _talentPageObjects = new();
    readonly List<GameObject> _codexPageObjects = new();
    public event Action OpenRequested;
    public event Action<string> BuyRequested;
    public event Action CloseRequested;
    public event Action CodexPageRequested;
    public event Action TalentPageRequested;
    // Meta palette (violet soul-ledger vs day gold vs battle neon dark).
    static readonly Color Violet = new Color(0.62f, 0.44f, 1f);
    static readonly Color MetaBg = new Color(0.07f, 0.05f, 0.12f, 0.97f);
    static readonly Color CardDim = new Color(0.16f, 0.12f, 0.24f);
    static readonly Color BoneWhite = new Color(0.941f, 0.929f, 0.902f);
    static readonly Color NeonCyan = new Color(0f, 1f, 0.82f);
    public void Initialize(Canvas canvas)
    {
        _canvas = canvas;
        _square = MakeSquareSprite();
        BuildEntryButton();
        BuildTalentPanel();
    }
    void BuildEntryButton()
    {

```

```

var go = new GameObject("TalentEntry", typeof(RectTransform), typeof(Image), typeof(Button));
go.transform.SetParent(_canvas.transform, false);
var rt = (RectTransform)go.transform;
rt.anchorMin = rt.anchorMax = new Vector2(0.5f, 0.5f);
rt.anchoredPosition = new Vector2(390, 850);
rt.sizeDelta = new Vector2(260, 96);
var img = go.GetComponent<Image>();
img.sprite = _square;
img.color = new Color(0.30f, 0.20f, 0.48f, 0.92f);
MakeText(go.transform, UiText.Get("talent_entry"), 40, Vector2.zero, TextAnchor.MiddleCenter, 260, 96).color
go.GetComponent<Button>().onClick.AddListener(() => OpenRequested?.Invoke());
}

void BuildTalentPanel()
{
    _panel = MakeOverlayPanel("TalentPanel", MetaBg);
    _titleText = MakeText(_panel, UiText.Get("talent_title"), 84, new Vector2(0, 620), TextAnchor.MiddleCenter,
    _titleText.color = Violet;
    _dayLabel = MakeText(_panel, UiText.Get("talent_day_fmt", "1"), 44, new Vector2(0, 520), TextAnchor.MiddleCenter,
    _dayLabel.color = BoneWhite;
    _walletText = MakeText(_panel, "", 40, new Vector2(0, 445), TextAnchor.MiddleCenter, 1040, 70);
    _walletText.color = NeonCyan;
    // — talent page (T018): branch rows + week-chain slots —
    for (int i = 0; i < 3; i++)
    {
        int row = i;
        var card = new GameObject("BranchRow" + row, typeof(RectTransform), typeof(Image));
        card.transform.SetParent(_panel, false);
        var crt = (RectTransform)card.transform;
        crt.anchorMin = crt.anchorMax = new Vector2(0.5f, 0.5f);
        crt.anchoredPosition = new Vector2(0, 290 - row * 150);
        crt.sizeDelta = new Vector2(1040, 130);
        var cimg = card.GetComponent<Image>();
        cimg.sprite = _square;
        cimg.color = CardDim;
        // texts[0]=main, texts[1]=milestone desc (filled per ShowTalent).
        MakeText(card.transform, "", 42, new Vector2(-110, 22), TextAnchor.MiddleLeft, 620, 60).color = BoneWhite;
        MakeText(card.transform, "", 32, new Vector2(-110, -36), TextAnchor.MiddleLeft, 620, 56).color = new Color(0.45f, 0.30f, 0.72f);
        MakeButtonOn(card.transform, UiText.Get("talent_buy"), new Vector2(400, 0), new Vector2(200, 100),
            new Color(0.45f, 0.30f, 0.72f), () => BuyRequested?.Invoke(_branchIds[row]));
        _talentPageObjects.Add(card);
    }
    _talentPageObjects.Add(MakeText(_panel, UiText.Get("talent_chain_foot"), 38, new Vector2(0, -195),
        TextAnchor.MiddleCenter, 1040, 70).gameObject);
    for (int i = 0; i < 7; i++)
    {
        var slot = MakeText(_panel, "D" + (i + 1), 40, new Vector2(-390 + i * 130, -300),
            TextAnchor.MiddleCenter, 120, 100);
        slot.color = new Color(0.35f, 0.30f, 0.45f);
        _slotTexts.Add(slot);
        _talentPageObjects.Add(slot.gameObject);
    }
}

```

```

    }
    _chainText = MakeText(_panel, "", 36, new Vector2(0, -420), TextAnchor.MiddleCenter, 1040, 80);
    _chainText.color = new Color(0.85f, 0.80f, 0.95f);
    _talentPageObjects.Add(_chainText.gameObject);
    // Corner page switch (talent page & codex page): the collection is one
    // tap away, no second hub button (one panel owns both codex faces).
    _talentPageObjects.Add(MakeButtonOn(_panel, UiText.Get("talent_to_codex"), new Vector2(430, 620), new Vector
        new Color(0.30f, 0.42f, 0.55f, 0.95f), () => CodexPageRequested?.Invoke()).gameObject);
    // — codex page (T019 slice 3): the 10-species roster + bonus progress —
    _codexProgressText = MakeText(_panel, "", 48, new Vector2(0, 290),
        TextAnchor.MiddleCenter, 1040, 90);
    _codexProgressText.color = Violet;
    _codexPageObjects.Add(_codexProgressText.gameObject);
    for (int i = 0; i < 10; i++)
    {
        int col = i % 5, row = i / 5;
        var slot = MakeText(_panel, "G" + (i + 1), 40, new Vector2(-400 + col * 200, -30 - row * 150),
            TextAnchor.MiddleCenter, 190, 120);
        slot.color = new Color(0.35f, 0.30f, 0.45f);
        _codexSlotTexts.Add(slot);
        _codexPageObjects.Add(slot.gameObject);
    }
    _codexBeltText = MakeText(_panel, "", 36, new Vector2(0, -340), TextAnchor.MiddleCenter, 1040, 80);
    _codexBeltText.color = new Color(0.85f, 0.80f, 0.95f);
    _codexPageObjects.Add(_codexBeltText.gameObject);
    _codexPageObjects.Add(MakeText(_panel, UiText.Get("talent_codex_foot"), 34,
        new Vector2(0, -430), TextAnchor.MiddleCenter, 1040, 70).gameObject);
    _codexPageObjects.Add(MakeButtonOn(_panel, UiText.Get("talent_to_talent"), new Vector2(-430, 620), new Vecto
        new Color(0.30f, 0.42f, 0.55f, 0.95f), () => TalentPageRequested?.Invoke()).gameObject);
    MakeButtonOn(_panel, UiText.Get("talent_close"), new Vector2(0, -560), new Vector2(420, 100),
        new Color(0.16f, 0.18f, 0.24f, 0.9f), () => CloseRequested?.Invoke());
    _hintText = MakeText(_panel, "", 34, new Vector2(0, -690), TextAnchor.MiddleCenter, 1040, 90);
    _hintText.color = new Color(0.95f, 0.87f, 0.6f);
    _panel.gameObject.SetActive(false);
}

/// &summary& Flip the panel between the talent page and the codex page
/// (shared chrome: title/day/wallet/close/hint stay put).&/summary&
void SetPage(bool codex)
{
    for (int i = 0; i < _talentPageObjects.Count; i++) _talentPageObjects[i].SetActive(!codex);
    for (int i = 0; i < _codexPageObjects.Count; i++) _codexPageObjects[i].SetActive(codex);
    _titleText.text = codex ? UiText.Get("talent_codex_title") : UiText.Get("talent_title");
}

/// &summary& Open/refresh the panel: branch rows rebuilt from the face data
/// (points/next cost/milestone move every buy, a cached layout would lie),
/// codex slots light per the claim latch, chain line shows today's task.&/summary&
public void ShowTalent(int dayIndex, int walletCoins, IReadOnlyList<BranchFace> branches,
    int nextPointCost, string chainStatus, bool[] weekClaimed)
{
    SetPage(codex: false);
}

```

```

        _dayLabel.text = UiText.Get("talent_day_fmt", dayIndex.ToString());
        SetWallet(walletCoins);
        _chainText.text = chainStatus;
        SetHint(UiText.Get("talent_hint_talent"));
        _branchIds.Clear();
        int rows = Math.Min(3, branches != null ? branches.Count : 0);
        for (int i = 0; i < rows; i++)
        {
            var face = branches[i];
            _branchIds.Add(face.Id);
            var row = _panel.Find("BranchRow" + i);
            var texts = row.GetComponentsInChildren<Text>();
            // texts[0]=main, texts[1]=desc, texts[2]=buy label (factory order).
            texts[0].text = UiText.Get("talent_branch_row_fmt", face.Name, face.Points.ToString(),
                face.Max.ToString(), nextPointCost.ToString());
            texts[1].text = face.NextMilestoneDesc;
        }
        for (int i = 0; i < _slotTexts.Count && i < weekClaimed.Length; i++)
        {
            bool lit = weekClaimed[i];
            _slotTexts[i].text = lit ? "D" + (i + 1) + " " : "D" + (i + 1);
            _slotTexts[i].color = lit ? NeonCyan : new Color(0.35f, 0.30f, 0.45f);
        }
        _panel.gameObject.SetActive(true);
    }

    /// <summary>One codex roster slot's display face (the launcher builds it from
    /// the cfg_enemy roster order + the session collection; names carry the 05 s4
    /// first-version authority until the loc table lands with the art batch).</summary>
    public struct CodexSlotFace
    {
        public string CodeName;
        public string NameCn;
        public bool Collected;
    }

    /// <summary>Open/refresh the codex page: roster slots light per the collection,
    /// the progress line reads the live bonus (CollectionBook math, honest data),
    /// the belt line shows the week-chain task.</summary>
    public void ShowCodex(int dayIndex, int walletCoins, IReadOnlyList<CodexSlotFace> roster,
        int collected, int total, float globalPct, string chainStatus)
    {
        SetPage(codex: true);
        _dayLabel.text = UiText.Get("talent_day_fmt", dayIndex.ToString());
        SetWallet(walletCoins);
        _codexProgressText.text = UiText.Get("talent_codex_progress_fmt", collected.ToString(),
            total.ToString(), (globalPct * 100f).ToString("0.#"));
        _codexBeltText.text = chainStatus;
        SetHint(UiText.Get("talent_hint_codex"));
        int n = Math.Min(_codexSlotTexts.Count, roster != null ? roster.Count : 0);
        for (int i = 0; i < n; i++)
        {

```

```

        var f = roster[i];
        _codexSlotTexts[i].text = f.CodeName + " " + f.NameCn + (f.Collecte ? " " : "");
        _codexSlotTexts[i].color = f.Collecte ? NeonCyan : new Color(0.35f, 0.30f, 0.45f);
    }
    _panel.gameObject.SetActive(true);
}

/// <summary>Buy success beat: violet flash with the branch name.</summary>
public void PlayBuyFlash(string branchName)
{
    StartCoroutine(BuyFlashRoutine(branchName));
}

IEnumerator BuyFlashRoutine(string branchName)
{
    var overlay = MakeOverlayPanel("BuyFlash", new Color(0.06f, 0.04f, 0.10f, 0.9f));
    var main = MakeText(overlay, UiText.Get("talent_buy_flash_fmt", branchName), 80, new Vector2(0, 90),
        TextAnchor.MiddleCenter, 1040, 130);
    main.color = Violet;
    PlayTone(587f, 0.16f);
    yield return new WaitForSeconds(0.7f);
    Destroy(overlay.gameObject);
}

public void SetWallet(int coins) => _walletText.text = UiText.Get("talent_wallet_fmt", coins.ToString());
public void SetHint(string hint) => _hintText.text = hint;
public void Hide() => _panel.gameObject.SetActive(false);
public bool IsVisible => _panel != null && _panel.gameObject.activeSelf;

// —— factory helpers (DayView proven pattern) ——
Button MakeButtonOn(Transform parent, string text, Vector2 pos, Vector2 size, Color color, Action onClick)
{
    var go = new GameObject(text, typeof(RectTransform), typeof(Image), typeof(Button));
    go.transform.SetParent(parent, false);
    var rt = (RectTransform)go.transform;
    rt.anchorMin = rt.anchorMax = new Vector2(0.5f, 0.5f);
    rt.anchoredPosition = pos;
    rt.sizeDelta = size;
    var image = go.GetComponent<Image>();
    image.sprite = _square;
    image.color = color;
    MakeText(go.transform, text, 40, Vector2.zero, TextAnchor.MiddleCenter, size.x, size.y).color = BoneWhite;
    var button = go.GetComponent<Button>();
    button.onClick.AddListener(() => onClick());
    return button;
}

RectTransform MakeOverlayPanel(string name, Color color)
{
    var go = new GameObject(name, typeof(RectTransform), typeof(Image));
    go.transform.SetParent(_canvas.transform, false);
    var rt = (RectTransform)go.transform;
    rt.anchorMin = Vector2.zero;
    rt.anchorMax = Vector2.one;
    rt.offsetMin = rt.offsetMax = Vector2.zero;

```

```

        var image = go.GetComponent<Image>();
        image.sprite = _square;
        image.color = color;
        return rt;
    }
    static Text MakeText(Transform parent, string text, int size, Vector2 pos, TextAnchor anchor, float w, float h)
    {
        var go = new GameObject("Text", typeof(RectTransform), typeof(Text));
        go.transform.SetParent(parent, false);
        var rt = (RectTransform)go.transform;
        rt.anchorMin = rt.anchorMax = new Vector2(0.5f, 0.5f);
        rt.anchoredPosition = pos;
        rt.sizeDelta = new Vector2(w, h);
        var t = go.GetComponent<Text>();
        t.font = UIFont.Resolve(); // T035: FontSet-driven CJK chain
        t.text = text;
        t.fontSize = size;
        t.alignment = anchor;
        t.color = new Color(0.91f, 0.89f, 0.85f);
        t.supportRichText = true;
        return t;
    }
    static Sprite MakeSquareSprite()
    {
        var tex = new Texture2D(8, 8, TextureFormat.RGBA32, false);
        var px = tex.GetPixels32();
        for (int i = 0; i < px.Length; i++) px[i] = new Color32(255, 255, 255, 255);
        tex.SetPixels32(px);
        tex.Apply(false, false);
        return Sprite.Create(tex, new Rect(0, 0, 8, 8), new Vector2(0.5f, 0.5f), 8f);
    }
    // Procedural placeholder tone (P08 pattern; formal clips swap at M2.5).
    void PlayTone(float freq, float seconds)
    {
        if (_toneSource == null) _toneSource = gameObject.AddComponent<AudioSource>();
        const int sr = 22050;
        int n = Mathf.Max(1, (int)(sr * seconds));
        var data = new float[n];
        for (int i = 0; i < n; i++)
        {
            float k = 1f - (float)i / n;
            data[i] = Mathf.Sin(2f * Mathf.PI * freq * i / sr) * k;
        }
        var clip = AudioClip.Create("tone", n, 1, sr, false);
        clip.SetData(data, 0);
        _toneSource.PlayOneShot(clip);
    }
}
// TutorialFlow.cs

```

```

using System;
namespace Sy.P01.Newbie
{
    /// <summary>
    ///     evt_newbie_step 1-5 ① ② ③ ④ Boss⑤ +
    ///     BattleSim /W3 / Boss / / —
    /// Play headless NewbieFlowCheck
    /// </summary>
    public sealed class TutorialFlow
    {
        public int Step { get; private set; }
        readonly Action<string> _hint;
        readonly Action<int> _onStep;
        public TutorialFlow(BattleSim sim, Action<string> hint, Action<int> onStep)
        {
            _hint = hint ?? delegate { };
            _onStep = onStep ?? delegate { };
            sim.FirstMoved += OnFirstMoved;
            sim.TalismanOffered += OnTalismanOffered;
            sim.TalismanPicked += OnTalismanPicked;
            sim.EliteKilled += OnEliteKilled;
            sim.BossKilled += OnBossKilled;
            sim.StateChanged += OnStateChanged;
            _hint(UiText.Get("tutorial_open"));
        }
        void Advance(int step)
        {
            if (Step >= step) return;
            Step = step;
            _onStep(step);
        }
        void OnFirstMoved()
        {
            Advance(1);
            _hint(UiText.Get("tutorial_moved"));
        }
        void OnTalismanOffered()
        {
            _hint(UiText.Get("tutorial_offer_fmt", NewbieConfig.EvolutionName));
        }
        void OnTalismanPicked(int index)
        {
            Advance(2);
            var t = NewbieConfig.Talismans[index];
            _hint(UiText.Get("tutorial_pick_fmt", t.Name, NewbieConfig.ChainPending(NewbieConfig.TalismanChainChars[inde
        }
        void OnEliteKilled()
        {
            Advance(3);
            _hint(UiText.Get("tutorial_elite_fmt", NewbieConfig.ChainComplete(NewbieConfig.TalismanChainChars[0])));
        }
    }
}

```

```

    }
    void OnBossKilled()
    {
        Advance(4);
        _hint(UiText.Get("tutorial_boss"));
    }
    void OnStateChanged(BattleSim.BattleState state)
    {
        if (state == BattleSim.BattleState.Won)
        {
            Advance(5);
            _hint(UiText.Get("tutorial_won"));
        }
    }
}

// WxBoardPostChannel.cs
#if SY_WECHAT
// X129 law: the DllImport surface only exists on armed weixin builds
// (BuildWeixin injects SY_WECHAT) - Editor/mock/douyin builds never compile
// this file, so the armed command pump and its jslib import simply do not
// exist there (the service entry is the honest no-op, zero drift).
using System.Runtime.InteropServices;
namespace Sy.P01.Newbie
{
    /// <summary>
    /// T036b: the armed main-domain board command pump. wx.getOpenDataContext
    /// ().postMessage is the ONLY channel into the open-data subdomain: every
    /// board open posts one idempotent refresh command, the subdomain re-reads
    /// the friend KV (getFriendCloudStorage) and repaints the sharedCanvas.
    /// The payload rides the shared jslib shape ({boardId, viewport:payload})
    /// and carries the session's own kills for the always-present "You"
    /// footer (the subdomain has no self-id API - the self row can never be
    /// flagged by matching, only stated by the main-domain truth). Fire-and-
    /// forget: the post is the honest unit; the painted board is the U014
    /// physical face. Zero shared-package changes (X236 law - same symbol
    /// the com.sy.platform bridge declares, same shape as the write channel).
    /// </summary>
    public static class WxBoardPoster
    {
        public const string BoardId = "friend_kills";
        public static void PostRefresh(int selfKills)
        {
            => WxBoardPostBridge.SyOpenDataPost(
                BoardId, $"{selfKills\":" + selfKills + "}");
        }
    }
    /// <summary>P01-local import of the shared jslib export (the jslib ships
    /// with the shared platform package this project references - zero
    /// shared-package changes, X236 law; distinct bridge name so the write
    /// channel's bridge and this one never collide).</summary>
    static class WxBoardPostBridge

```

```

    {
        [DllImport("__Internal")] internal static extern void SyOpenDataPost(
            string boardPtr, string payloadPtr);
    }
}
#endif
// WxBoardRelayChannel.cs
#if SY_WECHAT
// X129 law: the DllImport surface only exists on armed weixin builds
// (BuildWeixin injects SY_WECHAT) - Editor/mock/douyin builds never compile
// this file, so the armed relay sink and its jslib import simply do not
// exist there (the relay default keeps the no-op, zero drift).
using System.Runtime.InteropServices;
namespace Sy.P01.Newbie
{
    /// <summary>
    /// T036c: the armed WX board relay sink. The P01 wx package is a
    /// self-built thin adapter (no official unity-sdk JS), so the display
    /// chain rides the official ScreenCanvas mode directly through the
    /// P01-local SyBoardRelay jslib: wx.getOpenDataContext({sharedCanvasMode:
    /// 'screenCanvas'}) locks the shared singleton as an on-screen overlay
    /// (base library 3.6.6+; older clients ignore the option and keep the
    /// native delegation ladder - never empty on any device). RelayShow
    /// positions the overlay over the board row strip (device px, the
    /// relay service's rect math); RelayHide applies the official 1px
    /// off-screen hide recipe. The launcher posts one refresh after every
    /// mount (PostBoardRefresh): the main-domain resize clears the canvas
    /// by canvas law, the subdomain repaints it. Zero shared-package
    /// changes (X236 law - P01-local jslib, same bridge shape as the
    /// write/post channels).
    /// </summary>
    public sealed class WxBoardRelaySink : IBoardRelaySink
    {
        public void RelayShow(int x, int y, int w, int h)
            => WxBoardRelayBridge.SyBoardRelayShow(x, y, w, h);
        public void RelayHide()
            => WxBoardRelayBridge.SyBoardRelayHide();
    }
    /// <summary>P01-local import of the P01-local jslib export (the jslib
    /// ships in Assets/_Game/Plugins - zero shared-package changes, X236
    /// law; distinct symbol family from the shared bridge exports).</summary>
    static class WxBoardRelayBridge
    {
        [DllImport("__Internal")] internal static extern void SyBoardRelayShow(
            int x, int y, int w, int h);
        [DllImport("__Internal")] internal static extern void SyBoardRelayHide();
    }
}
#endif
// WxBoardWriteChannel.cs

```

```
#if SY_WECHAT
// X129 law: the DllImport surface only exists on armed weixin builds
// (BuildWeixin injects SY_WECHAT) - Editor/mock/douyin builds never compile
// this file, so the armed writer face and its jslib import simply do not
// exist there (the channel default keeps the honest no-op, zero drift).
using System.Runtime.InteropServices;
namespace Sy.P01.Newbie
{
    /// <summary>
    /// T036a: the armed main-domain write face. wx.setUserCloudStorage is
    /// the MAIN-domain KV write (the only domain allowed to write the self
    /// score; friend rows stay subdomain-read-only until T036b). The shared
    /// jslib export is fire-and-forget (the T013-B2 symbol ships no result
    /// callback), so the dispatch is the honest unit - the real &lt;=1s
    /// write clock is the U014 physical face. Exactly-once per value change:
    /// the BoardWriteOnceGuard swallows duplicate pushes, so a board
    /// re-open with an unchanged score never re-writes (KV field lock: the
    /// payload only ever goes out under OpenDataBoardService.KvKeyKills).
    /// </summary>
    public sealed class WxBoardWriteFace : IOpenDataBoardWriter
    {
        static readonly BoardWriteOnceGuard Guard = new();
        public bool WriteSelfKv(int kills)
        {
            Guard.TryPush(kills, v =>
                WxBoardBridge.SySetUserCloudStorage(
                    OpenDataBoardService.KvKeyKills, v.ToString()));
        }
        /// <summary>P01-local import of the shared jslib export (same symbol
        /// the com.sy.platform bridge declares; the jslib ships with the shared
        /// package this project references - zero shared-package changes, X236
        /// law, same shape as WxSubscribeBridge).</summary>
        static class WxBoardBridge
        {
            [DllImport("__Internal")] internal static extern void SySetUserCloudStorage(
                string kvKey, string kvValue);
        }
    }
}
#endif
// WxOpenDataBoard.cs
using System.Collections.Generic;
namespace Sy.P01.Newbie
{
    /// <summary>
    /// T022-iv: the armed-build friend kills board face. Real WX friend
    /// scores only exist inside the open data domain - the subdomain package
    /// + sharedCanvas feed is T036's row - so this face is the armed SOCKET:
    /// until that feed lands it serves the exact pseudo-friend ladder the
    /// mock serves, by DELEGATION (one roster source, no copied data, zero
    /// drift by construction; the board never dead-ends and never fabricates
    /// telemetry). When T036 wires the real feed in, this class grows the
```

```

    /// real-row source and the mock stays the Editor/gate face.
    /// Pure managed delegation - no DllImport/jslib native surface - so it
    /// compiles on every platform (unlike WxSubscribeFace, X129 native law);
    /// the DefaultBoardFaceFactory's SY_WECHAT define gates WHO uses it on
    /// each build, and FriendBoardCheck F8 asserts the delegation identity
    /// directly in plain Editor gates.
    /// Real-device verification ("friend board visible on a real phone") is
    /// the user physical face (U014) - this code face is N/A-justified there.
    /// </summary>
    public sealed class WxOpenDataBoard : IOpenDataBoard
    {
        public List<FriendBoardRow> GetFriendKillsBoard(int selfKills, int maxRows)
            => new MockOpenDataBoard().GetFriendKillsBoard(selfKills, maxRows);
    }
}

// WxSubscribeFace.cs
#if SY_WECHAT
// X129 law: the DllImport surface only exists on armed weixin builds
// (BuildWeixin injects SY_WECHAT) - Editor/mock/douyin builds never compile
// this file, so the default face stays the local mock (SubscribeService).
namespace Sy.P01.Newbie
{
    /// </summary>
    /// T022-iv-B: the armed-build WX ask face over the P01-local jslib result
    /// channel (WxSubscribeJsChannel). Placeholder law (G5/T001c): template
    /// ids carrying the placeholder prefix are NOT real console ids and never
    /// reach the device - the ask fails honestly as NotAsked (no ledger burn,
    /// no funnel events). Real console ids fire wx.requestSubscribeMessage
    /// through the channel; the sync return stays the honest pending Denied -
    /// the verified device grant (T022-iv-B result channel) is the only thing
    /// that ever lands a grant, never a fabricated sync grant.
    /// </summary>
    public sealed class WxSubscribeFace : ISubscribeFace
    {
        public SubscribeOutcome Request(P01Configs.SubscribeRow row, System.Action<bool> onDeviceResult)
        {
            string tplId = row.wxTemplateId;
            if (string.IsNullOrEmpty(tplId)
                || tplId.StartsWith(SubscribeService.PlaceholderPrefix))
                return SubscribeOutcome.NotAsked;

            // Real console id: fire the one-shot subscribe dialog. The
            // service records the ask (ledger + request event) on the sync
            // path; the granted stage only ever fires when the device
            // result arrives verified through the channel callback.
            WxSubscribeJsChannel.Ask("[\"" + tplId + "\"]", onDeviceResult);
            return SubscribeOutcome.Denied;
        }
    }
}
#endif

```

```

// WxSubscribeJsChannel.cs
#if SY_WECHAT
// X129 law: the DllImport surface only exists on armed weixin builds
// (BuildWeixin injects SY_WECHAT) - Editor/mock/douyin builds never compile
// this file, so the channel and its scene relay simply do not exist there.
using System;
using System.Collections.Generic;
using System.Runtime.InteropServices;
using UnityEngine;
namespace Sy.P01.Newbie
{
    /// <summary>
    /// T022-iv-B: the P01-local jslib result channel for subscribe asks.
    /// The shared com.sy.platform jslib resolves the wasm instance and calls
    /// SendMessage('SyJsBridge', 'OnJsResult', cbId + '\u001F' + json) - a
    /// broadcast every MonoBehaviour on the host object receives. This channel
    /// owns the P01 half of that contract with ZERO shared-package changes
    /// (P02/P06 pending-review byte stability, X236 law):
    /// - the host object is the same 'SyJsBridge' the shared suite uses;
    /// - the shared public JsBridgeReceiver component keeps serving suite
    ///   callbacks (ads/login/album) no matter which side built the host;
    /// - the local relay component feeds P01 subscribe results only.
    /// Creation order is order-proof: whichever side builds the host first,
    /// the other finds it and only adds its missing component, so a P01
    /// subscribe ask can never orphan a suite callback and vice versa.
    /// </summary>
    static class WxSubscribeJsChannel
    {
        static readonly Dictionary<string, Action<bool>>> Pending = new();
        static int _nextId;
        static bool _hostReady;
        /// <summary>Fire the ask and register the result callback. The jslib
        /// answers exactly once ({ok:true/false}) through the wx success/fail
        /// pair, delivered on the main thread by SendMessage - safe to touch
        /// the save slot directly from the callback.</summary>
        internal static void Ask(string tplIdsJson, Action<bool> onDeviceResult)
        {
            if (onDeviceResult == null) return; // no listener: nothing to wire
            EnsureHost();
            string cbId = "p01_subscribe_" + ++_nextId;
            Pending[cbId] = onDeviceResult;
            WxSubscribeBridge.SyRequestSubscribe(tplIdsJson, cbId);
        }
        /// <summary>Route one jslib result. Unknown ids (the shared suite's
        /// own callbacks) are ignored untouched; a malformed payload is an
        /// honest deny.</summary>
        internal static void Complete(string id, string json)
        {
            if (id == null) return;
            if (!Pending.Remove(id, out var onResult)) return;

```

```

        bool ok = false;
        try
        {
            var data = Sy.Core.Minijson.Deserialize(json) as Dictionary<string, object>;
            if (data != null && data.TryGetValue("ok", out var v)) ok = Convert.ToBoolean(v);
        }
        catch (Exception) { ok = false; }
        onResult(ok);
    }
    static void EnsureHost()
    {
        if (_hostReady) return;
        var host = GameObject.Find("SyJsBridge");
        if (host == null)
        {
            host = new GameObject("SyJsBridge");
            UnityEngine.Object.DontDestroyOnLoad(host);
        }
        if (host.GetComponent<Sy.Platform.Wx.JsBridgeReceiver>() == null)
            host.AddComponent<Sy.Platform.Wx.JsBridgeReceiver>();
        if (host.GetComponent<WxSubscribeResultRelay>() == null)
            host.AddComponent<WxSubscribeResultRelay>();
        _hostReady = true;
    }
}

/// <summary>Scene relay on the shared host: SendMessage from the jslib
/// broadcasts OnJsResult to every component - this one routes P01
/// subscribe results while the shared receiver keeps its own registry
/// (both components always coexist on the single host object).</summary>
[DisallowMultipleComponent]
sealed class WxSubscribeResultRelay : MonoBehaviour
{
    public void OnJsResult(string message)
    {
        int split = message.IndexOf('\u001F');
        string cbId = split < 0 ? message : message.Substring(0, split);
        string json = split < 0 ? "" : message.Substring(split + 1);
        WxSubscribeJsChannel.Complete(cbId, json);
    }
}

/// <summary>P01-local import of the shared jslib export (same symbol as
/// Sy.Platform.Wx.WxBridge.SyRequestSubscribe; the jslib ships with the
/// com.sy.platform package this project references).</summary>
static class WxSubscribeBridge
{
    [DllImport("__Internal")] internal static extern void SyRequestSubscribe(
        string tmplIdsJson, string cbId);
}
}
#endif

```