

# Speedaf API Integration

## Technical Questions for Production Switch

### Technical Questions for Speedaf - Production Deployment

These are the remaining technical integration questions we need clarified before switching our integration from UAT to the production API.

---

#### 1. Authentication & Request Signing

Q1. In UAT, the response 'data' field is sometimes returned as a plain JSON string (unparsed). In production, will 'data' always be encrypted/DES-CBC encoded, or does it remain as plain JSON?

Q2. Is the signature algorithm (MD5 of 'timestamp + secretKey + dataStr') identical in production, or does production use a different signing method?

---

#### 2. Order Creation ('/open-api/express/order/createOrder')

Q3. Which 'transportType' code should we use for standard domestic deliveries within Nigeria? We currently use 'TT02' (Air). Is there a Road/Ground option (e.g. 'TT01') that's more appropriate for local deliveries, and what is its code?

Q4. We use 'payMethod: "PA02"' (Monthly Merchant Billing). Please confirm: does this mean we will receive a monthly invoice for all waybills created? Are there any pre-conditions (credit limit, account setup) we need to complete before this works in production?

Q5. For 'parcelType', 'deliveryType', and 'shipType' - we use 'PT01', 'DE01', 'ST01'. Are these the correct codes for standard fashion apparel delivery? Please provide a full code reference list for our records.

Q6. The 'goodsType' field in 'itemList' - we use 'IT01'. What does this code represent? What code should we use for fashion apparel items (clothing, shoes, accessories)?

Q7. Is the 'platformSource' field ('TEST 345' in UAT) something we must change for production? What value should it be?

Q8. What is the maximum number of items allowed in 'itemList' for a single order? Are there restrictions on 'goodsWeight' or 'parcelWeight' (max kg)?

**Q9. The 'acceptAddress' field - how long can this string be? Is there a character limit?**

---

### **3. Tariff / Fee Calculation ('/open-api/fee/getFee')**

**Q10. Will the production API return real NGN shipping fees for '/open-api/fee/getFee'? If yes, should we call this endpoint live during checkout, or is it better to use a cached rate table?**

**Q11. How is the final package weight quantified and billed? Does Speedaf bill us based on the estimated 'parcelWeight' we submit during order creation, or do your couriers weigh the package upon collection/arrival at the warehouse and update the billing amount accordingly?**

- Note: We have implemented a category-based weight estimation system (e.g. Shoes: 1.2kg, Jackets: 1.5kg, Shirts: 0.3kg, Bags/Accessories: 0.2kg) to sum up weights at checkout/booking, but we need to know if you perform physical auditing.

**Q12. The tariff endpoint requires 'pickedTime' (we pass 'Date.now()'). Does this affect the returned fee in any way? For example, is there a future pickup time scheduling feature?**

---

### **4. Waybill & Shipment Tracking**

**Q13. We have two tracking endpoints: 'queryTrace' and 'queryOrder'. What is the difference? Should we use 'queryTrace' for customer-facing tracking, and 'queryOrder' for admin-level order status checks?**

**Q14. In the tracking response, the scan history is returned in fields such as 'trajectoryList', 'traceList', or 'scanList' - and we have not been able to confirm which one is correct. What is the exact field name that contains the list of scan/trajectory events in the production tracking response? (e.g. is it 'tracks' inside each waybill object?)**

**Q15. For each scan event in the tracking history, what are the exact field names for: scan timestamp, status description (in English), and scan location/city? (We are currently mapping 'time', 'msgEng'/'actionName', and 'optName'/'location'/'city').**

---

### **5. Webhook / Tracking Push Callback**

**Q16. Our webhook endpoint is at 'https://[our-domain]/api/webhooks/speedaf'. Do we need to register this URL in our merchant account portal, or do we send it directly to you via WhatsApp to configure it?**

**Q17. In the webhook callback payload Speedaf pushes to us, what are the exact field names for: waybill**

number, scan action code, action description in English, scan time, and scan city/location?

**Q18.** Does Speedaf sign or encrypt the webhook callback payload it sends TO us? If yes, what is the signature algorithm and what header is the signature sent in? We need to verify that callbacks are genuinely from Speedaf and not spoofed.

**Q19.** What HTTP response format does Speedaf expect from our webhook endpoint to acknowledge receipt? We currently return:

```
{ "success": true, "error": null, "data": null }
```

Is this correct? If we return a non-success body, will Speedaf retry? If yes - what is the retry policy?

**Q20.** Does Speedaf send webhook callbacks from a fixed set of IP addresses? If yes, please provide the IP whitelist so we can restrict our webhook endpoint to those IPs only for security.

---

## 6. Order Cancellation

**Q21.** If a cancellation fails because the order is already in transit, what is the recommended process - should we call a "recall/return" endpoint, or does it have to be handled offline?

---

## 7. Production Readiness & Go-Live

**Q22.** Is there a specific go-live checklist or production onboarding process we need to complete before switching from 'uat-api.speedaf.com' to 'apis.speedaf.com'?

**Q23.** Does Speedaf provide a Postman collection or Swagger/OpenAPI spec for your API?

**Q24.** If our production server calls your API and gets a timeout, what is the standard response timeout value we should set on our end?