


# COS30041 Create Secure and Scalable Software

## Lecture 03b Java Persistence API (JPA)



SWIN  
BUR  
\* NE \*

SWINBURNE  
UNIVERSITY OF  
TECHNOLOGY

Commonwealth of Australia  
*Copyright Act 1968*

**Notice for paragraph 135ZXA (a) of the *Copyright Act 1968***

### **Warning**

This material has been reproduced and communicated to you by or on behalf of Swinburne University of Technology under Part VB of the *Copyright Act 1968* (the Act).

The material in this communication may be subject to copyright under the Act. Any further reproduction or communication of this material by you may be the subject of copyright protection under the Act.

Do not remove this notice.

# Learning Objectives

- After studying the lecture material, you will be able to
  - ☐ Understand and describe what an entity class is
  - ☐ Understand and describe the features that Java Persistence API has to offer
  - ☐ Understand the issues involved in programming entity class using Java Persistence API
  - ☐ Program entity class
  - ☐ Program client applications that call the services provided by entity class

# Pre-requisite


- Database concepts
- Writing simple SQL statements
- JDBC, some knowledge would be good

# Outline

- Entity Class
- The Primary Key
- Programming a JPA application
  - Program the Entity Class
  - Use the EntityManager API
- Programming Example

# Object-relational Mapping, ORM

- A mapping between objects (in OOP) and database records



s1: Staff (Class)

-----  
name="Edmonds"  
room="EN508b"  
phone="92144367"  
-----

s1 is an object

ORM

JPA:

```
em.persist(s1);
```

Use the EntityManager API:

```
EntityManagerFactory emf = Persistence.createEntityManagerFactory("EX-EntityPU");  
EntityManager em = emf.createEntityManager();
```

# Roadmap

- **Entity Class**
- The Primary Key
- Programming a JPA application
  - Program the Entity Class
  - Use the EntityManager API
- Programming Example



# Entity Class

- [MEJB3] A Plain Old Java Object (POJO) that is used to persist objects that can be stored in permanent storage
  - Databases or Legacy systems
- [JEE7T;37-1] A lightweight persistence domain object
  - Typically, it represents a table in a relational database (RDB)
  - Each entity instance corresponds to a row in the table
- Example
  - Bank Account
  - Customer Data

# Why Entity Class?

- Is handy to treat data as objects
- Can associate simple methods with objects
- Can store the data in memory for performance
- Using POJO can achieve much simpler code
  - cf those in the EJB's Entity Bean (old Java EE 1.4 or earlier)
- Detached from EJB allowing it to exist in Application Client, hence no need to have separate DTOs
  - Changing attributes in entity class on the client side won't affect the "same" copy on the server, and hence will not affect those in the databases [Note: ORM only occurs on the server]
  - Easy to cause confusion, though!

# Terminologies

## ■ Entity Class Instance (usually on the server)

- The in-memory view of the database (as an instance of the entity class)

## ■ Entity Data

- The physical set of data stored in the database

## ■ Example

- Entity Class “Account” models the database table “Account”
- The “Account” entity class instance stores a particular “account” in the database
- Assume “Account” has 2 instance variables “accountId” and “accountBalance”, each refers to a particular field in the database table

# Entity Class Composition

The **data** that it represents

- All fields need to be serializable
- The Primary Key
- Map to an entity definition of a database schema using features provided by Java Persistence API

# Roadmap

- Entity Class
- **The Primary Key**
- Programming a JPA application
  - Program the Entity Class
  - Use the EntityManager API
- Programming Example

# The Primary Key

- The unique identifier of the entity data instance
  - May contain any number of attributes
  - Simple vs Composite
- Simple Primary Key
  - Use this when the primary key is just one data field
  - Use an instance variable in the Entity Class
  - Must be serializable
  - Use “@Id” annotation to indicate it is a simple primary key
- Composite Primary Key defined in Primary Key Class

# The Primary Key (cont'd)

## ■ The Primary Key Class

- ☐ Use a serializable object, if the primary key has multiple data fields
- ☐ **Must be public**
- ☐ Have a public default constructor
- ☐ **Must implement** the hashCode() and equals(Object other) methods
- ☐ Must be serializable
- ☐ Composite primary key must be represented and mapped to multiple fields of the entity class (corresponding names and types must match)

# Roadmap

- Entity Class
- The Primary Key
- **Programming a JPA application**
  - Program the Entity Class
  - Use the EntityManager API
- Programming Example



# Programming a JPA application

- Program the Entity Class
- Use the EntityManager API
- Program the client

# Program the Entity Class – Requirements

- Must be annotated with `@Entity`
  - `javax.persistence.Entity`
- Must have a public or protected, no-argument constructor
  - May have other constructors
- Must not be declared final
  - Not in the methods or persistent instance variables
- Must implement the `Serializable` interface
- Persistent instance variables
  - Must be declared private, protected, or package-private
  - Can only be accessed directly by the entity class's methods

For details, see  
[JEE7T,p.37-1]

# Program the Entity Class – Req. (cont'd)

- \*Persistent Field – persistence on instance variable
- Persistent Property – persistence on getter and setter

- Both fields and properties require

- ☐ Java primitive data types

- ☐ `java.lang.String`

- ☐ Other serializable types including

- ☐ Wrappers of Java primitive types, `java.math.BigInteger`, ...

- ☐ Enumerated types

- ☐ Other entities and/or collections of entities

- ☐ ...

For details, please see  
[JEE7T,p.37-1]

\*Note: The approach in this subject.

# Program the Entity Class – JPA

- [NetBeans 8.2] A normal Java POJO project

- **The Entity Class**

- **The Primary Key Class** (if needed)

- **The User-defined Exception Class** (Optional)

- **The Persistence Descriptor** – defines the database connections

- persistence.xml

- **The Vendor-Specific Files**

# Program the Entity Class – JPA

## ■ Naming Convention

- ☐ The Entity Class – Class (e.g. Employee)
- ☐ The Primary Key Class – ClassKey (e.g. EmployeePK)

# Roadmap

- Entity Class
- The Primary Key
- Programming a JPA application
  - Program the Entity Class
  - **Use the EntityManager API**
- Programming Example

# Use the Entity Manager API – JPA

- The EntityManager Class is to perform all ORM related operations on the entity class
- It is responsible for
  - Accessing the entity class data
  - Managing the persistence of the entity class data

# Using the EntityManager API – JPA (cont'd)

## ■ Entity lookup and queries

- ☐ Search and return the required database records to the applications

## ■ Database synchronization operations

- ☐ Update the relevant data

## ■ Entity life-cycle management

- ☐ Manage a limited number of entity class instances for probably the entire database



# Use the EntityManager API – JPA (cont'd)

- Java uses the famous “Factory Design Pattern” to create a reference to an entity manager object
- Steps:
  - Use database connection information stored in persistence.xml file to get an EntityManagerFactory object
    - `EntityManagerFactory emf = Persistence.createEntityManagerFactory("EX-EntityPU");`
  - Use the factory object to create an entityManager object
    - `EntityManager em = emf.createEntityManager();`

# Use the EntityManager API – JPA (cont'd)

- Once the entity manager object is obtained, use it to perform the following

- ☐ Create a database record – `em.persist()`
- ☐ Update a database record – `em.merge()`
- ☐ Delete a database record – `em.remove()`
- ☐ Search a database record – `em.find()`

- Use the Transaction API to manage the transaction

- ☐ Begin a transaction – use `transaction.begin()`
- ☐ Commit a transaction – use `transaction.commit()`

# Using the EntityManager API – Lookup and Query

- Use the EntityManager to get an instance of `javax.Persistence.Query` with specific query statement
- Execute the query: many possibilities – one here

- `*createQuery(String qlString)`

- Example: get all records from the Account Table

```
Query query =  
    entityManager.createQuery(  
        "SELECT a FROM Account a");  
return (List<Account>) query.getResultList();
```

\*Note: We will only use JPQL query for database independent purposes

# Using the EntityManager API – Lookup and Query (cont'd)

- Execute the query: other possibilities

- `*createNamedQuery(String queryName)`

- Need to define the query name using `@NamedQuery` annotation in the Entity Class (not the EntityManager class)

- `*@NamedQuery(name = queryName, queryString = qlString); or`

- `@NamedQuery(name = queryName, queryString = sqlString)`

- `createNativeQuery(String sqlString)`

\*Note: We will only use JPQL query for database independent purposes

# Using the EntityManager API – Synchronization

- Synchronization is “automatic” after calling `persist()`
- “Manual” synchronization is possible
  - `setFlushMode()`
    - COMMIT – synchronization occurs at commit time
    - AUTO – synchronization occurs at commit time **and** before query execution
  - `flush()` : Enforce synchronization of all entities in the persistence context
  - `refresh()` : Refresh the entity instance from the database

# Using the EntityManager API – Life Cycle

## ■ `persist()`

- ☐ Hand over the entity instance to the `EntityManager` class to manage the persistence
- ☐ Any changes of the attributes in the entity instance will be reflected in the corresponding database record

# Roadmap

- Entity Class
- The Primary Key
- Programming a JPA application
  - Program the Entity Class
  - Use the EntityManager API
- **Programming Example**

# Programming Example – EX-JPA-Customer

- WANT: An Entity Class “Customer” to allow a customer to deposit money to and withdraw money from their own accounts
- The Entity Class – `Customer.java`
- The EntityManager helper – `CustomerEM.java`
- The Client – `CustomerApp.java`
- Download `EX-JPA-Customer.zip` from Canvas



[https://www.tutorialspoint.com/jpa/jpa\\_entity\\_managers.htm](https://www.tutorialspoint.com/jpa/jpa_entity_managers.htm)

# References

- [MEJB3] R.P. Sriganesh, G. Brose, M. Silverman (2008) *Mastering Enterprise JavaBeans 3.0*, 4<sup>th</sup> ed., John Wiley & Sons
  - Chapter 6
- [JEE7T] E. Jendrock et al. (2014) *The Java EE 7 Tutorial*, Oracle, Sep 2014
  - Chapters 37 – 39