

Function Prototypes

In this assignment you are asked to code several functions and only given the function prototype, also known as the function signature, for instance:

```
int getSomething(Something *);
```

This prototype is not a complete function definition, it is simply the signature of the function. It is used by the compiler to do a first check of the application code to ensure that all components are being used correctly. The compiler checks each use of **getSomething** to ensure that it passes the address of a **Something**, and returns an **int** value. The compiler does not care whether or not the return value is used by the caller.

If the usage test indicates that all functions and variables are being used correctly, it continues and completes the full compilation of your code. If the usage test fails (function is not being used correctly) the compilation stops and an error message is posted.

Function Definition

The definition expands upon the prototype to tell the compiler **what** to do when a function is called (provides the function logic with the necessary instructions on **how** it is to be done).

Thus: **int** getSomething(Something *)

Becomes:

```
int getSomething(Something * meaningfulVariableName)
{
    int result = 0;
    //implement functionality here
    //result may be changed to another value
    return result;
}
```

Header Files

A header file may contain structure declarations, as you have already seen in MS2, and function prototypes. The functions and structures declared or prototyped must all relate to each other (highly cohesive), this is a best practice. So, for instance, in assignment 1, the file **contacts.h** only contains declarations and prototypes for variables and functions related to a Contact. This is not the place to include a definition of an unrelated struct or a function such as **int** getNumberOfOranges(Orange *).

Function Definition File

Functions are not defined (the function logic/body) in the header file, they are defined in another source file. In this case, since the header file is named `contacts.h`, the source file is named `contacts.c`. Again, only functions related to Contacts may be defined here, this is a best practice.

The contacts header file must be included at the beginning of the contacts source file:

```
#include "contacts.h"
```

The quotation marks indicate that the header file is in the same folder as the source file.

Best Practice

Commonly observed coding behaviours that other programmers expect and recognize. In this course, and other courses in the C/C++ programming stream, failure to abide by best practices may result in loss of marks. In real life, it may result in loss of job!