



Protocol Audit Report

Prepared by: Bikalpa

Table of Contents

- [Table of Contents](#)
- [Protocol Summary](#)
- [Disclaimer](#)
- [Risk Classification](#)
- [Audit Details](#)
 - [Scope](#)
 - [Roles](#)
- [Executive Summary](#)
 - [Issues found](#)
- [Findings](#)
- [High](#)
- [Medium](#)
- [Low](#)
- [Informational](#)
- [Gas](#)

Protocol Summary

The **OrderBook** contract is a peer-to-peer trading system designed for **ERC20** tokens like **wETH**, **wBTC**, and **wSOL**. Sellers can list tokens at their desired price in **USDC**, and buyers can fill them directly on-chain.

Disclaimer

Bikapa Regmi makes all effort to find as many vulnerabilities in the code in the given time period, but holds no responsibilities for the findings provided in this document. A security audit by the team is not an endorsement of the underlying business or product. The audit was time-boxed and the review of the code was solely on the security aspects of the Solidity implementation of the contracts.

Risk Classification

		Impact		
		High	Medium	Low
Likelihood	High	H	H/M	M
	Medium	H/M	M	M/L
	Low	M	M/L	L

We use the [CodeHawks](#) severity matrix to determine severity. See the documentation for more details.

Audit Details

Scope

|

src

|

OrderBook.sol

Roles

- 1. Seller - Who lists his order on the platform
- 2. buyer - Who buys the wrapped tokens giving usdc
- 3. Owner - Owner of the contract

Executive Summary

I have spendend 5 hr auditing codes and found only 2 vulnerability.

Issues found

Severity	Number of Issue Found
High	0
Medium	0
Low	0
gas	1
Info	1
Total	2

Findings

Lows

[L-1] The `_owner` shadows the state variable on `Ownable` contract.

Description : The constructor in `OrderBook` contract takes an argument of `_owner` and assigns that `_owner` to `Ownable` constructor. However, the `Ownable` contract uses `_ownable` address as a state variable. This affects the code readiability and clarity for those who reads code casually.

Recommended Mitigation :

```
-    constructor(address _weth, address _wbtc, address _wsol, address
_usdc, address _owner) Ownable(_owner) { }

+    constructor(address _weth, address _wbtc, address _wsol, address
_usdc, address _initialOwner) Ownable (_initialOwner) { }
```

Gas

[G-1] Public variable not used internally.

If a function is marked public but is not used internally, consider marking it as **external**.

► 6 Found Instances

- Found in src/OrderBook.sol [Line: 108](#)

```
function createSellOrder(
```

- Found in src/OrderBook.sol [Line: 139](#)

```
function amendSellOrder(
```

- Found in src/OrderBook.sol [Line: 178](#)

```
function cancelSellOrder(uint256 _orderId) public {
```

- Found in src/OrderBook.sol [Line: 195](#)

```
function buyOrder(uint256 _orderId) public {
```

- Found in src/OrderBook.sol [Line: 216](#)

```
function getOrder(uint256 _orderId) public view returns (Order
memory orderDetails) {
```

- Found in src/OrderBook.sol [Line: 221](#)

```
function getOrderDetailsString(uint256 _orderId) public view
returns (string memory details) {
```

