

Result_analysis

March 1, 2022

1 Analysis the results of hybrid PBC

In this notebook, we will analyse the results obtained for the **Toffoli toy example** using our hybrid PBC script.

We run the script simulating **3 virtual qubits** and demanding a precision $\epsilon_{desired} = 0.01$.

The number of samples is being determined as:

$$N = \frac{20 \cdot \sum_{i=1}^x \alpha_i^2}{\epsilon_{desired}^2},$$

and the actual relative error ϵ_{actual} as:

$$\epsilon_{actual} = \sqrt{20} \frac{\sigma_{samples}}{\sqrt{N}}.$$

Note that since necessarily $\sigma_{samples}^2 \leq \sum_{i=1}^x \alpha_i^2$ then $\epsilon_{actual} \leq \epsilon_{desired}$.

As a result, we will have 95%-confidence intervals given by $\mathbb{E}(\xi) \pm \epsilon_{actual}$.

```
[1]: import math
      from math import sqrt

      import numpy as np
      import json
      from matplotlib import pyplot as plt

[2]: def nr_samples(precision, virtual_qubits):
      weights_1vq = [1 / 2, (1 - sqrt(2)) / 2, 1 / sqrt(2)]

      sum_squares = 0
      for i in range(3**virtual_qubits):
          label = np.base_repr(i, base=3)
          label = str(label)
          if not len(label) == virtual_qubits:
              label = '0' * (virtual_qubits - len(label)) + label

          weight = 1
          for s in label:
              weight = weight * weights_1vq[int(s)]
```

```

        sum_squares += abs(weight)**2

    N = int(math.ceil(20 * sum_squares / precision**2))

    return N

```

```

[3]: precision = [0.1, 0.09, 0.07, 0.05, 0.03, 0.02, 0.01]
    vq = 3 # choosing 3 virtual qubits
    samples = []

    for p in precision:
        samples.append(nr_samples(p, vq))

    print(samples)

```

```
[997, 1231, 2035, 3988, 11078, 24924, 99696]
```

Because we run the code for the precision $\epsilon = 0.01$, we should have a total of 99 696 values to use for the computation of the probability p . We can use those values to estimate the expected value of this probability and determine how close it is to the exact value $p = 0$.

We can also determine the standard deviation of the sample, and use it to compute the appropriate confidence interval.

Since we have access to smaller sets of values as well, we can use the first M values to estimate the results that would have been obtained if we have requested a different precision (e.g., $\epsilon = \{0.10, 0.09, 0.07, 0.05, 0.03, 0.02\}$).

```
[4]: exact_value = 0
```

1.1 $\epsilon = 0.01 \Rightarrow N = 99\,696$

```

[5]: with open('Resources_data--virt3--probabilities.txt', 'r') as file_object:
    probabilities1 = json.load(file_object)

```

```

[6]: probabilities1 = np.array(probabilities1)
    prec = precision[-1]
    print(len(probabilities1) == samples[-1])

    mean1 = np.mean(probabilities1)
    std1 = np.std(probabilities1)
    error1 = sqrt(20) * std1 / sqrt(len(probabilities1))

    print(f'p= {round(mean1, 4)} +/- {round(error1, 4)}')
    print(error1 < prec)

```

```
True
```

```
p= 0.0002 +/- 0.0047
```

True

1.2 $\epsilon = 0.02 \Rightarrow N = 24924$

```
[7]: probabilities2 = probabilities1[:samples[-2]]
```

```
[8]: prec = precision[-2]
print(len(probabilities2) == samples[-2])

mean2 = np.mean(probabilities2)
std2 = np.std(probabilities2)
error2 = sqrt(20) * std2 / sqrt(len(probabilities2))

print(f'p= {round(mean2, 4)} +/- {round(error2, 4)}')
print(error2 < prec)
```

True

p= 0.0001 +/- 0.0094

True

1.3 $\epsilon = 0.03 \Rightarrow N = 11078$

```
[9]: probabilities3 = probabilities1[:samples[-3]]
```

```
[10]: prec = precision[-3]
print(len(probabilities3) == samples[-3])

mean3 = np.mean(probabilities3)
std3 = np.std(probabilities3)
error3 = sqrt(20) * std3 / sqrt(len(probabilities3))

print(f'p= {round(mean3, 4)} +/- {round(error3, 4)}')
print(error3 < prec)
```

True

p= 0.0003 +/- 0.0141

True

1.4 $\epsilon = 0.05 \Rightarrow N = 3988$

```
[11]: probabilities4 = probabilities1[:samples[-4]]
```

```
[12]: prec = precision[-4]
print(len(probabilities4) == samples[-4])

mean4 = np.mean(probabilities4)
std4 = np.std(probabilities4)
error4 = sqrt(20) * std4 / sqrt(len(probabilities4))
```

```
print(f'p= {round(mean4, 4)} +/- {round(error4, 4)}')
print(error4 < prec)
```

True
p= 0.0023 +/- 0.0233
True

1.5 $\epsilon = 0.07 \Rightarrow N = 2035$

```
[13]: probabilities5 = probabilities1[:samples[-5]]
```

```
[14]: prec = precision[-5]
print(len(probabilities5) == samples[-5])

mean5 = np.mean(probabilities5)
std5 = np.std(probabilities5)
error5 = sqrt(20) * std5 / sqrt(len(probabilities5))

print(f'p= {round(mean5, 4)} +/- {round(error5, 4)}')
print(error5 < prec)
```

True
p= 0.0029 +/- 0.0325
True

1.6 $\epsilon = 0.09 \Rightarrow N = 1231$

```
[15]: probabilities6 = probabilities1[:samples[-6]]
```

```
[16]: prec = precision[-6]
print(len(probabilities6) == samples[-6])

mean6 = np.mean(probabilities6)
std6 = np.std(probabilities6)
error6 = sqrt(20) * std6 / sqrt(len(probabilities6))

print(f'p= {round(mean6, 4)} +/- {round(error6, 4)}')
print(error6 < prec)
```

True
p= -0.0025 +/- 0.042
True

1.7 $\epsilon = 0.100 \Rightarrow N = 997$

```
[17]: probabilities7 = probabilities1[:samples[-7]]

[18]: prec = precision[-7]
      print(len(probabilities7) == samples[-7])

      mean7 = np.mean(probabilities7)
      std7 = np.std(probabilities7)
      error7 = sqrt(20) * std7 / sqrt(len(probabilities7))

      print(f'p= {round(mean7, 4)} +/- {round(error7, 4)}')
      print(error7 < prec)
```

True

p= -0.0021 +/- 0.0471

True

1.8 Plotting the data:

```
[19]: means = [mean7, mean6, mean5, mean4, mean3, mean2, mean1]
      errors = [error7, error6, error5, error4, error3, error2, error1]

      bot_bar = [means[i] - errors[i] for i in range(len(means))]
      heights = [2*errors[i] for i in range(len(means))]
```

```
[20]: fig = plt.figure()

      plt.bar([i for i in range(len(means))],
              heights,
              width=0.8,
              bottom=bot_bar,
              align='center',
              color='lightblue',
              label='Results: 95% CI')

      plt.errorbar([i for i in range(len(means))],
                   means,
                   color='blue',
                   marker='D',
                   markersize=4,
                   linestyle='None',
                   label='Results: means')

      plt.errorbar([i for i in range(len(means))],
                   [exact_value for _ in range(len(means))],
```

```

        color='green',
        marker='o',
        markersize=4,
        linestyle='None',
        label='Exact result')

plt.errorbar([i for i in range(len(means))],
            means,
            yerr=precision,
            color='red',
            linestyle='None',
            label='Precision bound')

plt.xticks([i for i in range(len(means))], precision, size=14)
plt.xlabel(r'$\epsilon$', fontsize=16)


#plt.ylim([0.05, 0.25])
plt.yticks(size=14)
plt.ylabel(r'$p$', fontsize=16)

plt.legend(fontsize=14)

plt.title('Hybrid PBC - Toffoli0 (3 virtual qubits)', fontsize=18)

plt.show()

```



Note that since the probability cannot be negative, whenever the expectation value is lower than zero we can replace its outcome by zero instead. Additionally, we can also stop the confidence interval (and precision bound) at zero.

```
[21]: new_heights = []
      lower_error = []

      for i in range(len(means)):
          if means[i] < 0:
              means[i] = 0
          new_heights.append(errors[i] + means[i])
          lower_error.append(means[i])

[22]: fig = plt.figure(constrained_layout=True, figsize=(10, 8))

      subfigs = fig.subfigures(2, 1, hspace=0.07)

      # Upper subfigure
      subplot = subfigs[0].add_subplot(111)
      plt.bar([i for i in range(len(means))],
              new_heights,
              width=0.8,
              align='center',
              color='lightblue',
              label='Results: 95% CI')

      plt.errorbar([i for i in range(len(means))],
                   means,
                   color='blue',
                   marker='D',
                   markersize=4,
                   linestyle='None',
                   label='Results: means')

      plt.errorbar([i for i in range(len(means))],
                   [exact_value for _ in range(len(means))],
                   color='green',
                   marker='o',
                   markersize=4,
                   linestyle='None',
                   label='Exact result')

      plt.errorbar([i for i in range(len(means))],
                   means,
                   yerr=[lower_error, precision],
```

```

        color='red',
        linestyle='None',
        label='Precision bound')

plt.plot(np.arange(-1, 8, 1), [exact_value for _ in np.arange(-1, 8, 1)],
        '--',
        color='green',
        linewidth=1)

plt.xlim([-0.75, 6.75])
plt.xticks([i for i in range(len(means))], precision, size=14)
plt.xlabel(r'$\epsilon$', fontsize=16)

plt.ylim([-0.005, 0.10])
plt.yticks(size=14)
plt.ylabel(r'$p$', fontsize=16)

plt.legend(fontsize=14)

plt.title('Hybrid PBC - Toffoli 0 (3 virtual qubits)', fontsize=18)

# Lower subfigure (left)
subplot = subfigs[1].add_subplot(121)
plt.bar([i for i in range(4)],
        new_heights[:4],
        width=0.8,
        align='center',
        color='lightblue',
        label='Results: 95% CI')

plt.errorbar([i for i in range(4)],
             means[:4],
             color='blue',
             marker='D',
             markersize=4,
             linestyle='None',
             label='Results: means')

plt.errorbar([i for i in range(4)], [exact_value for _ in range(4)],
             color='green',
             marker='o',
             markersize=4,
             linestyle='None',
             linewidth=1,
             label='Exact result')

plt.errorbar([i for i in range(4)],

```



```

        means[:4],
        yerr=[lower_error[:4], precision[:4]],
        color='red',
        linestyle='None',
        label='Precision bound')

plt.plot(np.arange(-1, 8, 1), [exact_value for _ in np.arange(-1, 8, 1)],
        '--',
        color='green',
        linewidth=1)

plt.xlim([-0.75, 3.75])
plt.xticks([i for i in range(4)], precision[:4], size=14)
plt.xlabel(r'$\epsilon$', fontsize=16)

plt.ylim([-0.001, 0.04])
plt.yticks(np.arange(0, 0.045, 0.005),
        [round(i, 3) for i in np.arange(0, 0.045, 0.005)],
        size=14)
plt.ylabel(r'$p$', fontsize=16)

# Lower subfigure (right)
subplot = subfigs[1].add_subplot(122)
plt.bar([i for i in range(4)],
        new_heights[3:],
        width=0.8,
        align='center',
        color='lightblue',
        label='Results: 95% CI')

plt.errorbar([i for i in range(4)],
        means[3:],
        color='blue',
        marker='D',
        markersize=4,
        linestyle='None',
        label='Results: means')

plt.errorbar([i for i in range(4)], [exact_value for _ in range(4)],
        color='green',
        marker='o',
        markersize=4,
        linestyle='None',
        label='Exact result')

plt.errorbar([i for i in range(4)],
        means[3:],

```

```

        yerr=[lower_error[3:], precision[3:]],
        color='red',
        linestyle='None',
        label='Precision bound')


plt.plot(np.arange(-1, 8, 1), [exact_value for _ in np.arange(-1, 8, 1)],
        '--',
        color='green',
        linewidth=1)

plt.xlim([-0.75, 3.75])
plt.xticks([i for i in range(4)], precision[3:], size=14)
plt.xlabel(r'$\epsilon$', fontsize=16)

plt.ylim([-0.001, 0.04])
plt.yticks(np.arange(0, 0.045, 0.005),
        [round(i, 3) for i in np.arange(0, 0.045, 0.005)],
        size=14)
plt.ylabel(r'$p$', fontsize=16)

fig.savefig("Probability_vs_precision.pdf", bbox_inches='tight')
plt.show()

```



[]: