

Lab Final

Course Code: CL205	Course Name: Operating Systems Lab
Instructor Name: Sumaiyah Zahid	
Student Roll No:	Section:

"If there is something, you don't know today. You will surely learn afterwards. Life is not an exam hall."
BEST OF LUCK!

Instructions

- Rules are made to break them. So, invent yours and I'll break.

Time: 90 minutes

Max Marks: 40 points

This program will create ____ child processes and ____ threads?

(5 marks)

```
int main()
{
    printf("OS\n");
    fork();
    pthread_create(&tid, NULL, thread, NULL);
    fork();
    printf("OS\n");
    pthread_create(&tid, NULL, thread, NULL);
    fork();
    pthread_create(&tid, NULL, thread, NULL);
    return 0;
}
```

Output

```
int main() {
    printf("%d\n", getpid());
    a=fork();
    printf("%d\n", getpid());
    if (a==0){
        printf("%d\n", getpid());
        fork();
        printf("%d\n", getpid());
    }
    printf("    Done!\n");
return 0;
}
```

Output

Write appropriate system calls in the blanks**(5 marks)**

```
int main(void) {
    int shmid;
    key_t key;
    char *shm, *s;
    key = 2211;
    fflush(stdin);
    if((shmid = _____(key, MAXSIZE, IPC_CREAT | 0666)) < 0)
        die("error");
    if((shm = _____ ( _____, NULL, 0)) == (char*) -1)
        die("error");
    for(s = shm; *s != '\0'; s++)
        putchar(*s);
    *shm = '*';
    printf("\n");
    exit(0);
}
```

Advantage of FIFO over pipe is

- a) related processes can communicate
- b) unrelated processes can communicate
- c) all of the mentioned
- d) none of the mentioned

Which is Fastest IPC?

- a) Message Queue
- b) shared memory
- c) Socket
- d) All of the mentioned

What are the two basic function for any module?**(5 marks)**

- 1. _____
- 2. _____

Command for compiling module _____

Command for module details _____

What is the output on the terminal after compiling?

```
printk(KERN_INFO "Hello World. \n");
printk(KERN_INFO "Final Paper of OS");
printk("GoodBye");
return 0;
```

In which pattern pthread_create and pthread_join can create a serial execution of threads and parallel. Illustrate by writing code for 3 threads.

(2 marks)


True or false: Code in an OpenMP program that is not covered by a pragma is executed by all threads. (1 marks)

Procom has 4 volunteers on their front desk.

- Volunteer 1 manages On day registration
- Volunteer 2 handles announcements
- Volunteer 3 handles sponsors
- Volunteer 4 resolve queries of participants

Implement this system using OpenMP for total 100 participants. Asuming 25 participants for each volunteer. (5 marks)

Write a sketch of a C program that uses Pthreads to execute the five functions in a way that is maximally parallel, but adheres to the above dependency graph.
 The edge from node B to node D means that functionB must be called, and must return, before functionD can be called. **(2 marks)**



Write all possible output on executing the code below?

(3 marks)

sem_t mutex;

Output

```

void* thread(void* arg)
{
    int a= *((int*)arg);
    printf("\nEnter...\n");
    sem_wait(&mutex);
    printf("\n %d Entered..\n",a);
    sleep(4);
    printf("\nJust Exiting...\n");
    sem_post(&mutex);
}
int main()
{
    sem_init(&mutex, 0, 1);
    pthread_t t1,t2;
    
```

```
pthread_create(&t1,NULL,thread,&0);
pthread_create(&t2,NULL,thread,&1);
pthread_join(t1,NULL);
pthread_join(t2,NULL);
sem_destroy(&mutex);
return 0;
}
```

The classic problems of producers (such as CPUs) and consumers (such as a printers) concerns one or more process data that one or more process consumes later through a single buffer. Systems must make sure that the producer won't try to add data to full a buffer, and the consumer won't try to make withdrawals from an empty buffer. And for the integrity of data only one process must be allowed to access the buffer at a time. Assume buffer contain 5 files maximum, design the procedures and consumers' processes using semaphores. **(5 marks)**

Write a code snippet which sets default behavior of ctrl+\, ignores ctrl+Z, assign funcA to ctrl+C.and func B to floating point error.
(5 marks)

Write output on executing the code below?

(2 marks)

```
int main(void)
{
    int child_pid, i;
    child_pid = fork();
    if (child_pid == 0)
    {
        for (i = 0; i < 20000000; i++)
        {
        }
        cout << "Bye from Child!" << endl;
    }
    else
    {
        sleep(1);
        kill(child_pid, SIGINT);
        cout << "Bye from Parent " << endl;
    }
}
```

Output

