



descramblerVerimatrix

Reference Manual

Version 1.3

19/12/2024

TABLE OF CONTENTS

1	Overview	3
2	descramblerVerimatrixClient (1.1)	4
2.1	Overview	4
2.2	Command Reference	4
2.2.1	GetClients	4
2.2.2	SetClients	4
2.2.3	DeleteClients	4
2.3	Type Reference	4
2.3.1	ClientConfig	4
2.3.2	DeleteClients.Request	5
2.3.3	DeleteClients.Response	5
2.3.4	GetClients.Request	5
2.3.5	GetClients.Response	5
2.3.6	GetClientsResponse	5
2.3.7	PaginationInfo	5
2.3.8	SetClients.Request	5
2.3.9	SetClients.Response	5
3	descramblerVerimatrixService (1.0)	6
3.1	Command Reference	6
3.1.1	GetServices	6
3.1.2	SetServices	6
3.1.3	DeleteServices	6
3.2	Type Reference	6
3.2.1	DeleteServices.Request	6
3.2.2	DeleteServices.Response	6
3.2.3	GetServices.Request	6
3.2.4	GetServices.Response	6
3.2.5	GetServicesResponse	6
3.2.6	PaginationInfo	7
3.2.7	ParentalGuidance	7
3.2.8	ServiceConfig	7
3.2.9	SetServices.Request	7
3.2.10	SetServices.Response	7
4	descramblerVerimatrixStatus (1.2)	8
4.1	Overview	8
4.2	Command Reference	8
4.2.1	GetClientStatus	8
4.2.2	GetStreamStatus	8
4.3	Type Reference	8
4.3.1	ClientStatus	8
4.3.2	GetClientStatus.Request	8
4.3.3	GetClientStatus.Response	9
4.3.4	GetStreamStatus.Request	9
4.3.5	GetStreamStatus.Response	9
4.3.6	StreamStatus	9
4.3.7	UuidList	9
5	validate (1.0)	10
5.1	Type Reference	10
5.1.1	BigIntRange	10
5.1.2	FloatRange	10
5.1.3	IntRange	10
5.1.4	Result	10

1 Overview

Changelog:

1.3

- **Added**
 - descramblerVerimatrixService version 1.0 was added

1.2

- **Changed**
 - descramblerVerimatrixClient version was bumped to 1.1
 - descramblerVerimatrixStatus version was bumped to 1.2

1.1

- **Changed**
 - descramblerVerimatrixStatus version was bumped to 1.1

2 descramblerVerimatrixClient (1.1)

2.1 Overview

Changelog:

1.1

- Added
 - The optional field operatorId was added to the type ClientConfig

2.2 Command Reference

2.2.1 GetClients

- message **GetClients.Request**
- message **GetClients.Response**

2.2.2 SetClients

- message **SetClients.Request**
- message **SetClients.Response**

2.2.3 DeleteClients

- message **DeleteClients.Request**
- message **DeleteClients.Response**

2.3 Type Reference

2.3.1 ClientConfig

Verimatrix Client Config

struct

serverIp	string Ip of the CA server
serverPort	int Port on the CA Server to use
timeout	int (seconds) Time before the connection resets
meab	optional string (optional) middleware authenticator, used to pass data to the CA server
operatorId	optional int (optional) When set, only ECMs with matching OperatorId are be decrypted and used

2.3.2 DeleteClients.Request

struct

ids **list of UUID**

2.3.3 DeleteClients.Response

empty **struct**

2.3.4 GetClients.Request

empty **struct**

2.3.5 GetClients.Response

GetClientsResponse

2.3.6 GetClientsResponse

struct

data **map** from **UUID** to **ClientConfig**
A map of outputs returned by the request.

info **PaginationInfo**
Meta information about the data - i.e the total number of items on the server

2.3.7 PaginationInfo

struct

totalEntries **int**

2.3.8 SetClients.Request

struct

data **map** from **UUID** to **ClientConfig**

2.3.9 SetClients.Response

empty **struct**

3 descramblerVerimatrixService (1.0)

3.1 Command Reference

3.1.1 GetServices

- message **GetServices.Request**
- message **GetServices.Response**

3.1.2 SetServices

- message **SetServices.Request**
- message **SetServices.Response**

3.1.3 DeleteServices

- message **DeleteServices.Request**
- message **DeleteServices.Response**

3.2 Type Reference

3.2.1 DeleteServices.Request

struct

ids **list of UUID**

3.2.2 DeleteServices.Response

empty **struct**

3.2.3 GetServices.Request

empty **struct**

3.2.4 GetServices.Response

GetServicesResponse

3.2.5 GetServicesResponse

struct

data **map** from **UUID** to **ServiceConfig**
A map of outputs returned by the request.

info **PaginationInfo**
Meta information about the data - i.e the total number of items on the server.

3.2.6 PaginationInfo

struct

totalEntries **int**

3.2.7 ParentalGuidance

Verimatrix Parental Guidance

struct

pid **int**
Preferred PID of the SCTE35 message. Valid PID range is [0x20, 0x1FAA].

3.2.8 ServiceConfig

Verimatrix Service Config

struct

service **UUID**
UUID of the DescramblerService object this setting is related to.

parentalGuidance **optional ParentalGuidance**
If set, a SCTE35 message containing the Verimatrix parental guidance rating level will be sent in the descrambled Transport Stream.

3.2.9 SetServices.Request

struct

data **map** from **UUID** to **ServiceConfig**

3.2.10 SetServices.Response

empty **struct**

4 descramblerVerimatrixStatus (1.2)

4.1 Overview

Changelog:

1.2

- Added
 - The rpc GetStreamStatus and the type StreamStatus are added

1.1

- Added
 - The optional field uniqueIdentifier was added to the type ClientStatus

4.2 Command Reference

4.2.1 GetClientStatus

Get status for clients

- message **GetClientStatus.Request**
- message **GetClientStatus.Response**

4.2.2 GetStreamStatus

Get status for clients

- message **GetStreamStatus.Request**
- message **GetStreamStatus.Response**

4.3 Type Reference

4.3.1 ClientStatus

State of descrambler client

struct

ecmCount	optional int Total number of successfully parsed ECMs
uniqueIdentifier	optional string VCAS client library unique identifier

4.3.2 GetClientStatus.Request

struct

ids	optional list of UUID
-----	------------------------------

4.3.3 GetClientStatus.Response

struct

data **map** from **UUID** to **ClientStatus**

4.3.4 GetStreamStatus.Request

struct

ids **optional list** of **UUID**

4.3.5 GetStreamStatus.Response

struct

data **map** from **UUID** to **StreamStatus**

4.3.6 StreamStatus

State of descrambler stream

struct

ratingLevel **optional int**
(optional number) 0-255, rating set in the ECM

4.3.7 UuidList

list of **UUID**

5 validate (1.0)

5.1 Type Reference

5.1.1 BigIntRange

struct

min	bigint
max	bigint

5.1.2 FloatRange

Float Range

struct

min	float Minimum value of the range
max	float Maximum value of the range

5.1.3 IntRange

Integer Range

struct

min	int Minimum value of the range
max	int Maximum value of the range

5.1.4 Result

Validation result

struct

result	bool True if config is valid and false otherwise.
msg	optional string An error message, which may be given if the result is invalid.