



hipEnc:1.7

API Reference

X Platform, IP JPEG XS Encoder 2110 1.18.0

13/08/2025

TABLE OF CONTENTS

1	Overview	7
2	commonTypes (1.0)	9
2.1	Type Reference	9
2.1.1	NmosVersionNumber	9
3	firewallTypes (1.0)	10
3.1	Type Reference	10
3.1.1	IpAddress	10
3.1.2	PaginatedRequest	10
3.1.3	PaginationInfo	10
3.1.4	SocketAddress	10
3.1.5	UUID	10
4	hipCardSettings (1.0)	11
4.1	Command Reference	11
4.1.1	GetCardSettings	11
4.1.2	SetCardSettings	11
4.2	Type Reference	11
4.2.1	CardSettings	11
4.2.2	ClockMode	11
4.2.3	GetCardSettings.Request	11
4.2.4	GetCardSettings.Response	11
4.2.5	SetCardSettings.Request	12
4.2.6	SetCardSettings.Response	12
5	hipEncStatus (1.4)	13
5.1	Overview	13
5.2	Command Reference	13
5.2.1	GetEncoderTransportStatus	13
5.2.2	ClearAllCounters	14
5.3	Type Reference	14
5.3.1	ClearAllCounters.Request	14
5.3.2	ClearAllCounters.Response	14
5.3.3	EncoderTransportStatus	14
5.3.4	EncoderTransportStatusRequest	14
5.3.5	EncoderTransportStatusResponse	14
5.3.6	EssenceTransportStatus	14
5.3.7	GetEncoderTransportStatus.Request	15
5.3.8	GetEncoderTransportStatus.Response	15
5.3.9	NetworkLatencyStatus	15
5.3.10	RTPStatus	15
5.3.11	SeamlessStatus	15
5.3.12	TransportStatus	16
6	hipEncTransport (1.4)	17
6.1	Overview	17
6.2	Type Reference	17
6.2.1	InputUdpSeamless	17
6.2.2	InputUdpSeamless.preferred	17
6.2.3	InputUdpSettings	18
6.2.4	SourceSettings	18
7	hipEncTypes (1.4)	19
7.1	Overview	19
7.2	Type Reference	19
7.2.1	AncPolicing	19
7.2.2	AudioPolicing	19
7.2.3	OptimalizationTarget	20
7.2.4	VideoPolicing	20

8	hipEncoder (1.4)	21
8.1	Overview	21
8.2	Command Reference	21
8.2.1	GetEncoders	21
8.2.2	SetEncoders	22
8.2.3	DeleteEncoders	22
8.3	Type Reference	22
8.3.1	DeleteEncoders.Request	22
8.3.2	DeleteEncoders.Response	22
8.3.3	Encoder	22
8.3.4	EncoderAncEssence	22
8.3.5	EncoderAudioEssence	23
8.3.6	EncoderEssenceSettings	23
8.3.7	EncoderSource2110	23
8.3.8	EncoderVideoEssence	23
8.3.9	GetEncoders.Request	24
8.3.10	GetEncoders.Response	24
8.3.11	JpegXsEncoding	24
8.3.12	SetEncoders.Request	24
8.3.13	SetEncoders.Response	24
9	hipIpInterface (1.2)	25
9.1	Overview	25
9.2	Command Reference	25
9.2.1	GetIpInterfaces	25
9.2.2	SetIpInterfaces	25
9.2.3	DeleteIpInterfaces	25
9.2.4	GetLldpNeighbors	25
9.3	Type Reference	25
9.3.1	DeleteIpInterfaces.Request	25
9.3.2	DeleteIpInterfaces.Response	26
9.3.3	GetIpInterfaces.Request	26
9.3.4	GetIpInterfaces.Response	26
9.3.5	GetLldpNeighbors.Request	26
9.3.6	GetLldpNeighbors.Response	26
9.3.7	GetLldpNeighborsRequest	26
9.3.8	GetLldpNeighborsResponse	26
9.3.9	IpInterface	26
9.3.10	IpInterfaceConfig	27
9.3.11	QuadPortName	27
9.3.12	SetIpInterfaces.Request	27
9.3.13	SetIpInterfaces.Response	27
10	hipNetworkStatus (1.3)	28
10.1	Overview	28
10.2	Command Reference	28
10.2.1	GetNetworkStatus	28
10.2.2	GetSfpStatus	28
10.3	Type Reference	28
10.3.1	GetNetworkStatus.Request	28
10.3.2	GetNetworkStatus.Response	28
10.3.3	GetSfpStatus.Request	28
10.3.4	GetSfpStatus.Response	28
10.3.5	GetSfpStatusRequest	29
10.3.6	GetSfpStatusResponse	29
10.3.7	LinkSpeed	29
10.3.8	NetworkStatus	29
10.3.9	NetworkStatusRequest	29
10.3.10	NetworkStatusResponse	30
11	hipPhysicalPorts (1.1)	31
11.1	Overview	31

11.2	Command Reference	31
11.2.1	GetPhysicalPorts	31
11.2.2	SetPhysicalPorts	31
11.3	Type Reference	31
11.3.1	GetPhysicalPorts.Request	31
11.3.2	GetPhysicalPorts.Response	31
11.3.3	GetPhysicalPortsResponse	31
11.3.4	PhysicalPort	31
11.3.5	SetPhysicalPorts.Request	32
11.3.6	SetPhysicalPorts.Response	32
11.3.7	SetPhysicalPortsRequest	32
12	hipStatus (1.4)	33
12.1	Overview	33
12.2	Command Reference	33
12.2.1	GetEssenceStatus	33
12.2.2	GetThumbnailPath	33
12.3	Type Reference	33
12.3.1	AncStatus	33
12.3.2	AudioStatus	34
12.3.3	DataIdentifier	34
12.3.4	EssenceStatus	34
12.3.5	EssenceStatusRequest	34
12.3.6	EssenceStatusResponse	35
12.3.7	EssenceThumbnailPathRequest	35
12.3.8	EssenceThumbnailPathResponse	35
12.3.9	GetEssenceStatus.Request	35
12.3.10	GetEssenceStatus.Response	35
12.3.11	GetThumbnailPath.Request	35
12.3.12	GetThumbnailPath.Response	35
12.3.13	VideoStatus	36
13	hipTestGenerator (1.0)	37
13.1	Type Reference	37
13.1.1	BitmapBackgroundProperty	37
13.1.2	Color	37
13.1.3	MovingBox	37
13.1.4	TestPattern	37
13.1.5	TextOverlay	37
13.1.6	TextPosition	38
13.1.7	VideoTestGenerator	38
14	hipTypes (1.4)	39
14.1	Overview	39
14.2	Type Reference	39
14.2.1	AudiolIndex	39
14.2.2	CodingCore	39
14.2.3	FrameRate	40
14.2.4	NumberOfChannels	40
14.2.5	Order	40
14.2.6	ResolutionScan	40
14.2.7	SignalLossAction	41
14.2.8	SignalLossActionAnc	41
14.2.9	SignalLossActionAudio	41
14.2.10	SignalLossActionVideo	41
14.2.11	SocketAddress	42
14.2.12	St2110AudioPacketTime	42
14.2.13	StartChannel	42
14.2.14	TimeReference	42
14.2.15	VideoFormat	42
15	hipValidate (1.0)	44

15.1	Type Reference	44
15.1.1	FloatRange	44
15.1.2	IntRange	44
15.1.3	Result	44
16	linkModes (1.3)	45
16.1	Type Reference	45
16.1.1	IpFecMode	45
16.1.2	IpLinkMode	45
16.1.3	IpLinkSpeed	45
17	Ildp (1.1)	46
17.1	Overview	46
17.2	Type Reference	46
17.2.1	IldpMedInventory	46
17.2.2	IldpMode	46
17.2.3	IldpNeighbor	46
17.2.4	IldpNeighborStruct	46
18	IldpProtocols (1.0)	48
19	networkManagerProtocols (1.1)	49
19.1	Overview	49
20	nmosConfig (1.0)	50
20.1	Type Reference	50
20.1.1	NmosConfig	50
21	nmosLabelConfig (1.0)	51
21.1	Overview	51
21.2	Type Reference	52
21.2.1	EssenceTypeStrings	52
21.2.2	NmosLabelConfig	52
21.2.3	ResourceLabelTemplates	52
22	nmosRegistryConfig (1.0)	53
22.1	Type Reference	53
22.1.1	DnsConfig	53
22.1.2	DnsConfig.mDns	53
22.1.3	DnsSdConfig	53
22.1.4	NmosRegistryConfigStruct	53
22.1.5	RegistryManualConfig	53
23	nmosRegistryStatus (1.0)	55
23.1	Type Reference	55
23.1.1	NmosRegistryStatus	55
24	nmosStatus (1.1)	56
24.1	Overview	56
24.2	Command Reference	56
24.2.1	GetNmosStatus	56
24.3	Type Reference	56
24.3.1	GetNmosStatus.Request	56
24.3.2	GetNmosStatus.Response	56
25	nmosStatusTypes (1.0)	57
25.1	Type Reference	57
25.1.1	NmosStatus	57
26	physicalIpPort (1.0)	58
26.1	Type Reference	58
26.1.1	PortName	58
27	sfpConstants (1.3)	59

27.1	Type Reference	59
27.1.1	Identifier	59
27.1.2	Transceiver	59
28	sfpStatus (1.4)	61
28.1	Type Reference	61
28.1.1	SfpDiagnostics	61
28.1.2	SfpStatus	61
29	st2110Types (1.1)	63
29.1	Type Reference	63
29.1.1	St2110Standard	63
30	st2110TypesLabels (1.1)	64

1 Overview

Changelog:

1.7

- **Changed**

- The imported package nmosConfig is bumped from 1.0 to 1.1.
- The imported package hipCardSettings is bumped from 1.2 to 1.3.

1.6

- **Added**

- nmosStatus 1.1.

1.5

- **Changed**

- hipEncoder from 1.3 to 1.4.
- hipEncTransport from 1.3 to 1.4.
- hipEncStatus from 1.3 to 1.4.
- hipEncTypes from 1.3 to 1.4.
- hipStatus from 1.3 to 1.4.
- hipTypes from 1.3 to 1.4.
- hipIpInterface from 1.0 to 1.2.
- hipNetworkStatus from 1.2 to 1.3.
- hipPhysicalPorts from 1.0 to 1.1.

- **Added**

- Added lldp 1.1.
- Added networkManagerProtocols 1.1.
- Added lldpProtocols 1.0.
- Added linkModes 1.3.

1.4

- **Changed**

- hipEncoder from 1.2 to 1.3.
- hipEncStatus from 1.2 to 1.3.
- hipEncTypes from 1.2 to 1.3.
- hipEncTransport from 1.2 to 1.3.
- hipStatus from 1.2 to 1.3.
- hipTypes from 1.2 to 1.2.

1.3

- **Added**

- hipIpInterface 1.0.

- hipNetworkStatus 1.0.
- hipPhysicalPorts 1.0.
- hipCardSettings 1.0.
- sfpConstants 1.0.
- sfpStatus 1.0.

1.2

- **Added**

- hipTestGenerator 1.0.

- **Changed**

- hipEncoder from 1.1 to 1.2.
- hipEncStatus from 1.1 to 1.2.
- hipEncTransport from 1.1 to 1.2.
- hipEncTypes from 1.1 to 1.2.
- hipStatus from 1.1 to 1.2.
- hipTypes from 1.1 to 1.2.

1.1

- **Changed**

- hipEncoder from 1.0 to 1.1;
- hipEncStatus from 1.0 to 1.1;
- hipEncTransport from 1.0 to 1.1;
- hipEncTypes from 1.0 to 1.1;
- hipStatus from 1.0 to 1.1;
- hipTypes from 1.0 to 1.1;

2 commonTypes (1.0)

2.1 Type Reference

2.1.1 NmosVersionNumber

Generic version number type for NMOS APIs

enum

V1_2

V1_3

3 firewallTypes (1.0)

3.1 Type Reference

3.1.1 IPAddress

string

3.1.2 PaginatedRequest

Instructs the server to return only a subset of the data found on the server

@param pageSize number of entries returned per request

@param pageNumber what page of the set to returned, determined by the slice [pageSize*pageNumber

struct

pageSize	int
pageNumber	int

3.1.3 PaginationInfo

struct

totalEntries	int
--------------	-----

the total number of entries on the server, before matching

3.1.4 SocketAddress

Tuple with IP address and port

struct

address	IPAddress
port	int

IP address, either IPv4 or IPv6

3.1.5 UUID

string

4 hipCardSettings (1.0)

4.1 Command Reference

4.1.1 GetCardSettings

- message **GetCardSettings.Request**
- message **GetCardSettings.Response**

4.1.2 SetCardSettings

CAUTION: always use the same UUID as the object all ready existing on the card.

- message **SetCardSettings.Request**
- message **SetCardSettings.Response**

4.2 Type Reference

4.2.1 CardSettings

- Settings for the operational mode of the card.
-
-

struct

clockMode

ClockMode

Type of clock synchronization protocol the card should use

4.2.2 ClockMode

Different types of clock synchronization protocols

enum

PTP

Sets the card to Precision Time Protocol (IEEE 1588)(PTP) time synchronization

LOCAL

Sets the card to Network Time Protocol (NTP) time synchronization or local clock if the card does not get a NTP lock.

4.2.3 GetCardSettings.Request

empty **struct**

4.2.4 GetCardSettings.Response

struct

data

map from **UUID** to **CardSettings**

4.2.5 SetCardSettings.Request

struct

data **map** from **UUID** to **CardSettings**

4.2.6 SetCardSettings.Response

empty **struct**

5 hipEncStatus (1.4)

5.1 Overview

Changelog:

1.4

- **Changed**
 - The imported package hipTypes is bumped from 1.3 to 1.4.

1.3

- **Changed**
 - The imported package hipTypes is bumped from 1.2 to 1.3.

1.2

- **Added**
 - The Command ClearAllCounters is added.
- **Changed**
 - The imported package hipTypes is bumped from 1.1 to 1.2.
 - The fields rtpSsrc and rtpPayloadType on type RTPStatus are changed from being int to being optional(int).
 - The fields packetsMissing and sequenceErrors on type RTPStatus are changed from type int to type bigint.
 - The field rtpStatus on type TransportStatus is no longer optional.

1.1

- **Added**
 - The type SeamlessStatus is added.
 - The field seamlessStatus is added to the type EssenceTransportStatus;
- **Changed**
 - The imported package hipTypes is bumped from 1.0 to 1.1.
 - The field timeReference on type NetworkLatencyStatus changes type from hipEncTypes.TimeReference to hipTypes.TimeReference.
- **Removed**
 - The imported package hipEncTypes 1.0 is removed.

5.2 Command Reference

5.2.1 GetEncoderTransportStatus

- message **GetEncoderTransportStatus.Request**
- message **GetEncoderTransportStatus.Response**

5.2.2 ClearAllCounters

- message **ClearAllCounters.Request**
- message **ClearAllCounters.Response**

5.3 Type Reference

5.3.1 ClearAllCounters.Request

empty **struct**

5.3.2 ClearAllCounters.Response

empty **struct**

5.3.3 EncoderTransportStatus

Encoder Transport Status

Status is reported for all configured essences.

struct

videoStatus	optional EssenceTransportStatus Video essence status
audioStatus	map from hipTypes.AudioIndex to EssenceTransportStatus Map of audio essence status
ancStatus	optional EssenceTransportStatus Anc essence status

5.3.4 EncoderTransportStatusRequest

struct

ids	optional list of UUID
-----	-------------------------------------

5.3.5 EncoderTransportStatusResponse

struct

data	map from UUID to EncoderTransportStatus
------	--

5.3.6 EssenceTransportStatus

Transport Status for an Essence

struct

pathA	optional TransportStatus Status for port D1 (empty if D1 not configured)
pathB	optional TransportStatus Status for port D2 (empty if D2 not configured)

seamlessStatus

optional SeamlessStatus

Seamless status (empty if seamless not configured)

5.3.7 GetEncoderTransportStatus.Request**EncoderTransportStatusRequest****5.3.8 GetEncoderTransportStatus.Response****EncoderTransportStatusResponse****5.3.9 NetworkLatencyStatus**

Network latency status

struct

timeReference

hipTypes.TimeReference

Time reference protocol

minDelay

float

Minimum timestamp difference (millisec)

maxDelay

float

Maximum timestamp difference (millisec)

5.3.10 RTPStatus

RTP status

struct

bitrate

float

packetsMissing

bigint

sequenceErrors

bigint

rtpPayloadType

optional int

rtpSsrc

optional int**5.3.11 SeamlessStatus**

Seamless status

struct

relativeDelay

int

Delay between inputs (millisec)

margin

int

Difference between relative delay and configured delay (millisec)

synchronised

bool

Inputs are synchronised (bool)

rtpSequenceErrors

int

Number of RTP sequence errors fixed by seamless

5.3.12 TransportStatus

Transport Status for a Single Path

struct

rtpStatus	RTPStatus RTP status
networkLatencyStatus	optional NetworkLatencyStatus Network latency status (empty if no bitrate)

6 hipEncTransport (1.4)

6.1 Overview

Changelog:

1.4

- **Changed**
 - The imported package hipTypes is bumped from 1.3 to 1.4.
 - InputUdpSettings sources field is changed to an optional string named source, to reflect the fact we only support a single source for the IGMPv3 SSM.

1.3

- **Changed**
 - The imported package hipTypes is bumped from 1.2 to 1.3.

1.2

- **Changed**
 - The imported package hipTypes is bumped from 1.1 to 1.2.

1.1

- **Changed**
 - The imported package hipTypes is bumped from 1.0 to 1.1.

6.2 Type Reference

6.2.1 InputUdpSeamless

Set the input in seamless transport mode (SMTPE-2022-7)

The two sources, a and b, must be setup at different interfaces

struct

a	InputUdpSettings UDP settings for the A pipe
b	InputUdpSettings UDP settings for the B pipe
preferred	InputUdpSeamless.preferred Preferred pipe
identical	bool Means the expected sources are 2022-7 compliant, i.e identical; If they are not a proper alarm will be raised
inputBufferSize	int Buffer for reconstructing missing packets on the input (1-400ms) [default 20ms]

6.2.2 InputUdpSeamless.preferred

enum

A
B
FLOATING

6.2.3 InputUdpSettings

UDP input settings

If destination is a multicast address IGMP join will be performed. A destination must be unique for a given interface.

struct

interfaceId	UUID Interface used
destination	hipTypes.SocketAddress Unicast or multicast address
source	optional string Optional IGMPv3 source address

6.2.4 SourceSettings

Source Settings of UDP input

variant

seamless	InputUdpSeamless Multiple sources in seamless mode (SMTPE-2022-7)
single	InputUdpSettings Single source

7 hipEncTypes (1.4)

7.1 Overview

Changelog:

1.4

- **Changed**
- The imported package hipTypes is bumped from 1.3 to 1.4.

1.3

- **Changed**
- The imported package hipTypes is bumped from 1.2 to 1.3.

1.2

- **Added**
 - The imported package hipTypes 1.2 is added.
- **Changed**
 - The type of the field format on type VideoPolicing are changed from VideoFormat to hipTypes.VideoFormat.
- **Removed**
 - The types ResolutionScan, FrameRate and VideoFormat are removed.

1.1

- ****Removed****
- The type TimeReference is removed.

7.2 Type Reference

7.2.1 AncPolicing

Ancillary Policing

Policing on the ancillary essence.

struct

maxBitrate

optional float

(Optional) Maximum policed bitrate of the ancillary essence [Mbps]

7.2.2 AudioPolicing

Audio Policing

Police on the Audio essences.

struct

optional float

maxBitrate

(Optional) Maximum policed bitrate of the audio essence
[Mbps]

7.2.3 OptimizationTarget

Optimization Target

Target of encoding optimization

enum

VISUAL

Optimize for optimal visuals

PSNR

Optimize for maximized Peak Signal To Noise Ratio

7.2.4 VideoPolicing

Video Policing

Policing on the video essence.

struct

maxBitrate

optional float

(Optional) Maximum policed bitrate of the video essence
[Mbps]

format

optional hipTypes.VideoFormat

(Optional) Allowed format of input video

8 hipEncoder (1.4)

8.1 Overview

Changelog:

1.4

- **Changed**

- The imported package hipEncTransport is bumped from 1.3 to 1.4.
- The imported package hipEncTypes is bumped from 1.3 to 1.4.
- The imported package hipTypes is bumped from 1.3 to 1.4.

1.3

- **Changed**

- The imported package hipTypes is bumped from 1.2 to 1.3.
- The imported package hipEncTypes is bumped from 1.2 to 1.3.
- The imported package hipEncTransport is bumped from 1.2 to 1.3.
- The field coreType in type JpegXsEncoding is added.

1.2

- **Added**

- The imported package hipTestGenerator 1.0 is added.
- The field testGenerator is added to EncoderVideoEssence;

- **Changed**

- The imported package hipEncTransport is bumped from 1.1 to 1.2.
- The imported package hipTypes is bumped from 1.1 to 1.2.
- The imported package hipEncTypes is bumped from 1.1 to 1.2.

1.1

- **Changed**

- The imported package hipEncTransport is bumped from 1.0 to 1.1.
- The imported package hipTypes is bumped from 1.0 to 1.1.
- The imported package hipEncTypes is bumped from 1.0 to 1.1.

8.2 Command Reference

8.2.1 GetEncoders

Get Encoder objects from database.

- message **GetEncoders.Request**
- message **GetEncoders.Response**

8.2.2 SetEncoders

Update Encoder objects in database.

- message **SetEncoders.Request**
- message **SetEncoders.Response**

8.2.3 DeleteEncoders

Delete Encoder objects from database.

- message **DeleteEncoders.Request**
- message **DeleteEncoders.Response**

8.3 Type Reference

8.3.1 DeleteEncoders.Request

struct

ids **list** of **UUID**

8.3.2 DeleteEncoders.Response

empty **struct**

8.3.3 Encoder

Encoder Config

Encoder configuration

struct

enable	bool Enable / disable encoder
label	string User label
source	EncoderSource2110 ST2110 source struct
onSignalLoss	hipTypes.SignalLossAction Action on signal loss

8.3.4 EncoderAncEssence

Encoder ST2110 Anc Essence

Specification for ST2110 ancillary essence source

struct

settings	EncoderEssenceSettings Essence settings
	hipEncTypes.AncPolicing

policing	Ancillary policing rules
----------	--------------------------

8.3.5 EncoderAudioEssence

Encoder ST2110 Audio Essence

Specification for ST2110 audio essence source

struct

settings	EncoderEssenceSettings Essence settings
st2110Standard	st2110Types.St2110Standard ST2110 audio standard
policing	hipEncTypes.AudioPolicing Essence policing rules

8.3.6 EncoderEssenceSettings

Encoder ST2110 Essence Settings

Settings for ST2110 essence source

struct

enable	bool Enable essence
label	string User label of essence
source	hipEncTransport.SourceSettings Transport settings

8.3.7 EncoderSource2110

Encoder ST2110 Source

Specification of ST2110 source

struct

videoEssence	optional EncoderVideoEssence Optional Video essence of source
audioEssences	map from hipTypes.AudioIndex to EncoderAudioEssence Map over audio essences
ancEssence	optional EncoderAncEssence Optional ancillary essence

8.3.8 EncoderVideoEssence

Encoder ST2110 Video Essence

Specification for ST2110 video essence source

struct

settings	EncoderEssenceSettings Essence settings
st2110Standard	st2110Types.St2110Standard ST2110 video standard
policing	hipEncTypes.VideoPolicing Essence policing rules
testGenerator	hipTestGenerator.VideoTestGenerator Video TestGenerator settings
encoding	optional JpegXsEncoding Encoding settings (set empty for passthrough)

8.3.9 GetEncoders.Request

empty **struct**

8.3.10 GetEncoders.Response

struct

data **map** from **UUID** to **Encoder**

8.3.11 JpegXsEncoding

Jpeg Xs Encoding Settings

struct

compressedBitrate	float Target bitrate [Mbps]
optimizationTarget	hipEncTypes.OptimizationTarget Optimization Target
coreType	hipTypes.CodingCore Type of encoding core

8.3.12 SetEncoders.Request

struct

data **map** from **UUID** to **Encoder**

8.3.13 SetEncoders.Response

empty **struct**

9 hiplInterface (1.2)

9.1 Overview

Changelog:

1.2

- **Changed**
 - The imported package hipPhysicalPorts is bumped from 1.0 to 1.1.

1.1

- **Added**
 - The lldp field is added to the IpInterface object.
 - The GetLldpNeighbors RPC is added

9.2 Command Reference

9.2.1 GetIpInterfaces

- message **GetIpInterfaces.Request**
- message **GetIpInterfaces.Response**

9.2.2 SetIpInterfaces

- message **SetIpInterfaces.Request**
- message **SetIpInterfaces.Response**

9.2.3 DeleteIpInterfaces

- message **DeleteIpInterfaces.Request**
- message **DeleteIpInterfaces.Response**

9.2.4 GetLldpNeighbors

Get LLDP Neighbors.

Returns data about the LLDP neighbor seen per interface. To see data for a specific port, LLDP must be enabled for that Interface.

- message **GetLldpNeighbors.Request**
- message **GetLldpNeighbors.Response**

9.3 Type Reference

9.3.1 DeleteIpInterfaces.Request

struct

ids

list of **UUID**

9.3.2 DeleteIpInterfaces.Response

empty **struct**

9.3.3 GetIpInterfaces.Request

empty **struct**

9.3.4 GetIpInterfaces.Response

struct

data **map** from **UUID** to **IpInterface**

9.3.5 GetLldpNeighbors.Request

GetLldpNeighborsRequest

9.3.6 GetLldpNeighbors.Response

GetLldpNeighborsResponse

9.3.7 GetLldpNeighborsRequest

Get LLDP Neighbors Request

struct

interface

optional list of **UUID**

List of UUIDs uniquely identifying IpInterfaces. Only LLDP Neighbors from the specified IpInterfaces are returned. If no value is set, the request will return neighbors from all ports that have LLDP enabled.

details

bool

If false only chassisID, mgmtIP, and portID will be returned for each LLDP Neighbor. If true all available information is returned.

9.3.8 GetLldpNeighborsResponse

struct

data **map** from **UUID** to **optional lldp.LldpNeighbor**

9.3.9 IpInterface

IP Interface

struct

label

string

User label

physicalPortName	physicalIpPort.PortName The physical port used by the ip interface
enabled	bool Enable/disable the IP interface
vlan	int Vlan number. vlan 0 indicates no vlan in use.
quad	optional QuadPortName Interface number when physical port is set to quad mode (4x10G). Is optional.
ipv4	optional IpInterfaceConfig IPv4 interface configuration. Is optional.
ipv6	optional IpInterfaceConfig IPv4 interface configuration. Is optional.
lldp	optional lldp.LldpMode The LldpMode to set for the port. Leaving this empty indicates LLDP off.

9.3.10 IpInterfaceConfig

IP Interface configuration

struct

ipAddress	string IP address
gateway	string Gateway address of the interface
netmask	int Netmask of the interface in CIDR subnet mask notation e.g /24 = 255.255.255.0

9.3.11 QuadPortName

enum

Q1	
Q2	
Q3	
Q4	

9.3.12 SetIpInterfaces.Request

struct

data	map from UUID to IpInterface
------	---

9.3.13 SetIpInterfaces.Response

empty **struct**

10 hipNetworkStatus (1.3)

10.1 Overview

Changelog:

1.3

- Changed
 - The imported package hipPhysicalPorts is bumped from 1.0 to 1.1.

1.2

- Changed
 - The imported package sfpStatus is bumped from 1.3 to 1.4.

1.1

- Added
 - The imported package sfpStatus 1.3 is added.
 - The command GetSfpStatus is added.

10.2 Command Reference

10.2.1 GetNetworkStatus

- message **GetNetworkStatus.Request**
- message **GetNetworkStatus.Response**

10.2.2 GetSfpStatus

- message **GetSfpStatus.Request**
- message **GetSfpStatus.Response**

10.3 Type Reference

10.3.1 GetNetworkStatus.Request

NetworkStatusRequest

10.3.2 GetNetworkStatus.Response

NetworkStatusResponse

10.3.3 GetSfpStatus.Request

GetSfpStatusRequest

10.3.4 GetSfpStatus.Response

GetSfpStatusResponse

10.3.5 GetSfpStatusRequest

Get SFP Status Request

struct

physicalports

optional list of UUID

List of UUIDs uniquely identifying PhysicalPorts. Only SFP Status from the specified PhysicalPorts are returned. If no value is set, the request will return SFP Status from all ports.

10.3.6 GetSfpStatusResponse

struct

data

map from UUID to **sfpStatus.SfpStatus**

10.3.7 LinkSpeed

LinkSpeed

enum

NO_LINK	No linkspeed
LINK_10_MBPS	10 Mbps
LINK_100_MBPS	100 Mbps
LINK_1_GBPS	1 Gbps
LINK_10_GBPS	10 Gbps
LINK_25_GBPS	25 Gbps
LINK_40_GBPS	40 Gbps

10.3.8 NetworkStatus

NetworkStatus

struct

macAddress	string Interface MAC address.
linkSpeed	LinkSpeed Linkspeed on interface.
rx	optional int Received bitrate on interface (kbps). Only applicable for the IP JPEG XS Encoder.
tx	optional int Transmitted bitrate on interface (kbps). Only applicable for the IP JPEG XS Decoder.

10.3.9 NetworkStatusRequest

NetworkStatusRequest

struct

ids

optional list of **UUID**

Optional list of interface uuids

10.3.10 NetworkStatusResponse

NetworkStatusResponse

struct

data

map from **UUID** to **NetworkStatus**

Map of networkstatus with interface uuid as key

11 hipPhysicalPorts (1.1)

11.1 Overview

Changelog:

1.1

- **Changed**
 - The portMode field in PhysicalPort was changed to linkMode and is using the IpLinkMode type from linkModes 1.3.
- **Added**
 - A fecMode field was added to the PhysicalPort object using the IpFecMode type from linkModes 1.3.

11.2 Command Reference

11.2.1 GetPhysicalPorts

- message **GetPhysicalPorts.Request**
- message **GetPhysicalPorts.Response**

11.2.2 SetPhysicalPorts

- message **SetPhysicalPorts.Request**
- message **SetPhysicalPorts.Response**

11.3 Type Reference

11.3.1 GetPhysicalPorts.Request

empty **struct**

11.3.2 GetPhysicalPorts.Response

GetPhysicalPortsResponse

11.3.3 GetPhysicalPortsResponse

struct

data **map** from **UUID** to **PhysicalPort**

11.3.4 PhysicalPort

Physical Port

struct

name **physicalIpPort.PortName**
Name of the physical port

label	string User label
linkMode	linkModes.IpLinkMode Port mode determines link speed and quad mode
fecMode	optional linkModes.IpFecMode Optional FEC mode
enabled	bool Enable / disable the physical port

11.3.5 SetPhysicalPorts.Request

SetPhysicalPortsRequest

11.3.6 SetPhysicalPorts.Response

empty **struct**

11.3.7 SetPhysicalPortsRequest

struct

data **map** from **UUID** to **PhysicalPort**

12 hipStatus (1.4)

12.1 Overview

Changelog:

1.4

- **Changed**
 - The imported package hipTypes is bumped from 1.3 to 1.4.

1.3

- **Changed**
 - The imported package hipTypes is bumped from 1.2 to 1.3.

1.2

- **Changed**
 - The imported package hipTypes is bumped from 1.1 to 1.2.
 - The field format on type VideoStatus is now optional.

1.1

- **Added**
 - The command GetThumbnailPath is added.
 - The field lineNumber is added to type DataIdentifier.
- **Changed**
 - The imported package hipTypes is bumped from 1.0 to 1.1.

12.2 Command Reference

12.2.1 GetEssenceStatus

Get Encoder essence status

- message **GetEssenceStatus.Request**
- message **GetEssenceStatus.Response**

12.2.2 GetThumbnailPath

Get Video thumbnail path

- message **GetThumbnailPath.Request**
- message **GetThumbnailPath.Response**

12.3 Type Reference

12.3.1 AncStatus

Ancillary Status

struct

dataIdentifiers

list of **DataIdentifier**
List of data identifiers

12.3.2 AudioStatus

Audio Status

struct

totalChannels

int
Total number of of Audio Channels

standard

optional st2110Types.St2110Standard
St2110 audio standard

packetTime

hipTypes.St2110AudioPacketTime
Packet time

12.3.3 DataIdentifier

Data Identifiers

The Data Identifier (DID) and Secondary Data Identifier (SDID) words which together indicate a type of ancillary data.

struct

did

int
Data Identifier word

sdid

int
Secondary Data Identifier word

lineNumber

int
Line number of the received DID/SDID pair

12.3.4 EssenceStatus

Essence Status

Status is reported for all configured essences that have bitrate.

struct

videoStatus

optional VideoStatus
Video status

audioStatus

map from **hipTypes.AudioIndex** to **AudioStatus**
Map of audio statuses

ancStatus

optional AncStatus
Ancillary status

12.3.5 EssenceStatusRequest

Essence Status Request

struct

ids

optional list of UUID

Optional list of Encoder/Decoder UUIDs to request status for. If ids are empty, status for all UUIDs present will be returned.

12.3.6 EssenceStatusResponse

Essence Status Response

struct

data

map from **UUID** to **EssenceStatus**

Map from Encoder/Decoder UUID to the related essence status structure.

12.3.7 EssenceThumbnailPathRequest

Essence Thumbnail Path Request

struct

ids

optional list of UUID

Optional list of Encoder/Decoder UUIDs to request thumbnail path for. If ids are empty, status for all UUIDs present will be returned.

12.3.8 EssenceThumbnailPathResponse

Essence Thumbnail Path Response

struct

data

map from **UUID** to **string**

Map from Encoder/Decoder UUID to the related essence thumbnail path.

12.3.9 GetEssenceStatus.Request

EssenceStatusRequest

12.3.10 GetEssenceStatus.Response

EssenceStatusResponse

12.3.11 GetThumbnailPath.Request

EssenceThumbnailPathRequest

12.3.12 GetThumbnailPath.Response

EssenceThumbnailPathResponse

12.3.13 VideoStatus

Video Status

struct

compressed	bool True if compressed, and false if raw
format	optional hipTypes.VideoFormat Video Resolution and Frame Rate

13 hipTestGenerator (1.0)

13.1 Type Reference

13.1.1 BitmapBackgroundProperty

Specifies the color property of the background in a bitmap.

enum

BLACK	
TRANSPARENT	

13.1.2 Color

A color defined in terms of RGB.

struct

red	int
green	int
blue	int

13.1.3 MovingBox

Specify the properties of a moving box to be used in a test image generator.

struct

enabled	bool
color	optional Color

13.1.4 TestPattern

Pattern to display through generator

enum

BLACK_PICTURE	Display black picture
COLOR_BARS	Display color bars

13.1.5 TextOverlay

Specify the properties of a text overlay to put on top of a test image.

Uses the label of the De/Encoder object as text to display. Text will be truncated after 36 characters

struct

enabled	bool
position	TextPosition
background	BitmapBackgroundProperty

13.1.6 TextPosition

Specify the vertical placement for the text.

enum

TOP
MIDDLE
BOTTOM

13.1.7 VideoTestGenerator

Defines how to generate a test image for a specific port.

struct

forceGenerator	bool
pattern	TestPattern
textOverlay	TextOverlay
movingBox	MovingBox

14 hipTypes (1.4)

14.1 Overview

Changelog:

1.4

- **Added**
 - The enum StartChannel

1.3

- **Added**
 - The value R2160P to ResolutionScan

1.2

- **Removed**
 - The values BLACK_PICTURE, MOVING_BOX and COLOR_BARS are removed from type SignalLossActionVideo.

1.1

- **Added**
 - The type TimeReference is added.

14.2 Type Reference

14.2.1 AudioIndex

Audio Index

enum

AUDIO_1	Audio index 1
AUDIO_2	Audio index 2
AUDIO_3	Audio index 3
AUDIO_4	Audio index 4
AUDIO_5	Audio index 5
AUDIO_6	Audio index 6
AUDIO_7	Audio index 7
AUDIO_8	Audio index 8

14.2.2 CodingCore

Coding Core Type

Type of Coding Core to use.

enum

UHD	Use Core that supports UHD/HD/SD
HD	Use Core that supports HD/SD

14.2.3 FrameRate

Frame Rate

Frame rate of the source.

enum

F24	24 fps
F23_98	23.98 fps
F25	25 fps
F29_97	29.97 fps
F30	30 fps
F47_95	47.95 fps
F48	48 fps
F50	50 fps
F59_94	59.94 fps
F60	60 fps

14.2.4 NumberOfChannels

Number of Channels

enum

CHANNELS_2	2 Mono Channels
CHANNELS_4	4 Mono Channels
CHANNELS_6	6 Mono Channels
CHANNELS_8	8 Mono Channels

14.2.5 Order

Order to put audio channel in.

enum

FIRST	Put audio channels first
SECOND	Put audio channels second
THIRD	Put audio channels third
FOURTH	Put audio channels fourth
FIFTH	Put audio channels fifth
SIXTH	Put audio channels sixth
SEVENTH	Put audio channels seventh
EIGHTH	Put audio channels eighth

14.2.6 ResolutionScan

Resolution and Scan

Resolution and scan mode of the source.

enum

R2160P	2096x2160 progressive
--------	-----------------------

R2KP	2048x1080 progressive
R1080P	1920x1080 progressive
R1080I	1920x1080 interlaced
R720P	1280x720 progressive
R576I	720x576 interlaced
R480I	720x480 interlaced

14.2.7 SignalLossAction

Signal Loss Action

Action taken on loss of bitrate on essences.

struct

videoAction	SignalLossActionVideo Action on video essence
audioAction	SignalLossActionAudio Action on audi essences
ancAction	SignalLossActionAnc Action on ancillary essence

14.2.8 SignalLossActionAnc

Signal Loss Action on ancillary essence

Action taken on loss of bitrate on the ancillary essence.

enum

MUTE	Mutes ancillary essence
TEST_GEN	Generates test ancillary essence

14.2.9 SignalLossActionAudio

Signal Loss Action on audio essences

Action taken on loss of bitrate on the audio essences.

enum

MUTE	Mutes audio essence
TEST_GEN	Generates test audio

14.2.10 SignalLossActionVideo

Signal Loss Action on video essence

Action taken on loss of bitrate on the video essence.

enum

MUTE	Mutes video essence
TEST_GEN	Display picture from test generator

14.2.11 SocketAddress

Socket address

Tuple with IP address and port

struct

address	string IP address, either IPv4 or IPv6
port	int Port number

14.2.12 St2110AudioPacketTime

ST2110 Audio packet time

enum

N_A	No audio packet time
US83_3	83,3 us packet time
US125	125 us packet time
MS1	1 ms packet time

14.2.13 StartChannel

Channel to start on, starts at 1 up to 15 (Only even numbered channel pairs)

enum

CHANNEL_1	Starting at Channel 1
CHANNEL_3	Starting at Channel 3
CHANNEL_5	Starting at Channel 5
CHANNEL_7	Starting at Channel 7
CHANNEL_9	Starting at Channel 9
CHANNEL_11	Starting at Channel 11
CHANNEL_13	Starting at Channel 13
CHANNEL_15	Starting at Channel 15

14.2.14 TimeReference

Time Reference

Protocol used for time reference

enum

NTP	NTP (Network Time Protocol) time source
PTP	PTP (Precision Time Protocol) time source

14.2.15 VideoFormat

Format of the video essence.

struct

resolutionScan

ResolutionScan

Resolution and scan mode of the source

frameRate

FrameRate

Framerate of the source

15 hipValidate (1.0)

15.1 Type Reference

15.1.1 FloatRange

Float Range

struct

min	float Minimum value of the range
max	float Maximum value of the range

15.1.2 IntRange

Integer Range

struct

min	int Minimum value of the range
max	int Maximum value of the range

15.1.3 Result

Validation result

struct

result	bool True if config is valid and false otherwise.
msg	optional string An error message, which may be given if the result is invalid.

16 linkModes (1.3)

16.1 Type Reference

16.1.1 IpFecMode

enum

NO_FEC	
RS_FEC	
FC_FEC	

16.1.2 IpLinkMode

enum

IP_10G	
IP_25G_COPPER	
IP_25G_OPTICAL	
IP_40G	
IP_4x10G	

16.1.3 IpLinkSpeed

enum

IP_10G	
IP_25G	
IP_40G	
IP_4x10G	
NO_LINK	

17 lldp (1.1)

17.1 Overview

```
# Changelog
```

```
## 1.1
```

```
- **Changed**
```

```
- Extracted the structure inside of the `LldpNeighbor` object definition into a new type cal
```

17.2 Type Reference

17.2.1 LldpMedInventory

LLDP-MED Inventory. Appear specific implementation in parentheses.

struct

hwRev	string Hardware Revision
swRev	string Software Revision (Software Version)
fwRev	string Firmware Revision (FPGA Version)
serial	string Serial Number
manufacturer	string Manufacturer ("Appear")
model	string Model ("X10" or "X20")
assetId	string Asset ID (Hardware ID)

17.2.2 LldpMode

Choose either private or public configuration of LLDP frames.

enum

PUBLIC	Only mandatory TLVs and port detail TLVs.
PRIVATE	LLDP-MED inventory in addition to the PUBLIC TLVs.

17.2.3 LldpNeighbor

LldpNeighborStruct

17.2.4 LldpNeighborStruct

The optional variables are only present if `GetLldpNeighborRequest.details` is set to true in the rpc request. The following descriptions are the Appear specific implementations of each LLDP TLV. If neighbors from other manufacturers are detected, TLV values might differ. The `LldpMode` is specified in

parentheses for variables that have different implementations based on the LldpMode set in the neighbor.

struct

chassisId	string MAC address of CTRL on MMI 1, fallback to CTRL on MMI 2 (PRIVATE) or "N/A" (PUBLIC).
mgmtIp	list of string IPv4 address of CTRL on MMI 1 and/or CTRL on MMI 2. Also IPv6 if enabled on the neighbor.
sysDescr	optional string Desktop Heading (PRIVATE) or "Unknown" (PUBLIC)
sysName	optional string Hostname (PRIVATE) or Interface.Port (PUBLIC)
portId	string MAC address of local port
portDescr	optional string Slot, Interface: Port-label
ttl	optional string Time-To-Live, how long an LLDP packet received from that neighbor should be considered valid.
lldpMedInventory	optional LldpMedInventory LLDP-MED Inventory

18 IldpProtocols (1.0)

19 networkManagerProtocols (1.1)

19.1 Overview

Changelog:

1.1

- **Changed**
 - The imported package hipIpInterface is bumped from 1.1 to 1.2.

1.0

- copied from firewall networkManagerProtocol.1.7

20 nmosConfig (1.0)

20.1 Type Reference

20.1.1 NmosConfig

Custom labels are enabled if the optional is set.

struct

registry	<code>nmosRegistryConfig.NmosRegistryConfigStruct</code>
labelTemplates	<code>optional nmosLabelConfig.NmosLabelConfig</code>

21 nmosLabelConfig (1.0)

21.1 Overview

Changelog

1.0

NMOS labelling

NMOS labelling API allows operator to define templates based on auto text options. This templates can be defined for node, device, source, flow, sender and receiver.

Version 1.0 allows six auto text options.

What are the auto text options?

- `${SLOT}` - The slot number of the card in use.
- `${DEV_ID}` - The Device number. **Not supported for Node templates.**
- `${ESS_GR}` - The label of the group where the essences belong to. **Not supported for Node templates.**
- `${ESS}` - The label of the Essence in question. **Not supported for Node and Device templates.**
- `${ESS_T}` - The Essence type: Video, Audio, Ancillary. This auto text option is substituted by what is defined in `EssenceTypeStrings` for each of the essences type. **Not supported for Node and Device templates.**
- `${ESS_T_INDEX}` - The number of the essence belonging to one of the essence type - video, audio, ancillary. **Not supported for Node and Device templates.**

How to use the NMOS Labelling.

- NMOS templates are set in the fields part of `ResourceLabelTemplates`. Unused templates should be set with an empty string.
- Each field in `ResourceLabelTemplates` can have as many auto text options as the operator wants, as long as they are supported for the respective template.
- `EssenceTypeStrings` strings will substitute the auto text option `${ESS_T}` with the defined string for the respective Essence type.

Example of strings to use for the fields in `ResourceLabelTemplates` and `EssenceTypeStrings`

- `nodeTemplate` - ECx210 Decoder ST2110 Sender Slot `${SLOT}`
- `deviceTemplate` - ECx210 Decoder Sender Slot `${SLOT}` ID `${DEV_ID}`
- `sourceTemplate` - ECx210 Slot `${SLOT}` ID `${DEV_ID}`, `${ESS_T}` Source: `${ESS}`, Group: `${ESS_GR}`, Essence Number: `${ESS_T_INDEX}`
- `flowTemplate` - ECx210 Slot `${SLOT}` ID `${DEV_ID}`, `${ESS_T}` Flow: `${ESS}`, Group: `${ESS_GR}`, Essence Number: `${ESS_T_INDEX}`
- `senderTemplate` - ECx210 Slot `${SLOT}` ID `${DEV_ID}`, `${ESS_T}` Sender: `${ESS}`, Group: `${ESS_GR}`, Essence Number: `${ESS_T_INDEX}`
- `receiverTemplate` - ECx210 Slot `${SLOT}` ID `${DEV_ID}`, `${ESS_T}` Receiver: `${ESS}`, Group: `${ESS_GR}`, Essence Number: `${ESS_T_INDEX}`
- `video` - Video
- `audio` - Audio
- `ancillary` - Anc

21.2 Type Reference

21.2.1 EssenceTypeStrings

Labels for each essence type to use when generating custom NMOS labels.

struct

video	string Video essence label
audio	string Audio essence label
ancillary	string Ancillary essence label

21.2.2 NmosLabelConfig

Custom NMOS labels configuration.

struct

resourceTemplates	ResourceLabelTemplates Templates for each NMOS resource
essenceStrings	EssenceTypeStrings Labels to use for each essence type

21.2.3 ResourceLabelTemplates

NMOS label templates for each NMOS resource.

struct

nodeTemplate	string Template string for the node label
deviceTemplate	string Template string for the device label
sourceTemplate	string Template string for the source label
flowTemplate	string Template string for the flow label
senderTemplate	string Template string for the sender label
receiverTemplate	string Template string for the receiver label

22 nmosRegistryConfig (1.0)

22.1 Type Reference

22.1.1 DnsConfig

Method to use for discovery of registry server

variant

mDns	DnsConfig.mDns Use mDNS to reach the registry server
dnsSd	DnsSdConfig Configuration parameters to use DNS-SD for discovery of registry service

22.1.2 DnsConfig.mDns

empty **struct**

22.1.3 DnsSdConfig

Configuration parameters for DNS-SD

struct

dnsServer	firewallTypes.IpAddress IPv4 address of DNS-SD server
search	string Search domain name

22.1.4 NmosRegistryConfigStruct

Configuration parameters for reaching the NMOS registry

struct

registryConfig	RegistryManualConfig Configuration parameters to use in case of failure in mDNS or DNS-SD (secondary/fallback method)
dnsConfig	DnsConfig Configuration parameters for mDNS or DNS-SD (primary method)

22.1.5 RegistryManualConfig

Registry information to be used in case registry server can not be reached by mDNS or DNS-SD.

struct

fallbackEnable	bool Enable use of given information as a fallback
	firewallTypes.IpAddress

registryIpAddr	IPv4 address of NMOS registry
registryPort	int Port number of NMOS registry
registryVersion	commonTypes.NmosVersionNumber Version of registry API

23 nmosRegistryStatus (1.0)

23.1 Type Reference

23.1.1 NmosRegistryStatus

NMOS registry status

struct

ipAddr

optional **firewallTypes.SocketAddress**

Currently used IP address and port number of the registry server. This value may have been obtained from DNS-SD, mDNS, or a manual IP entry.

registered

bool

True if there is an active connection to the registry server.

24 nmosStatus (1.1)

24.1 Overview

Changelog:

1.1

- ****Added****
 - The field 'nodeApi' was added to 'NmosStatus'.
- ****Changed****
 - The type NmosStatus was moved to the file 'nmosStatusTypes'.

24.2 Command Reference

24.2.1 GetNmosStatus

RPC for requesting NMOS status

- message **GetNmosStatus.Request**
- message **GetNmosStatus.Response**

24.3 Type Reference

24.3.1 GetNmosStatus.Request

empty **struct**

24.3.2 GetNmosStatus.Response

nmosStatusTypes.NmosStatus

25 nmosStatusTypes (1.0)

25.1 Type Reference

25.1.1 NmosStatus

NmosStatus Status of the NMOS service

struct

nmosRegistryStatus	nmosRegistryStatus.NmosRegistryStatus Status of the NMOS registry connection
nodeApi	map from physicalIpPort.PortName to string Map from port to the endpoint for NMOS Node API. Ex: PortName.D1 -> "10.20.10.34:8001", PortName.D2_2 -> "10.20.11.34:8001"

26 physicalIpPort (1.0)

26.1 Type Reference

26.1.1 PortName

enum

CTRL

D1

D2

D3

D4

D1_1

D1_2

D1_3

D1_4

D2_1

D2_2

D2_3

D2_4

D3_1

D3_2

D3_3

D3_4

D4_1

D4_2

D4_3

D4_4

27 sfpConstants (1.3)

27.1 Type Reference

27.1.1 Identifier

Physical Device Identifier Values. (SFF 8472 Rev12.3 spec Table 5-1)

enum

UNKNOWN	Unknown or unspecified
GBIC	GBIC
SOLDERED	Module soldered to motherboard (ex. SFF)
SFP_SFPP	SFP or SFP+
QSFP	QSFP+
QSFP28	QSFP28
NOT_USED	Not used by SFF 8472 Rev12.2.1. These values are maintained in the Transceiver Management section of SFF-8024.
VENDOR	Vendor specific

27.1.2 Transceiver

Transceiver Compliance Codes. (SFF 8472 Rev12.3 spec Table 5-3)

enum

ER_10G	10G Base-ER
LRM_10G	10G Base-LRM
LR_10G	10G Base-LR
SR_10G	10G Base-SR
ACTIVE_CABLE_40G	40G Active cable
LR4_40G	40G Base-LR4
SR4_40G	40G Base-SR4
CR4_40G	40G Base-CR4
PX	BASE-PX
BX10	BASE-BX10
FX_100	100BASE-FX
LX_100	100BASE-LX/LX10
T_1000	1000BASE-T
CX_1000	1000BASE-CX
LX_1000	1000BASE-LX
SX_1000	1000BASE-SX
ELECTRICAL_INTER_ENCLOSURE	Electrical inter enclosure
LONGWAVE_LASER_LL	Longwave laser LL
MEDIUM	Medium distance
LONG_DISTANCE	Long distance
INTERMEDIATE_DISTANCE	Intermediate distance
SHORT_DISTANCE	Short distance
VERY_LONG_DISTANCE	Very long distance
ACTIVE_CABLE	Active Cable
PASSIVE_CABLE	Passive Cable

LONGWAVE_LASER_LC	Longwave laser LC
SHORTWAVE_LASER_w_OFC	Shortwave laser w OFC
SHORTWAVE_LASER_wo_OFC	Shortwave laser w/o OFC
ELECTRICAL_INTRA_ENCLOSURE	Electrical intra enclosure
SINGLE_MODE	Singel mode
MULTIMODE_50um	Multimode 50um
MULTIMODE_50m	Multimode 50m
MULTIMODE_625m	Multimode 62.6m
VIDEO_COAX	Video coax
MINIATURE_COAX	Miniature coax
SHIELDED_TWISTED_PAIR	Shielded twisted pair
TWIN_AXIAL_PAIR	Twin axial pair
M_BYTES_SEC_100	100M bytes per sec
M_BYTES_SEC_200	200M bytes per sec
M_BYTES_SEC_400	400M bytes per sec
M_BYTES_SEC_1600	1600M bytes per sec
M_BYTES_SEC_800	800M bytes per sec
M_BYTES_SEC_1200	1200M bytes per sec
	Extended Specification Compliance. (SFF-8024 Rev 4.8 spec Table 4-4)
AOC_100G_AOC_25GAUI_C2M_BER_5_	100G AOC (Active Optical Cable) or 25GAUI C2M AOC. Providing a worst BER of $5 * 10^{-5}$
SR4_100G_BASE_SR_25G_BASE	100GBASE-SR4 or 25GBASE-SR
LR4_100G_BASE_LR_25G_BASE	100GBASE-LR4 or 25GBASE-LR
ER4_100G_BASE_ER_25G_BASE	100GBASE-ER4 or 25GBASE-ER
SR10_100G_BASE	100GBASE-SR10
CWDM4_100G	100G CWDM4
PSM4_PARALLEL_SMF_100G	100G PSM4 Parallel SMF
ACC_100G_ACC_25GAUI_C2M_BER_5_	100G ACC (Active Copper Cable) or 25GAUI C2M ACC. Providing a worst BER of $5 * 10^{-5}$
CR4_100G_BASE_25G_BASE_CR_CA_2	100GBASE-CR4 or 25GBASE-CR CA-L
CR_25G_BASE_CA_25G_S_50G_BASE_	25GBASE-CR CA-S
CR_25G_BASE_CA_25G_N_50G_BASE_	25GBASE-CR CA-N
ER4_40G_BASE	40GBASE-ER4
SR_4_X_10G_BASE	4 x 10GBASE-SR
PSM4_PARALLEL_SMF_40G	40G PSM4 Parallel SMF
G959_1_PROFILE_P1I1_2D1	G959.1 profile P1I1-2D1 (10709 MBd, 2km, 1310nm SM)
G959_1_PROFILE_P1S1_2D2	G959.1 profile P1S1-2D2 (10709 MBd, 40km, 1550nm SM)
G959_1_PROFILE_P1L1_2D2	G959.1 profile P1L1-2D2 (10709 MBd, 80km, 1550nm SM)
T_10G_BASE	10GBASE-T with SFI electrical interface
CLR4_100G	100G CLR4
AOC_100G_AOC_25GAUI_C2M_BER_10_	100G AOC or 25GAUI C2M AOC. Providing a worst BER of 10^{-12} or below
ACC_100G_ACC_25GAUI_C2M_BER_10_	100G ACC or 25GAUI C2M ACC. Providing a worst BER of 10^{-12} or below
DWDM2_100GE	100GE-DWDM2 (DWDM transceiver using 2 wavelengths on a 1550nm DWDM grid with a reach up to 80km)

28 sfpStatus (1.4)

28.1 Type Reference

28.1.1 SfpDiagnostics

Real Time Diagnostic for SFP/SFP+/QSFP28/QSFP+, with A2h/A0h memory space address in square brackets. (SFF 8472 Rev12.3 spec Table 9-11) (SFF 8636 Rev2.10 spec Table 6-1)

struct

temp	float Internally measured module temperature (°C). [96-97], [22-23]
vcc	float Internally measured supply voltage in transceiver (V). [98-99], [26-27]
txPwr	list of float Measured TX output power (mW). [102-103], [50-57]
rxPwr	list of float Measured RX input power (mW). [104-105], [34-41]

28.1.2 SfpStatus

SFP Status Data Fields, with A0h memory space address in square brackets. (SFF 8472 Rev12.3 spec Table 4-1) QSFP A0h memory space address is specified next to the SFP A0h. (SFF 8636 Rev 2.10 spec Table 6-14)

struct

identifier	sfpConstants.Identifier Type of transceiver (SFP/SFP+ or unknown). [0],[128]
transceiver	list of sfpConstants.Transceiver Code for electronic or optical compatibility [3-10], [131-138]
brNominal	float Nominal signalling rate, units of 100 MBd. [12], [140/222]
vendorName	string SFP vendor name. [20-35], [148-163]
vendorOUI	string SFP vendor IEEE company ID. [37-39], [165-167]
vendorPN	string Part number provided by SFP vendor. [40-55], [168-183]
vendorRev	string Revision level for part number provided by vendor. [56-59], [184-185]
wavelength	string Laser wavelength. [60-61], [186-187]
vendorSN	string Serial number provided by SFP vendor. [68-83], [196-211]
dateCode	string Vendor's manufacturing date code. [84-91], [212-219]

optional SfpDiagnostics

diagnostics

Optional Diagnostics Monitor Data.

29 st2110Types (1.1)

29.1 Type Reference

29.1.1 st2110Standard

The SMPTE ST2110 standards that describe video, audio or ancillary content.

enum

ST2110_20	ST2110 uncompressed video standard
ST2110_22	ST2110 compressed video standard
ST2110_30	ST2110 audio standard
ST2110_31	ST2110 AES3 formatted audio
ST2110_40	ST2110 ancillary standard

30 st2110TypesLabels (1.1)