

# CygSSH User Guide

---

© Copyright 2020-2025 by Bill Stewart

CygSSH is a convenient packaging of the Cygwin version of OpenSSH that provides a simple way to install and use the Cygwin version of OpenSSH on Windows.

This software is covered by the license agreements listed in appendix F.

# Contents

---

Chapter 1: Installing the Package	4
1.1 License Agreement	5
1.2 Information	5
1.3 Select Destination Location	5
1.4 Select Setup Type	5
1.5 Select Start Menu Folder	5
1.6 Select Additional Tasks	6
Chapter 2: Reinstalling, Upgrading or Downgrading	7
2.1 Reinstalling or Upgrading	7
2.2 Downgrading	7
Chapter 3: Uninstalling the Package	8
Chapter 4: Client Authentication	9
4.1 Using the SSH Client Commands	9
4.2 Using Other SSH Clients	10
Chapter 5: Server Authentication	11
5.1 Using the Local Access Group	11
5.2 Using Password Authentication	11
5.3 Using Public Key Authentication	12
5.3.1 Create the Directories on the Server	12
5.3.2 Grant the Account Permission to the Directories	12
5.3.3 Add the Account's Public Key to the <code>authorized_keys</code> File	13
5.4 Configuring an SFTP-Only Account	13
Chapter 6: Public Key Cryptography	15
6.1 Host Keys	15
6.2 Public Key Authentication	15

6.2.1 Creating a Key Pair . . . . .	16
6.2.1.1 Creating a Key Pair Using the <b>New-SSHKey.ps1</b> Script . . . . .	16
6.2.1.2 Create a Key Pair Using PuTTYgen . . . . .	16
6.2.2 Updating a Private Key . . . . .	17
Chapter 7: About Cygwin . . . . .	18
7.1 Cygwin File System Permissions . . . . .	18
7.2 Cygwin Account Names . . . . .	18
7.3 POSIX Path Names . . . . .	19
7.4 The Cygwin Home Directory . . . . .	19
Appendix A: The ChrootDirectory Setting . . . . .	20
Appendix B: Using rsync with SSH . . . . .	21
Appendix C: Documentation Links . . . . .	22
Appendix D: Windows PowerShell Scripts . . . . .	23
Appendix E: Acknowledgments . . . . .	24
Appendix F: License Agreements . . . . .	25
Appendix G: Open Source Source Code . . . . .	26
Appendix H: Version History . . . . .	27
Index . . . . .	31

# Chapter 1: Installing the Package

---

The system requirements are the following:

- Windows 8.1 64-bit or Windows Server 2012 R2 or later

The installer performs the following tasks:

- Creates the needed directories and copies the files
- Configures file and directory access control lists (ACLs)
- Configures the `fstab` file to disable Cygwin file system permission changes (see section 7.1)

The installer also performs the following tasks if the setup type is **full** (see section 1.4):

- Creates the OpenSSH server host keys (see section 6.1)
- Creates the local `sshd` account (see appendix A)
- Creates the local access group and updates the `sshd_config` file (see section 5.1)
- Adds a rule to the Windows firewall to allow communication to the OpenSSH server service
- If the **startservice** task is selected (see section 1.6), starts the OpenSSH server service

Regardless of the setup type, the installer then performs any other tasks selected on the **Select Additional Tasks** page (see section 1.6).

The installer package is built using the Inno Setup installer, so it supports all of Inno Setup's command line parameters.

Example installation command:

```
cygssh-version-setup.exe /SILENT /CLOSEAPPLICATIONS /SUPPRESSMSGBOXES
```

Replace *version* with the version (e.g., **9.8.0**).

The above command installs the package silently (i.e., without user interaction). The `/CLOSEAPPLICATIONS` parameter automatically stops running services and closes programs so that the installer can reinstall or upgrade the files. Stopped services will be automatically restarted after the installation completes. The `/SUPPRESSMSGBOXES` parameter suppresses message dialog boxes that would normally appear in an interactive installation.

If you want to prevent the installer from displaying its progress window during a silent install, use `/VERYSILENT` instead of `/SILENT`.

The installer also supports non-administrative install mode, which installs only the client files for the current user (does not require administrator privileges). To run in non-administrative install mode, use the `/CURRENTUSER` parameter on the command line.

You can also force the installer to uninstall the installed version before proceeding with installation; to do this, specify

the `/FORCEUNINSTALL` parameter on the command line. When you use this parameter, the installer detects if the package is already installed and automatically uninstalls it before proceeding with the installation.

When upgrading from certain older versions, the installer may decide it needs to perform an uninstall before upgrading. In these cases, the installer will behave as if the `/FORCEUNINSTALL` parameter is in use even if you don't specify it explicitly.

The following sections describe the pages of the installer wizard.

## 1.1 License Agreement

The **License Agreement** page of the installer wizard lists the license agreements used by the various software components. Installing the software implies an acceptance of all license agreements (see appendix F).

## 1.2 Information

The **Information** page of the installer wizard lists release notes for the current version of the package.

## 1.3 Select Destination Location

The **Select Destination Location** page of the installer wizard allows you to specify the directory path where the package will be installed. This is `C:\Program Files\CygSSH` by default (if `C:` is the system drive). If you started the installer using the `/CURRENTUSER` parameter, the default path will be like `C:\Users\username\AppData\Local\Programs\CygSSH` (i.e., install only for the current user).

You can specify a different destination path on the installer's command line by using the `/DIR="installpath"` command line parameter (where *installpath* is the directory path name).

Throughout this documentation, the installation directory is referred to as *installpath*.

Note that this page doesn't appear if you are reinstalling or upgrading.

## 1.4 Select Setup Type

The **Select Setup Type** page of the installer wizard allows you to choose the setup type. The setup types are as follows:

- **full** - Full installation (server and client files)
- **client** - Client installation (client files only)

You can specify the setup type on the command line using the `/TYPE="type"` command line parameter (where *type* is either **full** or **client**). The default setup type is **full**, so the only reason to use the `/TYPE` command line parameter is if you want to specify `/TYPE="client"` as the default (typically for a silent install).

Note that this page doesn't appear under the following conditions:

- If you specified `/CURRENTUSER` on the installer's command line, because `/CURRENTUSER` implies the **client** setup type
- If you previously installed using the **full** setup type, because selecting the **client** setup type does not remove the server files

## 1.5 Select Start Menu Folder

The **Select Start Menu Folder** page of the installer wizard allows you to specify the name of the Start menu folder where it will install application shortcut icons.

You can specify the folder name on the command line using the `/GROUP="name"` command line parameter (where *name* is the folder name). Alternatively, you can specify `/NOICONS` to prevent creation of any Start menu shortcuts.

Note that this page doesn't appear if you are reinstalling or upgrading.

## 1.6 Select Additional Tasks

The **Select Additional Tasks** page of the installer wizard allows you to select additional tasks the installer should perform. The additional tasks are as follows:

- **startservice** - Corresponds to the **Start OpenSSH server service** check box. Starts the OpenSSH server service. This task is not applicable if the setup type is **client** (see section 1.4). This task is selected by default.
- **modifypath** - Corresponds to the **Add to system Path** (or **Add to user Path**) check box. Adds the *installpath*\bin directory to the system or user Path environment variable if it does not already exist. This task is selected by default. (This task does not appear if *installpath*\bin is already in the system or user Path.)
- **resetconfig** - Restores the OpenSSH configuration files (*ssh\_config* and/or *sshd\_config*) to default values. Use this task with caution if you have made any customizations to the *etc\ssh\_config* and/or *etc\sshd\_config* files. When you select this task, the installer renames the existing *ssh\_config* and/or *sshd\_config* files with *-timestamp* appended (where *timestamp* is the current year, month, day, hour, minute, and second) before installing default copies of the configuration file(s). This task is not selected by default.

You can specify one or more of the additional tasks on the command line using the `/TASKS="task[ , task[...]]"` command line parameter (where *task* is one or more of the above task names, separated by `,` characters).

For an interactive (i.e., not silent) installation, the `/TASKS` parameter specifies which tasks are selected by default; you can change the defaults on the page as you install.

For a silent installation, the `/TASKS` parameter dictates the list of tasks the installer will perform. For example, if you specify `/TASKS="startservice" /SILENT` on the installer's command line, the installer will **only** perform the `startservice` task.

To indicate 'no tasks', specify `/TASKS=""` on the installer's command line.

Note that if you do not select the `modifypath` task when you install, you will need to do one of the following before running commands:

- Change to the *installpath*\bin directory before running the command
- Specify the path to the command when you want to run it

## Chapter 2: Reinstalling, Upgrading or Downgrading

---

This chapter describes how to reinstall, upgrade, and downgrade the package.

### 2.1 Reinstalling or Upgrading

Reinstalling or upgrading the package is as simple as running the installer:

- If the installer is the same version as the installed version, it will reinstall the installed version.
- If the installer is a newer version than the installed version, it will upgrade the installed version.

A reinstall or upgrade cannot proceed if the OpenSSH server service or any of the programs in the package are currently running. If any are running, the installer will prompt for permission to stop running services and close any programs.

You can prevent the prompt from appearing by specifying the `/CLOSEAPPLICATIONS` parameter on the installer's command line. This is particularly useful when using the `/SILENT` parameter (see chapter 1).

### 2.2 Downgrading

To perform a downgrade in versions older than 9.8.0, do one of the following:

- Uninstall the installed version (see chapter 3) and install the older version, or
- Use the `/FORCEUNINSTALL` parameter (see chapter 1).

If you are installing an older version of the package that doesn't support the `/FORCEUNINSTALL` parameter, you will need to uninstall and reinstall.

To downgrade in versions 9.8.0 and newer, simply install the desired version. The installer will detect the downgrade condition and uninstall the newer version automatically before installing the desired version.

## Chapter 3: Uninstalling the Package

---

To uninstall the package, use the standard means of accessing installed applications on your version of Windows (e.g., the **Programs and Features** applet in the Control Panel), and uninstall it from there.

If you want to uninstall silently (without user interaction), do the following:

1. Determine the filename of the uninstall program. The file is in *installpath* and is named like `uninsnnn.exe` (where *nnn* is 3 digits - normally 000).
2. Run the executable with the `/SILENT` command line parameter.

For example, if the uninstaller executable is `C:\Program Files\CygSSH\unins000.exe`, the command line to uninstall silently is the following:

```
"C:\Program Files\CygSSH\unins000.exe" /SILENT
```

You can also replace `/SILENT` with `/VERYSILENT` to prevent the uninstaller from displaying its progress window.

The uninstall program does not remove the following items:

- Configuration files in the `etc` directory
- The `lastlog` file in the `var\log` directory
- The `users\SYSTEM\.ssh` directory or its contents
- Any other user created files
- The local `sshd` user account



## Chapter 4: Client Authentication

---

This chapter describes how to authenticate to an OpenSSH server using SSH client software.

### 4.1 Using the SSH Client Commands

The CygSSH package provides several SSH client commands:

- The **scp** command copies files to an SSH server
- The **ssh** command establishes an interactive shell session with an SSH server
- The **sftp** command establishes a file transfer session with an SSH server

**Note:** It's recommended to run the **ssh** and **sftp** SSH client commands using the **mintty** command (e.g., **mintty ssh** rather than just **ssh**). If you run these SSH client commands without the **mintty** command, line wrapping and other features may not work as expected.

Example 1:

```
mintty sftp COMPUTER1+localuser@computer1
```

This command establishes a file transfer session to `computer1` using the account `COMPUTER1+localuser`.

Example 2:

```
mintty ssh -i /cygdrive/c/Users/KenDyer/.ssh/kenprivkey KenDyer@computer2
```

This command establishes an interactive shell session to `computer2` using the `KenDyer` account using public key authentication (see section 6.2), using the file `C:\Users\KenDyer\.ssh\kenprivkey` as the private key.

Example 3:

```
scp "/cygdrive/C/Program\ Files/CygSSH/etc/sshd_config"  
"bkpsvc@server1:/cygdrive/C/Program\ Files\CygSSH/etc"
```

(All on one line) This command copies the `sshd_config` file from the current computer to a remote computer.

When using the Cygwin SSH client commands, note that path names must be in POSIX format, using the `\` character to 'escape' spaces where necessary (see section 7.3).

If you haven't connected to an SSH server before, the command will prompt you to store the server's host key fingerprint (see section 6.1) in the `known_hosts` file. The default path of the `known_hosts` file is in the `.ssh` directory in the user's home directory (see section 7.4).

You can also use the **rsync** command over an SSH connection to transfer files more efficiently (see appendix B).

See appendix C for links to the documentation for the **ssh**, **scp**, **sftp**, and **rsync** commands.

## 4.2 Using Other SSH Clients

See the documentation for the SSH client for more information on how to use it to connect to an SSH server.

Popular Windows SSH clients include the following:

**PuTTY** - <https://www.chiark.greenend.org.uk/~sgtatham/>

**WinSCP** - <https://winscp.net/>

## Chapter 5: Server Authentication

---

This chapter describes how to configure the OpenSSH server service to permit logons using password authentication (see section 5.2) or public key authentication (see section 5.3).

### 5.1 Using the Local Access Group

By default, the OpenSSH server service only allows accounts that are members of the `SSH Users` local group to log on. The installer (see chapter 1) will create the `SSH Users` local group if it does not exist. This local group is referred to as the *local access group*.

The local access group is empty by default, which means you must explicitly add accounts to the local access group to allow logon via SSH.

If the computer is an Active Directory domain member, nested domain groups are supported. For example, you can add a domain group as a member of the `SSH Users` local group, and all members of the domain group will be granted access to log on using SSH.

If you have an Active Directory domain, you can manage the membership of the `SSH Users` local group using a Group Policy Object (GPO).

The installer (see chapter 1) automatically updates the `sshd_config` file at installation time with the following line:

```
AllowGroups "[computername+]SSH Users"
```

If the computer is a domain member, the installer adds the computer name and + prefix (see section 7.2). Otherwise, the computer name and + prefix are not used.

If the computer name changes, or if the computer is removed as a domain member, you will need to manually edit the `sshd_config` file as follows:

- If the computer name changes, update the computer name on the `AllowGroups` line of the file.
- If the computer is removed as a domain member, remove the computer name and + character on the `AllowGroups` line.

Once complete, save the `sshd_config` file and restart the OpenSSH server service.

### 5.2 Using Password Authentication

Once an account is a member of the local access group on the OpenSSH server (see section 5.1), that account can log on using an SSH client using the account's password. No further configuration is required.

The account name must use Cygwin format (see section 7.2).

## 5.3 Using Public Key Authentication

*Public key authentication* is a means of authenticating an SSH logon without needing the account's password (see section 6.2).

To authenticate an account using a public key instead of a password, you must first create a key pair (see section 6.2.1).

Once you have a key pair, you will need to complete all of the following configuration steps to enable public key authentication for the account:

- Ensure the account is a member of the local access group (see section 5.1)
- Create the directories on the server (see section 5.3.1)
- Grant the account permission to the directories (see section 5.3.2)
- Add the account's public key to the `authorized_keys` file (see section 5.3.3)

### 5.3.1 Create the Directories on the Server

To allow an account to authenticate using a public key (see section 5.3), you must create a directory named for the account in the `installpath\users` directory, and a `.ssh` directory within that directory.

This section also applies to setting up an SFTP-only account (see section 5.4).

The account name must use Cygwin format (see section 7.2).

For example, suppose the current computer is a domain member, and you want to allow the `KenDyer` account in the computer's domain to authenticate.

In this example you would create the following directories on the server:

- `installpath\users\KenDyer`
- `installpath\users\KenDyer\.ssh`

### 5.3.2 Grant the Account Permission to the Directories

To allow an account to authenticate using a public key (see section 5.3), you must update the directory's access control list (ACL) to grant the account at least read (**RX**) access to the directory and its subdirectories.

This section also applies to setting up an SFTP-only account (see section 5.4).

You can use the **icacls** command to grant the permissions.

First, open an elevated PowerShell console (i.e., right-click the PowerShell icon and choose Run as administrator).

Run a command like the following:

```
icacls "installpath\users\cygwinaccountname"  
/grant "windowsaccountname:(CI)(OI)access"
```

(All on one line)

Replace `cygwinaccountname` with the Cygwin account name (see section 7.2), replace `windowsaccountname` with the Windows account name, and replace `access` with either **M** for modify access or **RX** for read-only access.

For example, suppose the current computer is a member of the `FABRIKAM` domain and you are setting the permissions

for the KenDyer account in that domain. The command to grant modify access would be as follows:

```
icacls "C:\Program Files\CygSSH\users\KenDyer"  
/grant "FABRIKAM\KenDyer:(CI)(OI)M"
```

(All on one line)

If you want to grant read-only access instead:

```
icacls "C:\Program Files\CygSSH\users\KenDyer"  
/grant "FABRIKAM\KenDyer:(CI)(OI)RX"
```

(All on one line)

### 5.3.3 Add the Account's Public Key to the `authorized_keys` File

To allow an account to authenticate using a public key (see section 5.3), you must add the account's public key to the `authorized_keys` file.

The `authorized_keys` file is a text file in the account's `.ssh` directory that contains one line for each public key for the account. (The OpenSSH documentation describes the `authorized_keys` file format.)

If you use the **New-SSHKey.ps1** script to generate a key pair (see section 6.2.1.1), you can use the generated public key (`.pub`) file as the `authorized_keys` file for the account.

If you use **PuTTYgen** to generate a key pair (see section 6.2.1.2), you can use the text box labeled **Public key for pasting into OpenSSH authorized\_keys file** as the content of the `authorized_keys` file. If you have a `.ppk` file, open it in **PuTTYgen**. It will put the public key in the text box, and you can copy it from there (make sure there are no line breaks).

For example, suppose the current computer is a member of the FABRIKAM domain, and you want to allow the KenDyer account in that domain to authenticate.

In this example, the file `installpath\users\KenDyer\.ssh\authorized_keys` would contain the public key(s) used to authenticate the KenDyer account.

## 5.4 Configuring an SFTP-Only Account

This section describes how to configure an SFTP-only account (i.e., the account can only connect to the OpenSSH server using a file transfer client such as **sftp** or **WinSCP**).

To configure an SFTP-only account, first create the directories for it (see section 5.3.1) and set the permissions (see section 5.3.2).

Next, create an `sftp` directory inside the account's directory.

Next, add lines like the following to the end of the `sshd_config` file:

```
Match User accountname  
    X11Forwarding no  
    AllowTcpForwarding no  
    PermitTTY no  
    ChrootDirectory /users/%u/sftp  
    ForceCommand internal-sftp
```

Replace *accountname* with the account's Cygwin account name (see section 7.2).

The `ChrootDirectory` setting is not a true security control on Windows and is used only to limit the file system view on SFTP-only accounts (see appendix A).

Once complete, save the `sshd_config` file and restart the OpenSSH server service.

**Note:** You can't prevent the `cygdrive` and `dev` directories from appearing on the client side of the SFTP connection, but they don't cause any problems, either.

Example configuration:

Suppose the current computer is a domain member named `COMPUTER1`, and local account `sftponly` will be an SFTP-only account.

In this example, first create the following directories on the OpenSSH server:

- `installpath\users\COMPUTER1+sftponly`
- `installpath\users\COMPUTER1+sftponly\sftp`

Next, grant the `sftponly` account at least read (**RX**) access to the `installpath\users\COMPUTER1+sftponly` directory and its subdirectories.

Then, add the following lines to the end of the `sshd_config` file:

```
Match User COMPUTER1+sftponly
    X11Forwarding no
    AllowTcpForwarding no
    PermitTTY no
    ChrootDirectory /users/%u/sftp
    ForceCommand internal-sftp
```

If the account will authenticate using a public key instead of a password (see section 5.3), add the `AuthenticationMethods publickey` setting; e.g.:

```
Match User COMPUTER1+sftponly
    AuthenticationMethods publickey
    X11Forwarding no
    AllowTcpForwarding no
    PermitTTY no
    ChrootDirectory /users/%u/sftp
    ForceCommand internal-sftp
```

(You must also add the `authorized_keys` file to the account's `.ssh` directory, as described in section 5.3.3.)

Once complete, save the `sshd_config` file and restart the OpenSSH server service.

## Chapter 6: Public Key Cryptography

---

*Public key cryptography*, sometimes also called *asymmetric cryptography*, is an encryption technique that uses two cryptographically related signatures--a *public key* and a *private key*. (The public key and private key are typically referred to as a *key pair*.) The public key is used to encrypt, and the private key is used to decrypt. It is not computationally feasible to generate a private key based on a public key.

OpenSSH uses public key cryptography to ensure the communication between an SSH client and the OpenSSH server are encrypted.

### 6.1 Host Keys

A *host key* is a cryptographic signature that uniquely identifies an OpenSSH server to SSH clients.

The installer (see chapter 1) automatically creates the necessary host key files at installation time.

The files containing the host keys are stored in *installpath\etc* and are named using the format *ssh\_host\_keytype\_key[.pub]*, where *keytype* is **ecdsa**, **ed25519**, or **rsa**. The *.pub* suffix indicates the public key. Each key type represents an encryption algorithm supported by OpenSSH.

For example, the file *ssh\_host\_ed25519\_key* contains the private host key for the ED25519 encryption algorithm, and the file *ssh\_host\_ed25519\_key.pub* contains its associated public key.

The private key files are configured with restricted access control lists (ACLs) to prevent unauthorized access (**SYSTEM:F** and **Administrators:F** only).

SSH clients can identify an SSH server by its unique *host key fingerprint*. An SSH server's host key fingerprints are unique for each encryption algorithm it supports. When an SSH client connects to an SSH server for the first time using a particular encryption algorithm, the default behavior is for the SSH client to display the server's host key fingerprint for validation.

SSH clients can store an SSH server's host key fingerprint for later comparison. If the host key fingerprint for a particular algorithm is different the next time the client connects, it may indicate the server has been compromised. Host keys fingerprints are a mechanism to validate the identity of the server to which you're connecting.

The **Get-SSHHostKeyFingerprint.ps1** script displays host key fingerprints for SSH servers. You can use this script on an SSH server to display the server's host key fingerprint(s) in either md5 or sha256 format.

The Cygwin SSH client commands (see section 4.1) store known host keys in the *known\_hosts* file in the current user's home directory (see section 7.4).

### 6.2 Public Key Authentication

*Public key authentication* is a means of authenticating an SSH logon without needing the account's password.

To use public key authentication to authenticate an account in OpenSSH, you will need to create a key pair. The private key is used on the client side of the SSH connection, and the public key is used on the server side.

The account name must use Cygwin format (see section 7.2).

## 6.2.1 Creating a Key Pair

This section describes different ways to create a key pair.

### 6.2.1.1 Creating a Key Pair Using the `New-SSHKey.ps1` Script

The `New-SSHKey.ps1` script is a wrapper for the `ssh-keygen` command. Using the script is straightforward: Open a PowerShell command window, run the script, it will prompt for the information it needs:

1. It will prompt you to enter the name of the private key file. The default path is the `.ssh` directory in the current user's home directory (see section 7.4). Press Enter without entering anything to use the default file name or enter a new file name.
2. It will prompt you to enter a passphrase. If you specify a passphrase, you must enter it every time you want to use the key.
3. It will prompt you to enter a comment. The comment is intended to help you identify the key. Press Enter without entering anything to use the default comment, or enter a new comment.

Sample command output follows:

```
PS C:\Users\accountname> New-SSHKey
Key type: ed25519
Enter file in which to save the key (C:\Users\accountname\.ssh\id_ed25519):
Enter passphrase (leave empty for no passphrase):
Confirm passphrase (leave empty for no passphrase):
Comment (accountname@hostname): My SSH key
Generating public/private ed25519 key pair.
Your identification has been saved in /cygdrive/c/Users/accountname/.ssh/id_ed25519.
Your public key has been saved in /cygdrive/c/Users/accountname/.ssh/id_ed25519.pub.
The key fingerprint is:
SHA256:w5UB4i5qymXdQX/7ErHgbglow77s6Q6h/kaN0iavKbA My SSH key
The key's randomart image is:
+--[ED25519 256]--+
|   E...+O+.=O.   |
|  . oo O+ =.=O   |
| . =.O*  . ...   |
| o Bo .. =       |
| = + . S         |
| = . = o o       |
| o o  = .        |
| . . +.+         |
|   o.o..         |
+-----[SHA256]-----+
Restricted permissions on file 'C:\Users\accountname\.ssh\id_ed25519'.
```

The `New-SSHKey.ps1` script will attempt to restrict the permissions on the private key file to protect it from unauthorized access, but it may not be able to do this if the private key file is saved in a location where you don't have sufficient permissions to change the file's access control list (ACL). It's strongly recommended to store the private key in a location where you have permission to change the file's ACL so it will be protected from unauthorized access.

The file paths output by the `ssh-keygen` command are in POSIX format (see section 7.3).

### 6.2.1.2 Create a Key Pair Using `PuTTYgen`

To create a key pair using **PuTTYgen**, do the following:



1. Open the **PuTTYgen** program.
2. At the bottom of the **PuTTYgen** window, select **ED25519** as the type of key to generate.
3. Click the **Generate** button.
4. Move the mouse in the **PuTTYgen** window to generate randomness.
5. The text box near the top of the **PuTTYgen** window (labeled **Public key for pasting into OpenSSH authorized\_keys file**) contains the public key for use on the OpenSSH server. (The line of text in this text box corresponds to the `.pub` file generated using the **New-SSHKey.ps1** script.)
6. You can specify a comment and/or a passphrase in the corresponding text boxes.
7. Click the **Save** button to save the private key in PuTTY (`.ppk`) format.

It's strongly recommended to store the private key file in a location with a restricted access control list (ACL), particularly if the private key is not protected with a passphrase.

## 6.2.2 Updating a Private Key

You can use the **Edit-SSHKey.ps1** script to update the passphrase or comment of a private key file. The command syntax is as follows:

```
Edit-SSHKey "filename" -Passphrase
```

or:

```
Edit-SSHKey "filename" -Comment
```

Replace *filename* with the name of the private key file.

The script will prompt you to enter a new passphrase or comment.

If you specify `-Comment`, the script will create a replacement public key file with a new comment (same filename but with `.pub` appended).

Hint: If you lose the public key file associated with a private key file, simply run **Edit-SSHKey.ps1** with the `-Comment` parameter. Enter an updated comment, and a new public key file will be created (same filename as private key, but with `.pub` appended).

## Chapter 7: About Cygwin

---

Cygwin is a set of Windows DLLs (dynamically linked libraries) that provides substantial POSIX-compatible API (application programming interface) compatibility.

In effect, Cygwin is a POSIX emulation layer that allows programmers to compile POSIX-compatible source code into Windows executables with minimal changes.

This has several effects on programs that use the Cygwin emulation layer, as described in the following sections.

### 7.1 Cygwin File System Permissions

By default, Cygwin programs will attempt to reproduce POSIX-style file permissions using Windows access control lists (ACLs). This can result in unexpected permission problems when running Cygwin-based file management tools such as **rsync**.

To avoid this problem, the installer (see chapter 1) configures the file systems in the *installpath\fstab* file to use the `noacl` option for all directories.

Please see the following references in the Cygwin documentation for more information:

- File Permissions - <https://cygwin.com/cygwin-ug-net/ntsec.html#ntsec-files>
- The Cygwin Mount Table - <https://cygwin.com/cygwin-ug-net/using.html#mount-table>

### 7.2 Cygwin Account Names

Account names in Windows use the following format: *[authorityname\]accountname* (where *authorityname* is a computer name or domain name). The authority name isn't used in all circumstances (such as with the BUILTIN and NT AUTHORITY authorities).

Cygwin programs use the `+` rather than the `\` character to separate authority names from account names.

Cygwin's account naming rules are as follows:

- Well-known and built-in accounts will be named as in Windows, without an authority name. Examples: `Administrators` or `SYSTEM`
- If the computer **is not** a domain member, the authority name is not used. Example: `Administrator` (not `COMPUTERNAME+Administrator`)
- If the computer **is** a domain member, accounts from the computer's domain are used without an authority name. Example: `kendyer` (not `DOMAIN1+kendyer`)
- Accounts from other domains use the domain name as the authority name. Example: `DOMAIN2+lynndyer`
- Local computer accounts of a domain member computer use the computer name as the authority. Example: `COMPUTERNAME+localuser`

See the Cygwin documentation for more details about how Cygwin maps between Windows and POSIX account names.

The **Get-AccountName.ps1** script outputs one or more account names in both Windows and Cygwin formats:

- The script will output the Windows and Cygwin account names for the current account if you run it without parameters
- The script will output the Windows and Cygwin account names for one or more accounts if you provide the account name(s) as a parameter (the script also accepts pipeline input)

Run the command **Get-Help Get-AccountName** for more information about the script.

**Note:** OpenSSH server versions older than 8.0 required that Cygwin account names be specified using *exact case*. This requirement was removed starting in OpenSSH version 8.0.

## 7.3 POSIX Path Names

Cygwin programs use POSIX path names (such as `/etc/fstab`) rather than Windows path names (such as `C:\Program Files\CygSSH\etc\fstab`).

For example, the root directory (`/`) corresponds to *installpath* (e.g., `C:\Program Files\CygSSH`).

Windows drive letters (e.g., `C:`) are found in the `/cygdrive` directory (e.g., `/cygdrive/c` corresponds to `C:`).

The **cygpath** command allows you to easily translate Windows path names into a POSIX path names and vice-versa. Use the `-w` parameter to tell **cygpath** you want the Windows path.

Example Command	Example Output
<code>cygpath "C:\Program Files"</code>	<code>/cygdrive/c/Program Files</code>
<code>cygpath C:\Users\KenDyer</code>	<code>/cygdrive/c/Users/KenDyer</code>
<code>cygpath -w /</code>	<code>C:\Program Files\CygSSH</code>
<code>cygpath -w /etc/fstab</code>	<code>C:\Program Files\CygSSH\etc\fstab</code>

In the first example, note that the quotes are required since the path name contains spaces.

If you need to specify a path name that contains spaces on a Cygwin program's command line, it may be necessary, depending on the command, to 'escape' the spaces in the path using the `\` character (see section 4.1 for an example).

## 7.4 The Cygwin Home Directory

A user's *home directory* is the default path location for files owned by that user. By default, Cygwin maps the user's home directory to `/home/accountname` (see section 7.3 for more about POSIX path names).

The default can cause confusion, though, because it means that Cygwin and Windows have two separate home directory paths. For example, the Windows home directory for the KenDyer account might be `C:\Users\KenDyer` but the default Cygwin home directory would be something like `C:\Program Files\CygSSH\home\KenDyer`.

To avoid the confusion, the CygSSH package uses the `nsswitch.conf` file to set Cygwin's home directory to the same home directory that Windows uses. The file contains the following line:

```
db_home: /%H
```

The `%H` placeholder means 'Windows home directory in POSIX format.'

See the Cygwin documentation for more details about the `nsswitch.conf` file.

## Appendix A: The ChrootDirectory Setting

---

On a POSIX-compliant operating system (e.g., Linux), the OpenSSH `ChrootDirectory` setting uses the `chroot` system call to restrict an account's access to a specific path in the file system: The account cannot access any file or directory outside of that specific path. In POSIX terminology, this is sometimes referred to as a *chroot jail*.

The Cygwin emulation layer used by OpenSSH on Windows (see chapter 7) has a limited implementation of `chroot` because the Windows operating system does not have a direct equivalent of this system call. Consequently, Cygwin's limited implementation of `chroot` is not a true security control because it can sometimes permit the account to 'escape' from the 'jail.' (It's important to understand that even if the account 'escapes' from the 'jail,' the account is still restricted by Windows security controls; it's just that the limited Cygwin `chroot` jail isn't enforced as an *additional* security control.)

Even though Cygwin's implementation `chroot` is not a true security control, we can still use the `ChrootDirectory` setting in `sshd_config` to restrict the file system view for an SFTP-only account (see section 5.4).

Using the `ChrootDirectory` setting in `sshd_config` requires the following two items be in place:

1. The `passwd` file in the `etc` directory must specify that the Windows `SYSTEM` account is user number 0 (this corresponds to the POSIX `root` user account)
2. The local `sshd` account (known as the *privsep account*) must exist, and it must be **enabled** (it must *not* be disabled as stated in the OpenSSH documentation)

These two items are taken care of automatically at installation time (they don't need to be configured manually).

## Appendix B: Using rsync with SSH

---

The **rsync** command is an efficient file and directory replication tool that supports replication over an SSH connection so that the data is encrypted in transit.

The syntax for replicating data to a remote computer using an SSH connection is as follows:

```
rsync options -e "ssh [sshoptions]" "source" "accountname@hostname:dest"
```

Where:

- *options* is one or more command line options for the **rsync** command
- *sshoptions* is one or more command line options for the **ssh** command
- *source* is the source path in POSIX format (see section 7.3); do not use \ to escape spaces in the source path
- *accountname* is the account name to connect with, in Cygwin format (see section 7.2)
- *hostname* is the remote computer name
- *dest* is the destination path in POSIX format (see section 7.3); escape spaces in the destination path using \ unless using **rsync**'s **-s** option (recommended)

Example command 1:

```
rsync -lrvz -e "ssh" "/cygdrive/c/Users/KenDyer/Backup Files/"  
"KenDyer@computer3:/cygdrive/c/Users/KenDyer/Backup Files"
```

(All on one line) This command replicates the C:\Users\KenDyer\Backup Files directory to the same path on computer3 using the KenDyer account.

Example command 2:

```
rsync -lrvz -e "ssh -i /cygdrive/c/Users/filerepl/.ssh/ed25519"  
"/cygdrive/c/ProgramData/App Name/"  
"filerepl@server2:/cygdrive/c/ProgramData/App Name"
```

(All on one line) This command replicates the directory C:\Program Data\App Name to the computer server2 using the filerepl account. Note the use of a private key file, specified as a POSIX path (see section 7.3).

Note that the source path in the example commands uses a trailing / to prevent creating a new directory in the destination path.

See appendix C for a link to **rsync**'s documentation.

## Appendix C: Documentation Links

---

**OpenSSH** - <https://www.openssh.com/manual.html>

**Cygwin** - <https://www.cygwin.com/cygwin-ug-net/cygwin-ug-net.html>

**rsync** - <https://rsync.samba.org/documentation.html>

**Inno Setup** - <http://www.jrsoftware.org/ishelp/>

## Appendix D: Windows PowerShell Scripts

---

The following list describes the Windows PowerShell scripts provided by the CygSSH package.

**Edit-SSHKey.ps1** - Updates a private key file's comment or passphrase (see section 6.2.2)

**Get-AccountName.ps1** - Outputs an account's name in both Cygwin and Windows format (see section 7.2)

**Get-SSHHostKeyFingerprint.ps1** - Outputs SSH host key fingerprint(s) from one or more computer(s) (see section 6.1)

**New-SSHKey.ps1** - Creates a key pair (see section 6.2.1)

**Set-FstabConfig.ps1** - Used by the installer to create a default `fstab` file (see section 7.1)

**Set-SSHGroup.ps1** - Used by the installer to create the local access group and update the `sshd_config` file (see section 5.1)\*

**Set-SSHHostKey.ps1** - Used by the installer to create the OpenSSH server host keys (see section 6.1)\*

**Set-SSHService.ps1** - Used by the installer to install, start, stop, and uninstall the OpenSSH server service\*

\* Only installed when setup type is **full** (see section 1.4)

**Note:** Use the **Get-Help** cmdlet to get online help information for any of the PowerShell scripts.

## Appendix E: Acknowledgments

---

Special thanks to the authors of the following software packages for their generous contributions:

**Cygwin** - <https://www.cygwin.com/>

**OpenSSH** - <https://www.openssh.com/>

**winpty** - <https://github.com/rprichard/winpty/>

**rsync** - <https://rsync.samba.org/>

**Inno Setup** - <http://www.jrsoftware.org/>

**Halibut** - <https://www.chiark.greenend.org.uk/~sgtatham/halibut/>

**PathMgr.dll** - <https://github.com/Bill-Stewart/PathMgr/>



## Appendix F: License Agreements

---

This package contains software from multiple sources:

- **Cygwin** - <https://www.cygwin.com/licensing.html>
- **OpenSSH** - <https://cvsweb.openbsd.org/src/usr.bin/ssh/LICENCE?rev=HEAD>
- **rsync** - <https://rsync.samba.org/GPL.html>
- **winpty** - <https://github.com/rprichard/winpty/blob/master/LICENSE>
- **PathMgr.dll** - <https://github.com/Bill-Stewart/PathMgr/>
- **UninsIS.dll** - <https://github.com/Bill-Stewart/UninsIS/>

See appendix G for source code availability for software components that require making the source code available.

### Windows PowerShell Script License

In addition to the above, the package contains a set of Windows PowerShell scripts written by Bill Stewart that are used for installing and managing the software. The Windows PowerShell scripts are covered by the MIT license:

Copyright © 2019-2025 by Bill Stewart.

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

## Appendix G: Open Source Source Code

---

Some of the software components used by the CygSSH package have a license that requires the agent (a person or organization) who distributes the software to provide the source code for the software being distributed.

To meet this requirement for the CygSSH package, a zip file archive of the source code for the included software components covered by this kind of license is available at the following URL:

<https://github.com/Bill-Stewart/CygSSH/tree/master/usr/src>

From that page, do the following:

1. Click the **History** button to view the history of the **src** directory.
2. Click the **View at this point in the history** button for the desired version to view the **src** directory for that version.
3. Click the **source.zip** file to download that version of the source code files.

The source code is generally of interest only to developers.

## Appendix H: Version History

---

### 10.0.2 (2025-08-26)

- Updated to OpenSSH 10.0p2 and latest Cygwin packages.

### 10.0.1 (2025-05-14)

- Updated to OpenSSH 10.0p1-1 and latest Cygwin packages.
- Updated to Inno Setup 6.4.3.

### 9.9.0 (2024-12-09)

- Updated to OpenSSH 9.9p1-1 and latest Cygwin packages.
- Corrected client-only **mintty** issue.

### 9.8.0 (2024-07-10)

- Updated to OpenSSH 9.8p1-1 and latest Cygwin packages.
- Updated **Get-SSHHostKeyFingerprint.ps1** script not to use temporary files thanks to improvements in the **ssh-keyscan** tool.
- Updated to Inno Setup 6.3.2.

### 9.7.0 (2024-05-08)

- Updated to OpenSSH 9.7p1 and latest Cygwin packages.
- Added **Get-SSHHostKeyFingerprint.ps1** script.

### 9.4.1 (2023-08-10)

- Updated to OpenSSH 9.4p1-1 and latest Cygwin packages.

### 9.3.2 (2023-07-27)

- Updated to OpenSSH 9.3-p2-1 and latest Cygwin packages.
- Corrected installer bug: PathMgr.dll file not installed in per-user installation.
- Corrected installer bug: cygserver files installed in per-user installation.

### 9.3 (2023-03-28)

- Installer version synchronized with OpenSSH version.

### 9.2.3.0 (2023-02-04)

- Updated to OpenSSH 9.2 and latest packages (Cygwin, etc.).

### 3.0 (2022-12-06)

- Updated to OpenSSH 9.1, Cygwin 3.4, and rsync 3.2.7.
- Removed 32-bit and downlevel OS support.
- Removed **downloadsource** task.
- Minor tweaks.

### 2.2 (2022-08-11)

- Updated to OpenSSH 9.0.
- Updated Cygwin and Cygwin packages.

### 2.2 (2022-03-29)

- Updated to OpenSSH 8.9.
- Updated Cygwin packages.
- Uninstall fix: Only delete **PathMgr.dll** when package is uninstalled.

### 2.1 (2022-01-20)

- Updated Cygwin packages.
- Fix: Avoid multiple downloads of source code if **downloadsource** task is selected and user navigates backward then forward through setup wizard.

### 2.0 (2021-11-01)

- Updated to OpenSSH 8.8.
- Updated Cygwin packages.
- Added **downloadsource** installer task to download the source code during the installation process (see section 1.6).
- Added optional **resetconfig** installer task to reset the `ssh_config` and/or `sshd_config` files.
- Added support for **/FORCEUNINSTALL** installer command-line parameter (see chapter 1 and section 2.2).
- Updated installer to use more secure permissions for the `usr` and `tmp` directories.
- Added elevation check to **Set-FstabConfig.ps1** and **Set-SSHHostKey.ps1**.
- Changed permission update commands to use the Windows **icacls** command.
- Moved automatic executable detection to a more appropriate stage in the install process.

### 1.7 (2021-03-12)

- Updated Cygwin packages.
- Installer behavior change: If adding to the Path is selected, the installer will add to the beginning of the Path rather than the end. This change was made because newer versions of Windows have OpenSSH client utilities in the

system Path by default that can cause compatibility problems with the Cygwin programs. (Note that this change will not be effective if installing in non-administrative installation mode because the directories in the system Path always appear before the current user Path.)

- Removed clickable hyperlinks in RTF documents displayed by the installer to prevent accidental launching of an elevated browser.

#### 1.6 (2021-03-05)

- Updated to OpenSSH 8.5 and mintty 3.4.6.

#### 1.6 (2021-02-04)

- Dropped support for Windows Vista/Windows Server 2008 to increase the security of the installer.
- Updated Cygwin packages.
- Updated installer to use **PathMgr.dll** for system/user Path management.
- Updated PowerShell scripts to avoid informational messages from PowerShell parsers and to improve readability.
- Fixed typo in **New-SSHKey.ps1** script that caused an error message "Bits has bad value 0 (too small)".
- Updated documentation to mention addition of Windows firewall rule addition and fixed some typos.

#### 1.5

- Added missing DLLs that broke rsync.

#### 1.4

- Updated OpenSSH to version 8.4.
- Updated rsync to version 3.2.3.
- Updated Cygwin and associated packages.
- Added default nanorc configuration file.

#### 1.3

- Updated Cygwin and associated packages.
- Updated runposh tool to 1.3 (compile using FPC 3.2.0).
- Installer tweak: Clean `\usr\share` and `\usr\src` directories when installing.
- Package standardization: Installed application version matches installer version.

#### 1.2

- Updated OpenSSH to version 8.3.
- Added **mkgroup**, **mkpasswd**, and **ssh-pageant** tools.
- Updated **runposh** tool to version 1.2.
- Added default `cygserver.conf` and `virrc` configuration files.

#### 1.1

- Updated OpenSSH service not to use the Windows ConPTY API calls in newer versions of Windows by setting the `disable_pcon` setting in the `CYGWIN` environment variable. (The CygSSH package doesn't need the ConPTY support since it uses **winpty**.) See <https://cygwin.com/cygwin-ug-net/using-cygwinenv.html> for details.
- Added recommendation to run **ssh** and **sftp** using **mintty**.
- Updated **runposh** tool to version 1.1.

## 1.0

- Initial version.

# Index

---

Access Control List (ACL)	12, 18	host keys	15
access group, local	11	icacfs	12
account names, Cygwin	18	icons	5
acknowledgments	24	Inno Setup	4, 22
Active Directory	11	installation, client	5
additional tasks (installer)	6	installation, full	5
AllowGroups setting	11	installer additional tasks	6
AllowTcpForwarding setting	13	installer setup type	5
AuthenticationMethods setting	14	installpath	5
authentication, public key	15	install, silent	4
authorized_keys file	13	interactive shell	9
case-sensitive account names	19	jail (chroot)	20
chroot	20	key comment	17
ChrootDirectory setting	13, 20	key pairs	15, 16
chroot jail	20	key passphrase	17
client installation	5	known_hosts file	9, 15
/CLOSEAPPLICATIONS parameter	4, 7	license agreements	25
comment, key	17	links, documentation	22
ConPTY	30	local access group	11
cryptography, public key	15	Match User setting	14
/CURRENTUSER parameter	4, 5, 6	mintty	9, 30
cygdrive directory (SFTP-only)	14	modifypath installer task	6
cygpath command	19	New-SSHKey.ps1	16, 23
Cygwin	18, 22	noacl option (fstab file)	18
Cygwin account names	18	non-administrative install mode	4
CYGWIN environment variable	30	nsswitch.conf file	19
dev directory (SFTP-only)	14	open source	26
disable_pcon	30	OpenSSH	22
documentation links	22	passphrase, key	17
Edit-SSHKey.ps1	17, 23	passwd file	20
emulation	18	password authentication, using	11
firewall	4	path (environment variable)	6
ForceCommand setting	13	path names, POSIX	19
/FORCEUNINSTALL parameter	4, 28	permissions	12, 18
fstab file	18	POSIX	18
full installation	5	POSIX path names	19
Get-AccountName.ps1	19, 23	PowerShell scripts	23
Get-SSHHostKeyFingerprint.ps1	15, 23	.ppk file	17
Group Policy (GPO)	11	private key	15
home directory	19	privsep account	20
host key fingerprint	9, 15	.pub file	16

public key	15
public key authentication	15
public key authentication, using	12
public key cryptography	15
PuTTY	10
PuTTYgen	17
release history	27
root user account	20
rsync	18, 21, 22
scp command	9
service, start	6
Set-FstabConfig.ps1	23
Set-SSHGroup.ps1	23
Set-SSHHostKey.ps1	23
Set-SSHService.ps1	23
setup type (installer)	5
sftp command	9
SFTP-only	13
shell (interactive)	9
shortcuts	6
silent install	4
/SILENT parameter	4, 7
silent uninstall	8
source code	26
ssh command	9
ssh_config file	6
sshd account	4, 8, 20
sshd_config file	4, 6, 11, 13
.ssh directory	9, 12, 13
ssh-keygen command	16
SSH Users (local access group)	11
Start menu	5
startservice installer task	6
/SUPPRESSMSGBOXES parameter	4
system Path	6
system requirements	4
uninstall	8
user Path	6
using password authentication	11
using public key authentication	12
version history	27
Windows PowerShell scripts	23
WinSCP	10