

PERSONAL STATEMENT

Jianming Xing

The Hong Kong Polytechnic University
MSc in Intelligent Robotics Engineering

On a Dobot CR5, I learned that faster-looking execution can be less reliable. In my tests, non-blocking execution increased apparent command frequency, but a new policy inference could use an intermediate in-motion arm state before the preceding action chunk had finished. The resulting corrections drove the robot back and forth. I therefore used blocking, short-horizon ServoP action chunks, accepting lower apparent frequency to preserve state-action consistency and trajectory quality. This sharpened my guiding question: how can learning, control, timing, sensing, and safety form one reliable robot system?

My preparation combines complementary disciplines by design. In June 2025, I earned a B.Eng. in Mechanical Design, Manufacturing and Automation at Harbin Institute of Technology, Weihai. That degree and robotics projects grounded me in kinematics, robot modeling, and physical constraints. I am now pursuing a second bachelor’s degree in Computer Science and Technology at Harbin Institute of Technology, Shenzhen, expected in June 2027. This is not a departure from mechanical engineering, but a deliberate expansion from modeling machines to building the algorithms, data pipelines, and interfaces through which they perceive, learn, and act. Together, these perspectives let me examine embodied systems from physical and computational sides.

That combination became concrete in a CR5 data-collection and inference loop using an Orbbec Astra2 RGB-D camera, an electric gripper, and ROS2. I made RGB timestamps the HDF5 master clock, aligning robot states, target actions, and gripper feedback through binary search and linear interpolation. Using Fast DDS shared memory and RGB-only capture, I reduced recorded frame drops from 27.15% to the 2.57%-4.74% range. Rather than equate throughput with quality, I paired this transport improvement with schema, motion, workspace, and slow-playback checks before using or replaying an episode. I then converted synchronized episodes to LeRobot v2.0 and adapted OpenPI for CR5, using consistent seven-dimensional state and action semantics across collection, training configuration, and WebSocket-served deployment. The client translated policy chunks into ServoP arm targets and Modbus gripper commands. This continuity mattered because a dataset field is not merely a storage choice: it defines what the policy learns to predict and what the hardware later interprets. The project therefore made reliability a chain of aligned decisions across clocks, representations, validation, and execution timing.

A complementary research thread examines action representation. As a Research Assistant at iLearn, I am second author of Hermite Action Tokenizer for VLA, an unsubmitted working paper, and I am responsible for its discrete autoregressive tokenization branch. Working on this branch made representation a control question: what trajectory structure should tokenization preserve, and how should gripper decisions be encoded separately? The method separates seven-dimensional action chunks into six-dimensional end-effector trajectories and gripper states, with shared breakpoints removing endpoint redundancy and quantization seams. Under this offline protocol, which averages four LIBERO subsets with 8-by-7 action chunks, Hermite’s Endpoint MSE was approximately 99.7% lower than FAST and 82.6% lower than BEAST. These results show codec fidelity under the stated conditions; they do not establish online rollout performance or physical-robot error. The research showed that action encoding constrains what a model can express; CR5 deployment showed that execution schedules determine which state the model observes and what its command controls. Reliable embodied intelligence therefore

depends on representation and execution being joined through synchronized data.

During the Xbotics Embodied AI Community Internship, I migrated Isaac Lab's ANYmal-C navigation task into a MotrixLab NumPy environment. My judgment was to treat migration as interface preservation, not transcription. I refactored reset and step flows, command sampling, observations, rewards, and termination, corrected MuJoCo heightfield frames, added spawn and goal constraints, and used reward and termination regression checks. Earlier, in the HIT Weihai HERO RoboMaster Team's Vision Group, I helped modularize image acquisition, vision processing, and communication synchronization as ROS2 nodes and worked on host-MCU timing. These experiences reinforced that coordinate, interface, and timing assumptions must be explicit for integration.

My immediate goal is an R&D engineering role in robotics or embodied AI, connecting learning methods to sensing, control, and deployment. I want to strengthen my ability to design and evaluate real-hardware systems, where representation, timing, and physical constraints must be reconciled. After gaining stronger real-system experience, I may pursue doctoral study; it remains an option rather than a predetermined destination. I therefore seek graduate training whose curriculum and applied opportunities can close gaps between my integration experience and the robot systems I want to build. Dependable robots in industrial settings must do more than keep a policy and controller internally consistent: they must operate within task procedures, hardware limits, and constraints created by shared human workspaces. My representation research and CR5 deployment give me a technical starting point, but not yet the human-aware and operational perspective required for such systems. The MSc in Intelligent Robotics Engineering at The Hong Kong Polytechnic University (PolyU) would let me develop that perspective across learning, control, and robotic operation.

The published 2027/28 curriculum lists Embodied Robot Intelligence and Advanced Control Technology as core subjects, which would connect learned actions to physical behavior and deepen the feedback reasoning behind my ServoP decision. If offered when I register, the elective Industrial Human-Robot Systems and Automation would add human-aware workflows and industrial operating constraints that my previous projects did not address. If I were eligible for and selected the dissertation route, its seven taught subjects plus a Dissertation could support a study of how learned robot behavior should adapt when operating procedures, workspace limits, and task allocation change. I would contribute experience tracing behavior across synchronized data, policy interfaces, and robot commands, while using the programme to learn how those technical layers should adapt in human-aware industrial operation.