### **RELATÓRIO TÉCNICO**

# Uma Revisão Estruturada sobre as Vulnerabilidades de Segurança em Ambientes IoT

# Uma Revisão Estruturada sobre as Vulnerabilidades de Segurança em Ambientes IoT

#### 1. Introdução

#### 1.1. Contexto

O atributo de segurança é um dos principais fatores de impacto tanto em sistemas tradicionais quanto em ambientes de sistemas complexos, atrelado ao grau de atenção e cuidado com que os dados devem ser manuseados.

Em ambientes IoT, o atributo de segurança passa a exigir um cuidado redobrado com os seus sistemas de software e dispositivos, por se tratar de dados coletados e compartilhados por diferentes dispositivos e capturando os mais variados tipos de informação, exigindo um certo nível de privacidade. Entretanto, sabemos da fragilidade e dos perigos que espreitam pela rede, gerando muitas ameaças e destacando certas vulnerabilidades que esses sistemas contêm.

No entanto, conhecer as vulnerabilidades que permeiam esses cenários, garante que ameaças possam ser antecipadas e estratégias de mitigação possam ser traçadas para minimizar os riscos de invasão ou roubo de dados. Por este motivo, em uma tentativa de preencher essa lacuna crítica em ambientes IoT e em resposta às preocupações sobre as vulnerabilidades que permeiam as camadas de sistemas IoT, nosso principal objetivo é identificar e elencar as vulnerabilidades conhecidas em ambientes IoT, permitindo dessa forma ter uma base de informações sobre vulnerabilidade apontadas por estudos na área.

Para isso, essa Revisão Estruturada foi planejada e executada de forma a destacar com base em análises detalhadas as vulnerabilidades de segurança existentes em ambientes IoT. Ressaltamos uso da técnica Snowballing (Forward e Backward) para obter uma maior precisão nos resultados alcançados.

#### 2. Definicões

As definições referentes aos conceitos básicos de vulnerabilidade de segurança vêm da (ISO/IEC 27000 Tecnologia da informação — Técnicas de segurança — Sistemas de gerenciamento de segurança da informação — Visão geral e vocabulário). Onde vulnerabilidade é definida como:

- "Fraqueza de um ativo ou controle, que pode ser explorada por uma ou mais ameaças."
- "Weakness of an asset or control, that can be exploited by one or more threats."

#### 3. Questões de Pesquisa

#### 3.1. Objetivo

O objetivo da pesquisa deste estudo é identificar vulnerabilidades de segurança em sistemas de software e dispositivos IoT.

#### 3.2. Questões

#### 3.2.1. Problema

Aparentemente, não há disponibilidade de solução unificada que forneça os quesitos de segurança que necessitam ser tratados no desenvolvimento de sistemas de software IoT. Sendo assim, conhecer os principais pontos de vulnerabilidade em sistemas deste tipo pode ajudar a mitigar grande parte dos principais e mais comuns riscos associados a esses sistemas de software.

#### 3.2.2. Questão Principal

Quais vulnerabilidades afetam e podem ser identificadas em sistemas de software IoT?

#### 4. Estratégia de Busca

Os dados extraídos e analisados neste estudo serão identificados por meio da biblioteca digital SCOPUS, por integrar uma grande quantidade de outras bibliotecas no seu acervo de dados. Snowballing será usado para complementar as buscas.

#### 4.1. Idioma e Expressão de Busca

O idioma escolhido para a busca e seleção dos trabalhos foi o Inglês.

A busca foi restringida usando-se palavras-chave específicas para encontrar as publicações de interesse. A expressão de busca foi definida seguindo o princípio PICOC (Petticrew & Roberts, 2006)¹ na forma como os sinônimos são separados pelo conector lógico "OR" e os termos que compõem a string são separados por "AND", utilizando dos parâmetros "Population", "Intervention", "Comparison", "Outcome", e "Context".

<sup>&</sup>lt;sup>1</sup> Petticrew, Mark and Helen Roberts. Systematic Reviews in the Social Sciences: A Practical Guide. Oxford, UK: Blackwell Publishing Ltd, 2006, doi:10.1002/9780470754887.

PICOC	STRING
Population	"ambient intelligence" OR "assisted living" OR "multiagent systems" OR "systems of systems" OR "Cyber-Physical Systems" OR "Industry 4" OR "fourth industrial revolution" OR "web of things" OR "contemporary software systems" OR "smart manufacturing" OR digitalization OR digitization OR "digital transformation" OR "smart cit*" OR "smart building" OR "smart health" OR "smart environment" OR "smart grid"; AND
Intervention	"security" OR "vulnerability" OR "weakness" OR "Invasion" OR "threat" OR "attack" OR "anomaly" OR "malware" OR "confidentiality" OR "auditability" OR "risk"; AND
Comparison	Não Disponível
Outcome	"taxonomy" OR "categories" OR "classification" OR "Catalog"; AND
Context	"internet of things" OR "Internet of Everything" OR "IoT"

Para a Scopus, a string de busca utilizada foi:

TITLE-ABS-KEY ( ( "ambient intelligence" OR "assisted living" "systems of systems" "Cyber-Physical "multiagent systems" OR OR Systems" OR "Industry 4" OR "fourth industrial revolution" OR "web of things" OR "contemporary software systems" OR "smart manufacturing" OR digitalization OR digitization OR "digital transformation" OR "smart cit\*" OR "smart building" OR "smart health" OR "smart environment" OR "smart grid" OR "autonomous system") AND ("security" OR "vulnerability" OR "weakness" OR "Invasion" OR "threat" OR "attack" OR "anomaly" OR "malware" OR "confidentiality" OR "auditability" OR "risk" OR "menace") AND ("taxonomy" OR "categories" OR "classification" OR "Catalog" ) AND ("internet of things" OR "Internet of Everything" OR "IoT" ))

#### 4.2. Snowballing

Snowballing está sendo aplicado com as fontes selecionadas para extração de dados a partir das estratégias de busca automática. Aplicamos a estratégia do *Snowballing Forward* e *Backward* usando a Scopus como ferramenta para identificar as citações e demais referências.

#### 5. Processo de Seleção dos Estudos

Foram realizados os seguintes procedimentos de seleção na execução da string de busca da scopus:

- a. Aplicação dos critérios de seleção baseado no título, resumo e palavras-chave dos artigos;
- b. Aplicação dos critérios de seleção baseado na leitura completa dos artigos selecionados na etapa anterior.

Depois de finalizar a seleção por meio do motor de busca, usamos o conjunto de artigos incluídos para executar o snowballing backward (um nível) and forward seguindo o seguinte fluxo:

- a. Aplicação dos critérios de seleção baseado no Título dos artigos;
- b. Aplicação dos critérios de seleção baseado no Resumo dos artigos;
- Aplicação dos critérios de seleção baseado na Leitura completa dos artigos aceitos.

#### 6. Critérios de Seleção

#### 6.1. Critério de Inclusão

- Apresentar cenários focados em segurança em sistemas de software loT; e
- Identificar as vulnerabilidades identificadas dentro destes cenários.
- O trabalho deve ser escrito no idioma inglês.

#### 6.2. Critério de Exclusão

- Não estar disponível ou acessível por completo;
- Estudos Duplicados.

#### 7. Processo de Extração

Para cada fonte candidata, o procedimento de extração é realizado utilizando o modelo apresentado na Seção 7.1.

#### 7.1. Modelo de Extração

A) Dados da publicação:			
Título:	indica o título do trabalho		
Autor(es):	nome dos autores		
Fonte de Publicação:	local de publicação		
Ano da Publicação:	ano de publicação		

Resumo:	texto contendo uma descrição do resumo			
B) Dados derivados do obje	tivo:			
Vulnerabilidades	Quais as vulnerabilidades em sistemas de software IoT são destacadas no estudo?			

#### 8. Relatório da Execução

Data de Execução Scopus: 08/2022

Foram identificados 638 resultados de documentos. Eliminando proceedings e livros, restaram 492 no total.

Incluídos para extração de dados:

Após a análise do título e resumo, o número de documentos selecionados foi reduzido para 76. Em seguida, aplicamos o filtro de leitura de texto completo, reduzindo-o para 39 documentos finais, utilizados para a extração e analise das informações relevantes para o estudo.

- Incluídos pelo Snowballing
  - Backward snowballing: Foram identificados e incluídos um total de 86 artigos;
  - Forward snowballing: Foram identificados e incluídos um total de 43 artigos

O conjunto final de artigos selecionados:

- Pelo motor de busca (Scopus)
- [A1]. Saha. T. et al. (2022), "SHARKS: Smart Hacking Approaches for Risk Scanning in Internet-of-Things and Cyber-Physical Systems Based on Machine Learning," in IEEE Transactions on Emerging Topics in Computing, vol. 10, no. 2, pp. 870-885, doi: 10.1109/TETC.2021.3050733.
- [A2]. AbuEmera, E. A., ElZouka H. A. and Saad A. A. (2022), "Security Framework for Identifying threats in Smart Manufacturing Systems Using STRIDE Approach," 2nd International Conference on Consumer Electronics and Computer Engineering (ICCECE), Guangzhou, China, pp. 605-612, doi: 10.1109/ICCECE54139.2022.9712770.
- [A3]. Auliar, R. B. and Bekaroo G. (2021). "Security in IoT-based Smart Homes: A Taxonomy Study of Detection Methods of Mirai Malware and Countermeasures," 2021 International Conference on Electrical, Computer, Communications and Mechatronics Engineering (ICECCME), Mauritius, Mauritius, pp. 1-6, doi: 10.1109/ICECCME52200.2021.9590841.
- [A4]. Tomur, E. et al. (2021) "SoK: Investigation of Security and Functional Safety in Industrial IoT," 2021 IEEE International Conference on Cyber Security and

- Resilience (CSR), Rhodes, Greece, pp. 226-233, doi: 10.1109/CSR51186.2021.9527921.
- [A5]. Karie N. M. et al. (2021). "A Review of Security Standards and Frameworks for IoT-Based Smart Environments," in IEEE Access, vol. 9, pp. 121975-121995, doi: 10.1109/ACCESS.2021.3109886.
- [A6]. Davis B. D., Mason J. C. and Anwar M. (2020). "Vulnerability Studies and Security Postures of IoT Devices: A Smart Home Case Study," in IEEE Internet of Things Journal, vol. 7, no. 10, pp. 10102-10110, doi: 10.1109/JIOT.2020.2983983.
- [A7]. Akhunzada A., Islam S. U. and Zeadally S. (2020), "Securing Cyberspace of Future Smart Cities with 5G Technologies," in IEEE Network, vol. 34, no. 4, pp. 336-342, doi: 10.1109/MNET.001.1900559.
- [A8]. Sengupta, J., Ruj, S. and Das Bit, S. (2020). A Comprehensive Survey on Attacks, Security Issues and Blockchain Solutions for IoT and IIoT. Journal of Network and Computer Applications, 149, art. no. 102481. doi: 10.1016/j.jnca.2019.102481.
- [A9]. Roohi A., Adeel M. and Shah M. A. (2019), "DDoS in IoT: A Roadmap Towards Security & Countermeasures," 2019 25th International Conference on Automation and Computing (ICAC), Lancaster, UK, pp. 1-6, doi: 10.23919/IConAC.2019.8895034.
- [A10]. Akbar M. A. et al. (2021) "A Multicriteria Decision Making Taxonomy of IOT Security Challenging Factors," in IEEE Access, vol. 9, pp. 128841-128861, doi: 10.1109/ACCESS.2021.3104527.
- [A11]. Mahapatra, S.N., Singh, B.K. and Kumar, V. (2020). A Survey on Secure Transmission in Internet of Things: Taxonomy, Recent Techniques, Research Requirements, and Challenges. Arab J Sci Eng 45, 6211–6240. https://doi.org/10.1007/s13369-020-04461-2.
- [A12]. Wustrich L., Pahl M. and Liebald S. (2020)."Towards an Extensible IoT Security Taxonomy," 2020 IEEE Symposium on Computers and Communications (ISCC), Rennes, France, pp. 1-6, doi: 10.1109/ISCC50000.2020.9219584.
- [A13]. Mrabet, H. et al. (2020). A Survey of IoT Security Based on a Layered Architecture of Sensing and Data Analysis. Sensors, 20(13), 3625. https://doi.org/10.3390/s20133625.
- [A14]. Yang P., Xiong N. and Ren J. (2020). "Data Security and Privacy Protection for Cloud Storage: A Survey," in IEEE Access, vol. 8, pp. 131723-131740, doi: 10.1109/ACCESS.2020.3009876.

- [A15]. Yin, X.C. et al. (2019). Toward an Applied Cyber Security Solution in IoT-Based Smart Grids: An Intrusion Detection System Approach. Sensors, 19(22), 4952. https://doi.org/10.3390/s19224952.
- [A16]. Wazid, M et al. (2019). Authentication in cloud-driven IoT-based big data environment: Survey and outlook. Journal of Systems Architecture, 97, pp. 185-196. doi: 10.1016/j.sysarc.2018.12.005.
- [A17]. Sicato, J. C. S. et al. (2019). VPNFilter Malware Analysis on Cyber Threat in Smart Home Network. Appl. Sci. 9, 2763. https://doi.org/10.3390/app9132763.
- [A18]. Panchal A. C., Khadse V. M. and Mahalle P. N. (2018). "Security Issues in IIoT: A Comprehensive Survey of Attacks on IIoT and Its Countermeasures". IEEE Global Conference on Wireless Computing and Networking (GCWCN), Lonavala, India, pp. 124-130, doi: 10.1109/GCWCN.2018.8668630.
- [A19]. Heartfield, R., Loukas, G., Budimir, S., Bezemskij, A., Fontaine, J.R.J., Filippoupolitis, A., Roesch, E. (2018). A taxonomy of cyber-physical threats and impact in the smart home (Open Access). *Computers and Security*, 78, pp. 398-428. doi: 10.1016/j.cose.2018.07.011.
- [A20]. Hayashi, Y., Verbauwhede I. and Radasky, W. A. (2018). "Introduction to EM information security for IoT devices". IEEE International Symposium on Electromagnetic Compatibility and IEEE Asia-Pacific Symposium on Electromagnetic Compatibility (EMC/APEMC), Suntec City, Singapore, pp. 735-738, doi: 10.1109/ISEMC.2018.8393878.
- [A21]. Alqassem, I. and Svetinovic, D. (2014). "A taxonomy of security and privacy requirements for the Internet of Things (IoT)". IEEE International Conference on Industrial Engineering and Engineering Management, Selangor, Malaysia, pp. 1244-1248, doi: 10.1109/IEEM.2014.7058837.
- [A22]. Reda, H.T., Anwar, A., Mahmood, A. (2022). Comprehensive survey and taxonomies of false data injection attacks in smart grids: attack models, targets, and impacts (Open Access). Renewable and Sustainable Energy Reviews, 163, art. no. 112423. doi: 10.1016/j.rser.2022.112423.
- [A23]. Shah, Y. and Sengupta, S. (2020). "A survey on Classification of Cyber-attacks on IoT and IIoT devices," 2020 11th IEEE Annual Ubiquitous Computing, Electronics & Mobile Communication Conference (UEMCON), New York, NY, USA, pp. 0406-0413, doi: 10.1109/UEMCON51285.2020.9298138.
- [A24]. Zhao, W., Yang, S. and Luo X. (2020). "On Threat Analysis of IoT-Based Systems: A Survey," 2020 IEEE International Conference on Smart Internet of Things (SmartIoT), Beijing, China, pp. 205-212, doi: 10.1109/SmartIoT49966.2020.00038.

- [A25]. Kamaldeep, Dutta, M. and Granjal, J. (2020). "Towards a Secure Internet of Things: A Comprehensive Study of Second Line Defense Mechanisms," in IEEE Access, vol. 8, pp. 127272-127312, doi: 10.1109/ACCESS.2020.3005643.
- [A26]. Sookhak, M., Tang H. and Yu F. R. (2018). "Security and Privacy of Smart Cities: Issues and Challenge," 2018 IEEE 20th International Conference on High Performance Computing and Communications; IEEE 16th International Conference on Smart City; IEEE 4th International Conference on Data Science and Systems (HPCC/SmartCity/DSS), Exeter, UK, pp. 1350-1357, doi: 10.1109/HPCC/SmartCity/DSS.2018.00224.
- [A27]. Prakash S. and Jaiswal S. (2018). "Security Challenges in IoT enabled Smart Grid: Taxonomy of Novel Techniques and Algorithm," 3rd International Conference on Inventive Computation Technologies (ICICT), Coimbatore, India, pp. 577-582, doi: 10.1109/ICICT43934.2018.9034345.
- [A28]. Sfar, A. R., Chtourou Z. and Challal Y. (2017). "A systemic and cognitive vision for IoT security: A case study of military live simulation and security challenges". International Conference on Smart, Monitored and Controlled Cities (SM2C), Sfax, Tunisia, pp. 101-105, doi: 10.1109/SM2C.2017.8071828.
- [A29]. Thing V. L. L. and Wu J. (2016). "Autonomous Vehicle Security: A Taxonomy of Attacks and Defences". IEEE International Conference on Internet of Things (iThings) and IEEE Green Computing and Communications (GreenCom) and IEEE Cyber, Physical and Social Computing (CPSCom) and IEEE Smart Data (SmartData), Chengdu, China, pp. 164-170, doi: 10.1109/iThings-GreenCom-CPSCom-SmartData.2016.52.
- [A30]. Sookhak, M., Tang, H., He, Y. and Yu, F. R. (2019). "Security and Privacy of Smart Cities: A Survey, Research Issues and Challenges," in IEEE Communications Surveys & Tutorials, vol. 21, no. 2, pp. 1718-1743, Secondquarter, doi: 10.1109/COMST.2018.2867288.
- [A31]. Patnaik, R., Srujan Raju, K., Sivakrishna, K. (2021). Internet of Things-Based Security Model and Solutions for Educational Systems. In: Kumar, R., Sharma, R., Pattnaik, P.K. (eds) Multimedia Technologies in the Internet of Things Environment. Studies in Big Data, vol 79. Springer, Singapore. https://doi.org/10.1007/978-981-15-7965-3\_11.
- [A32]. Han, T., Jan, S. R. U., Tan, Z., Usman, M., Jan, M. A., Khan, R., & Xu, Y. (2020). A comprehensive survey of security threats and their mitigation techniques for next-generation SDN controllers. Concurrency and Computation: Practice and Experience, 32(16), e5300.
- [A33]. Sahmi, I., Mazri, T. and Hmina, N. (2019). Study of the Different Security Threats on the Internet of Things and their Applications. In Proceedings of the 2nd

International Conference on Networking, Information Systems & Security (NISS19). Association for Computing Machinery, New York, NY, USA, Article 68, 1–6. https://doi.org/10.1145/3320326.3320402.

- [A34]. Benzarti, S., Triki, B. and Korbaa, O. (2017). "A survey on attacks in Internet of Things based networks," 2017 International Conference on Engineering & MIS (ICEMIS), Monastir, Tunisia, pp. 1-7, doi: 10.1109/ICEMIS.2017.8273006.
- [A35]. Xu, H., Sgandurra, D., Mayes, K., Li, P., Wang, R. (2017). Analysing the Resilience of the Internet of Things Against Physical and Proximity Attacks. In: Wang, G., Atiquzzaman, M., Yan, Z., Choo, KK. (eds) Security, Privacy, and Anonymity in Computation, Communication, and Storage. SpaCCS 2017. Lecture Notes in Computer Science, vol 10658. Springer, Cham. https://doi.org/10.1007/978-3-319-72395-2\_27.
- [A36]. Gupta, A., and Gupta, S. K. (2022). Flying through the secure fog: A complete study on UAV-Fog in heterogeneous networks. International Journal of Communication Systems, 35(13), e5237.
- [A37]. Ali, R.F., Muneer, A., Dominic, P.D.D., Taib, S.M., Ghaleb, E.A.A. (2021). Internet of Things (IoT) Security Challenges and Solutions: A Systematic Literature Review. In: Abdullah, N., Manickam, S., Anbar, M. (eds) Advances in Cyber Security. ACeS 2021. Communications in Computer and Information Science, vol 1487. Springer, Singapore. https://doi.org/10.1007/978-981-16-8059-5\_9.
- [A38]. Rahimi, H., Zibaeenejad, A., Rajabzadeh, P. and Safavi A. A. (2018). On the Security of the 5G-IoT Architecture. In Proceedings of the international conference on smart cities and internet of things (SCIOT '18). Association for Computing Machinery, New York, NY, USA, Article 10, 1–8. https://doi.org/10.1145/3269961.3269968.
- [A39]. Elham Kariri. (2022). IoT Powered Agricultural Cyber-Physical System: Security Issue Assessment, IETE Journal of Research, DOI: 10.1080/03772063.2022.2032848.

#### 8.1 Extração dos Dados

Seguindo o modelo de extração informado na seção anterior, os dados desejados foram identificados e extraídos dos artigos selecionados, a extração dos dados podem ser consultadas no apêndice deste relatório.

#### 9. Relatório da Revisão

Nesta seção serão apresentados a listagem das vulnerabilidade identificadas na revisão executada. Foram identificadas 72 vulnerabilidades, em uma listagem não envolvendo os resultados do snowballing, destacadas na Tabela 1. As

vulnerabilidades foram organizadas inicialmente em quatro categorias: *Device*, *Application, Network* e *Peopleware*.

Tabela 1 - Lista de Vulnerabilidades

Artigos	Vulnerabilities	Categoria
13, 5, 23, 4, 17	Broken Authentication	Application
9, 31, 38, 1, 25, 17, 6	Buffer Overflow	Application
8	Data Inconsistency	Application
8, 13, 11, 21, 9, 37, 27, 18, 4, 24	Insecure Access Management	Application
11, 31	Insecure Interface Configuration	Application
11, 5, 37, 33, 26	Insecure Management of Data	Application
5, 23, 31, 33, 15, 24	Insecure Software	Application
5	Lack of Active Device Monitoring	Application
5	Lack of Standardization	Application
9	Low Quality Level Code	Application
19, 21, 2, 24	Non-repudiation	Application
32, 18, 33, 17, 6, 24	SQL Injections	Application
11, 27	Weak/lack In-app Encryption	Application
38, 26, 24	Malicious code in-app	Application
24	Systems Low-cost	Device
8, 19	Channel Voice	Device
19, 10, 23, 35, 24	Default Configuration	Device
8, 5, 21, 39, 18, 25	Device Spoofing	Device
19, 10, 30, 20, 24	Electromagnetic Emanations Leaking	Device
16, 22, 30, 24, 26	Energy Restraints	Device
8, 11, 19, 10	Heterogeneous Interaction	Device
11, 19, 10, 5, 16, 9, 37, 39, 38, 30, 25, 26, 36	Insecure Data Transfer and Storage	Device
10, 5, 23, 35, 31, 1, 4, 24	Insecure Firmware	Device
31, 30, 24	Insecure Initialization	Device
5, 37, 3, 36	Insecure Password	Device
5, 24	Insufficient Testing	Device
8, 23, 16, 29, 30, 4, 12, 6, 20, 24	Lack of Side Channel Protection	Device
10, 5, 23, 28, 21, 35, 29, 9, 37, 30, 4, 33, 25	Lack of Strong Authentication	Device
11, 10, 28, 16, 9, 37, 30, 33, 25,	Low Computing Power	Device

12, 6, 24		
35, 9	Low Data Transmission Range	Device
8, 34, 35, 29, 33, 24	Malicious Code Injection	Device
35, 39, 7, 12, 20, 24	Obtaining Console Access	Device
16, 39, 33, 12, 17, 24	Physical Damage	Device
8, 19, 5, 34, 23, 39, 7, 33, 25, 17, 20, 24, 36	Physical Tampering	Device
8, 31, 37, 33, 12, 17, 6, 24	Sleep Deprivation	Device
35, 38	Tag Cloning	Device
11, 23, 35, 16, 39, 38, 7, 4, 33, 12, 6, 24	Unprotected Physical Access	Device
5, 23, 28, 21, 35, 29, 37, 38, 30, 27, 18, 4, 25	Weak Access Control	Device
10, 5, 29, 31, 38, 30, 27, 25, 36	Weak/leak of Encrypt	Device
31	Insecure physical interface	Device
8, 19, 34, 35, 29, 31, 38, 7, 33, 6, 36	Channel Interference	Network
32	Communication Overhead	Network
8, 13, 34, 23, 22, ´14, 37, 7, 30, 1, 25, 26, 36	Data Leak or Breach	Network
11, 19, 5, 23, 22, 39, 38, 33, 17, 24	Eavesdropping	Network
8, 11, 10, 34, 38, 7, 4, 33, 12, 17, 6, 24	Fake/Malicious Node	
11, 19, 10, 35, 30, 25, 26	Heterogeneous Communication	Network
14, 30, 18	Insecure Server	Network
11	Insecure Update Mechanisms	Network
8, 11,5, 28, 21, 16, 37, 38, 30, 27, 18, 25, 6, 2, 36	Lack of Proper Authenticatication Mechanisms	Network
23, 18, 4	Lack of Strong Password	Network
19, 5, 22, 31, 25, 24	Lack Secure Communication Protocols	Network
10	Configure network repeatedly	Network
32	Single-Point Dependency	Network
32, 8, 11	Spoofing Signal	Network
32, 8, 11, 19, 28, 21, 29, 14, 37, 39, 38, 7, 30, 27, 33, 25, 2, 24	Unauthorized Access	Network
5, 23, 18	Unsecured Network	Network
23, 7, 3, 18, 15	Unused Ports Enable	Network
19, 5, 29, 14, 31, 37, 39, 30, 27, 18, 1, 2, 26	Weak/lack Encryption in Communication	Network

22, 36	Physical properties of the power system	Network
19	Wifi De-authentication	Network
29	Insecure traffic control	Network
24, 36	Centralized architecture	Network
8, 35, 17	Access Malicious Link	Peopleware
19	Identifying the Product Vendor	Peopleware
5, 15, 12	Knowledge the System	Peopleware
10	Lack of Technical Support	Peopleware
19, 10, 28, 39, 17	Personal and Social Circumstances	Peopleware
34, 23, 39, 38, 18, 33, 12, 6, 24, 36	Phishing	Peopleware
19, 5, 39, 7, 33, 6	Social Engineering	Peopleware
5	Untrusted Device Acquisition	Peopleware
5	Vendor Security Posture	Peopleware

#### 10. Conclusão

Diante da expansão significativa pela qual os dispositivos loT tem passado nos ultimos anos, é visível seu potencial de engajamento nos mais variados setores, o que requer uma atenção especial para como comporta e manipula seus dados, já que para tecnologias loT a variedade de dados sensíveis é realmente grande.

Por esse motivo, a segurança nos ambientes loT passa a ser um componente crucial para o funcionamento adequado desse tipo de tecnologia. E dentre os principais vetores associados à segurança, destacamos as Vulnerabilidades como campo de estudo com impacto significativo na retenção de danos associados à ameaças ou ataques que possam interferir diretamente no desempenho das tecnologias loT.

Esse relatório busca apresentar um conjunto de vulnerabilidades identificadas no contexto da IoT, classificadas inicialmente entre quatro categorias ligadas às principais camadas da IoT (Física, Aplicação e Rede), com o acréscimo do *Peopleware*, onde são associadas as vulnerabilidades ligadas diremente ao agente humano. Foram catalogadas com as buscas 70 vulnerabilidades, dentre os estudos identificados apenas pela maquina de busca. Os dados do processo de Snowballing serviram para dar suporte e reforçar os achados da revisão, já que durante a extração não foram identificados novos pontos de vulnerabilidades.

Esperamos como este relatório, permitir que pesquisadores que atuam na area de desenvolvimento de sistemas iot possam prever riscos de segurança associados a seus projetos baseadis nessa listagem de vulnerabilidades e até mesmo estimar formas de mitigá-las que permitam que seus sistemas sejam cada vez mais seguros.

## APÊNDICE A – EXTRAÇÃO DE DADOS DA REVISÃO ESTRUTURADA

Autor(es): Fonte de Publicação: Ano da Publicação: Resumo:  Cy de fur cri ve inh ha su pre vu inc no rea reç tec ne tha be or of wit de tin- km de tha be su B) Dados derivados do objetivo:	ber-physical systems (CPS) and Internet-of-Things (IoT) vices are increasingly being deployed across multiple actionalities, ranging from healthcare devices and wearables to cical infrastructures, e.g., nuclear power plants, autonomous nicles, smart cities, and smart homes. These devices are therently not secure across their comprehensive software, rdware, and network stacks, thus presenting a large attack face that can be exploited by hackers. In this article, we essent an innovative technique for detecting unknown system merabilities, managing these vulnerabilities, and improving ident response when such vulnerabilities are exploited. The velty of this approach lies in extracting intelligence from known al-world CPS/IoT attacks, representing them in the form of gular expressions, and employing machine learning (ML) chiniques on this ensemble of regular expressions to generate we attack vectors and security vulnerabilities. Our results show at 10 new attack vectors and 122 new vulnerability exploits can successfully generated that have the potential to exploit a CPS an IoT ecosystem. The ML methodology achieves an accuracy 97.4 percent and enables us to predict these attacks efficiently
Autor(es): Fonte de Publicação: Ano da Publicação: Resumo: Cy de fur cri ve inh ha su pre vu inc no rea reç tec ne tha be or of wit de in- kn de the me se ad B) Dados derivados do objetivo:	chine Learning ha, T. and Aaraj, N. and Ajjarapu, N. and Jha, N.K.  ETransactions on Emerging Topics in Computing  22 ber-physical systems (CPS) and Internet-of-Things (IoT) vices are increasingly being deployed across multiple actionalities, ranging from healthcare devices and wearables to cical infrastructures, e.g., nuclear power plants, autonomous nicles, smart cities, and smart homes. These devices are erently not secure across their comprehensive software, rdware, and network stacks, thus presenting a large attack face that can be exploited by hackers. In this article, we esent an innovative technique for detecting unknown system nerabilities, managing these vulnerabilities, and improving ident response when such vulnerabilities are exploited. The velty of this approach lies in extracting intelligence from known al-world CPS/IoT attacks, representing them in the form of gular expressions, and employing machine learning (ML) chniques on this ensemble of regular expressions to generate w attack vectors and security vulnerabilities. Our results show at 10 new attack vectors and 122 new vulnerability exploits can successfully generated that have the potential to exploit a CPS an IoT ecosystem. The ML methodology achieves an accuracy 97.4 percent and enables us to predict these attacks efficiently
Autor(es): Fonte de Publicação: Ano da Publicação: Resumo:  Cy de fur cri ve inh ha su pre vu inc no rea reç tec ne tha be or of wit de in- kn de the me se ad B) Dados derivados do objetivo:	ha, T. and Aaraj, N. and Ajjarapu, N. and Jha, N.K.  E Transactions on Emerging Topics in Computing  22  ber-physical systems (CPS) and Internet-of-Things (IoT) vices are increasingly being deployed across multiple actionalities, ranging from healthcare devices and wearables to cical infrastructures, e.g., nuclear power plants, autonomous nicles, smart cities, and smart homes. These devices are increatly not secure across their comprehensive software, rdware, and network stacks, thus presenting a large attack face that can be exploited by hackers. In this article, we seen an innovative technique for detecting unknown system inerabilities, managing these vulnerabilities, and improving ident response when such vulnerabilities are exploited. The velty of this approach lies in extracting intelligence from known al-world CPS/IoT attacks, representing them in the form of gular expressions, and employing machine learning (ML) chniques on this ensemble of regular expressions to generate we attack vectors and security vulnerabilities. Our results show at 10 new attack vectors and 122 new vulnerability exploits can successfully generated that have the potential to exploit a CPS an IoT ecosystem. The ML methodology achieves an accuracy 197.4 percent and enables us to predict these attacks efficiently
Fonte de Publicação: Ano da Publicação: Resumo:  Cy de fur cri ve inh ha su pre vu inc no rea reg tec ne tha be or of wit de in- kn de the me se ad B) Dados derivados do objetivo:	ber-physical systems (CPS) and Internet-of-Things (IoT) vices are increasingly being deployed across multiple actionalities, ranging from healthcare devices and wearables to cical infrastructures, e.g., nuclear power plants, autonomous nicles, smart cities, and smart homes. These devices are terently not secure across their comprehensive software, rdware, and network stacks, thus presenting a large attack face that can be exploited by hackers. In this article, we seen an innovative technique for detecting unknown system nerabilities, managing these vulnerabilities, and improving ident response when such vulnerabilities are exploited. The velty of this approach lies in extracting intelligence from known al-world CPS/IoT attacks, representing them in the form of gular expressions, and employing machine learning (ML) chniques on this ensemble of regular expressions to generate we attack vectors and security vulnerabilities. Our results show at 10 new attack vectors and 122 new vulnerability exploits can successfully generated that have the potential to exploit a CPS an IoT ecosystem. The ML methodology achieves an accuracy 97.4 percent and enables us to predict these attacks efficiently
Ano da Publicação:  Resumo:  Cy de fur cri ve inh ha su pre vu inc no rea reç tec ne tha be or of wit de in- kn de the me se ad  B) Dados derivados do objetivo:	ber-physical systems (CPS) and Internet-of-Things (IoT) vices are increasingly being deployed across multiple actionalities, ranging from healthcare devices and wearables to cical infrastructures, e.g., nuclear power plants, autonomous nicles, smart cities, and smart homes. These devices are terently not secure across their comprehensive software, rdware, and network stacks, thus presenting a large attack face that can be exploited by hackers. In this article, we esent an innovative technique for detecting unknown system nerabilities, managing these vulnerabilities, and improving ident response when such vulnerabilities are exploited. The velty of this approach lies in extracting intelligence from known al-world CPS/IoT attacks, representing them in the form of gular expressions, and employing machine learning (ML) chniques on this ensemble of regular expressions to generate w attack vectors and security vulnerabilities. Our results show at 10 new attack vectors and 122 new vulnerability exploits can successfully generated that have the potential to exploit a CPS an IoT ecosystem. The ML methodology achieves an accuracy 97.4 percent and enables us to predict these attacks efficiently
Resumo:  Cy de fur cri ve inh ha su pre vu inc no rea reç tec ne tha be or of wit de in- kn de the me se ad  B) Dados derivados do objetivo:	ber-physical systems (CPS) and Internet-of-Things (IoT) vices are increasingly being deployed across multiple actionalities, ranging from healthcare devices and wearables to cical infrastructures, e.g., nuclear power plants, autonomous nicles, smart cities, and smart homes. These devices are therently not secure across their comprehensive software, rdware, and network stacks, thus presenting a large attack face that can be exploited by hackers. In this article, we essent an innovative technique for detecting unknown system nerabilities, managing these vulnerabilities, and improving ident response when such vulnerabilities are exploited. The velty of this approach lies in extracting intelligence from known al-world CPS/IoT attacks, representing them in the form of gular expressions, and employing machine learning (ML) chiniques on this ensemble of regular expressions to generate we attack vectors and security vulnerabilities. Our results show at 10 new attack vectors and 122 new vulnerability exploits can successfully generated that have the potential to exploit a CPS an IoT ecosystem. The ML methodology achieves an accuracy 97.4 percent and enables us to predict these attacks efficiently
de fur cri ve inh ha su pre vu inc no rea reç tec ne tha be or of with de in-kn de the me se ad	vices are increasingly being deployed across multiple actionalities, ranging from healthcare devices and wearables to cical infrastructures, e.g., nuclear power plants, autonomous nicles, smart cities, and smart homes. These devices are erently not secure across their comprehensive software, rdware, and network stacks, thus presenting a large attack face that can be exploited by hackers. In this article, we esent an innovative technique for detecting unknown system nerabilities, managing these vulnerabilities, and improving ident response when such vulnerabilities are exploited. The velty of this approach lies in extracting intelligence from known al-world CPS/IoT attacks, representing them in the form of gular expressions, and employing machine learning (ML) chniques on this ensemble of regular expressions to generate we attack vectors and security vulnerabilities. Our results show at 10 new attack vectors and 122 new vulnerability exploits can successfully generated that have the potential to exploit a CPS an IoT ecosystem. The ML methodology achieves an accuracy 197.4 percent and enables us to predict these attacks efficiently
B) Dados derivados do objetivo: "D	h an 87.2 percent reduction in the search space. We monstrate the application of our method to the hacking of the vehicle network of a connected car. To defend against the own attacks and possible novel exploits, we discuss a fense-in-depth mechanism for various classes of attacks and e classification of data targeted by such attacks. This defense echanism optimizes the cost of security measures based on the nsitivity of the protected resource, thus incentivizing its
"D	option in real-world CPS/loT by cybersecurity practitioners
the ne "TI da ea	ue to the absence of sender and receiver addresses in the data mes, every ECU can freely publish and receive messages from a bus. While this enables easier addition of new ECUs to the twork, it poses a grave security threat to the system."  In allows a malicious node on the CAN bus to receive all the ta frames through sniffing. The absence of encryption makes it sier to analyze the collected frames."
bro	sing the details of the data frames, the adversary can badcast malicious frames on the bus by spoofing a particular de. Absence of authentication schemes compromises the

for transmission on the bus than messages from climate control sensors."
"Since the CAN protocol is bereft of authentication schemes and time-stamp verification, the recorded frame packets can be sent on the CAN bus at inconvenient time instances to launch various attacks."
"The other vulnerabilities that we consider in our experiments are ECU buffer overflows"
"and malware injection through ECU firmware updates"

A) Dados da publicação:	
Título:	Security Framework for Identifying threats in Smart Manufacturing Systems Using STRIDE Approach
Autor(es):	Abuemera, E.A. and Elzouka, H.A. and Saad, A.A.
Fonte de Publicação:	2nd International Conference on Consumer Electronics and Computer Engineering, ICCECE
Ano da Publicação:	2022
Resumo:	Cyber security is still the main argument in any system development lifecycle that needs more concern. There are still numerous challenges associated with conducting a threat modeling approach for smart manufacturing systems. One of these challenges is the lack of a threat database based on the expertise of highly skilled researchers in this field. Hence this study attempts to address this gap by developing a components catalog and a rule-based threat database to address potential security threats in smart manufacturing systems saving time and effort. Specifically, it performs STRIDE-based threat modeling against a smart factory use case using Microsoft Threat Modelling Tool. The threat evaluation process is conducted with this research to determine the severity of threats and give a preliminary estimation of the overall system's risk
B) Dados derivados do objetivo:	
	"In the use case, there is no method for logging and recording events. As a result, the processes are vulnerable to repudiation threats and might deny previous events."
Vulnerabilidades	"Information disclosure threats are due to the lack of encryption. Attackers can simply decode and understand unencrypted messages."  "Although most elevation of privilege threats is due to the lack of access control rules based on authorization, the elevation of
	privilege on EE-1 by tricking the operator into opening a crafted PowerPoint document is due to Windows OLE Remote Code Execution vulnerability"

A) Dados da publicação:									
Título:	Security	in	IoT-based	smart	homes:	Α	taxonomy	study	of
	detection	me	ethods of mir	ai malw	are and	cou	ntermeasur	es	

Autor(es):	Auliar, R.B. and Bekaroo, G.
Fonte de Publicação:	International Conference on Electrical, Computer,
	Communications and Mechatronics Engineering, ICECCME
Ano da Publicação:	2021
Resumo:	During recent years, there has been widespread adoption of the Internet and swift digitization within various sectors, including smart homes. These also led to the rapid growth of the Internet of Things (IoT), which is expected to proliferate further, where 50 billion IoT devices are estimated to be connected to the Internet by 2030. However, the growth in connected IoT devices to the Internet has not been without challenges. IoT devices are known to have various vulnerabilities that could be exploited by attackers, thus hindering security of devices and users. Recently, the use of Mirai malware by attackers gained significant attention as it has the capability to transform IoT connected devices into remotely controlled bots, which can be utilized as part of a botnet in large-scale network attacks. Taking cognizance of the importance to secure against this type of malware, this study presents a taxonomy review on the techniques that can potentially be used to detect Mirai malware along with countermeasures for securing against such malware
B) Dados derivados do objetivo:	
	"Strengthening Password Protection - Each device must consist of a unique password instead of common passwords for specific model since Mirai botnets target lists of hardcoded passwords"  "Disabling Unused Ports - Unused ports such as SSH, and Telnet among others should be disabled by default for end users might not be aware of open ports and could hence be targeted by Mirai botnets."
Vulnerabilidades	"Monitoring Open Ports - Open ports should be monitored to analyze traffic that could source from a malicious origin."
	"Restructuring Device Firmware - Device firmware are often exploited via the use of various methods and tools that analyze firmware for issues pertaining to authentication and to bypass backdoors"
	"Ensuring Proper Configuration - In addition, open connections must not be with default configuration for wireless communications."

A) Dados da publicação:	
Título:	SoK: Investigation of security and functional safety in industrial IoT
Autor(es):	Tomur, E. and Gulen, U. and Soykan, E.U. and Akif Ersoy, M. and Karakoc, F. and Karacay, L. and Comak, P.
Fonte de Publicação:	IEEE International Conference on Cyber Security and Resilience, CSR
Ano da Publicação:	2021
Resumo:	There has been an increasing popularity of industrial usage of Internet of Things (IoT) technologies in parallel to advancements in connectivity and automation. Security vulnerabilities in

industrial systems, which are considered less likely to be exploited in conventional closed settings, have now started to be a major concern with Industrial IoT. One of the critical components of any industrial control system turning into a target for attackers is functional safety. This vital function is not originally designed to provide protection against malicious intentional parties but only accidents and errors. In this paper, we explore a generic IoT-based smart manufacturing use-case from a combined perspective of security and functional safety, which are indeed tightly correlated. Our main contribution is the presentation of a taxonomy of threats targeting directly the critical safety function in industrial IoT applications. Besides, based on this taxonomy, we identified particular attack scenarios that might have severe impact on physical assets like manufacturing equipment, even human life and cyber-assets like availability of Industrial IoT application. Finally, we recommend some solutions to mitigate such attacks based mainly on industry standards and features of mobile advanced security communication technologies.

#### B) Dados derivados do objetivo:

"Unauthorized physical access of any malicious party to the devices belonging to the safety control system may present a threat to take control of a safety-related asset like Safety Program"

"Manipulation of Software - Attacks are possible on assets which can be used to configure and parameterize the safety systems like Engineering Workstation. Malicious modifications of safety programs, safety parameters or any other software/hardware on safety controller, safety actuator and safety sensor can be done to adversely affect the operation of functional safety"

"There can be attacks that aim malicious intervening with cyclic communication between Safety Controller (Safety Program), Safety Actuator and Safety Sensor. Attacker may aim to obstruct, destruct or modify"

"Attacks can be performed on the Safety Controller over network via its remote programming or monitoring interfaces. Similar to the reported weaknesses in IoT devices, safety controllers are also prone to weak authentication and authorization practices."

"If they are accessible remotely, any type of attacker may try to break authentication, for instance, by using unchanged default passwords or applying a brute force attack"

"Vulnerabilities in built-in security features of safety devices (actuator, sensor or controller) can be exploited because of weak credential management, firmware update from untrusted source or lack of side channel protection".

"Malware injected into Safety Program either directly or indirectly via Engineering Workstation can allow attackers to manipulate safety program code in such a way that it does not command switching into fail-safe mode when there is potentially dangerous situation or it commands to do so when there is no such situation."

"(Denial of Service): Injection of a high volume of packets in the OT network or flooding of malicious traffic to overload system

#### Vulnerabilidades

resources in Safety Program	by attackers can cause disruption in
timely operation of the overall	Il safety function."

A) Dados da publicação:		
Título:	A Review of Security Standards and Frameworks for IoT-Based Smart Environments	
Autor(es):	Karie, N.M. and Sahri, N.M. and Yang, W. and Valli, C. and Kebande, V.R.	
Fonte de Publicação:	IEEE Access	
Ano da Publicação:	2021	
B) Dados derivados do objetivo:	Assessing the security of IoT-based smart environments such as smart homes and smart cities is becoming fundamentally essential to implementing the correct control measures and effectively reducing security threats and risks brought about by deploying IoT-based smart technologies. The problem, however is in finding security standards and assessment frameworks that best meets the security requirements as well as comprehensively assesses and exposes the security posture of IoT-based smar environments. To explore this gap, this paper presents a review of existing security standards and assessment frameworks which also includes several NIST special publications on security techniques highlighting their primary areas of focus to uncover those that can potentially address some of the security needs of IoT-based smart environments. Cumulatively a total of 80 ISO/IEC security standards, 32 ETSI standards and 37 different conventional security assessment frameworks which included 70 NIST special publications on security techniques were reviewed To present an all-inclusive and up-to-date state-of-the-ar research, the review process considered both published security standards and assessment frameworks as well as those under development. The findings show that most of the conventional security standards and assessment frameworks do not directly address the security needs of IoT-based smart environments but have the potential to be adapted into IoT-based smar environments. With this insight into the state-of-the-art research on security standards and assessment frameworks, this study helps advance the IoT field by opening new research directions as well as opportunities for developing new security standards and assessment frameworks, this study is proposed in this paper which also maps the identified challenges to potential proposed solutions.	
	"Data and Information Leakage: In any IoT smart environment without proper security mechanisms that protect data and information from malware and other malicious intruders, personal information could easily be leaked resulting in security breaches."	
Vulnerabilidades	"With information moving in and around IoT-based smar environments and over to the Internet, malicious attackers car take advantage of unsecured network communications and stea data as it is being transmitted between the connected IoT devices which can lead to other serious security breaches."	

"Many cloud-based IoT devices and systems are known to have security vulnerabilities and can easily be victims of hacking and cyberattacks as data transmission like video data from cameras may not even be encrypted when sent over the internet."

"Because of the lack of standardization in many IoT-based smart environments, rogue software can easily find its way into IoT devices through firmware upgrade and trusted boot, device acquisition as well as apps and services."

"Because of the lack of specialized universal approved IoT security standards or security assessment frameworks, some devices may be manufactured with poor security baselines such as old and unpatched embedded operating systems and software, weak, guessable, or hard-coded passwords, insecure data transfer and storage, among others. This makes such IoT devices vulnerable to different security threats and attacks."

"With the growing innovation of IoT technologies, many users are yet to understand how modern IoT devices are designed and function. This makes it easy for attackers to use social engineering to trick IoT device users into providing sensitive data or information which can be used to gain access into smart environment networks, such as smart homes and smart cities, putting everyone's life at risk."

"Insufficient IoT Device Testing and Updates: Most of the IoT devices are produced quickly to meet the increasing market demands and hence do not undergo proper testing or follow any acceptable security standards or assessment frameworks"

"Users mostly put their trust in the manufactures to test the IoT devices as well as provide security control measures. However, due to high demands, many manufacturers focus more on creating and releasing new products to the market without having proper testing or putting security control measures in place."

"Lack of Active Device Monitoring: Monitoring IoT devices can be challenging. This is because most of the existing monitoring tools and practices especially those focusing on the cloud were traditionally designed to monitor time-series metric data with no focus on modern IoT devices or their processes."

"The lack of efficient and robust security protocols including proper IoT security standards, assessment frameworks and safeguards could lead to security breaches in smart environments leading to personal data exfiltration."

"With many IoT devices in smart environments lacking strong authentication or access control mechanisms, it becomes easy for intruders to impersonate a legitimate user and use the credentials or any other information that gives them access to existing IoT resources in an IoT-based smart environment."

"Denial of Service (DoS/DDoS): With the advancement in technology, hackers can try to cause a DoS/DDoS to existing hubs in IoT-based smart environment networks or the sensors themselves."

"With the rapid growth in the number and usage of IoT devices,
other security threats may also exist in IoT-based smart
environments such as home invasions, trespass, falsification
rogue and counterfeit IoT devices, botnet attacks, physical
attacks, unintentional damage or loss, disasters and outages,
failures or malfunctions, dynamic systems, authentication,
unsecured wireless network problems, side-channel attack,
man-in-the-middle, identity theft, advanced persistent threat
(APT), jamming, function creep, buffer overflow, large-scale
unauthorized data mining, surveillance, unauthorized access or
deletion or modification of data, worms, viruses and malicious
code, the openness of the networked systems, weak passwords,
fixed firmware, resource constraints, headless nature of IoT
devices, tamper-resistant packages, heterogeneous protocols,
dynamic characteristics, longevity expectations among many
other security threats."

A) Dados da publicação:	
Título:	Vulnerability Studies and Security Postures of IoT Devices: A Smart Home Case Study
Autor(es):	Davis, B.D. and Mason, J.C. and Anwar, M.
Fonte de Publicação:	IEEE Internet of Things Journal
Ano da Publicação:	2020
Resumo:	Internet-of-Things (IoT) technology has revolutionized our daily lives in many ways-whether it is the way we conduct our day-to-day activities inside our home, or the way we control our home environments remotely. Unbeknownst to the users, with the adoption of these 'smart home' technologies, their personal space becomes vulnerable to security and privacy attacks. We conducted studies of vulnerabilities and security posture of smart home IoT devices. We started with a literature review on known vulnerability studies of the IoT devices, considering four categories of attacks: 1) physical; 2) network; 3) software; and 4) encryption. We then conducted our own vulnerability experiments that compared security postures between well known and lesser known vendors through misuse and abuse case analysis, followed by a review of coverage in major vulnerability databases. Based on our analysis, the main finding was the need for a stronger focus on the security posture of lesser known vendor devices as they are often less regulated and faceless scrutiny.
B) Dados derivados do objetivo:	
	1) Physical: "Some physical attacks are as follows: node tampering, radio-frequency (RF) interference on RF identifiers (RFIDs), node jamming in wireless sensor networks, malicious node injection, physical damage, social engineering, sleep deprivation, and malicious code injection."
Vulnerabilidades	2) Network:  "The network attacks identified in [9] are traffic analysis, RFID spoofing/cloning/unauthorized access, sinkhole, man in the middle, Denial of Service (DoS), routing information, and sybil."  3) Software:  "Some of the software attacks that have been presented in [9] are phishing, malicious scripts, Trojan horse, spyware, adware, and

DoS that exploit buffer overflows, SQL injections, and other types of vulnerabilities."
4) Encryption:
"Because IoT devices have limited computing power to support strong cryptographic protocols, they are vulnerable to the side channel, cryptanalysis, and man-in-the-middle attacks."
"The main vulnerability that exists is the "motherboard hack" vulnerability. The motherboard hack is an attack where the bulb is cracked open gaining access to the motherboard within the smart light bulb. Some manufactures store unencrypted information, e.g., WiFi SSID and encryption key in plaintext, in this location."

A) Dados da publicação:	
Título:	Securing Cyberspace of Future Smart Cities with 5G Technologies
Autor(es):	Akhunzada, A. and Islam, S.U. and Zeadally, S.
Fonte de Publicação:	IEEE Network
Ano da Publicação:	2020
Resumo:	Future smart cities promise to dramatically improve the quality of life and have been attracting the attention of many researchers in recent years. The integration of IoT with their corresponding service delivery models to manage a city's asset securely remains a significant challenge. The deployment of diverse IoT technologies and several architectural components and novel entities of emerging ICT solutions opens up new security threats and vulnerabilities. Large-scale, seamless communication among multiple IoT technologies is highly dependent on the operations of the underlying wireless access technologies such as WSNs, SDR, CR and RFID. We present thematic layered taxonomies to highlight the potential security vulnerabilities, attacks, and challenges of key IoT enabling technologies which underpin the development of smart cities. We also identify potential requirements and key enablers that play a vital role in the development of secure smart cities. Finally, we discuss various open issues that need to be addressed to unlock the full potential of 5G for future smart cities.
B) Dados derivados do objetivo:	
	"To start with, the wide deployment of SDR requires an adequate level of physical safety and security. SDR (Software Defined Radio) has reconfiguration capabilities which enable it to download various new radio applications and diverse communication links. Consequently, SDR is vulnerable to malicious modifications and injections due to its open communication without any integrity checks on the transmitted data."
Vulnerabilidades	"Device cloning is a frequently used term in traditional wireless communications. It represents unauthorized access to diverse services offered by another SDR device. Device cloning is a major security threat to the emerging 5G communication networks."
	"Moreover, SDR devices and components are easily programmable and accessible in an open environment and are vulnerable to sophisticated MATE attacks."

"The physical layer is vulnerable to sophisticated attacks such as unauthorized access, which subsequently leads to alteration of cognitive messages, and jamming attacks that severely affect spectrum sensing and sharing abilities. Moreover, the physical layer is also vulnerable to disruption of the cognitive engine as well as masquerading both as a primary user and a cognitive node."

"Moreover, the physical layer is also vulnerable to manipulation of various control messages and system commands. The physical layer is also vulnerable to channel interference."

"The strategic layer of RFID is vulnerable to location privacy attacks and social engineering attacks."

"The network layer can also experience spoofing attacks, selective forwarding attacks, and is vulnerable to a variety of DoS attacks."

"For instance, to ensure the availability of the SDR, the underlying operating system must be designed with features that do not allow backdoor accounts and patches with vulnerable open ports and services."

A) Dados da publicação:	
Título:	A Comprehensive Survey on Attacks, Security Issues and
	Blockchain Solutions for IoT and IIoT
Autor(es):	Sengupta, J. and Ruj, S. and Das Bit, S.
Fonte de Publicação:	Journal of Network and Computer Applications
Ano da Publicação:	2020
Resumo:	In recent years, the growing popularity of Internet of Things (IoT) is providing a promising opportunity not only for the development of various home automation systems but also for different industrial applications. By leveraging these benefits, automation is brought about in the industries giving rise to the Industrial Internet of Things (IIoT). IoT is prone to several cyberattacks and needs challenging approaches to achieve the desired security. Moreover, with the emergence of IIoT, the security vulnerabilities posed by it are even more devastating. Therefore, in order to provide a guideline to researchers, this survey primarily attempts to classify the attacks based on the objects of vulnerability. Subsequently, each of the individual attacks is mapped to one or more layers of the generalized IoT/IIoT architecture followed by a discussion on the countermeasures proposed in literature. Some relevant real-life attacks for each of these categories are also discussed. We further discuss the countermeasures proposed for the most relevant security threats in IIoT. A case study on two of the most important industrial IoT applications is also highlighted. Next, we explore the challenges brought by the centralized IoT/IIoT architecture and how blockchain can effectively be used towards addressing such challenges. In this context, we also discuss in detail one IoT specific Blockchain design known as Tangle, its merits and demerits. We further highlight the most relevant Blockchain-based solutions provided in recent times to counter the challenges posed by the traditional cloud-centered applications. The blockchain-related solutions provided in the context of two of the most relevant applications for each of IoT

and IIoT is also discussed. Subsequently, we design a taxonomy of the security research areas in IoT/IIoT along with their corresponding solutions. Finally, several open research directions relevant to the focus of this survey are identified.

#### B) Dados derivados do objetivo:

"Refers to the act of physically modifying a device (e.g. RFID) or communication link."

"Here the attacker injects malicious code onto a physical device by compromising it which may help him/her launch other attacks too."

"RF Interference/Jamming: Attacker creates and sends noise signals over the Radio Frequency (RF)/WSN signals to launch DoS attacks on the RFID tags/sensor nodes thereby hindering communication."

"Fake Node Injection: Attacker drops a fake node between two legitimate nodes of the network to control data flow between them."

"Sleep Denial Attack: Attacker keeps the battery powered devices awake by feeding them with wrong inputs. This causes exhaustion in their batteries leading to shutdown."

"Side Channel Attack: In this attack, the attacker collects the encryption keys by applying timing, power, fault attack etc."

"Permanent Denial of Service (PDoS): Also known as phlashing, is a type of DoS attack, wherein an IoT device is completely damaged via hardware sabotage. The attack is launched by destroying firmware or uploading a corrupted BIOS using a malware."

"For example, using device spoofing attack, attackers can obtain a camera's password of any length and combination. Also by enumerating all possible MAC addresses the attacker can launch device scanning attack to find all online cameras."

"Their experiments reveal that the home automation system is vulnerable to brute force attacks revealing the passwords. It also reveals that the smart meters can be hijacked to launch ransomware attacks against other systems."

"security vulnerabilities of Virtual Personal Assistant (VPA) based IoT devices such as Amazon Echo and Google Home. These systems are vulnerable to attacks like voice squatting and voice masquerading."

"RFID Spoofing: The attacker first spoofs an RFID signal to get access of the information imprinted on the RFID tag."

"RFID Unauthorized Access: An attacker is able to read, modify or delete data present on RFID nodes because of the lack of proper authentication mechanisms.

"In a wormhole attack, an attacker maliciously prepares a low-latency link and then tunnels packets from one point to another through this link."

#### Vulnerabilidades

"Here, a single malicious node claims multiple identities (known as sybil nodes) and locates itself at different places in the network." "An attacker may capture a signed packet and resend the packet multiple number of times to the destination. This keeps the network busy leading to a DoS attack. "in DDoS multiple compromised nodes attack a specific target by flooding messages, or connection requests to slow down or even crash the system server/network resource." "Data Inconsistency: In IoT, attack on data integrity leading to inconsistency of data in transit or data stored in a central database is referred to as Data Inconsistency." "Access control implies giving access to authorized users and denying access to unauthorized users. With unauthorized access, malicious users can gain data ownership or access sensitive data." "Data breach or memory leakage refers to the disclosure of personal, sensitive or confidential data in an unauthorized manner."

A) Dados da publicação:	
Título:	DDoS in IoT: A roadmap towards security countermeasures
Autor(es):	Roohi, A. and Adeel, M. and Shah, M.A.
Fonte de Publicação:	25th IEEE International Conference on Automation and
	Computing
Ano da Publicação:	2019
Resumo:	In this era of digitization, more and more technologies are spurring up but are failing to make a successful impact due to the security and privacy issues. Internet of Things (IoT) has made its mark recently and being end-consumer oriented, makes it more prone towards being exploited. There are many types of security attacks in the IoT which can compromise the end user data and services. The most common and devastating security attack in the IoT is a Denial of Service (DoS)/Distributed Denial of Service (DDoS) attack. In this paper, the contributions are: we provide a structured comprehensive overview of the existing research on DDoS Attacks, its security countermeasures in the context of IoT. We survey latest vulnerabilities and their security solutions over the period 2014-2019. With elaborate discussion on IoT architecture and underlying security threats impacting each layer in the IoT, we have grouped existing approaches and derived taxonomy. With this concise overview, the paper seeks to provide an understanding of the pertaining models adopted by different researchers.
B) Dados derivados do objetivo:	
Vulnerabilidades	"Devices being used at Perception Layer experience resource constraints with respect to their application at the user end. Moreover, technologies such as RFID, NFC, Bluetooth, ZigBee e.t.c lack data transmission range which can be exploited by the intruder."
	"Middleware layer is responsible for analyzing the data which has been collected via the sensor nodes. Computational and

processing resources are required extensively on this layer. Securing data in this layer which is usually referred as cloud and authentication are concerns which are to be addressed"
"Attacker usually targets unauthorized access towards the Application being used which is usually available via the Internet. This User Interface extends attackers access to sensitive data of the user which through different penetration techniques, vulnerabilities, bugs in the programs, low quality level code, inducing buffer overflow e.t.c."

A) Dados da publicação:	
	A Multipritoria Decision Making Toyonomy of IOT Cocumity
Título:	A Multicriteria Decision Making Taxonomy of IOT Security Challenging Factors
Autor(es):	Akbar, M.A. and Alsanad, A. and Mahmood, S. and Alothaim, A.
Fonte de Publicação:	IEEE Access
Ano da Publicação:	2021
Resumo:  B) Dados derivados do objetivo:	Internet of things (IoT) is leading a new digital age. IoT is regarded as the significant frontier that can improve almost all aspect of our lives. Currently, the IoT technology faces several challenges to academic researchers and industry practitioners, mainly that related with security of data. The objective of this study is to develop a prioritization-based taxonomy of the challenging factors that could hinders the security of IoT. By conducting the literature review and questionnaire survey studies 21 challenging factors were identified that are reported in existing literature and in real-world practices. Moreover, the identified challenging factors are mapped in the core domain of IoT (i.e. smart city, smart home, smart wearable's and smart health care); and apply the fuzzy-AHP approach to rank the identified challenging factors with respect to their criticality for security of IoT technology. The application of fuzzy-AHP is novel in this research area as it is successfully applied in other domains of information technology to address the multi-criterion decision making problems. This study is contributing by providing a prioritization-based taxonomy of the IoT security challenging factors that could help the practitioners and research community to revise and develop the new strategies for the secure IoT.
B) Baace derivades de esjenve.	"Smart cities comprised of several heterogenous IoT devices in
	order to achieve various objectives. However, malicious IoT node could be connected to IoT system in order to collect and exchange data from other devices."
Vulnerabilidades	"Increasing number of IoT devices connected to smart city will generate huge amount of data. However, these devices do not have potential to store and process data, therefore data generated by these devices need to be sent to cloud in order to process and analyze."  "Thus, IoT devices do not have enough capability to encrypt and
	decrypt data that pose the integrity and authenticity of data as critical challenge."

"Generally, cryptographic algorithms are used to ensure data privacy from unauthorized access. Due to low power and computation of IoT devices there is a risk of malicious attacks and leakage of personal information, as advanced cryptographic techniques could not be employe"

"The smart world anticipated that several smart home appliances will be interconnected to home network. However, these devices need to be configured to home network repetitively and may prone to different security attacks. This could be tedious task for householder in order to manage these devices manually so external expert need to be called to control several security threats."

"However, IoT devices consisting of software and hardware are less in numbers and due to heterogeneous nature, firmware is not updated frequently that causes a variety of security threats."

"Thus, firmware of IoT devices for smart homes need to be updated automatically in order to cope with novel security vulnerability, as there is lack of technical support."

"Smart home network could be compromised by attacker and permit them to send RTS (Request to send)/CTS (clear to send) messages in bulk. Thus, smart devices should be capable enough to stop these devices from receiving messages in bulk and deplete their resources."

"Interdependence Behavior of Devices - Various smart home devices connected each other in a network in order to achieve a particular objective."

"However, location could be altered by attackers if he/she could receive radio signal and analyze them, if the location information altered by attacker this could impede emergency services."

"Smart devices come without any built-in security mechanism and these devices store data locally without any encryption method."

"Furthermore, strong cryptographic algorithm could not be implemented because these devices are resource constrained."

A) Dados da publicação:	
Título:	A Survey on Secure Transmission in Internet of Things:
	Taxonomy, Recent Techniques, Research Requirements, and Challenges
Autor(es):	Mahapatra, S.N. and Singh, B.K. and Kumar, V.
Fonte de Publicação:	Arabian Journal for Science and Engineering
Ano da Publicação:	2020
Resumo:	Internet of things (IoT) is one of the emerging paradigms in the
	current era that has attracted many researchers due to its

widespread applications. Due to the open nature of the device accessibility and heterogeneity, a rapid increase in connected devices leads to several vulnerabilities and threats in the IoT devices. Hence, security is one of the important concern and main challenge to be addressed for the guaranteed data transmission in IoT environment. In this review work, we analyze the secure transmission of data in IoT and investigate the recent approaches in IoT security and their requirements and open issues. We present a taxonomy model for the secure transmission in IoT security which includes architecture/layers. communication topology, and classification techniques which are categorized under cluster, trust, routing, blockchain, and location-based approaches. First, we briefly discuss the architecture of the IoT ecosystem that consists of three layers namely perception, network, and application layer which support the basic task such as transmission, sensing, and processing. Next, we classify the communication mechanism into different scenarios involved in the various network for the transmission of data in the IoT environment. Then, we investigate the recent approaches for secure communication to overcome certain attacks in IoT and analyze their strength and limitations. Finally, we discuss the security requirements, threats, and vulnerabilities faced by the current IoT system, and numerous open research challenges that are needed to be addressed for the efficient transmission of data as future research directions.

#### B) Dados derivados do objetivo:

"Currently, security factors such as privacy, secure storage and management, authorization, and communication as well as access control are the critical and challenging issues in the IoT environment."

"Due to the limited processing capability, traditional security methods suffer from various setbacks and often do not detect the physical threats in the network."

"So, proper authentication and encryption are required for preventing such attacks from the spiteful users."

"In this technology, there are some of the possible vulnerabilities, unauthorized tag cloning, attacks on availability and authenticity, spoofing, counterfeiting, DoS attack, eavesdropping, and replay attacks."

#### Vulnerabilidades

"However, there are several security threats and vulnerabilities faced by cloud users, such as identity management, and heterogeneity issues in IoT devices that makes the data transmission unreachable to an user identity authentic node, physical and infrastructure security, encryption, data access controls, system complexity, and misconfiguration of software."

"There are several reasons in observing the cyber-attacks are: Many IoT devices can be operated by unattended humans, thus it is easy for an attacker to access and an adversary can steal sensitive data over wireless networks by eavesdropping."

"Some of the security issues with IoT devices such as insecure mobile interface, insufficient authentication, and insecure network service, and poor physical security, lack of transport encryption,

	privacy concerns, and insecure web interface insufficient security configurability."
	"The IoT connected resources have more demand for updating and the frequency of the messages causes latency which results in network vulnerabilities."
	"Due to the hardware limitations on storage, processing, and energy, high overhead and data traffic is a critical criterion in the field of secure data transmission."
	"Due to the hardware limitations on storage, processing, an energy, high overhead and data traffic is a critical criterion in the

A) Dados da publicação:	
Título:	Towards an Extensible IoT Security Taxonomy
Autor(es):	Wüstrich, L. and Pahl, MO. and Liebald, S.
Fonte de Publicação:	IEEE Symposium on Computers and Communications , Vol. 2020-July
Ano da Publicação:	2020
Resumo:	Security is essential in the Internet of Things (IoT). IoT threat classifications are often non-intuitive to use. Identifying relevant properties of an attack is difficult and requires reading details of the attack. We therefore propose a simple-to-use naming scheme for IoT threat classification. It is based on the affected layers and the affected security goals. We evaluate the usefulness of the chosen approach by applying it to common IoT threats.
B) Dados derivados do objetivo:	
Vulnerabilidades	"Access to devices and the capability to record and replay a signal are sufficient for this attack. As the attacker then impersonates a legitimate sender"  "In order to save energy, some devices have a sleep mode. The attacker interacts with the device to prevent it from entering the low powered mode to drain its battery."  "This renders the device unavailable (CP.AVAIL). For a success, adversary needs network access to interact with the node. It also needs knowledge about the commands it can send to the node to keep it from the sleep mode."  "IoT devices embedded into the environment they can also be physically damaged"
	"Another class of attacks that predominantly affects devices on CP due to their limited computing power and level of exposure are side channel attacks"  "By analyzing physical characteristics like power consumption of the device during computations the secret is inferred"  "In a Sybil attack, the adversary assumes multiple identities of other nodes in the network"

"In case an attacker is able modify the running application by
using malware, a Trojan horse or is able to install a malicious
update, the integrity on the application layer is violated"

A) Dados da publicação:	
Título:	A survey of IoT security based on a layered architecture of
	sensing and data analysis
Autor(es):	Mrabet, H. and Belguith, S. and Alhomoud, A. and Jemai, A.
Fonte de Publicação:	Sensors (Switzerland)
Ano da Publicação:	2020
Resumo:  B) Dados derivados do objetivo:	The Internet of Things (IoT) is leading today's digital transformation. Relying on a combination of technologies, protocols, and devices such as wireless sensors and newly developed wearable and implanted sensors, IoT is changing every aspect of daily life, especially recent applications in digital healthcare. IoT incorporates various kinds of hardware, communication protocols, and services. This IoT diversity can be viewed as a double-edged sword that provides comfort to users but can lead also to a large number of security threats and attacks. In this survey paper, a new compacted and optimized architecture for IoT is proposed based on five layers. Likewise, we propose a new classification of security threats and attacks based on new IoT architecture. The IoT architecture involves a physical perception layer, a network and protocol layer, a transport layer, an application layer, and a data and cloud services layer. First, the physical sensing layer incorporates the basic hardware used by IoT. Second, we highlight the various network and protocol technologies employed by IoT, and review the security threats and solutions. Transport protocols are exhibited and the security threats against them are discussed while providing common solutions. Then, the application layer involves application protocols and lightweight encryption algorithms for IoT. Finally, in the data and cloud services layer, the main important security features of IoT cloud platforms are addressed, involving confidentiality, integrity, authorization, authentication, and encryption protocols. The paper is concluded by presenting the open research issues and future directions towards securing IoT, including the lack of standardized lightweight encryption algorithms, the use of machine-learning algorithms to enhance security and the related challenges, the use of Blockchain to address security challenges in IoT, and the implications of IoT deployment in 5G and beyond.
Vulnerabilidades	"According to the 2017 OWASP application security flaws review, the ten most critical web application security risks are: injection, broken authentication, sensitive data exposure, XML external entities (XXE), broken access control, security misconfiguration, cross-site scripting (XSS), insecure deserialization, and using components with known vulnerabilities."

A) Dados da publicação:	
Título:	Data Security and Privacy Protection for Cloud Storage: A Survey

Autor(es):	Yang, P. and Xiong, N. and Ren, J.
Fonte de Publicação:	IEEE Access
Ano da Publicação:	2020
Resumo:	The new development trends including Internet of Things (IoT), smart city, enterprises digital transformation and world's digital economy are at the top of the tide. The continuous growth of data storage pressure drives the rapid development of the entire storage market on account of massive data generated. By providing data storage and management, cloud storage system becomes an indispensable part of the new era. Currently, the governments, enterprises and individual users are actively migrating their data to the cloud. Such a huge amount of data can create magnanimous wealth. However, this increases the possible risk, for instance, unauthorized access, data leakage, sensitive information disclosure and privacy disclosure. Although there are some studies on data security and privacy protection, there is still a lack of systematic surveys on the subject in cloud storage system. In this paper, we make a comprehensive review of the literatures on data security and privacy issues, data encryption technology, and applicable countermeasures in cloud storage system. Specifically, we first make an overview of cloud storage, including definition, classification, architecture and applications. Secondly, we give a detailed analysis on challenges and requirements of data security and privacy protection in cloud storage system. Thirdly, data encryption technologies and protection methods are summarized. Finally, we discuss several open research topics of data security for cloud storage.
B) Dados derivados do objetivo:	
Vulnerabilidades	"When data is outsourced to the cloud, its security is vulnerable. Encryption is an effective technique to protect data security. The essence of data encryption is to transform the original plaintext file or data into an string of unreadable code by some algorithms, which is usually called ciphertext."
	"Besides, identity and attribute leakage issues are also threatening the privacy of data owners and authorized users."

A) Dados da publicação:	
Título:	Toward an applied cyber security solution in iot-based smart
	grids: An intrusion detection system approach
Autor(es):	Yin, X.C. and Liu, Z.G. and Nkenyereye, L. and Ndibanje, B.
Fonte de Publicação:	Sensors (Switzerland)
Ano da Publicação:	2019
Resumo:	We present an innovative approach for a Cybersecurity Solution based on the Intrusion Detection System to detect malicious activity targeting the Distributed Network Protocol (DNP3) layers in the Supervisory Control and Data Acquisition (SCADA) systems. As Information and Communication Technology is connected to the grid, it is subjected to both physical and cyber-attacks because of the interaction between industrial control systems and the outside Internet environment using IoT technology. Often, cyber-attacks lead to multiple risks that affect infrastructure and business continuity; furthermore, in some cases, human beings are also affected. Because of the traditional peculiarities of process systems, such as insecure real-time protocols, end-to-end general-purpose ICT security mechanisms are not able to fully secure communication in SCADA systems. In

	this paper, we present a novel method based on the DNP3 vulnerability assessment and attack model in different layers, with feature selection using Machine Learning from parsed DNP3 protocol with additional data including malware samples. Moreover, we developed a cyber-attack algorithm that included a classification and visualization process. Finally, the results of the experimental implementation show that our proposed Cybersecurity Solution based on IDS was able to detect attacks in real time in an IoT-based Smart Grid communication environment.
B) Dados derivados do objetivo:	
Vulnerabilidades	"Attacks often happen by using steps such as reconnaissance, which consists of gathering information about the targeted system; scanning, which is about finding any weakness or vulnerability in the system by looking for any open ports; and running a service through the port."

A) Dados da publicação:	
Título:	Authentication in cloud-driven IoT-based big data environment: Survey and outlook
Autor(es):	Wazid, M. and Das, A.K. and Hussain, R. and Succi, G. and Rodrigues, J.J.P.C.
Fonte de Publicação:	Journal of Systems Architecture
Ano da Publicação:	2019
Resumo:	The Internet of Things (IoT) is composed of different networked objects (i.e., smart devices) which are interconnected to gather, process, refine, and exchange meaningful data over the Internet. These objects are assigned to their respective IP addresses, and they are able to send and receive data over a network without any human assistance. IoT offers different types of applications, such as, but not limited to, smart traffic monitoring, smart home, smart health care and smart cities, to name a few. In a Cyber-Physical System (CPS), computing elements coordinate and communicate with sensor devices, which monitor cyber and physical indicators, and actuators, and also modify the cyber and physical environment where they run. The synergy of computational as well as physical components, specifically the use of CPSs, led to the advancement of IoT implementations. In a cloud-driven IoT-based big data environment, a cloud-based platform is used to store the data generated by IoT devices (normally by sensor devices) which further can be considered as a big data warehouse. This environment is highly scalable and provides important real-time event processing (for example, in critical scenarios like surveillance and monitoring of an industrial plant). In IoT-based critical applications, the real-time data access is obligatory as and when it is required. Such access the real-time data directly from the IoT sensors. Sometimes authorized user may also request for big data query processing and big data analytics over the data stored in cloud servers to figure out hidden patterns of some phenomena (i.e., chances of fire in an industrial plant in future). Therefore, we need secure authentication schemes for cloud-driven IoT-based big data environment in which a legitimate user and an IoT sensor can mutually authenticate each other and establish a common session key for secure communication. In this context, this paper first discusses the network and threat models of the authentication schemes for cloud-driven IoT-based big dat

	existing authentication schemes applicable for cloud-driven IoT-based big data environment is also discussed, which covers a comparative study of these schemes. We identify and briefly discuss some future research challenges in designing the authentication schemes and other security protocols for cloud-driven IoT-based big data environment that need to be addressed in the future.
B) Dados derivados do objetivo	:
Vulnerabilidades	"we need secure authentication schemes for cloud-driven IoT-based big data environment in which a legitimate user and an IoT sensor can mutually authenticate each other, and then can establish a common session key for their secure communication"  "Furthermore, "A" can physical capture some IoT sensors or smart sensing devices to obtain the stored credentials in those devices with the help of sophisticated power analysis attacks."  "The smart devices, such as IoT sensors, in the cloud-driven IoT-based big data environment may be failed due to energy issue or can be physically stolen by the adversary."
vuiriciabilidades	"Some identified issues and challenges include limited computation power and memory storage, energy requirement, scalability, mobility, support for heterogeneous devices, dynamic security updates, protection against physical capturing, and security and privacy of IoT sensors data at the big data warehouse."  "This phase is required when some sensing nodes are physically captured by an adversary or some sensing nodes are exhausted because of a power failure"

A) Dados da publicação:	
Título:	Vpnfilter malware analysis on cyber threat in smart home network
Autor(es):	Sicato, J.C.S. and Sharma, P.K. and Loia, V. and Park, J.H.
Fonte de Publicação:	Applied Sciences (Switzerland)
Ano da Publicação:	2019
Resumo:	Recently, the development of smart home technologies has played a crucial role in enhancing several real-life smart applications. They help improve the quality of life through systems designed to enhance convenience, comfort, entertainment, health of the householders, and security. Note, however, that malware attacks on smart home devices are increasing in frequency and volume. As people seek to improve and optimize comfort in their home and minimize their daily home responsibilities at the same time, this makes them attractive targets for a malware attack. Thus, attacks on smart home-based devices have emerged. The goals of this paper are to analyze the different aspects of cyber-physical threats on the smart home from a security perspective, discuss the types of attacks including advanced cyber-attacks and cyber-physical system attacks, and evaluate the impact on a smart home system in daily life. We have come up with a taxonomy focusing on cyber threat attacks that can also have potential impact on a smart home system and identify some key issues about VPNFilter malware that constitutes large-scale Internet of Things (IoT)-based botnet malware infection. We also discuss the defense mechanism against this threat and mention the most infected routers. The specific objective of this paper is to

	provide efficient task management and knowledge related to VPNFilter malware attack.
B) Dados derivados do objetivo:	The state of the s
D) Dados delivados do objetivo.	"This type of attack depends on the injection of data in web applications wherein it facilitates the interpretation and execution of malicious data in an unexpected way by exploiting program errors"
	"A buffer whose memory is allocated by a program is an example of temporary storage to deal with a surplus of data"
	"Authentication attack plays an important role in the protection of IoT security and privacy. The process of confirming the identity or truth of an object is known as authentication. This kind of attack is a way of exploiting and discovering security holes in web applications."
	"Denial of service attack: in this type of attack, a hacker denies a service to authorize the user or even creates delays through resources, generating a large amount of data."
Vulnerabilidades	"Sybil attack: in this kind of attack, a single attacker can actually take over the networking, and multiple identities in the network are presented to the victim's node, which allows the victim's node to perform multiple operations, thus defeating the purpose of redundancy."
	"Sleep deprivation attack: The perception layer is limited by the battery power in the node. To prolong the life of the battery, it is necessary for the device to sleep when not in operation. This type of attack attempts to subvert this process by constantly controlling and sending information to the network devices."
	"Radio frequency jamming attack: This attack targets one of the key technologies of this layer, which consists of sensor nodes, cameras, actuators, tags / RFID readers, cell phones, tablets, GPS, and others to communicate in the smart home."
	"Tampering attack: This type of attack is launched when the attacker is much closer to the network device and is forced to break hardware without any permission."
	"Router platforms belonging to Linksys, TP-Link, Qnap, Netgear, and MikroTik implement home networks on internet gateways, making them more susceptible to the VPNFilter malware attack."
	"Several technical vulnerabilities are found to have been caused by human weaknesses."

A) Dados da publicação:	
Título:	Security Issues in IIoT: A Comprehensive Survey of Attacks on
	IIoT and Its Countermeasures
Autor(es):	Panchal, A.C. and Khadse, V.M. and Mahalle, P.N.
Fonte de Publicação:	IEEE Global Conference on Wireless Computing and Networking, GCWCN
Ano da Publicação:	2019

Resumo:	Industrial Internet of Things (IIoT) applications connect machines, sensors and actuators in high-stake manufacturing industries. Industrial systems are using the potential of IoT to reduce the unnecessary operational cost and increase the usability and reliability of the industrial assets to achieve more profits. However, such smart Industries need connectivity and interoperability to enhance performance which makes them susceptible to various attacks. Recent attacks on Cyber-physical systems raise a strong security concern as such attacks causes a huge property loss and may also lead to life threatening situations. In this paper we discuss the potential security threats to the Industries adapting to IIoT and study the various attacks that are possible on the components in the layered IIoT architecture and some of the preventive measures. Finally, we propose IIoT attack taxonomy which would help in mitigating the risks of the attacks.
B) Dados derivados do objetivo	
Vulnerabilidades	"DoS is an attack performed on a network to restrict a server from serving its client, DoS attacks target network bandwidth or services."  "Firewalls can be used to allow or deny access to the requests, DoS attack detection using IDS and better authentication and authorization system can help to avoid such attacks."  "To perform a side channel attacks on cloud a malicious virtual machine is placed in cloud to target the system implementation of cryptographic algorithms."  "Today most of the services in cloud still use simple username and password type of single factor knowledge-based authentication."  "Phishing attacks happen when the attackers trick user to interact with the original looking fake webpages or emails, and gain access to one's confidential data. Educating people about such attack is the best way to defense against phishing."  "SQL Injection: SQLi refers to an injection attack wherein attacker injects malicious input to get confidential data stored in database, delete database and bypass authentication."  "Remote Code Execution occurs when an attacker exploits vulnerability in the system to introduce a malware that can control the target system remotely."  "IP Spoofing: An attacker purposefully impersonates as another device by modifying the packet header with a forged IP address."  "The best way to defend against sniffing attacks is to encrypt all the data passing over the communication channel."

A) Dados da publicação:	
Título:	A taxonomy of cyber-physical threats and impact in the smart
	home
Autor(es):	Heartfield, R. and Loukas, G. and Budimir, S. and Bezemskij, A. and Fontaine, J.R.J. and Filippoupolitis, A. and Roesch, E.
Fonte de Publicação:	Computers and Security

Ano da Publicação:	2018
Resumo:	In the past, home automation was a small market for technology enthusiasts. Interconnectivity between devices was down to the owner's technical skills and creativity, while security was non-existent or primitive, because cyber threats were also largely non-existent or primitive. This is not the case any more. The adoption of Internet of Things technologies, cloud computing, artificial intelligence and an increasingly wide range of sensing and actuation capabilities has led to smart homes that are more practical, but also genuinely attractive targets for cyber attacks. Here, we classify applicable cyber threats according to a novel taxonomy, focusing not only on the attack vectors that can be used, but also the potential impact on the systems and ultimately on the occupants and their domestic life. Utilising the taxonomy, we classify twenty five different smart home attacks, providing further examples of legitimate, yet vulnerable smart home configurations which can lead to second-order attack vectors. We then review existing smart home defence mechanisms and discuss open research problems.
B) Dados derivados do objetivo:	
Vulnerabilidades	"a breach of confidentiality, integrity and availability resulting from a vulnerability in a single device may result in shared exploitation across interdependent systems"  "As the vast majority of smart home platforms rely on the home Internet gateway to reach respective cloud services in order to function, if an attacker can compromise a smart home Internet gateway they may be able to disrupt or gain control of almost every Internet-connected device in the household."  "this does not protect against attacks that have penetrated the network and may originate from the Internet or from inside the network, such as malware infections and social engineering."  "as HAPCAN utilises the CAN protocol, the protocol itself is at risk to several additional CAN vulnerabilities, such as request overload and false request to send"  "UPB has no encryption and therefore any attack that is able to sniff data from the powerline (such as using a rogue UPB node) is able to read and inject data in the network."  "the signals containing sensor data or actuation commands can be captured by an adversary in the vicinity, which makes strong encryption and countermeasures against replay attacks particularly important. At the same time, wireless control can be rather trivially disrupted via communication jamming."  "WiFi de-authentication is by no means new, but in the context of the smart home, the loss of WiFi means loss of Internet connectivity in the household, on which IoT platforms are increasingly dependent in order to function."  "then identifying the product vendor allows attackers to analyse the smart home and target known vulnerabilities in its devices."
	"Within the context of the smart home, it is the occupants who make the ultimate decision to install a new wireless security lock, presence sensor or voice-controlled assistant, as privacy and

security concerns are carried out according to occupants' risk attitude, personal and social circumstances"

"The threat landscape relates to the communication medium and control software used, as well as threats in the supply chain, side channel attacks and the sensory channel."

"NFC is vulnerable to remote eavesdropping attacks assuming that an attacker has a powerful enough receiver to capture a NFC signal"

"As workflow automation platforms can gain significant access in defining, controlling and triggering system behaviour and interaction in the smart home, this makes them a prime target for semantic social engineering attacks."

"Here, an example would be the electromagnetic emanations leaking from unfiltered powerlines."

"Increasingly, smart home devices come equipped with Internet access which are left poorly secured and as a result expose vulnerabilities over physical privacy."

"Unauthorised access to this information would likely lead to unauthorised physical actuation as a second-order physical effect (P-UA)."

"Within the smart home, non-repudiation is associated to an occupant's ability to provide evidence that distinguishes legitimate computer activity generated by themselves or fellow occupants and activity which has been executed by a malicious actor."

"In the smart home, this information may now be picked up more easily by exploiting poorly protected IoT devices with built-in microphone systems, such as personal assistant services "

A) Dados da publicação:	
Título:	A taxonomy of cyber-physical threats and impact in the smart home
Autor(es):	Heartfield, R. and Loukas, G. and Budimir, S. and Bezemskij, A. and Fontaine, J.R.J. and Filippoupolitis, A. and Roesch, E.
Fonte de Publicação:	Computers and Security
Ano da Publicação:	2018
Resumo:	In the past, home automation was a small market for technology enthusiasts. Interconnectivity between devices was down to the owner's technical skills and creativity, while security was non-existent or primitive, because cyber threats were also largely non-existent or primitive. This is not the case any more. The adoption of Internet of Things technologies, cloud computing, artificial intelligence and an increasingly wide range of sensing and actuation capabilities has led to smart homes that are more practical, but also genuinely attractive targets for cyber attacks. Here, we classify applicable cyber threats according to a novel taxonomy, focusing not only on the attack vectors that can be used, but also the potential impact on the systems and ultimately on the occupants and their domestic life. Utilising the taxonomy, we classify twenty five different smart home attacks, providing

further examples of legitimate, yet vulnerable smart home configurations which can lead to second-order attack vectors. We then review existing smart home defence mechanisms and discuss open research problems.

## B) Dados derivados do objetivo:

A consequence of technology convergence in the smart home is the cascading effect of compromise of one system to others. For example, a breach of confidentiality, integrity and availability resulting from a vulnerability in a single device may result in shared exploitation across interdependent systems. A secure system may be rendered vulnerable by the insecurities of a lesser protected platform on which it relies.[...]

As the vast majority of smart home platforms rely on the home Internet gateway to reach respective cloud services in order to function, if an attacker can compromise a smart home Internet gateway they may be able to disrupt or gain control of almost every Internet-connected device in the household.[...] As of May 2018, an initial report by Cisco Talos dramatically reinforced the growing vulnerability of home internet gateways by identifying a large scale advanced persistent threat against SOHO routers titled VPNFilter.[...]

- [...], this does not protect against attacks that have penetrated the network and may originate from the Internet or from inside the network, such as malware infections and social engineering.
- [...], UPB has no encryption and therefore any attack that is able to sniff data from the powerline (such as using a rogue UPB node) is able to read and inject data in the network.
- [...], the signals containing sensor data or actuation commands can be captured by an adversary in the vicinity, which makes strong encryption and countermeasures against replay attacks particularly important. At the same time, wireless control can be rather trivially disrupted via communication jamming.
- [...]WiFi de-authentication is by no means new, but in the context of the smart home, the loss of WiFi means loss of Internet connectivity in the household, on which IoT platforms are increasingly dependent in order to function. Whilst the vulnerability in question was addressed in 2009 by introduction of the 802.11w RFC, which strengthened the authenticity and integrity of WiFi management packets, consumer-based router manufacturers do not often implement this extension into their WiFi protocol stack. So, even though 802.11w is available in most recent Linux kernels and Windows OS (since Windows 8), often this feature must be disabled in order for it to be compatible with household WiFi routers.
- [...] then identifying the product vendor allows attackers to analyse the smart home and target known vulnerabilities in its devices.

Within the context of the smart home, it is the occupants who make the ultimate decision to install a new wireless security lock, presence sensor or voice-controlled assistant, as privacy and security concerns are carried out according to occupants' risk

## Vulnerabilidades

attitude (Rahmati et al., 2018), personal and social circumstances[...]

For the immediate future, the smart home technology landscape is likely to be volatile, consisting of both legacy and emerging IoT platforms, each with their own security risks. The threat landscape relates to the communication medium and control software used, as well as threats in the supply chain, side channel attacks and the sensory channel.

However, due to a lack of definable NFC wireless communication standards and a proliferation of NFC-enabled systems, a number of vulnerabilities have been found across a range of NFC implementations. For example, NFC is vulnerable to remote eavesdropping attacks assuming that an attacker has a powerful enough receiver to capture a NFC signal (Kennedy and Hunt, 2008) (by design, NFC requires extremely close proximity between the transponder and receiver, e.g., up to 10 cm).[...]

As workflow automation platforms can gain significant access in defining, controlling and triggering system behaviour and interaction in the smart home, this makes them a prime target for semantic social engineering attacks (Heartfield and Loukas, 2016). Whilst an attacker may not necessarily target a specific vulnerability in workflow automation platforms themselves, a successfully crafted phishing email that deceives a user into divulging their account's username and password potentially provides an attacker with the ability to edit, delete and create new workflow automation rules in the target household.[...]

Here, an example would be the electromagnetic emanations leaking from unfiltered powerlines. Enev et al. (2011) have demonstrated the viability of measuring a home's powerline activity with such accuracy that they could identify what the occupants were watching on television. Their method was reproducible and accurate enough across a wide range of modern television sets.

Increasingly, smart home devices come equipped with Internet access which are left poorly secured and as a result expose vulnerabilities over physical privacy. For example, Internet device scanning search engines (such as Shodan), allow attackers to identify open ports of nodes, indexing the header or banner information of responsive nodes; which can include information such device type, model, vendor, firmware version other open protocols.[...]

[...] Unauthorised access to this information would likely lead to unauthorised physical actuation as a second-order physical effect (P-UA).

Within the smart home, non-repudiation is associated to an occupant's ability to provide evidence that distinguishes legitimate computer activity generated by themselves or fellow occupants and activity which has been executed by a malicious actor. [...]

[...]In the past, threats to this communication medium were low as only very targeted attacks (such as physical bugging) posed a

risk. In the smart home, this information may now be picked more easily by exploiting poorly protected IoT devices with built-microphone systems, such as personal assistant services (e.	-in
Google Home, Amazon Echo), children toys and oth voice-controlled house-hold appliances.	_

A) Dados da publicação:		
Título:	Introduction to em information security for IoT devices	
Autor(es):	Hayashi, Y. and Verbauwhede, I. and Radasky, W.A.	
Fonte de Publicação:	IEEE International Symposium on Electromagnetic Compatibility	
Ano da Publicação:	2018	
Resumo:	With the advent of the Internet of Things (IoT), many electronic devices (e.g., smart meters, surveillance cameras, mobile devices, and multiple sensors) are interconnected. Each device gathers data and uploads it to servers via communication networks. Servers store the large volumes of received data in databases. Applications analyze this data and extract valuable information. Finally, based on this information, new services (in domains such as smart cities, public safety, e-commerce, medical, healthcare, or automobile) are provided. In this data flow, systems and applications in the upper layer trust the hardware in the lower layer, which includes data-gathering devices. If the collected information is intentionally modified by adversaries, services in the upper layer could be disrupted. Therefore, to ensure service continuity in the IoT, it is important to secure the hardware layer in which data are harvested and transmitted. In this paper, we focus on hardware-level security in IoT systems and classify the schemes proposed for physical security of IoT into three categories. We also provide examples for each of these and explain threats and countermeasures.	
B) Dados derivados do objetivo	B) Dados derivados do objetivo:	
Vulnerabilidades	The vulnerability due to electromagnetic waves can be largely classified into three categories: (1) electromagnetic emanation resulting from information processing within devices, (2) intentional electromagnetic interference to devices, and (3) intentional modification of system circuit configuration	

A) Dados da publicação:	
Título:	A taxonomy of security and privacy requirements for the Internet of Things (IoT)
Autor(es):	Alqassem, I. and Svetinovic, D.
Fonte de Publicação:	International Conference on Industrial Engineering and Engineering Management
Ano da Publicação:	2014
Resumo:	Capturing security and privacy requirements in the early stages of system development is essential for creating sufficient public confidence in order to facilitate the adaption of novel systems such as the Internet of Things (IoT). However, security and privacy requirements are often not handled properly due to their wide variety of facets and aspects which make them difficult to formulate. In this study, security-related requirements of IoT heterogeneous systems are decomposed into a taxonomy of quality attributes, and existing security mechanisms and policies are proposed to alleviate the identified forms of security attacks and to reduce the vulnerabilities in the future development of the

	loT systems. Finally, the taxonomy is applied on an loT smart grid scenario.
B) Dados derivados do objetivo:	
	Access control mechanisms limit access to various system's resources (e.g., data, services, hardware, etc.) by identifying who can access what resources, and constrain what a legitimate user can do by controlling who is doing what in the system.
	- 1) Identification
	The focus of the identification is to uniquely identify objects and manage their identities while considering security and high scalability aspects of the IoT. Reaching a consensus on how to identify objects involved in the IoT and managing their identities is fundamental for constructing robust authentication and authorization mechanisms.
	- 2) Authentication
Vulnerabilidades	- 2) Authentication  While authorization defines the rights and privileges after an entity gains access to a system, authentication, i.e., identity verification, plays a vital role before establishing a communication channel between two entities. In the IoT, authentication protocol should be developed to confirm mutual trust between different objects, users or systems by verifying their identities
	- 3) Authorization
	Authorization is the process of granting, denying or limiting access to data, resources or applications within a system. One possible approach for object and user authorization in the IoT is Role-Based Access Control (RBAC). RBAC is an access management technique for multi user and multi-application online systems. In RBAC each role has different functions, an entity can have one or more roles and management of permission is carried out based on entity's role(s)
	Dealing with transaction disputes to assure fair exchange is a common security concern in the business field which will be engaged in the IoT. Thus, it is necessary to build in non-repudiation into the design of the appropriate transport protocol that deals with network failures and prevents a dishonest entity from cheating, deceiving about its real identity or aborting a transaction (i.e., roll-back attack)

A) Dados da publicação:	
Título:	Comprehensive survey and taxonomies of false data injection attacks in smart grids: attack models, targets, and impacts
Autor(es):	Reda, H.T. and Anwar, A. and Mahmood, A.
Fonte de Publicação:	Renewable and Sustainable Energy Reviews
Ano da Publicação:	2022
Resumo:	Smart Grid is organically growing over the centrally controlled power system and becoming a massively interconnected cyber–physical system with advanced technologies of fast communication and intelligence (such as Internet of Things, smart meters, and intelligent electronic devices). While the convergence

	of a significant number of cyber–physical elements has enabled the Smart Grid to be far more efficient and competitive in addressing the growing global energy challenges, it has also introduced a large number of vulnerabilities in the cyber–physical space culminating in violations of data availability, integrity, and confidentiality. Recently, false data injection (FDI) has become one of the most critical types of cyberattacks, and appears to be a focal point of interest for both research and industry. To this end, this paper presents a comprehensive review in the recent advances of the FDI attacks, with particular emphasis on adversarial models, attack targets, and impacts on the Smart Grid infrastructure. This review paper aims to provide a thorough understanding of the incumbent threats affecting the entire spectrum of the Smart Grid. Related literature are analyzed and compared in terms of their theoretical and practical implications to the Smart Grid cybersecurity. In conclusion, a vast range of technical limitations of existing false data attack research is identified, and a number of future research directions is recommended.
B) Dados derivados do objetivo:	
Vulnerabilidades	[] Moreover, as attacks from cyber criminals on the power grid continue to rise in complexity and frequency, it is inevitable that various parts of the Smart Grid are vulnerable to the incumbent attacks. Therefore, it is required to provide strong attack defence across the EMS and to deploy secure communication protocols.  []For example, in wireless sensor networks (WSNs), the inherent wireless communication and broadcast channels between the nodes increase the vulnerability of adversaries that may eavesdrop on all traffic, inject false data reports containing erroneous sensor readings, or can even deplete the already limited energy capacity of sensor nodes[]  []The vulnerability issues in the SE problem can be investigated with respect to the various cyber-and physical elements, including Physical properties of the power system, communication systems, IEDs, and AMIs. Related attack targets also include transmission lines [101], [112], topology [69], [99], [132], and system observability [106].

A) Dados da publicação:	
Título:	A survey on Classification of Cyber-attacks on IoT and IIoT devices
Autor(es):	Shah, Y. and Sengupta, S.
Fonte de Publicação:	Annual Ubiquitous Computing, Electronics and Mobile Communication Conference
Ano da Publicação:	2020
Resumo:	Internet of Things (IoT) devices have gained popularity in recent years. With the increased usage of IoT devices, users have become more prone to Cyber-attacks. Threats against IoT devices must be analyzed thoroughly to develop protection mechanisms against them. An attacker's purpose behind launching an attack is to find a weak link within a network and once discovered, the devices connected to the network become the primary target for the attackers. Industrial Internet of Things (IIoT) emerged due to the popularity of IoT devices and they are used to interconnect machines, sensors, and actuators at large

manufacturing plants. By incorporating IIoT at their facilities companies have benefited by reducing operational costs and increasing productivity. However, as IIoT relies on utilizing the Internet to operate it is vulnerable to Cyber-attacks if security is not taken into consideration. After seeing the advantages of IIoT, a new version of smart industries has been introduced called Industry 4.0. Industry 4.0 combines cloud and fog computing, cyber-physical systems (CPS), and data analytics to automate the manufacturing process. This paper surveys the different classifications of attacks that an attacker can launch against these devices and mentions methods of mitigating such attacks1

## B) Dados derivados do objetivo:

[...]However, if the data is encrypted and the attackers obtain the key that's used to encrypt the data, the information can be modified.[...]

Once the malicious firmware has been transferred to the intended device the only other piece of information that the attacker needs is the architecture of the device's processor which can be easily located by looking at the device's manual. The attacker uses the flaws which exist in the verification of firmware updates to their advantage and the malicious code runs once the firmware updates are installed.

Software failure: Smart home systems depend on software to be controlled and operated upon. Any existence of vulnerabilities in the implementation of the software makes those systems a primary target for attackers.

# Vulnerabilidades

[...]DoS and DDoS attacks target a vulnerability that is found in the Transmission Control Protocol (TCP) [11]. In order to connect to the Internet, devices use the TCP's three-way handshake methodology. These attacks exploit TCP's handshake by directing a high volume of requests to establish a TCP connection with the target server.

Eavesdropping involves illegally listening to personal conversations in real-time by monitoring emails, phone calls, or video conferences

[...]An attacker can listen in on the conversations when the data is being transferred through unsecured servers, when unwanted ports are left open, or when the device is connected to unsecured public Wi-Fi networks.

Passwords are often considered as important keys which are used to unlock personal information. Password attacks are carried out using various methods such as password guessing, password resetting, and password capturing. Password guessing, as the name suggests, involves the attacker inputting commonly used password combinations until they find a match. Password re-usage is also another major problem as once the attacker knows the password they can use it to access multiple accounts[...]

Side Channel Attacks: Performing side channel attacks on M2M machines requires physical access to these machines. Attackers can use the peripheral information of the physical devices to

extract confidential information from them. These types of attacks can also help attackers retrieve cryptography algorithms keys from the devices [...]

An attacker requires physical access to an M2M device and takes full control of it. This form of attack is achieved by physically damaging or replacing a node in the device.[...]

When accessing cloud services a user must enter authentic credentials. However, the authentication process and mechanisms are highly vulnerable and often targeted. Many cloud services still utilize single-factor authentication and a simple username and password requirements. Attackers use this vulnerability to their advantage when trying to disrupt services or steal information from an enterprise taking advantage of cloud computing.

Phishing is used to trick people into entering their personal information or downloading malicious software that is capable of spreading malware. The most common form of phishing attacks are emails that contain links to fake websites, and/or malicious attachments [...]

Implementing poor password requirements is the primary reason IoT/IIoT networks are targeted.

Outdated software may contain flaws that allow attackers to gain access to personal information. Companies often release software updates when the current version contains security vulnerabilities or bugs that can be exploited by attackers. Always ensure to download updates from trusted sources and if possible enroll the device to automatically install updates from the manufacturer's website.

When setting up the environment for IoT/IIoT devices ensure that they are kept separate from the rest of the devices to limit the possibility of an external device causing problems. Keeping these devices in a separate private network also eliminates the possibility of an attacker infecting other devices and spreading the malware in the network. Another benefit of this implementation is that only authorized users are going to have the ability to access and modify data.

Changing default settings: Many times the default settings that are assigned by the device manufacturers benefit the company rather than its users. Manufacturers often add or enable features that are not essential in the operation of the device that aids attackers in launching their attacks. These settings should be checked and changed immediately after the device is purchased and setup.

A) Dados da publicação:	
Título:	On Threat Analysis of IoT-Based Systems: A Survey
Autor(es):	Zhao, W. and Yang, S. and Luo, X.

Access attack. It is also called advanced persistent threat, which refers to the gaining of unauthorized access to the IoT network with the aim of collecting sensitive information.

Denial of service (DoS) or distributed denial of service attacks (DDoS). These types of attacks aim to overwhelm the target system with network traffic to essentially make it unable to provide services to legitimate clients. Like any other online systems, IoT devices are vulnerable to DoS/DDoS attacks as well.

The middleware layer:

Signature wrapping. This attack exploits a vulnerability exists in XML signatures, which effectively invalidate the properties offered by the digital signature, such as non-repudiation.

Man-in-the-middle. This attack would be successful if the MQTT publish-subscribe protocol is used and the proxy for the protocol is compromised.

At the application layer:

Access control attack. This attack exploits the vulnerability in access control and an adversary may gain access to resources illegally, which could lead to the theft of confidential information or compromise the integrity of the entire system.

## Physical Layer:

Insecure configuration. If the IoT software configuration and initiation are not done properly, the devices might be compromised remotely. Not only the data collected by the devices may be stolen, the devices themselves could be used to launch a DDoS attack, as the malware Mirai has demonstrated.

Physical security. Low-cost IoT devices that must be deployed in unprotected field are inevitably facing physical threats.

## Network Layer:

Resource depletion. This includes all attacks that aim to render the device unavailable due to exhaustion of available memory to perform its normal operations, such as the replay, duplicate, and fragmentation attacks that exploit the vulnerabilities of the 6LoWPAN protocol used by IoT devices.

Routing protocols. This include all attacks on routing protocols used by IoT devices. One routing protocol is the RPL, which was designed to run on top of low power and lossy networks.

Título:	Towards a Secure Internet of Things: A Comprehensive Study of Second Line Defense Mechanisms
Autor(es):	Kamaldeep and Dutta, M. and Granjal, J.
Fonte de Publicação:	IEEE Access
Ano da Publicação:	2020
B) Dados derivados do objetivo	The Internet of Things (IoT) exemplifies a large network of sensing and actuating devices that have penetrated into the physical world enabling new applications like smart homes, intelligent transportation, smart healthcare and smart cities. Through IoT, these applications have consolidated in the modern world to generate, share, aggregate and analyze large amount of security-critical and privacy sensitive data. As this consolidation gets stronger, the need for security in IoT increases. With first line of defense strategies like cryptography being unsuited due to the resource constrained nature, second line of defense mechanisms are crucial to ensure security in IoT networks. This paper presents a comprehensive study of existing second line of defense mechanisms for standardized protocols in IoT networks. The paper analyzes existing mechanisms in three aspects: Intrusion Detection Systems (IDS), Intrusion Prevention Systems (IPS) and Intrusion Response Systems (IRS). We begin by providing an overview of standardized protocol stack, its layers and defensive security systems in IoT. From there, we build our narrative by presenting an extended taxonomy of IDS, IPS and IRS classifying them on their techniques, deployment, attacks, datasets, evaluation metrics and data pre-processing methods. We then thoroughly review, compare and analyze the research proposals in this context, considering the unique characteristics involved in these systems. Based on the extensive analysis of the existing defensive security systems, the paper also identifies open research challenges and directions for effective design of such systems for IoT networks, which could guide future research in the area.
Vulnerabilidades	of buffer overflow in constrained devices. UDP, being an unreliable, connectionless and lighter protocol, has been accepted as de facto standard in IoT. But, UDP has inherent weakness whereby attackers can launch DDoS attacks, one them being the UDP flooding attack. The most promising standard application layer protocol for small IoT devices is CoAP [14].  As an extremely heterogeneous technology, security is a critical aspect of IoT on multiple levels of securing data, communication and networks. Attacks on IoT have become extremely targeted and sophisticated. As already discussed, first line of defense mechanisms like cryptography are insufficient due to the resource constrained nature of IoT devices which limits their ability to host and implement sophisticated cryptographic algorithms in real time. Also, the ad hoc nature of IoT networks lets devices connect to each other at runtime, typically for shorter durations, consequently creating a collaborative network.  Denial of Service (DoS) Attacks: The second most common and the easiest to launch is the DoS attack and when this attack is launched by multiple compromised systems on a single victim, it is termed as Distributed Denial of Service (DDoS) attacks. Also

operation by flooding it with (possibly incorrect) requests, preventing the node to accept and process legitimate requests.[]
Spoofing Attacks: Various other classes of attacks detected in the IoT include impersonation or spoofing attack, physical tampering of devices, man-in-the-middle, data integrity, authentication and adversarial attacks.
Penetration Attacks: Penetration attacks exploit vulnerabilities in the system and involve any unauthorized access or modifications to system's resources and data. In such attacks, attackers gain control of the system by exploiting a number of software flaws.[]

A) Dados da publicação:	
A) Dados da publicação: Título:	Security and Privacy of Smart Cities: Issues and Challenge
Autor(es):	Sookhak, M. and Tang, H. and Yu, F.R.
Fonte de Publicação:	International Conference on High Performance Computing and
Torric de l'ablicação.	Communications
Ano da Publicação:	2019
Resumo:	Smart city has been emerged as a new paradigm to dynamically optimize the resources in cities and provide better facilities and quality of life for the citizens. Despite the potential vision of smart cities, security and privacy issues remain to be carefully addressed. In this paper, we present a comprehensive survey of security and privacy issues of smart cities, and categorize the present and future developments within this area. We also describe a thematic taxonomy of security and privacy issues of smart cities to highlight the requirements for designing a secure smart city, identify the existing security and privacy solutions, and present open research issues and challenges of security and privacy in smart cities.
B) Dados derivados do objetivo:	
Vulnerabilidades	Heterogeneous Interaction and the Requirement of the Lightweight Cryptographic Algorithm: The connected devices and smart objects usually interact in heterogeneous environments due to the diversity of manufacturers and enterprises for designing such devices under different standards, protocols, and technical requirements. As a result, it is very difficult to propose a security method that can meet the requirements, homogeneity, and interoperability criteria of all smart city devices.
	Secure Storage and Transaction Logging: []because of the presence of unverified storage services and mismatched security policies, there are several vulnerabilities that threaten the security of auto-tiering databases: (i) The auto-tiering databases automatically reallocate the data based on the rate of the access requests with the range of rarely accessed to critical information.
	Data and Computation Outsourcing: Cloud computing provides an effective way to store the huge amount of collected data and perform the computation with minimum overhead on connected devices in the smart cities. However, by outsourcing the data in the remote servers, the physical control over the data is taken

away and the management of data is delegated to an untrusted CSP.
Anonymity: []Designing an efficient end-to-end anonymity method to protect user privacy on the basis of concealing data communication paths is still a critical challenge in smart cities because of the large number of IoT devices (e.g., sensors) for data collection.[]

A) Dados da publicação:	
Título:	Security Challenges in IoT enabled Smart Grid: Taxonomy of Novel Techniques and Algorithm
Autor(es):	Prakash, S. and Jaiswal, S.
Fonte de Publicação:	International Conference on Inventive Computation Technologies
Ano da Publicação:	2018
Resumo:	The traditional power system network is under a process of evolution to Smart Grids (SGs) to take care of the issues like uni-directional communication, energy wastage, information flow, security and resource sharing. Smart grid is an electrical grid which provides energy to the end users with effectiveness efficiency. Smart grid offer bi-directional information flow between service providers and consumers, including power generation, transmission, consumption, distribution and its use frameworks. Due to its vast usage and huge network electronic power conditioning, power distribution, control of the production of energy and its distribution becomes difficult. To overcome such problems Internet of Things will provide the necessary support to smart grid so that easy transmission and power distribution will take place with much needed convenient system to operate. Smart grid is also using the internet facility for exchange of data which makes the system more vulnerable and prone to cyber-attack. In this paper, there has been a constant effort to analyse the different methods to solve the above problems by employing different strategies algorithms.
B) Dados derivados do objetivo:	
Vulnerabilidades	Access control-it is a security technique that can be used to provide physical and technical security. It is the process of limiting unauthorized or unwanted indulgence of any unauthorized access.
	Cryptography techniques for securing IOT aided SG. Cryptography is science art and study of hiding essential information from the perspective of keeping information safe.

A) Dados da publicação:	
Título:	A systemic and cognitive vision for IoT security: A case study of military live simulation and security challenges
Autor(es):	Sfar, A.R. and Chtourou, Z. and Challal, Y.
Fonte de Publicação:	International Conference on Smart, Monitored and Controlled Cities
Ano da Publicação:	2017
Resumo:	Securing data, objects, networks, systems and people in the Internet of Things (IoT) will have a prominent role in the research and standardization activities of the next years. The high connectivity of intelligent objects and their severe constraints lead

	to many security challenges, which are not included into the classical formulation of security problems and solutions. To help interested researchers to contribute to this research area, an IoT security roadmap overview is presented in this work based on a novel cognitive and systemic vision. The role of each component of the approach will be explained and relations with the other elements and their impact on the overall system will be detailed. According to the novel taxonomy of IoT vision, a case study of military live simulation will be presented to highlight components and interactions of the systemic and cognitive approach. Then, a discussion of security questions about privacy, trust, identification and access control will be provided, and different research challenges will be highlighted.
B) Dados derivados do objetivo:	T
Vulnerabilidades	Their behavior depends on their personalities, skills, knowledge, motivations, expectations, visions, etc. To address security questions related to people in IoT context, it is meaningful to handle them within a systemic approach by providing a global revision of rules and practices. For example, we consider different types of human profiles such as consumers, end users, service or technology providers, etc. All of them are necessary in controlling and improving security issues.  Identification/Access Control: Used to identify and localize objects, systems and persons. Due to its specific features (size, ubiquity, heterogeneity, etc.), IoT architecture has to consider access and identification of any intelligent object by any remote system through a global identification and addressing system would be mandatory.  Auto-Immunity: Concerns exclusively intelligent objects because they may be exposed to physical attacks in hostile areas (absence of communication channel, limitations of memory and calculation capacity, limited physical defense, etc.).

A) Dados da publicação:	
Título:	Autonomous Vehicle Security: A Taxonomy of Attacks and Defences
Autor(es):	Thing, V.L.L. and Wu, J.
Fonte de Publicação:	local de publicação
Ano da Publicação:	2017
Resumo:	texto contendo uma descrição do resumo
B) Dados derivados do objetivo:	
Vulnerabilidades	An attack vector is a path or means by which an adversary can gain unauthorized access to a target system. It is also an enabler for adversaries to carry out vulnerability exploitation on the target systems. Adversaries could gain unauthorized access to autonomous vehicles via either physical access (or close proximity access) or wireless remote access.  - Side-channel attacks: A side-channel attack refers to attacks that result in revealing useful information regarding the transmitted data or the internal working of the system through alternative paths.

<ul> <li>Code Modification: []Defences against such attacks is to ensure connections to the vehicle are password-protected so that only authorized personnel are granted access, and that only authorized and verified code modification can be carried out.</li> <li>Code Injection</li> </ul>
Jamming attacks are availability attacks against the wireless medium or the external facing sensors. Consequently, the authorized communication is disrupted[]
Encryption is fundamental and crucial in protecting vehicular data transmission. Through encryption, the confidentiality of the data transmission can be assured.
To ensure that the controllers of the AV can be trusted, certificates can be issued to support the authentication process

A) Dados da publicação:	
Título:	Security and Privacy of Smart Cities: A Survey, Research Issues
	and Challenges
Autor(es):	nome dos autores
Fonte de Publicação:	local de publicação
Ano da Publicação:	ano de publicação
Resumo:	texto contendo uma descrição do resumo
B) Dados derivados do objetivo:	
Vulnerabilidades	[]One of the best ways to secure the smart cities communications is to develop lightweight cryptographic methods for encrypting and decrypting data and creating a shared secret key among various nodes.[]  Viruses, worms, and other malware have the capability to overwhelm the systems through the boot sectors where in the such viruses are located as an executable code and are able to be distributed to the other systems through the Internet connection or upon booting the other system using infected disks.[] Indeed, secure boot is designed as an additional layer to protect the system against the pre-boot process. Secure booting is a technology for helping the system firmware to check the existence of a cryptographic signature for the system boot loader.  Autenticação, Identificação e Controle de Acesso  Secure Authentication and Access Control for IoT-Based Objects: The smart devices, like smart phones and sensing nodes, are responsible to collect data in the smart cities, suffer from resource limitation, e.g., energy resources and processing power. As a result, protecting the security of data in such devices requires proposing a lightweight cryptographic algorithm that incurs
	minimum computation cost on them

A) Dados da publicação:	
Título:	Internet of Things-Based Security Model and Solutions for Educational Systems
Autor(es):	Patnaik, R. and Raju, K.S. and Sivakrishna, K.
Fonte de Publicação:	Studies in Big Data
Ano da Publicação:	2021
Resumo:	Today the applications of Internet of things (IoT) are progressing rapidly in variety of domains. This encouraged to develop new applications (e.g., smart grid, smart home, smart cities, wearables, and vehicle networking) advancement as well. The emerging application of IoT is exposed toward security, privacy issues, and its challenges. The main objective of this work is to enhance security in the educational system (ES) using IoT devices. We propose several techniques to avail device identification, authenticate the user, and collect the data from various devices. As the IoT sensors are easily negotiable, it allows unauthorized users/devices that are able to steal and override the data from the cloud. This paper represents a brief summary of IoT security threats and challenges and their classification based on the application domain. The authors identified challenges in security issues in IoT-based educational systems and some probable solutions on security. In this research, the authors propose the incremental Gaussian mixture model (IGMM), blockchain, and EdgeSec as a probable solution for security and machine learning (ML) techniques. In this model, few solutions, like IGMM for authorizing the device, blockchain for the encryption of data during transfer in the information network, ML algorithms for identifying and authorizing devices, and EdgeSec, offer a security profile to collect a huge amount of data about each device in the connected IoT environment. The identified model is used for enhancing security in IoT-based educational systems.
B) Dados derivados do objetivo:	Physical Level:
Vulnerabilidades	Jamming Adversaries: This kind of attack is done by decreasing of network that sent frequency signal without following the any protocols.  Insecure Initialization: To ensure a proper and secure network service in IoT, we must initialize and configure IoT devices in the physical layer without deviating secrecy and obstacle to the network.  Insecure Physical Interface: Debugging exploits to negotiated
vuillei abiliuaues	nodes in the network by the poor physical security with the help of physical interface and tools  Sleep Deprivation Attack: IoT devices are designed to consume low power so these are getting into sleep mode. The attackers are trying to not enter the device into sleep mode. It is known as sleep deprivation  Middle Level  Buffer Reservation Attack: Nodes are accessing the buffer to

storing of packets, by sending broken packets it may be exploited by an attacker
[] It is ensured that the use of cryptographic mechanisms secure data communication over IoT devices
Logical Level
[]Application layer is consisting of various types of applications for a different purpose, which is sometimes vulnerable.
Insecure Interfaces: The IoT service interfaces used in cloud, Web, and mobile are responsible for susceptible to several attacks, which causes loss of privacy of the data
Insecure of Software/Firmware: The software/firmware may cause several susceptibilities which make IoT insecure

A) Dados da publicação:	
Título:	A comprehensive survey of security threats and their mitigation techniques for next-generation SDN controllers
Autor(es):	Han, T. and Jan, S.R.U. and Tan, Z. and Usman, M. and Jan,
. ,	M.A. and Khan, R. and Xu, Y.
Fonte de Publicação:	Concurrency and Computation: Practice and Experience
Ano da Publicação:	2020
Resumo:	Software Defined Network (SDN) and Network Virtualization (NV) are emerged paradigms that simplified the control and management of the next generation networks, most importantly, Internet of Things (IoT), Cloud Computing, and Cyber-Physical Systems. The Internet of Things (IoT) includes a diverse range of a vast collection of heterogeneous devices that require interoperable communication, scalable platforms, and security provisioning. Security provisioning to an SDN-based IoT network poses a real security challenge leading to various serious security threats due to the connection of various heterogeneous devices having a wide range of access protocols. Furthermore, the logical centralized controlled intelligence of the SDN architecture represents a plethora of security challenges due to its single point of failure. It may throw the entire network into chaos and thus expose it to various known and unknown security threats and attacks. Security of SDN controlled IoT environment is still in infancy and thus remains the prime research agenda for both the industry and academia. This paper comprehensively reviews the current state-of-the-art security threats, vulnerabilities, and issues at the control plane. Moreover, this paper contributes by presenting a detailed classification of various security attacks on the control layer. A comprehensive state-of-the-art review of the latest mitigation techniques for various security breaches is also presented. Finally, this paper presents future research directions and challenges for further investigation down the line.
B) Dados derivados do objetivo:	
Vulnerabilidades	In SDN (Software Defined Network), all network-related functionalities are managed, controlled and secured from a centralized controller. The single-point dependency and programmable nature of an SDN controller make it a potential choice for the attackers. If security of the controller is compromised, the whole network is vulnerable to various attacks.[]

The southbound interface needs to be protected and secured against communication overhead. Therefore, unnecessary communication that results in congestion at this interface needs to be avoided for the smooth functioning of the network.[...]

DoS/DDoS attacks: The denial-of-service (DoS) and distributed DoS (DDoS) are the most common attacks launched by cyber criminals, cyber extortionists, and hackers.

Spoofing attacks on the SDN controller: The controller is the backbone of an SDN network as it manages and controls the whole network. Due to its centralized nature, it is vulnerable to many types of security attacks. One such attack is spoofing attack. In spoofing attacks, an adversary launches attacks on a legal entity (server/system) by mimicking a legitimate user. [...]

The only thing that an attacker requires is the same privileges as a normal user. On the other hand, during SQL injection attacks, a perpetrator modifies the anticipated effect of an SQL query by injecting new SQL keywords or operators into the query. [...]

A) Dados da publicação:	
Título:	Study of the different security threats on the internet of things and their applications
Autor(es):	Sahmi, I. and Mazri, T. and Hmina, N.
Fonte de Publicação:	International Conference Proceeding Series
Ano da Publicação:	2019
Resumo:	The Internet of Things is one of the revolutions of the industry 4.0. It will change our lives mode. It will be present in every domain: healthcare, transportation, at home, agriculture generally in the city. Everyone will be connected to the Internet by the IoT. Furthermore, to realize this vision, the communication through IoT must be secure. So, it's one of the greatest challenges faced by the scientist's community today in their recent researches. This paper is a study of the different security threats on the Internet of Things by category in one hand: on data and network, on privacy and on system and IoT, and on the other hand we will details some threats on application's domain like smart home and smart city.
B) Dados derivados do objetivo:	<u>,                                      </u>
Vulnerabilidades	physical attacks: Node Tampering: The attacker can cause damage to a sensor node, by physically replacing the entire node or part of its hardware or even electronically interrogating the nodes to gain access and alter sensitive information [8]. RF Interference on RFIDs: The attacker by creating and sending noise signals over the Radio Frequency signals [9], the noise signals will interfere with the RFID signals hindering communication.
	Malicious Node Injection: The attacker deploy a new malicious node between two or more nodes of the IoT system, hence controlling all data flow; this is also known as Man in The Middle Attack [8].  Physical Damage: The attacker can physically damage devices of the IoT network with the purpose of impacting the availability of service [8].

Sleep Deprivation Attack: This attack, keeps the nodes awake which will result in a more power consumption, and will cause the nodes to shut down [8].

Malicious Code Injection: The attacker compromises a node by physically injecting it with malicious code that would give him access to the IoT system [8].

Social Engineering: The attacker manipulates users of an IoT system, to extract private information [8].

#### network's attacks:

RFID Cloning: An attacker clones an RFID tag by copying data from the victim's RFID tag, onto another RFID tag [8].

RFID Unauthorized Access: The attacker can read, modify or even delete data on the RFID nodes, Because of the lack of proper authentication mechanisms in most RFID systems [11].

The attacker over the network manages to interfere between two sensor nodes, accessing restricted data, violating the privacy of the two nodes by monitoring, eavesdropping and controlling the communication between the two sensor nodes [12].

Denial of Service: An attacker can bombard an IoT network with more traffic data that it can handle which can result in a successful Routing Information Attacks by spoofing, altering or replaying routing information can complicate the network and create routing loops [13].

IoT devices have limited resources so they are more vulnerable than the others, so it's necessary to study the different vectors of vulnerabilities:

IoT Device Memory: Most of the IoT devices have a limited memory capacity and therefore external memory is needed to satisfy the demands. This will open threat points for the system in many ways [1].

IoT Web Interfaces: Most of the IoT devices may have a web interface which needs to be connected to database servers. One of the major security threats for such systems is SQL injection and cross-site scripting are some of the attacks that could impact the web interfaces IoT [17].

loT device network services: Inability to execute high-level encryption algorithms on loT devices make it vulnerable to information disclosure attacks. Due to the resource constraints such as computational power and data storage capacity, loT devices are not expected to perform payload verification and integrity checking which make the system insecure [17].

IoT device software update: Software update is one process which should never fail or compromise in an IoT based system. Manually updating the patches for every IoT device may not be feasible. A cloud-based approach is one solution, but since the cloud also imposes security threats, updating the software patches for IoT devices is still under research [1].

IoT Data storage methods: Due to limited processing power and storage capacity, the data stored in IoT devices may be unencrypted. Most of IoT devices will support only symmetric encryption [1].

IoT AAA services: IoT Authentication, Authorization, and Accounting (AAA) services will be a challenging task. Because of the distributed nature of IoT systems, the device responsible for AAA will be under great challenge [1].

Phishing Attacks: The attacker gains access to confidential data by spoofing the authentication credentials of a user, usually through infected emails or phishing websites [14].  Malicious Scripts: The user that controls the gateway can be fooled into running executable active-x scripts which could result in a complete system shut down or data theft [18].  Denial of Service: An attacker can execute DoS or distributed denial of service DDoS attacks on the affected IoT network through the application layer, affecting all users in the network [18]
From physical attack, malicious code injection attack has been the dangerous attack since it is not only stopping the services but also modify the data.

A) Dados da publicação:	
Título:	A survey on attacks in Internet of Things based networks
Autor(es):	Benzarti, S. and Triki, B. and Korbaa, O.
Fonte de Publicação:	International Conference on Engineering and MIS
Ano da Publicação:	2018
Resumo:	Nowadays, the study of the security of IoT has caught many attentions of researchers. Improving our world to be a better environment building a city of dreams which is called smart city is a trend field of research. In this context, objects will be connected to the Internet interacting with each other making the world more smarter. The variety of networks building makes the IoT vulnerable. Smart home, smart grid, Smart transport, WSN, UASN, UWASN, etc make our lives more easier by offering intelligent services that save time and effort. However, each network is exposed to some attacks that can disturb its performance. In this paper, we present a classification of attacks from various networks involved in IoT. This classification distinguish common and specific attacks from each network and use some criteria like the security attributes, congestion, disturbance. Also, some existing security solutions are presented in details in order to expose the security requirements to protect IoT.
B) Dados derivados do objetivo:	T
Vulnerabilidades	COMMON ATTACKS IN IoT NETWORKS:  Jamming: In physical layer, jamming is considered as the primary DOS attack [10]. It has the ability to disturb the communication of an appliance or a network by a powerful jamming source like diffusing radio signals [3].  Sinkhole attack: The attacker becomes attractive by offering optimal paths to reach the base station with powerful connections which pushes the transmitting nodes to change their routing tables to route data by the malicious node.  Tampering: It is important to mention that an adversary can tamper with the device and use it to insert impostor to the system, use the device maliciously or out of its intended functionality [3]  Denial of Service attack: It refers to the property of being inaccessible when requested by an authorized user.
	especifics smart home attacks: Malicious Code Injection: As indicated by his name, this attack injects a malicious code through the debugging interface of the device.

ACK Attack: The wireless channel can be eavesdropped in order to send a fake ACK[3].  Phishing/Pharming: In this case, a malicious entity attempts to guide the user of the device to another server or for marketing purposes or to try to deceive to steal personal information
Specific attacks in smart grid: Access through database links: As we know, the activities of a system are saved in databases. Whereas, if these databases are configured improperly, an attacker can access to them and may control the network system[5].

A) Dados da publicação:	
Título:	Analysing the resilience of the internet of things against physical and proximity attacks
Autor(es):	Xu, H. and Sgandurra, D. and Mayes, K. and Li, P. and Wang, R.
Fonte de Publicação:	Lecture Notes in Computer Science (including subseries Lecture Notes in Artificial Intelligence and Lecture Notes in Bioinformatics)
Ano da Publicação:	2017
Resumo:	The Internet of Things (IoT) technology is being widely integrated in many areas like smart-homes, smart-cities, healthcare, and critical infrastructures. As shown by some recent incidents, like the Mirai and BrickerBot botnets, security is a key issue for current and future IoT systems. In this paper, we examine the security of different categories of IoT devices to understand their resilience under different security conditions for attackers. In particular, we analyse IoT robustness against attacks performed under two threat models, namely (i) physical access of the attacker, (ii) close proximity of the attacker (i.e., RFID and WiFi ranges). We discuss the results of the tests we performed on different categories of IoT devices, namely IP cameras, OFo bike locks, RFID-based smart-locks, and smart-home WiFi routers. The results show that most of IoT devices do not address basic vulnerabilities, which can be exploitable under different threat models.
B) Dados derivados do objetivo:	
Vulnerabilidades	Physical Attack. In this threat model, an attacker can physically interact with the IoT device without notification to Alice. For example, the attacker can access the hardware, and read and modify the default IoT device's settings, which may impact the privacy and authentication credentials of Alice.
133.333303	[] , the user that will scan this QR Code with their mobiles phones will be redirected to a fake website that may request downloading a trojanized app that is similar to OFo app.[] d when the user scans the code she will download a fake app update, which gives an attacker remote access to it.

A) Dados da publicação:	
Título:	Flying through the secure fog: A complete study on UAV-Fog in
	heterogeneous networks
Autor(es):	Gupta, A. and Gupta, S.K.
Fonte de Publicação:	International Journal of Communication Systems
Ano da Publicação:	2022

#### Resumo:

A drone or unmanned aerial vehicles (UAVs) is becoming a trending area for researchers worldwide. UAV's contribution is increasing in day-to-day life, whether it is in a military zone, disaster management, healthcare sector, smart cities, Internet of Things (IoT), urban air mobility, and many more. In contrast, UAV's limited computational capability and low-energy sources pose significant challenges for real-time data processing, storage, networking, and security that are critical in emergencies such as floods, earthquakes, and cyclones. UAVs are rapidly used to satisfy user requirements as well as services. As the demand for UAVs aided heterogeneous wireless networks increases in critical emergencies, fog computing serves several benefits to fulfill users' demands in terms of low latency, support, data storage, mobility, availability, scalability, and so on. This study aims to present a comprehensive study with their technical aspects for understanding fog computing, security issues, privacy concerns, and risks, along with its solutions. This paper suggests the collaboration of UAV-Fog architecture based on the four-tier network consisting of smart things, local UAVs, UAV-Fog, and cloud server, to control UAV's data and also described some of the security issues faced by this cloud infrastructure. Further, this research article also sheds new light on some scenarios of UAV-Fog for such deployments, applications, opportunities, challenges, and their major security threats and their countermeasures. Afterward, we design taxonomy of the collaboration of UAV-Fog with their respective approaches.

#### B) Dados derivados do objetivo:

Authentication has become one of the security problems that are most concerned in this network since large services are delivered on a wide scale.[...]

Cyber-attacks: Cryptography algorithms for smart devices to tackle device tampering

Man-in-the-middle attack: It is a type of attack in which an attacker intervenes in an ongoing conversation or data transmission. After placing themselves in the "middle" of the conversation or transmission, the perpetrators pose as both legal parties.

#### Vulnerabilidades

DoS and DDoS attack: DoS attacks are performed by flooding the target system with traffic requests or sending more data that causes the UAV's network to crash. The DDoS deals with more devices sending traffic requests to crash the whole system.

Jamming: When RF noise is actively induced to disrupt aerial and ground services or restrict devices in a network from communicating with each other, this is known as jamming. The jamming attacks will degrade the quality of services.

Phishing: It is a type of cyber-attack in which the attacker sends a fraud message to ground users in order to gain the credentials and sensitive information of the network users

## A) Dados da publicação:

Título:

Internet of Things (IoT) Security Challenges and Solutions: A Systematic Literature Review

Autor(es):	Ali, R.F. and Muneer, A. and Dominic, P.D.D. and Taib, S.M. and Ghaleb, E.A.A.
Fonte de Publicação:	Communications in Computer and Information Science
Ano da Publicação:	2021
Resumo:	The Internet of Things (IoT), often known as the Internet of Everything, is a new technological paradigm visualized as a worldwide network of interconnected machines. IoT brings another dimension into Information Technology (IT), where machines can communicate with various machines and humans. Researchers and IT industry produced various IoT devices, architectures. Different ways are introduced to implement and use IoT concepts. IoT is getting more intention in ideas like smart homes and smart cities, raising security concerns. This article aims to gather the reported security issues, the classification of those issues, and the solutions that were provided against those IoT security issues.
B) Dados derivados do objetivo:	
Vulnerabilidades	Every object in the IoT platform needs to be identified by the system and other objects. Every object needs to be authenticated before interacting with the system or other objects in the IoT platform [12][13]. Ensuring the data is available to authorized persons or objects is a critical task. Management of data is also vital to protect and manage that data so that the authorized objects will get their data [14]. A key management system needs to be enabled for ensuring confidentiality.  They also gave the reason for these attacks; the devices either had unpatched vulnerabilities or used default passwords. The solution to these malware's is mainly related to energy consumption patterns and OpCode.[]  IoT, as we know, has small storage and processing power, so DNS security models cannot be implemented. It poses threats like DNS Cache Poisoning and Man-In-The-Middle attacks [18, 19].  Denial of Service (DOS), Denial of Sleep (also called sleep deprivation) attacks is flooding-type attacks where the device is flooded with requests until it stops responding and consumes all its energy (battery) to respond to these flooding requests. It is sometimes called an exhaustion attack as well.[]  IoT systems are vulnerable to many vulnerabilities, including encryption, decryption mechanisms, intruding into the network, and flooding requests. Whenever an attack happens, it exploits the vulnerabilities found in the system because every attack targets some specific vulnerabilities and then exploits them. The Authors proposed a fog-based distributed attack detection mechanism for IoT. []

A) Dada da sublicação	
A) Dados da publicação:	
Título:	On the security of the 5G-IoT architecture
Autor(es):	Rahimi, H. and Zibaeenejad, A. and Rajabzadeh, P. and Safavi,
, ,	A.A.
Fonte de Publicação:	International Conference Proceeding Series
Ano da Publicação:	2018
Resumo:	In this paper, we study the security aspects of the new 5G-IoT
	architecture, which is recently developed by this research team.

We classify potential security attacks at each layer of the 5G-IoT architecture. As the main contribution of this work, we propose a security taxonomy for the 5G-IoT architecture in the context of smart city applications. This taxonomy consists of five layers to confront the studied attacks and to protect the privacy of clients. The number of layers is selected according to the types of attacks where each attack type affects a particular layer of the 5G-IoT architecture.

## B) Dados derivados do objetivo:

## Physical Device Layer:

Unauthorized Access to the Tags. The lack of effective authentication techniques for RFID systems allows attackers to easily access tags. In WSNs, if an attacker has access to the network, he can easily use the whole network.

Tag Cloning. Cloning RFID tags is an effective attack in the physical layer. By this attack, the important information could be captured by reverse engineering or directly from its deployment environment.

RF Jamming. In this attack, RF signals are sent to the network to disturb communication between the tags and readers. Attackers could employ RF jamming to prevent readers from communicating with all tags by interfering with all the signals within its range.

## Communication Layer:

DoS Attack. A Denial of Service (DoS) network attacker engages the victim with flooding of requests by making a large mass of network traffic.

Sybil Attack. A node in the system shows multiple pseudonymous identities to a victim node. This action is able to deceive the victim node to perform an action multiple time.

Eavesdropping. Eavesdropping includes a blocking of data flow between two connected devices. In the IoT systems, it occurs on the network layer to takes the form of information sniffing. During data communication, we use privacy as a technique to provide security with efficient access control corresponding eavesdropping.

#### Application Layer:

Code Injection. In this attack, attackers for a variety of purposes such as stealing data, getting system control, and propagating worms inject malicious codes into the system to exploit program errors.

Buffer Overflow. In this threat, attackers use program vulnerabilities to involve the violation of the bounds of code or data buffer. In fact, attackers put a long series of data to a specified area, to make the system overflow.

Phishing Attack. In this threat, attackers act like a real user or authorized institution to receive sensitive information from users such as passwords and credit card details.

## Perception Layer

Access Control. IoT devices largely preserve the information in the RFID tags cannot be caught at insistence, instead to block privacy leak users. In addition, it consists of label failure, processor certainty, analysis of antenna energy, etc.

Data Encryption. Data security of RFID system necessitates encryption of the RFID signal, using the appropriate algorithm.

## Vulnerabilidades

displacement calculation realizes RFID system data encryption Physical Security Design. This contains both node and antenn design. The node design means hardware composition design and security processor selection, processor link, radio frequence circuit design, data acquiring unit design; whereas antenn design has to have high communication range, high flexibility stability, etc

A) Dados da publicação:	
Título:	IoT Powered Agricultural Cyber-Physical System: Security Issue
Titulo.	Assessment
Autor(es):	Kariri, E.
Fonte de Publicação:	IETE Journal of Research
Ano da Publicação:	2022
Resumo:	Smart farming or development in agriculture Cyber-Physical Systems has led to the development of various IOT based innovative platforms to aid automated systems for precision agriculture. There are smart devices (IoT devices, smart vehicles, UAVs, ROVs, and drones) and sensors (magnetic, electrochemical, and mechanical sensors)constantly connected at the edge and procure data that is uploaded to cloud-based interfaces for further processing. The sensors can be maneuvered using an insecure, intelligent farming system to create choreographed cybersecurity attacks on a particular farm. End-to-end system is achieved by putting together smart devices, communication media, uploading data to the cloud, intermediate nodes, and processing this data at a central unit like the cloud or intermediate processing at other nodes. Cyber-physical systems are a combination of many technologies, resulting in a large number of security threats. This chapter is to delineate the attack vectors and categories of threats that can be performed on these innovative IOT based agricultural products; if not appropriately secured, can lead to more strategized and sophisticated security attacks that can hinder production for a region under effect and thus bringing down the economy and food stocks of Nations who implemented smart agriculture.
B) Dados derivados do objetivo:	
Vulnerabilidades	Node Tampering/Jamming: Equipment such as actuators, sensors are generally embedded in nature, having a single task to perform. Therefore, these nodes cannot have more security forefront. Attacks like node tampering, jamming are more prevalent.  Interferences/Insider Attacks: The perception layer in IoT is more susceptible to insider attacks wherein eavesdropping; interferences can be introduced by injecting an external agent in disguise.  Physical Damage: Physical damage to equipment can be natural as a result of calamity or otherwise. It can lead to null values at receiving end or missed values, which can cause an imbalance in the real-time processing of data.  Unauthorized Access: To provide for crops through smart IOT based agriculture deployments, it is highly important to properly monitor conditions in real-time.  Denial of Service: According to [5], in precision agricultural systems, the denial of service is more frequent towards users using smart services; the threats can be due to poorly managed

systems, disruption to PNT(positioning, navigation, and timing) systems that use GPS to collect information for processing.

Encryption: Encryption of contents is extremely important when the data is transmitted or stored; the practice helps to secure the parameter to a vast extent

Social Engineering: A naive user is often the most insecure point in the complete network; Phishing is another social engineering attack strategy that is generally used to lure the users into clicking on synonymous links to gain access;