

Intro to piping and Data Manipulation

JEPA

02/06/2017

Contents

Libraries and Data	1
Data Manipulation with Dplyr and Tidyr	2
Dplyr	2
Arrange	2
Filter	3
Group_by* (plus summarise)	4
Mutate	5
Rename	6
Select	6
slice	8
The “bind” family	8
The “join” family	10
Intersect	11
Union	11
Setdiff	11
Tidyr	11
Gather	11
Unite and Separate	12
The Piping operator %>%	12
Combo!	13

Libraries and Data

```
#If you downloaded tidyverse
#install.packages('tidyverse')
#library(tidyverse)

#install.packages('dplyr')
library(dplyr)

#install.packages('tidyr')
library(tidyr)

#install.packages('ggplot2')
library(ggplot2)

Alaska <- read.csv("./Data/Alaska.csv") #Sea around Us data for Alaska
USA <- read.csv("./Data/USAP.csv") #Sea around Us data for USA
```

Data Manipulation with Dplyr and Tidyr

Despite being separate, these two packages work together as one. Their main function is to manipulate data frames and keep things “tydi”. In some cases you can also make basic data creation. Both packages follow the same syntax and can use the pipe operator, I normally don’t even know which function is from what package so I often just call both.

Plus: Most functions are self explanatory like `select` or `filter`!

Dplyr

Arrange

The `arrange` function allows you to, literally, arrange your data by any value of a column

Basic structure:

```
New_Table <- arrange(Data, column_to_arrange_by)
```

Note: If you want to do from Top <- Bottom you can use `desc()` within the function

Note: when doing multiple variables the order is important since it will start with the first one

```
#You can arrange by characters (A -> Z)
```

```
Arrange_Example <- arrange(Alaska, common_name)
```

```
head(Arrange_Example[5:7], 3)
```

```
##   year scientific_name common_name
## 1 1964      Haliotis    Abalones
## 2 1964      Haliotis    Abalones
## 3 1966      Haliotis    Abalones
```

```
#You can arrange by characters (A <- Z) using desc()
```

```
Arrange_Example2 <- arrange(Alaska, desc(common_name))
```

```
head(Arrange_Example2[5:7], 3)
```

```
##   year  scientific_name      common_name
## 1 1984 Sebastes flavidus Yellowtail rockfish
## 2 1985 Sebastes flavidus Yellowtail rockfish
## 3 1987 Sebastes flavidus Yellowtail rockfish
```

```
# you can do multiple characters:
```

```
Arrange_Example3 <- arrange(Alaska, common_name, functional_group, desc(commercial_group))
```

```
head(Arrange_Example3[7:9], 3)
```

```
##   common_name      functional_group commercial_group
## 1   Abalones Other demersal invertebrates      Molluscs
## 2   Abalones Other demersal invertebrates      Molluscs
## 3   Abalones Other demersal invertebrates      Molluscs
```

```
# And naturally, you can also arrange by numeric factors
```

```
Arrange_Example4 <- arrange(Alaska, uncertainty_score, desc(tonnes))
```

```
head(Arrange_Example4[4:6],3)
```

```
##   uncertainty_score year      scientific_name
## 1                   1 2010 Oncorhynchus tshawytscha
## 2                   1 1989 Oncorhynchus tshawytscha
## 3                   1 1988 Oncorhynchus tshawytscha
```

Filter

The `filter` function allows you to, literally, filter your data by any category or number.

Basic structure:

```
New_Table <- filter(Data, column_to_filter_by == "category")
```

filter operators:

`a == b` a is equal to b `a != b` a is not equal to b `a > b` a is greater than b `a < b` a is less than b `a >= b` a is greater than or equal to b `a <= b` a is less than or equal to b `a %in% b` a is an element in b

#You can filter by character

```
Filter_Example <- filter(Alaska,
                          common_name == "Clams")
```

```
head(Filter_Example[1:5], 5)
```

```
##           area_name area_type      data_layer
## 1 USA (Alaska, Subarctic)    eez Reconstructed domestic catch
## 2 USA (Alaska, Subarctic)    eez Reconstructed domestic catch
## 3 USA (Alaska, Subarctic)    eez Reconstructed domestic catch
## 4 USA (Alaska, Subarctic)    eez Reconstructed domestic catch
## 5 USA (Alaska, Subarctic)    eez Reconstructed domestic catch
##   uncertainty_score year
## 1                   1 1950
## 2                   1 1951
## 3                   1 1952
## 4                   1 1953
## 5                   1 1954
```

#You can filter by numeric input too

```
Filter_Example2 <- filter(Alaska,
                           year == 2009)
```

```
head(Filter_Example2[1:5], 5)
```

```
##           area_name area_type      data_layer
## 1 USA (Alaska, Subarctic)    eez Reconstructed domestic catch
## 2 USA (Alaska, Subarctic)    eez Reconstructed domestic catch
## 3 USA (Alaska, Subarctic)    eez Reconstructed domestic catch
## 4 USA (Alaska, Subarctic)    eez Reconstructed domestic catch
## 5 USA (Alaska, Subarctic)    eez Reconstructed domestic catch
##   uncertainty_score year
## 1                   4 2009
## 2                   4 2009
## 3                   2 2009
## 4                   4 2009
```

```
## 5                                4 2009
```

```
# Note: you can do ==, <= or !=
```

```
# you can do multiple characters:
```

```
Selection <- c("Clams","Octopuses")
```

```
Filter_Example3 <- filter(Alaska,  
                          common_name %in% Selection)
```

```
head(Filter_Example3[4:8], 5)
```

```
##      uncertainty_score year scientific_name common_name  
## 1                      1 1950      Bivalvia      Clams  
## 2                      1 1950    Octopodidae    Octopuses  
## 3                      1 1951      Bivalvia      Clams  
## 4                      1 1951    Octopodidae    Octopuses  
## 5                      1 1952      Bivalvia      Clams  
##              functional_group  
## 1 Other demersal invertebrates  
## 2              Cephalopods  
## 3 Other demersal invertebrates  
## 4              Cephalopods  
## 5 Other demersal invertebrates
```

```
# NOTE: remember that in R there are multiple ways to get to the same result!
```

```
#Wait! What if I want to filter by multiple columns!?
```

```
Filter_Example4 <- filter(Alaska,common_name == "Clams",  
                          reporting_status == "Unreported") # Will give me all clams that are unreported
```

```
#You can also filter by NA
```

```
Filter_NA_Example1 <- filter(Alaska,is.na(uncertainty_score)) #Extract only NA's
```

```
head(Filter_NA_Example1[1:4],3)
```

```
##              area_name area_type      data_layer  
## 1 USA (Alaska, Subarctic)      eez Inferred foreign catch  
## 2 USA (Alaska, Subarctic)      eez Inferred foreign catch  
## 3 USA (Alaska, Subarctic)      eez Inferred foreign catch  
##      uncertainty_score  
## 1                    NA  
## 2                    NA  
## 3                    NA
```

```
Filter_NA_Example2 <- filter(Alaska,!is.na(uncertainty_score)) #Clear NA's
```

Group_by* (plus summarise)

The `group_by` function allows you to group your data by common variables for future (immediate) calculations. This function needs the “pipe operator”

Basic structure:

```
New_Table <- Data %>% group_by(column_1,column_2...) %>% second_function()
```

#Simple group_by

```
Group_by_Example <- Alaska %>%  
  group_by(common_name) %>%  
  summarise(n()) #tells you how many rows of each "common_name" you have
```

```
head(Group_by_Example, 3)
```

```
## # A tibble: 3 × 2  
##   common_name `n()`  
##   <fctr> <int>  
## 1 Abalones 52  
## 2 Alaska plaice 9  
## 3 Alaska pollock 290
```

#Multiple

```
Group_by_Example2 <- Alaska %>%  
  group_by(common_name,uncertainty_score) %>%  
  summarise(n()) %>% #tells you how many rows of each "common_name" you have  
  arrange(uncertainty_score)
```

```
head(Group_by_Example, 3)
```

```
## # A tibble: 3 × 2  
##   common_name `n()`  
##   <fctr> <int>  
## 1 Abalones 52  
## 2 Alaska plaice 9  
## 3 Alaska pollock 290
```

Mutate

The `mutate` function allows you to create a new column in the data-set. The new column can have characters or numbers.

Basic structure:

```
New_Table <- mutate(Data, Name_New_Column = action)
```

#Functions

```
Mutate_Example1 <- mutate(Alaska, Log = log(tonnes))
```

```
head(Mutate_Example1[13:16], 3)
```

```
##   reporting_status  tonnes landed_value    Log  
## 1 Unreported    13.8030    20235.2 2.624886  
## 2 Reported    1483.9740    2175505.9 7.302479  
## 3 Unreported    389.9891    571724.0 5.966119
```

#In data calculations (per row)

```
Mutate_Example2 <- mutate(Alaska, Price_plus_Ton = (landed_value+tonnes))
```

```
head(Mutate_Example2[13:16], 3)
```

```
##   reporting_status   tonnes landed_value Price_plus_Ton
## 1      Unreported    13.8030      20235.2      20249
## 2        Reported 1483.9740    2175505.9    2176990
## 3      Unreported   389.9891    571724.0    572114
```

#Or characters...

```
Mutate_Example3 <- mutate(Alaska, Country = "USA")
```

```
head(Mutate_Example3[13:16], 3)
```

```
##   reporting_status   tonnes landed_value Country
## 1      Unreported    13.8030      20235.2      USA
## 2        Reported 1483.9740    2175505.9      USA
## 3      Unreported   389.9891    571724.0      USA
```

```
Mutate_Example4 <- mutate(Mutate_Example3, Country = paste("In",year,Country,"harvested",round(tonnes,2),
```

```
paste(Mutate_Example4[1,16])
```

```
## [1] "In 1950 USA harvested 13.8 tonnes of Marine fishes nei"
```

```
paste(Mutate_Example4[5387,16])
```

```
## [1] "In 1979 USA harvested 18.7 tonnes of Squids"
```

Rename

The `rename` function is another “self explanatory” it allows you to rename the columns

Basic structure:

```
New_Table <- rename(Data,New_Name = Old_Name)
```

```
Rename_Example <- rename(Alaska, Weight = tonnes)
```

Select

The `select` function is one of those “of-course it does that” function cus it allows you to, wait for it... SELECT any column you want.

Basic structure:

```
New_Table <- select(Data,number or name of column)
```

Note: Re-ordering of values happens here!

#Select by column number

```
Select_Example1 <- select(Alaska, 6)
```

```
head(Select_Example1,3)
```

```
##           scientific_name
## 1 Marine fishes not identified
## 2 Marine fishes not identified
## 3 Marine fishes not identified
```

```
#Select by multiple column numbers
Select_Example2 <- select(Alaska, 4,5,6,7)
```

```
head(Select_Example2, 3)
```

```
##      uncertainty_score year      scientific_name      common_name
## 1                    1 1950 Marine fishes not identified Marine fishes nei
## 2                    3 1950 Marine fishes not identified Marine fishes nei
## 3                    3 1950 Marine fishes not identified Marine fishes nei
```

```
# You can also do (4:7) and even (4:6,15)
```

```
#Select by name
```

```
Select_Example3 <- select(Alaska, area_name,year,scientific_name,tonnes)
```

```
head(Select_Example3, 3)
```

```
##              area_name year      scientific_name      tonnes
## 1 USA (Alaska, Subarctic) 1950 Marine fishes not identified 13.8030
## 2 USA (Alaska, Subarctic) 1950 Marine fishes not identified 1483.9740
## 3 USA (Alaska, Subarctic) 1950 Marine fishes not identified 389.9891
```

```
# You can drop columns from a dataframe
```

```
Select_Example4 <- select(Select_Example3, -area_name,year)
```

```
head(Select_Example4, 3)
```

```
##      year      scientific_name      tonnes
## 1 1950 Marine fishes not identified 13.8030
## 2 1950 Marine fishes not identified 1483.9740
## 3 1950 Marine fishes not identified 389.9891
```

```
#Note, you can also drop using -
```

```
#And you can also re-order your columns!
```

```
Select_Example5 <- select(Select_Example3, scientific_name,year,tonnes,area_name)
```

```
head(Select_Example5, 3)
```

```
##              scientific_name year      tonnes      area_name
## 1 Marine fishes not identified 1950 13.8030 USA (Alaska, Subarctic)
## 2 Marine fishes not identified 1950 1483.9740 USA (Alaska, Subarctic)
## 3 Marine fishes not identified 1950 389.9891 USA (Alaska, Subarctic)
```

```
#And you don't have to write everything
```

```
Select_Example6 <- select(Select_Example5, scientific_name,
                          everything())
```

```
head(Select_Example5, 3)
```

```
##              scientific_name year      tonnes      area_name
## 1 Marine fishes not identified 1950 13.8030 USA (Alaska, Subarctic)
## 2 Marine fishes not identified 1950 1483.9740 USA (Alaska, Subarctic)
## 3 Marine fishes not identified 1950 389.9891 USA (Alaska, Subarctic)
```

slice

The `slice` function works like the `select` function but for rows. So, if you want to extract an specific row, a set of rows, or a range between values, use `slice`!

Basic Structure

```
New_Data <- slice(Old_Data, number)
```

```
#Select by row number
```

```
Slice_Example1 <- slice(Alaska, 3948)
```

```
Slice_Example1
```

```
##           area_name area_type           data_layer
## 1 USA (Alaska, Subarctic)      eez Reconstructed domestic catch
##   uncertainty_score year      scientific_name      common_name
## 1           3 1973 Clupea pallasii pallasii Pacific herring
##           functional_group commercial_group fishing_entity
## 1 Medium pelagics (30 - 89 cm)   Herring-likes           USA
##   fishing_sector catch_type reporting_status tonnes landed_value
## 1   Industrial   Landings      Reported 15792.9    23152391
```

```
#Select by multiple rows
```

```
Slice_Example2 <- slice(Alaska, 1000:3948)
```

```
head(Slice_Example2, 3)
```

```
##           area_name area_type           data_layer
## 1 USA (Alaska, Subarctic)      eez Reconstructed domestic catch
## 2 USA (Alaska, Subarctic)      eez Reconstructed domestic catch
## 3 USA (Alaska, Subarctic)      eez Reconstructed domestic catch
##   uncertainty_score year      scientific_name      common_name
## 1           3 1957 Hippoglossus stenolepis Pacific halibut
## 2           1 1957 Hippoglossus stenolepis Pacific halibut
## 3           3 1957 Clupea pallasii pallasii Pacific herring
##           functional_group commercial_group fishing_entity
## 1   Large flatfishes (>=90 cm)   Flatfishes           USA
## 2   Large flatfishes (>=90 cm)   Flatfishes           USA
## 3 Medium pelagics (30 - 89 cm)   Herring-likes           USA
##   fishing_sector catch_type reporting_status tonnes landed_value
## 1   Artisanal   Landings      Reported 12564.60000 18419703.60
## 2   Recreational Landings      Unreported  11.14694   16341.42
## 3   Industrial   Landings      Reported 53656.10001  78659842.61
```

```
<<<<<<< HEAD # Joining Data with dplyr ===== # ##Joining Data with dplyr >>>>>>>
7e3de76fb81ad0e0f103bc0ac3937709fca1c5be
```

The “bind” family

These functions will help us bind two or more data-sets in one depending on different variables.

bind_cols

The `bind_cols` function allows us to bind two data-sets by column.

Basic Structure

```
New_Data <- bind_cols(Data1, Data2)
```

```
#Lets just assume that we have two different data sets
```

```
Data1 <- select(Alaska, 1)
```

```
Data2 <- select(Alaska, 2)
```

```
# View(Data2)
```

```
#Now we bind the columns together
```

```
Bind_Cols_1 <- bind_cols(Data1, Data2)
```

```
head(Bind_Cols_1, 3)
```

```
##           area_name area_type
## 1 USA (Alaska, Subarctic)    eez
## 2 USA (Alaska, Subarctic)    eez
## 3 USA (Alaska, Subarctic)    eez
```

bind_rows

The bind_rows function is a sister-function of bind_cols but for binding rows.

Basic Structure

```
New_Data <- bind_rows(Data1, Data2)
```

```
#Lets just assume that we have two different data sets
```

```
Data1 <- slice(Alaska, 1:3)
```

```
Data2 <- slice(Alaska, 10800:10802)
```

```
#Now we bind the columns together
```

```
Bind_Row_1 <- bind_rows(Data1, Data2)
```

```
head(Bind_Row_1, 6)
```

```
##           area_name area_type          data_layer
## 1 USA (Alaska, Subarctic)    eez Reconstructed domestic catch
## 2 USA (Alaska, Subarctic)    eez Reconstructed domestic catch
## 3 USA (Alaska, Subarctic)    eez Reconstructed domestic catch
##   uncertainty_score year      scientific_name      common_name
## 1             1 1950 Marine fishes not identified Marine fishes nei
## 2             3 1950 Marine fishes not identified Marine fishes nei
## 3             3 1950 Marine fishes not identified Marine fishes nei
##           functional_group      commercial_group fishing_entity
## 1 Medium demersals (30 - 89 cm) Other fishes & inverts          USA
## 2 Medium demersals (30 - 89 cm) Other fishes & inverts          USA
## 3 Medium demersals (30 - 89 cm) Other fishes & inverts          USA
##   fishing_sector catch_type reporting_status   tonnes landed_value
## 1   Subsistence   Landings      Unreported    13.8030      20235.2
## 2   Artisanal     Landings       Reported   1483.9740     2175505.9
## 3   Artisanal     Landings      Unreported    389.9891      571724.0
##           area_name area_type          data_layer
```

```
## 1 USA (Alaska, Subarctic)      eez Reconstructed domestic catch
## 2 USA (Alaska, Subarctic)      eez Reconstructed domestic catch
## 3 USA (Alaska, Subarctic)      eez Reconstructed domestic catch
##   uncertainty_score year      scientific_name common_name
## 1                   4 2009 Anoplopoma fimbria  Sablefish
## 2                   2 2009 Anoplopoma fimbria  Sablefish
## 3                   4 2009 Anoplopoma fimbria  Sablefish
##               functional_group commercial_group fishing_entity
## 1 Large bathydemersals (>=90 cm)  Scorpionfishes          USA
## 2 Large bathydemersals (>=90 cm)  Scorpionfishes          USA
## 3 Large bathydemersals (>=90 cm)  Scorpionfishes          USA
##   fishing_sector catch_type reporting_status      tonnes landed_value
## 1      Industrial  Landings      Reported  1074.516856  1575241.711
## 2      Subsistence Landings      Unreported    5.002588    7333.794
## 3      Artisanal   Landings      Reported  11175.083144  16382671.889
```

The “join” family

anti_join

This function will allow you to select all variables that are **not** the same within two data-sets. Note, both data-sets must have at least one similar category/column.

Basic Structure

```
Data_Name <- anti_join(Dataset1, Dataset2, by="similar category")
```

Lets us know what variables from one dataset are not present in some other dataset

```
#Lets assume we want to know how many species are fished in Alaska and not in the continental US
Diff_Species <- anti_join(Alaska, USA, by="scientific_name")

#Lets assume we want to know how many species are fished in Alaska and not in the continental US
Similar_Species <- anti_join(Alaska, USA, by="scientific_name")

#You can also do it by more than one variable
Diff_Species2 <- anti_join(Alaska, USA, by=c("scientific_name", "reporting_status"))
```

semi_join

This function does the opposite as the anti join, letting you select those variables shared by two data-sets.

```
#Now we want to know how many species are fished in BOTH Alaska and the continental US
Same_Species <- semi_join(Alaska, USA, by="scientific_name")

#Note: just like anti_join, you can do it for more than one variable
```

Inner_join

Inner_join will let you combine variables (rows) from different data-sets into one data-set based on a category/column that you choose

```
#Now we want to know how many species are fished in BOTH Alaska and the continental US
Inner_Species <- inner_join(Alaska, USA, by="scientific_name")
```

```
## Warning in inner_join_impl(x, y, by$x, by$y, suffix$x, suffix$y): joining
## factors with different levels, coercing to character vector
```

```
#Note: just like anti_join, you can do it for more than one variable
```

```
#Lets just assume that we have two different data sets
```

```
Data1 <- select(Alaska, 7,8)
```

```
Data2 <- select(Alaska, 7,11)
```

```
#Both Data 1 have two columns from which one is "common_name". In the case of Data 1 the second column
```

```
Inner_Example <- inner_join(Data1, Data2, by="common_name")
```

```
#The result will be a data-set with the "common_name", "functional_group" and "fishing_sector"
```

```
head(Inner_Example,3)
```

```
##           common_name           functional_group fishing_sector
## 1 Marine fishes nei Medium demersals (30 - 89 cm)    Subsistence
## 2 Marine fishes nei Medium demersals (30 - 89 cm)    Artisanal
## 3 Marine fishes nei Medium demersals (30 - 89 cm)    Artisanal
```

Left_join

```
#Now we want to know how many species are fished in BOTH Alaska and the continental US
```

```
Left_Species <- left_join(Alaska, USA, by="scientific_name")
```

```
## Warning in left_join_impl(x, y, by$x, by$y, suffix$x, suffix$y): joining
## factors with different levels, coercing to character vector
```

```
#Note: just like anti_join, you can do it for more than one variable
```

Right_join

```
#Now we want to know how many species are fished in BOTH Alaska and the continental US
```

```
Right_Species <- right_join(Alaska, USA, by="scientific_name")
```

```
## Warning in right_join_impl(x, y, by$x, by$y, suffix$x, suffix$y): joining
## factors with different levels, coercing to character vector
```

```
#Note: just like anti_join, you can do it for more than one variable
```

Intersect

Union

Setdiff

Tidyr

Gather

The `gather` function allows us to convert long data into short format. This is specifically helpful for plotting since it will allow you to set categories to data.

Note: The `spread` function is exactly the opposite to `gather` and has the same structure

```
# For example, if you want to have a division between scientific and common name to plot the tonnes you
Data1<- select(Alaska, 6,7,15)
Gather_Example <- gather(Data1, key='Name_Type', value='Species', 1:2)
```

```
## Warning: attributes are not identical across measure variables; they will
## be dropped
```

```
head(Gather_Example,5)
```

```
##   landed_value      Name_Type      Species
## 1    20235.198 scientific_name Marine fishes not identified
## 2   2175505.884 scientific_name Marine fishes not identified
## 3    571724.021 scientific_name Marine fishes not identified
## 4    12045.723 scientific_name Marine fishes not identified
## 5     664.751 scientific_name Miscellaneous aquatic invertebrates
```

Unite and Separate

These functions are used to unite or spread dates on a dataset

```
#Assuming that our data set had a date column with year/month/day this is how we would do it...
Separate_Example <- separate(Alaska,year,c("year", "month", "day"), sep = "-")
```

```
#Note: ignore the warning message, is because we don't have a month/day format
```

```
head(Separate_Example[5:7],3)
```

```
##   year month  day
## 1 1950  <NA> <NA>
## 2 1950  <NA> <NA>
## 3 1950  <NA> <NA>
```

```
# And then we can also go backwards
```

```
Unite_Example <- unite(Separate_Example,"Date",year, month, day, sep = "-")
```

```
head(Unite_Example[4:6],3)
```

```
##   uncertainty_score      Date      scientific_name
## 1                1 1950-NA-NA Marine fishes not identified
## 2                3 1950-NA-NA Marine fishes not identified
## 3                3 1950-NA-NA Marine fishes not identified
```

```
#Note that, because month and day are NA's, the new column has them together
```

The Piping operator %>%

Many R packages like `dplyr`, `tidyr`, `ggplot2` and `leaflet`, allows you to use the pipe (`%>%`) operator to chain functions together. Chaining code allows you to streamline your workflow and make it easier to read.

When using the `%>%` operator, first specify the data frame that all following functions will use. For the rest of the chain the data frame argument can be omitted from the remaining functions.

NOTE: for Mac users the pipe symbol “%>%” shortcut is: command + shit + m. For windows users is: Ctrol + Shift + m

```
Pipie_Example <- Alaska %>%  
  filter(year >= 2000) %>% #Lets filter the years above 2000  
  select(area_name,scientific_name,tonnes,year) %>% #We only care about these data  
  group_by(scientific_name,year) %>%  
  summarise(Mean = mean(tonnes),  
            SD = sd(tonnes),  
            N = n()) %>% #Give me the mean and sd of each species each year  
  mutate(Round_Mean = round(Mean,2), Round_SD = round(SD,2)) %>% #create a log version of mean and the  
  transmute(Log_Mean = log(Round_Mean,2),  
            Log_SD = log(Round_SD,2)) %>%  
  semi_join(USA,  
            by="scientific_name")
```

Adding missing grouping variables: `scientific_name`

Combo!




Figure 1: S

One of the beauties of tidyverse is that you can mix several packages in one code like this graph:

```
Pipie_Example <- Alaska %>%  
  filter(year >= 2000) %>% #Lets filter the years above 2000  
  select(area_name,scientific_name,tonnes,year) %>% #We only care about these data  
  group_by(scientific_name,year) %>%  
  summarise(Mean = mean(tonnes),  
            SD = sd(tonnes),  
            N = n()) %>% #Give me the mean and sd of each species each year  
  mutate(Round_Mean = round(Mean,2), Round_SD = round(SD,2)) %>% #create a log version of mean and the  
  transmute(Log_Mean = log(Round_Mean,2),  
            Log_SD = log(Round_SD,2)) %>%  
  ggplot(., #It tells ggplot2 to use the data you are piping  
    aes(  
      x=Log_Mean,  
      y=Log_SD  
    )) +  
  geom_point()
```

Pipie_Example

