



[Center for Machine Learning and Intelligent Systems](#)

[About](#) [Citation Policy](#) [Donate a Data Set](#) [Contact](#)

☒ Repository ☐ Web



[View ALL Data Sets](#)

Human Activity Recognition Using Smartphones Data Set

Download: [Data Folder](#), [Data Set Description](#)

Abstract: Human Activity Recognition database built from the recordings of 30 subjects performing activities of daily living (ADL) while carrying a waist-mounted smartphone with embedded inertial sensors.

Data Set Characteristics:	Multivariate, Time-Series	Number of Instances:	10299	Area:	Computer
Attribute Characteristics:	N/A	Number of Attributes:	561	Date Donated	2012-12-10
Associated Tasks:	Classification, Clustering	Missing Values?	N/A	Number of Web Hits:	138056

Source:

Jorge L. Reyes-Ortiz, Davide Anguita, Alessandro Ghio, Luca Oneto.
 Smartlab - Non Linear Complex Systems Laboratory
 DITEN - Università degli Studi di Genova, Genoa I-16145, Italy.
activityrecognition '@' smartlab.ws
www.smartlab.ws

Data Set Information:

The experiments have been carried out with a group of 30 volunteers within an age bracket of 19-48 years. Each person performed six activities (WALKING, WALKING_UPSTAIRS, WALKING_DOWNSTAIRS, SITTING, STANDING, LAYING) wearing a smartphone (Samsung Galaxy S II) on the waist. Using its embedded accelerometer and gyroscope, we captured 3-axial linear acceleration and 3-axial angular velocity at a constant rate of 50Hz. The experiments have been video-recorded to label the data manually. The obtained dataset has been randomly partitioned into two sets, where 70% of the volunteers was selected for generating the training data and 30% the test data.

The sensor signals (accelerometer and gyroscope) were pre-processed by applying noise filters and then sampled in fixed-width sliding windows of 2.56 sec and 50% overlap (128 readings/window). The sensor acceleration signal, which has gravitational and body motion components, was separated using a Butterworth low-pass filter into body acceleration and gravity. The gravitational force is assumed to have only low frequency components, therefore a filter with 0.3 Hz cutoff frequency was used. From each window, a vector of features was obtained by calculating variables from the time and frequency domain.

Check the README.txt file for further details about this dataset.

Attribute Information:

For each record in the dataset it is provided:

- Triaxial acceleration from the accelerometer (total acceleration) and the estimated body acceleration.
- Triaxial Angular velocity from the gyroscope.
- A 561-feature vector with time and frequency domain variables.
- Its activity label.
- An identifier of the subject who carried out the experiment.

Relevant Papers:

N/A

Citation Request:

[1] Davide Anguita, Alessandro Ghio, Luca Oneto, Xavier Parra and Jorge L. Reyes-Ortiz. Human Activity Recognition on Smartphones using a Multiclass Hardware-Friendly Support Vector Machine. International Workshop of Ambient Assisted Living (IWAAL 2012). Vitoria-Gasteiz, Spain. Dec 2012

Supported By:



In Collaboration With:



[About](#) || [Citation Policy](#) || [Donation Policy](#) || [Contact](#) || [CML](#)