Portfolio Component 1: Data Exploration

Objectives:

- In class, we covered how to do data exploration with statistical functions in R
- In this assignment, you recreate that functionality in C++ code
- This will prepare us to write algorithms in C++ in future assignments

Turn in:

- Upload your C++ code and document to your portfolio, and create a link to it on your index page
- Upload your C++ code and document to eLearning

Instructions:

- 1. In the C++ IDE of your choice:
 - a. Read the csv file (now reduced to 2 columns) into 2 vectors of the appropriate type. See the "reading in cpp" picture at the end of the document.
 - b. Write the following functions:
 - 1. a function to find the sum of a numeric vector
 - 2. a function to find the mean of a numeric vector
 - 3. a function to find the median of a numeric vector
 - 4. a function to find the range of a numeric vector
 - 5. a function to compute covariance between rm and medv (see formula on p. 74 of pdf)
 - 6. a function to compute correlation between rm and medv (see formula on p. 74 of pdf); Hint: sigma of a vector can be calculated as the square root of variance(v, v)
 - c. Call the functions described in 1-4 for rm and separately for medv. Call the covariance and correlation functions for rm and medv together. Print results for each function.
- 2. Write a short document:
 - a. copy/paste runs of your code showing the output
 - b. describing your experience using built-in functions in R versus coding your own functions in C++
 - c. describe the descriptive statistical measures mean, median, and range, and how these values might be useful in data exploration prior to machine learning
 - d. describe the covariance and correlation statistics, and what information they give about two attributes. How might this information be useful in machine learning?
- 3. Create a link to this document and your code on your index page.

Grading Rubric:

Element	Points
Step 1 C++ code	70
Step 2 Overview document	20
Step 3 Create links to the document and code on the index page	10
Total	100

Grading Rubric:

- 90 and above for exceptional work
- 80-89 for good work
- 70-79 for average work
- below 70 for low quality work

One way to read in a csv file in C++, feel free to do this another way if you prefer

```
int main(int argc, char** argv) {
ifstream inFS;
                   // Input file stream
string line;
string rm_in, medv_in;
const int MAX_LEN = 1000;
vector<double> rm(MAX LEN);
vector<double> medv(MAX_LEN);
// Try to open file
cout << "Opening file Boston.csv." << endl;</pre>
inFS.open("Boston.csv");
if (!inFS.is_open()) {
   cout << "Could not open file Boston.csv." << endl;</pre>
   return 1; // 1 indicates error
// Can now use inFS stream like cin stream
// Boston.csv should contain two doubles
cout << "Reading line 1" << endl;</pre>
getline(inFS, line);
// echo heading
cout << "heading: " << line << endl;</pre>
int numObservations = 0;
while (inFS.good()) {
    getline(inFS, rm_in, ',');
    getline(inFS, medv_in, '\n');
    rm.at(numObservations) = stof(rm_in);
    medv.at(numObservations) = stof(medv_in);
    numObservations++;
}
rm.resize(numObservations);
medv.resize(numObservations);
cout << "new length " << rm.size() << endl;</pre>
cout << "Closing file Boston.csv." << endl;</pre>
inFS.close(); // Done with file, so close it
cout << "Number of records: " << numObservations << endl;</pre>
cout << "\nStats for rm" << endl;</pre>
print_stats(rm);
cout << "\nStats for medv" << endl;</pre>
print_stats(medv);
cout << "\n Covariance = " << covar(rm, medv) << endl;</pre>
cout << "\n Correlation = " << cor(rm, medv) << endl;</pre>
cout << "\nProgram terminated.";</pre>
 return 0;
```

Caution: All course work is run through plagiarism detection software comparing students' work as well as work from previous semesters and other sources.