




EIE4512 - Digital Image Processing

Tutorial

Qin Wang

qinwang@cuhk.edu.cn

School of Science and Engineering
The Chinese University of Hong Kong, Shen Zhen



February 27, 2019



Agenda

Corrupt an image with noise

Spatial noise filter

Adaptive spatial filter



Corrupt an image with noise

- ▶ Degradation Function

$$g(x, y) = H[f(x, y)] + \eta(x, y)$$

- ▶ Function Definition

```
g = imnoise(f, type, parameters)
```

- ▶ Adding Gaussian noise of mean m, variance var

```
g = imnoise(f, 'gaussian', m, var)
```

- ▶ Adding Gaussian noise with zero-mean, local variance V

```
g = imnoise(f, 'localvar', V)
```

- ▶ Corrupting Image with salt and pepper noise with density d

```
g = imnoise(f, 'salt & pepper', d)
```

Spatial noise filter

- Spatial filtering on image G using a TYPE filter of size M by N.

`F = SPFILT(G, TYPE, M, N, PARAMETER)`

- Ex:following

<code>F = SPFILT(G, 'amean', M, N)</code>	Arithmetic mean filtering.
<code>F = SPFILT(G, 'gmean', M, N)</code>	Geometric mean filtering.
<code>F = SPFILT(G, 'hmean', M, N)</code>	Harmonic mean filtering.
<code>F = SPFILT(G, 'chmean', M, N, Q)</code>	Contraharmonic mean filtering of order Q. The default is Q = 1.5.
<code>F = SPFILT(G, 'median', M, N)</code>	Median filtering.
<code>F = SPFILT(G, 'max', M, N)</code>	Max filtering.
<code>F = SPFILT(G, 'min', M, N)</code>	Min filtering.



Adaptive Spatial Filter

- ▶ An M-function implements Adaptive Spatial Filter, g is the input image, S_{\max} is the maximum size of the adaptive filter window.

`f = adpmedian(g, Smax)`