

# XML INJECTION MUTATION FOR WEB SERVICES VULNERABILITY TESTING BASED ON SOAP MESSAGES

Bimal Varghese  
Simi Stephen

Federal Institute of Science and Technology  
Mookkannoor  
Angamaly

18 May 2015

# Outline

## 1 INTRODUCTION

- Web Service
- Vulnerability Testing of Web Service

## 2 LITERATURE SURVEY

- METHODS COMPARISON

## 3 METHODOLOGY

- SOAP message mutation
- Mutation Operators
- Workload Generation
- Attackload Generation

## 4 EXPERIMENTAL RESULTS

## 5 CONCLUSION

# INTRODUCTION

# Web Service

- Common way of implementing SOA.
- Widely used in the Internet.
- Good Encapsulation and Strong Integration capabilities making it more useful.
- Architecture of Web Service may cause security vulnerabilities.
  - Quality and Reliability of Web Service must be heavily tested.

# Vulnerability Testing of Web Service

## ■ Components in WS.

- WSDL.
- SOAP.
- XML.
- UDDI.

# Vulnerability Testing of Web Service

- Components in WS.
  - WSDL.
  - SOAP.
  - XML.
  - UDDI.
- Vulnerability refers to flaws in the service that threaten the security of the Application/computer system.
- Traditional Software testing methods may not work with Webs Services.
  - Heterogeneous nature.
  - Lack of User Interface (UI).

# Difficulties in Testing Web Service

## Factors that contributing to the difficulty of Web Service Testing

- 1 Different development and application environments.
- 2 The characteristics of Web service distribution, discovery, and dynamic bindings.
- 3 The need for a service interface for Web service design and implementation when applying automatic testing methods and techniques

## Shortcomings in Web Service Testing

- The need for significant human intervention in the process.
- Simple performance and access testing have been performed.
- Extensible Markup Language (XML) in web service considered only for data transmission and not of data storage



# Literature Survey

# [1] Automated Robustness Testing of Web Service

Presents a framework for automatically generating and execution of web service.

## Method

### 1 Code Generator

- 1 Generate necessary code to implement a service consumer

### 2 Test Generation

- 1 Generated test class is supplied to a test generation tool such as JCrasher inorder to generate JUnit test.

### 3 Test Execution

- Invoke test case and call web service. Collect response from web service.

## [2] Exploring Perturbation Based Testing for Web Service

- Extended approach based on XML message perturbation
- Utilized SOAP Perturbation operators and a Web service Testing tool ( SMAT-WS )

### SOAP Perturbation Operator

SOAP perturbation primitive operators include.

- 1 *Null (n)*
- 2 *Incomplete (n)*
- 3 *Inversion (n)*
- 4 *ValueInversion (n)*
- 5 *Mod\_Len (n)*
- 6 *Space (n)*

## [3] Efficient Web Services Message Exchange by SOAP Bundling Framework

- A SOAP message bundling framework is Proposed.
- Framework enables bundling of multiple messages into one message.
- Application developers do not have to consider the service granularity for performance reasons.

## [4] Generating Test Cases for Web Services Using Data Perturbation

- Existing XML messages are modified based on rules defined on the message grammars, and then used as tests.
- Data perturbation uses 2 methods to test Web services :
  - Data value perturbation :**  
modifies values according to the data type.
  - Interaction perturbation .:**  
classifies the communication messages into two categories : RPC communication and data communication

## [5] Adaptive Random Testing : the ART of Test Case Diversity

### Base Idea

- Many program faults result in failures at contiguous areas of the input domain - failure patterns.
- For detecting failure patterns, ART systematically filters randomly generated candidates.

## Contd...

### Adaptive Random Testing

#### Principle

- Given a set of previously executed test cases that have not revealed any failures, new test cases located away from these old ones are more likely to reveal failures.

#### Types of ART methods

- Fixed Size Candidate Set ART (FSCS-ART) :  
Candidate with largest distance from current Test case is considered next.
- Restricted Random Testing (RRT) :  
Create Exclusion zone for current test case.  
Take random selection if it lie outside the zone.

## [6] Testing Web Services by XML Perturbation

- Web services uses XML to describe and transmit data.
- XML schema is utilized to generate data formats and test cases.
- Some applications and web services do not validate XML messages against an XML schema, and sometimes no schema exists.



## Contd...

## XML Data Model

- An XML schema can be modeled as a tree.

XML tree  $T = (N, D, X, E, n_r)$ , where :

- $N$  is a finite set of elements and attribute nodes.
- $D$  is a finite set of built-in and derived data types.
- $X$  is a finite set of constraints (integrity and representation).
- $E$  is a finite set of edges.
- $n_r$  is the root node.

## [7] Combinatorial Mutation Approach to Web Service Vulnerability Testing

Combinatorial mutation testing focuses on using combinations of at least two faulty input data parameter to find faults within the software.

- A set of operators that can be combined are presented
- SOAP message is obtained by parsing the WSDL file, and data perturbation techniques are adopted to generate simple initial test data.
- A combinatorial testing method is developed.

## Contd...

## Mutation Operator Design

Two perturbation policies which directly act on the SOAP message are used

- Data Value perturbation :  
modifies values in SOAP messages according to their data types
- Interaction perturbation :  
consider the data values and data relationships

## [8] Worst-Input Mutation Approach to Web Services Vulnerability Testing Based on SOAP Messages

Proposed Worst Input Mutation approach based on SOAP message mutation.

### Method

- Worst Input Mutation :  
Utilizing characteristics of SOAP message.
- Automatic Test Case Generation :  
Test Case Generation based on Farthest Neighbor (TCFN) algorithm
- A prototype Web Service Vulnerability Testing Tool is implemented

TABLE: Comparison of various Testing Approaches

SI.No	Paper	Approach	Technology
1	Automated Robustness Testing of Web Service	Automatic code generator and testing framework	Existing java Technology
2	Exploring Perturbation Based Testing for Web Service	XML message perturbation	SOAP Perturbation operators
3	Efficient Web Services Message Exchange by SOAP Bundling Framework	Multiple message bundling	SOAP message bundling framework
4	Generating Test Cases for Web Services Using Data Perturbation	Data perturbation	RPC and Data communication
5	Adaptive Random Testing : the ART of Test Case Diversity	Fixed Size Candidate Set ART (FSCS-ART) Restricted Random Testing (RRT)	Random candidate generation
6	Testing Web Services by XML Perturbation	XML schema perturbation	XML Tree Data Model
7	Combinatorial Mutation Approach to Web Service Vulnerability Testing	Combinations of at least two faulty input data parameter to find faults	SOAP message mutation
8	Worst-Input Mutation Approach to Web Services Vulnerability Testing Based on SOAP Messages	Farthest Neighbor Approach	SOAP message mutation

# METHODOLOGY

## Current Scenario

- Test case generation :- An effective way of testing the credibility of Softwares.
- Web Service components depend mainly on XML.
- Both WSDL & SOAP component of Web service depend on XML.
- Efficient Test cases for Web Service depends on XML.
- Efficient mutation of XML will be an effective Test case.

# SOAP message mutation

- Existing SOAP message mutation drawbacks are.
  - Redundancy of data in the SOAP message.
  - Low efficiency of the mutation operators.
  - One mutant injected at one time



# Mutation Operators

- Based on SOAP messages.
- XML model for SOAP message can be considered as an Extended Regular Tree Grammar.
- eRTG (extended RTG) contains 6 tuples  $\langle E; N; DT; P; A; n_s \rangle$ 
  - E is a finite set of elements ;
  - N is a finite set of non-terminals
  - DT is a finite set of data types int, string, bool, numerical, char, object
  - P is a finite set of production rules
  - $n_s$  is the starting non-terminal
  - A is a 2-tuple  $\langle n; type \rangle$  n - number of parameters and “type” - parameter type.

## Cont ...

Given a set of all element instances  $N$

- Mutation operator  $r = f(n_1, n_2, \dots, n_i)$ .
  - $f$  - a function.
  - $(n_1, n_2, \dots, n_i) \in N$  for  $i \geq 1$  with arbitrary data type.
  - $r$  outputs mutated  $(n_1, n_2, \dots, n_i)$  with the same data type as the input  $(n_1, n_2, \dots, n_i)$

## Security rule for testing the vulnerability of Web services.

- $VWS = G(r)$ , where  $r = f(n_1, n_2, \dots, n_i)$  is the mutation operator for the tested Web service
- $G(r)$  the vulnerability that is triggered by  $r$
- $n_i \in N$  the Web service input parameters.




FIGURE: Steps to generate combinatorial data to Web service vulnerability testing

# Workload Generation

- Specific workload for each service need to be generated.
- Workload is generated based on the following steps :
  - 1 Generate test values for each input parameter
  - 2 Generate test calls for each operations
  - 3 Execute call for each operation

# Attackload Generation

- Based on number and type of SOAP message parameters, input domain is partitioned.
- Corresponding test case is then selected.

XML Injection Attack
<i>count(/child :: node())</i>
<i>x'orname() = ' username' or ' x' = ' y</i>
<i>&lt; name &gt;',')) ; phpinfo(); exit; /* &lt; /name &gt;</i>
<i>&lt;![CDATA[&lt; script &gt; varn = 0; while(true)n ++; &lt; /script &gt;]] &gt;</i>
<i>*/*</i>

FIGURE: Examples of XML Injection Attack Loads

## Specific Combinatorial Methods are

- *Data Value Perturbation* : intended to check the integrity of data validity of the system.
  - The combinatorial test data are generated by calling minimum K factors (K=2) of PS
- *Interaction Perturbation* : To check the integrity of the various interaction mechanism such as data retrieval and communications between the system.
  - Based on the faults generally occurring among the parameters of the adjacent locality principle,  $k = \lceil (i + j)/2 \rceil$

# EXPERIMENTAL RESULTS

## Experimental implementation

Web service vulnerability testing system (WSVTS) is implemented in C#




FIGURE: The WSVTS framework.



Four main function modules

- 1 SOAP message generator
- 2 SOAP message mutation generator
- 3 Test case generator
- 4 Vulnerability analyzer





FIGURE: Flow chart of the Web Service vulnerability testing system









FIGURE: Combinatorial Test cases for XML injection 2

## Comparison with other system



**FIGURE:** Comparison of the overall efficiency of SOAPUI, WSVTS, SMAT-WS.

# CONCLUSION

- Due to specific nature of Web services, traditional software testing techniques cannot be completely adopted to test Web services.
- Test data generation is an important content of testing Web service
- By designing appropriate SOAP message mutation operators, the security of Web services can be tested from the client side
- Vulnerability and faults can be identified from the user's perspective.



# REFERENCES

- [1] K. Yue, X.L. Wang, A.Y. Zhou, "Underlying Techniques for Web Services : A Survey", Journal of Software, Vol. 15, No. 3, 2004, pp.428-442.
- [2] T. Takase and K. Tajima, "Efficient web service message exchange by SOAP bounding framework," in the 11th IEEE International Enterprise Distributed Object Computing, Annapolis, MD, USA, 2007, pp. 63-72.
- [3] L. Wu, X. K. Li, and H. Wang, "Research on the reliability testing of web service based on fault injection technology," Journal of Chinese Computer System, vol. 28, no. 1, pp. 127-131, 2007.
- [4] Y. Jiang, G.M. Xin, J.H. Shan, et al. "A Method of Automated Test Data Generation for Web Service", Journal of Computer, Vol. 28, No. 4, 2005, pp.568-577.
- [5] C. A. Sun, G. Wang, B. H. Mu, H. Liu, Z. S. Wang, and T. Y. Chen, " A metamorphic relation-based approach to testing web services without oracles," International Journal of Web Services Research, vol. 9, no. 1, pp. 51-73, 2012.
- [6] M.P. Papazoglou, "Web Services Principles and Technology", Pearson Prentice Hall, Holland, 2010, pp. 99-100.
- [7] L. F. de Almeida and S. R. Vergilio, " Exploring perturbation based testing for web services," presented at the IEEE International Conference on Web Services, Chicago, USA,

- [8] L. Novak and A. Zamulin, "A formal model for XML schema," in Proceedings of the 21st International Conference on Data Engineering Workshops, Tokyo, Japan, pp. 1283-1293, 2005.
- [9] S. Bekrar, C. Bekrar, R. Groz, and L. Mounier, "Finding software vulnerabilities by smart fuzzing," in Proceedings of the Fourth IEEE International Conference on Software Testing, Verification and Validation, Berlin, Germany, 2011, pp. 427-430.
- [10] J. Offutt and W. Xu, "Generating test cases for web services using data perturbation," ACM SIGSOFT Software Engineering Notes, vol. 29, no. 5, pp. 1-10, 2004.
- [11] A. C. V. de Melo and P. Silveira, "Improving data perturbation testing techniques for web services", Information Science, vol. 181, no. 3, pp. 600-619, 2011.
- [12] W. Xu, J. Offutt, J. Luo, "Testing Web Services by XML Perturbation", Proc. of the 16th IEEE International Symposium on Software Reliability Engineering (ISSRE'05), IEEE Computer Society, 2005, pp.257-266
- [13] W.T. Tsai, R. Paul Y. Wang, et al, "Extending WSDL to Facilitate Web Services Testing", Proc. of the 7th IEEE International Symposium on High Assurance Systems Engineering (HASE'02), IEEE Computer Society, 2002, pp.171- 172.

- [14] M. Evan, S. Bas, T. Xie, "Automated Testing and Response Analysis of Web Services", 2007 IEEE International Conference on Web Services (ICWS 2007), IEEE Computer Society, 2007, pp.647-654..
- [15] M.S. Harry, S.H. Huan, "WSDLTest-A Tool for Testing Web Services", Proc. of the 8th IEEE International Symposium on Web Site Evolution (WSE'06), IEEE Computer Society, 2006, pp.14-21.
- [16] X.Y. Bai, W.L. Dong, W.T. Tsai, Y. Chen, "WSDL-based Automatic Test Case Generation for Web Services Testing", Proc. of the 2005 IEEE International Workshop on Service-oriented System Engineering (SOSE'05), IEEE Computer Society, 2005, pp.207-212.
- [17] J.F. Chen, Y.S. Lu, X.D. Xiao, "A Fault Injection Model of Component Security Testing", Journal of Computer Research and Development, Vol. 46, No. 7, 2009, pp.1127-1135.
- [18] Tom Henzinger, Ranjit Jhala, Rupak Majumdar, Dirk Beyer, "Blast (berkeley lazy abstraction software verification tool) model checker."  
<<http://embedded.eecs.berkeley.edu/blast/>> (last access May 2010).
- [19] H. Huang, W. Tsai, R. Paul, Y. Chen, "Automated model checking and testing for composite Web services," in : ISORC '05 : Proceedings of the Eighth IEEE International Symposium on Object-Oriented Real-Time Distributed Computing (ISORC'05), IEEE Computer Society, Washington, DC, USA, 2005, pp. 300–307.

- [20] K.Z. Watkins, "Introducing Fault-Based Combinatorial Testing to Web Services", Proc. of the IEEE SoutheastCon 2010 (SoutheastCon), 2010, pp.131-134.
- [21] P. C. Jorgensen., "Software Testing : A Craftsman's Approach", Third Edition, CRC Press, USA, 2011, pp.315-324.
- [22] SoapUI, SmartBear software, [http ://www.soapui.org](http://www.soapui.org), 2012.
- [23] Mikio Aoyama, Sanjiva Weerawarana, Hiroshi Maruyama, Clemens Szyperski, Kevin Sullivan, and Doug Lea. "Web services engineering : Promises and challenges." In Proceedings of the 24th International Conference on Software Engineering, Orlando, Florida, May 2002.
- [24] G. Canfora, M. Di Penta, "Testing services and service-centric systems : challenges and opportunities," IT Professional, 2006, pp. 10–17.
- [25] G. Canfora, M. Di Penta, "Service-oriented architectures testing : a survey," in : Andrea De Lucia, Filomena Ferrucci (Eds.), ISSSE, Lecture Notes in Computer Science, vol. 5413, Springer, 2009, pp. 78–105.

# THANK YOU