

## Assignment Four

# Free Monads

---

Due: 2024-10-6

**Synopsis:** Implementing free monad-based interpreters for a small arithmetic language.

## 1 Introduction

In this assignment you will implement an interpreter for APL, based on free monads. In particular, you will extend what you developed in the exercises with new effects and new ways of interpreting them. Since the handout for the assignment differs from the solution to the exercises, do **not** base the assignment on your own solutions to the exercises. You **must** use the assignment handout. Specifically, you'll be implementing the following:

- Try-catch effects.
- A pure and IO-based interpretation of key-value store effects.
- Interactive missing key recovery.
- A transactional computation effect.

For all tasks you are expected to add appropriate tests to the file `Interp_Tests.hs`. For information on how to test the IO-based effects, please refer to the week 4 exercises.<sup>1</sup> Do not rename any of the definitions already present in the handout and do not change their types unless the assignment text explicitly instructs you to do so.

To make testing easier, we recommend that you **replace the definition of `eval`** in `APL.Eval` with your version of `eval` from your solution to assignment 2. A complete version of `eval` is not needed to fully solve the assignment; all functionality in this assignment can be tested without

---

<sup>1</sup>[github.com/diku-dk/ap-e2024-pub/tree/main/week4#testing-runevalio](https://github.com/diku-dk/ap-e2024-pub/tree/main/week4#testing-runevalio)

using `eval` by constructing appropriate `EvalM` values (directly or by using the interface functions in `APL.Monad`).

## 2 Task: The TryCatchOp Effect

The `TryCatchOp` effect is for exception handling. A `TryCatchOp m1 m2` effect says to interpret `m1`; if it fails (i.e., returns a `Left` value), then interpret `m2`. Otherwise, the result is the result of interpreting `m1`. For example,

```
> runEval $ Free $ TryCatchOp (failure "Oh no!") (pure "Success!")
([], Right "Success!")
> divZero = CstInt 1 'Div' CstInt 0
> runEval $ eval $ TryCatch (CstInt 5) divZero
([], Right $ ValInt 5)
> badEq1 = CstInt 0 'Eq1' CstBool True
> runEvalIO $ eval $ TryCatch badEq1 divZero
Left "Division by zero"
```

To start, extend `EvalOp` with a `TryCatchOp` constructor:

```
-- APL.Monad
data EvalOp a
  = ...
  | TryCatchOp a a
```

and extend `EvalOp`'s `Functor` instance appropriately. Also complete the definition of `catch`.

Lastly, add support for `TryCatchOp` effects to `runEval` ' in `APL.InterpPure` and to `runEvalIO` ' in `APL.InterpIO`; **runEval and runEvalIO do not need to treat TryCatchOp identically; for example, when interpreting TryCatchOp m1 m2 it's permissible for the effects of m1 to be visible in m2 in runEvalIO but not visible in runEval (or vice versa).**

## 3 Task: Key-value Store Effects

In this task, you'll add `KvGetOp` and `KvPutOp` operations for reading and storing values from the key-value store, respectively. For example,

```

> put0 m = KvPutOp (ValInt 0) (ValInt 1) m
> get0 = Free $ KvGetOp (ValInt 0) $ \val -> pure val
> runEval $ Free $ put0 get0
([],Right (ValInt 1))

```

Start by extending the `EvalOp` type with the `KvGetOp` and `KvPutOp` constructors:

```

-- APL.Monad
data EvalOp a
  = ...
  | KvGetOp Val (Val -> a)
  | KvPutOp Val Val a

```

then, extend `EvalOp`'s `Functor` instance appropriately. Next, complete the definitions of `evalKvGet` and `evalKvPut` using `KvGetOp` and `KvPutOp`, respectively.

Finally, extend `runEval` in `APL.InterpPure` to support `KvGetOp` and `KvPutOp` effects as follows:

- On `KvGetOp key k` effects, `runEval` should lookup the key in the state (the function lookup will be useful). If the key is contained in the state with value `val`, continue interpreting on `k val`. Otherwise, fail by returning a `Left` with an appropriate error message.
- On `KvPutOp key val m` effects, `runEval` should insert the association `(key, val)` into the state. If the key already exists in the state, it should be replaced by the new association.

### 3.1 Using a Database File for the Key-Value Store

Rather than storing the key-value store in a pure manner and passing state around as a parameter during interpretation (as you did in `runEval`), in `runEvalIO` we can instead write the key-value to a database file on disk.

To keep things simple, the database will just be a simple text file. We need a way read and write data from the database—the following functions are provided to do so:

```

-- APL.InterpIO
writeDB :: FilePath -> State -> IO ()
readDB  :: FilePath -> IO (Either Error State)

```

Note that `readDB` returns an error in the form of a `Left`-expression when trying to read an invalid database; if this happens, your interpreter should simply propagate the error and return the `Left`-expression.

For simplicity, the database can only store `ValInt` and `ValBool` values; function values are **not** supported. Your implementation is **not** expected to handle storing/reading of `ValFun` values to/from the database.

Your task is to modify `runEvalIO` so that it stores state (i.e., the key-value store) in a database file and to add support for `KvGetOp` and `KvPutOp` effects to `runEvalIO`.

To start, add support for state effects to `runEvalIO` so that it stores state in the database file:

- On `StatePutOp s k` effects, `runEvalIO` should write the state `s` to the file `db`, where `db` is the `FilePath` parameter to `runEvalIO`. If the file already exists, you should simply overwrite it. (Don't check if the file exists nor try to read from it—just write the state to the file; if the file already exists, it will be overwritten). Use `writeDB` to write the state to the database file.
- On `StateGetOp k` effects, `runEvalIO` should read the database in from `db` (using `readDB`) and then pass it to the `k` function. (An empty database file is created when the interpreter runs, so the database file will always exist.)

Finally, extend `runEvalIO` to support `KvGetOp` and `KvPutOp` effects as follows:

- On `KvGetOp key k` effects, `runEvalIO` should read the database in from `db` and then lookup the key in the database. As with `runEval`, return `Left` if the key doesn't exist in the database. Otherwise, pass the associated value to `k` and continue.
- On `KvPutOp key val m` effects, `runEvalIO` should read the database in from the `db` file to get a value of type `State`; let's call this value `dbState`. It should then insert the association `(key, val)` into `dbState` to construct a new state `dbState'`. As with `runEval`, if the key `key` already exists, the corresponding association should be

replaced by the new one. Finally, overwrite the db database file with dbState' by using writeDB.<sup>2</sup>

For your testing, remember that the database only supports ValInt and ValBool values; you do **not** need to add tests for storing/reading ValFun values. Also note that runEvalIO clears the database on each execution, so database values will **not** persist between invocations of runEvalIO.

### 3.2 Missing keys

Having a database is great and all, but our computations still fail if we look for a key that isn't in the database. Since runEvalIO already uses IO, instead of failing, we can interactively prompt the user to specify the value of a missing key during interpretation.

Here's an example of how this should work:

```
> runEvalIO $ eval $ KvGet $ CstInt 0
Invalid key: ValInt 0. Enter a replacement: ValInt 5
Right (ValInt 5)
> runEvalIO $ evalKvGet $ ValInt 0
Invalid key: ValInt 0. Enter a replacement: ValBool True
Right (ValBool True)
```

Add support for this functionality to runEvalIO'. To do so, you'll need to modify how runEvalIO' interprets KvGetOp key k effects. When the key key doesn't exist in the database file, your implementation must print a message to the terminal saying that the given key is invalid and then prompt the user for a replacement. The entered replacement should either be a ValInt or a ValBool. All other inputs (notably, ValFun values) are **not** supported. To convert the input string into a Val, use the provided readVal :: String -> Maybe Val function in APL.InterpIO. When the input is invalid (i.e., not of the form specified above), readVal will return Nothing; in this case, your interpreter should fail with an appropriate message:

---

<sup>2</sup>This isn't a particularly efficient way to insert a key-value pair—we do it this way for simplicity.

```
> runEvalIO $ eval $ KvGet $ CstInt 0
Invalid key: ValInt 0. Enter a replacement: lol
Left "Invalid value input: lol"
```

**Hint:** You can use the prompt `:: String -> IO String` function defined in `APL.InterpIO` to get input from the user.

**Hint 2:** To test your missing key handling, you can use `captureIO` to simulate input like so:

```
-- APL.Interp_Tests
testCase "Missing key test" $ do
  (_, res) <-
    captureIO ["ValInt 1"] $
      runEvalIO $
        Free $ KvGetOp (ValInt 0) $ \val -> pure val
  res @?= Right (ValInt 1),
```

## 4 Task: TransactionOp effect

Another thing we might want for our database is to have *transactional* or *atomic* writes to it. First, add the `TransactionOp` effect to the `EvalOp` type:

```
-- APL.Monad
data EvalOp a
  = ...
  | TransactionOp (EvalM ()) a
```

Notice that it has an `EvalM()` payload—when this payload is interpreted, any effects that **change the state (i.e., the key-value store)** should be all-or-nothing: that is, they should only be manifested if the computation succeeds (i.e, it returns result `Right ()`). If the computation fails (returns `Left e`), then the **state (i.e., the key-value store)** should be rolled back to the point it was at before the payload was executed. For example,

```
> goodPut = evalKvPut (ValInt 0) (ValInt 1)
> badPut  = evalKvPut (ValInt 0) (ValBool False) >> failure "die"
> get0    = KvGet (CstInt 0)
> runEval $ transaction goodPut >> eval get0
([],Right (ValInt 1))
```

```
> runEval $ transaction badPut >> eval get0
([],Left "Invalid key: ValInt 0")
```

Note that even if the enclosed computation fails, the error should not be propagated. For example,

```
> runEval $ transaction badPut
([],Right ())
```

Extend the Functor instance of EvalOp to support TransactionOp and, using TransactionOp, complete the definition of the transaction function.

As usual, extend runEval' with support for TransactionOp effects. To do so, you should only keep changes to the **state (i.e., the key-value store)** from executing the enclosed EvalM () computation if it succeeds; otherwise continue execution with the prior state. You **must** include the result from any PrintOp effects that occurred before the failure (in the transactional computation) in the final output, regardless of whether or not the transactional computation succeeded:

```
> runEval $ transaction (evalPrint "weee" >> failure "oh shit")
(["weee"],Right ())
```

You must also correctly handle **nested transactions**. For example,

```
> runEval $ transaction (goodPut >> transaction badPut) >> eval get0
([],Right (ValInt 1))
> runEval $ transaction (transaction badPut) >> eval get0
([],Left "Invalid key: ValInt 0")
```

Next, add support for TransactionOp to runEvalIO'. You should only manifest writes to the database if the whole transactional computation succeeds. To do this, before execution of the transactional computation, make a temporary copy of the database file. To make temporary databases, use the withTempDB function, which creates a fresh temporary database, passes it to a function returning an IO-computation, executes the computation, deletes the temporary database, and finally returns the result of the computation:

```

-- APL.InterpIO
withTempDB :: (FilePath -> IO a) -> IO a
withTempDB m = do
    tempDB <- newTempDB -- Create a new temp database file.
    res <- m tempDB      -- Run the computation with the new file.
    removeFile tempDB    -- Delete the temp database file.
    pure res             -- Return the result of the computation.

```

Note that `newTempDB` ensures that the database `tempDB` is fresh; i.e. that there are no other files named `tempDB`. You **must** use `withTempDB` to create temporary databases; **do not** use `newTempDB`. To copy a database, use the `copyDB` function:

```

-- APL.InterpIO
copyDB :: FilePath -> FilePath -> IO ()

```

During execution of the transactional computation, perform all writes and reads on the temporary database file. If the computation succeeds, subsequently copy the temporary database to the actual database and continue interpreting. If it fails, simply continue interpreting. As before, you must also correctly handle nested transactions. **Hint:** The function you pass `withTempDB` should call `copyDB` to copy the database to the temporary database. If the transactional computation succeeds, you will have to call `copyDB` again to copy the temporary database back.

## 5 Code handout

The code handout consists of the following nontrivial files.

- `a4.cabal`: Cabal build file. **Do not modify this file.**
- `runtests.hs`: Test runner. **Do not modify this file.**
- `src/APL/AST.hs`: AST definition. **Do not modify this file.**
- `src/APL/Eval.hs`: An incomplete evaluator corresponding to the solution to the week 2 exercises. You should **replace the definition of `eval`** with your complete version of `eval` from your solution to assignment 2.



- `src/APL/InterpIO.hs`: Contains the incomplete IO-based `runEvalIO` interpreter.
- `src/APL/InterpPure.hs`: Contains the incomplete pure `runEval` interpreter.
- `src/APL/Interp_Tests.hs`: An interpreter test suite where you will add plentiful tests.
- `src/APL/Monad.hs`: Contains all things related to the evaluation monad. Note that some definitions from assignment 2 have moved from `APL.Eval` to `APL.Monad` in this assignment; e.g. `Val` and definitions related to the environment.
- `src/APL/Util.hs`: Utility functions needed for serialization, testing IO, and making temporary database files. You can safely ignore this file. **Do not modify this file.**

## 6 Your Report

You are expected to comment on the *interesting* details of your implementation. You are *not* expected to give a line-by-line walkthrough of your code. Most importantly, you are expected to reflect on the *quality* of your code:

- Do you think it is functionally correct? Why or why not?
- Is there some improvement you'd have liked to make, but didn't have the time?

It is more important to be aware of the strengths or shortcomings of your solution, than it is to have a complete solution.

### 6.1 The structure of your report

Your report must be structured exactly as follows:

**Introduction:** Briefly mention very general concerns, your own estimation of the quality of your solution, and possibly how to run your tests.

**A section for each task:** Mention whether your solution is functional, which cases it fails for, and what you think might be wrong.

**A section answering the following numbered questions:**

1. Consider interpreting a `TryCatchOp m1 m2` effect where `m1` fails after performing some key-value store effects.
  - (a) Is there a difference between your pure interpreter and your IO-based interpreter in terms of whether the key-value store effects that `m1` performed before it failed are visible when interpreting `m2`? If so, why?
  - (b) Suppose you've implemented your interpreters such that the key-value store effects that `m1` performed before it failed are always **visible** when interpreting `m2`. **Without changing the interpreters**, is it possible to have different behavior where the key-value store effects in `m1` are **invisible** in `m2`? If so, how? If not, why not?
2. Why does the computation payload in the  
`TransactionOp (EvalM ()) a`  
constructor return a `()` value? Do any other return types make sense? Justify your answer.

All else being equal, **a short report is a good report.**

## 7 Deliverables for This Assignment

You must submit the following items:

- A single PDF file, A4 size, no more than 5 pages, describing each item from report section above.
- A single zip/tar.gz file with all code relevant to the implementation, including at least all the files from the handout. For this assignment it is not necessary to add additional files.

Remember to follow the general assignment rules listed on the course homepage.

## **8 Assessment**

You will get written qualitative feedback, and points from zero to four. There are no resubmissions, so please hand in what you managed to develop, even if you have not solved the assignment completely.