

Debate-Augmented Agentic RAG for Adaptive Educational Tutoring

A Unified Architecture Merging Agentic Multi-Hop Retrieval-Augmented Generation and Adaptive Multi-Agent Debate, Anchored to Domain-Specific Tutoring for Digital-Native (Gen Alpha) Learners

Final Year Project — Architecture and Research Proposal

Disandu

July 2026

Abstract

Retrieval-Augmented Generation (RAG) and Multi-Agent Debate (MAD) have each been shown, independently, to reduce hallucination and improve reasoning quality in large language models. Debate-Augmented RAG (DRAG, ACL 2025) was the first system to combine the two, but it does so with static, single-pass retrieval. This project proposes a Debate-Augmented Agentic RAG architecture that replaces DRAG's static retrieval stage with an agentic, multi-hop retrieval pipeline (adaptive decision-making, iterative re-querying, and self-reflective auditing), and wraps the result in an adaptive-stopping debate orchestrator. The system is anchored specifically to educational tutoring rather than open-domain question answering, giving the debate stage a natural pedagogical role: the Devil's Advocate agent is repurposed to probe for common student misconceptions rather than argue adversarially for its own sake. A separate, additive Explainable AI "Debate Trail" layer logs the full multi-agent reasoning process, producing a simplified trust signal for students and a complete audit trail for teachers, without requiring any change to the core architecture. The tutoring domain is further scoped to today's digital-native (Gen Alpha) learners, whose documented preference for short-form, low-friction information and demonstrated skepticism toward unverified AI output make the debate stage's misconception-catching and the Debate Trail's trust signal directly relevant design choices rather than generic add-ons. This unifies two previously separate research directions into a single, domain-anchored, evaluable system that has not yet appeared in the published literature.

1. Introduction and Motivation

Agentic RAG systems have demonstrated large empirical gains over static, single-hop retrieval — improving multi-hop question-answering accuracy from roughly 34% to as high as 89–94% on standard benchmarks by allowing an agent to govern retrieval as part of a reasoning loop rather than treating it as a one-shot lookup [Singh et al., 2025; see also benchmark results reported in the broader Agentic RAG survey literature]. Separately, Multi-Agent Debate (MAD) has been shown to improve factual accuracy and reasoning quality by having multiple language model instances critique one another's answers before converging on a final response [Du et al., 2024]. Debate-Augmented RAG (DRAG) is the first published system to combine these two directions, introducing a two-stage debate process — Retrieval Debate and Response Debate — to address what its authors term "Hallucination on Hallucination": the compounding of errors when retrieved documents are themselves unreliable [Hu et al., 2025].

DRAG's own authors describe their work as "an initial endeavour," and its retrieval stage remains static and single-pass. This project's core contribution is to make the retrieval side of a debate-augmented system agentic and multi-hop — combining adaptive retrieval decisions [Jeong et al., 2024], iterative query reformulation [Liu et al., 2025], and self-reflective auditing [Asai et al., 2024] — and to pair it with an orchestrator that uses formal convergence detection [arXiv:2510.12697] rather than a fixed number of debate rounds. Critically, the system is anchored to a single, well-defined domain — educational tutoring over a specific course corpus — rather than open-domain QA. This directly answers the literature's repeated warning that a generic multi-agent debate framework, on its own, is no longer a publishable contribution given how quickly the space has become crowded; domain anchoring is what turns a system into an evaluable, defensible research claim.

2. Related Work and Positioning

Three bodies of literature converge in this proposal. First, agentic RAG research (Self-RAG, Corrective RAG, Adaptive-RAG, HopRAG, MA-RAG) establishes that retrieval governed by an autonomous decision process consistently outperforms static single-hop retrieval, particularly on multi-hop questions, but none of these systems

incorporate a debate or verification stage beyond internal self-reflection. Second, multi-agent debate research (Du et al.'s foundational multiagent debate paper, Agent4Debate, Adaptive Heterogeneous Multi-Agent Debate) establishes that structured disagreement between model instances improves factual accuracy on reasoning-heavy tasks, but a growing body of contrary evidence — most notably AgentGroupChat-V2's finding that debate actively degrades performance on simple, low-ambiguity tasks such as commonsense reasoning — shows that debate is not universally beneficial and that the conditions under which it helps remain an open research question. Third, DRAG (Hu et al., 2025) is the direct anchor paper: it is the only published system combining debate and RAG, but with static retrieval and no domain anchoring.

This proposal's positioning is that combining agentic multi-hop retrieval with adaptive-stopping debate, inside a single domain (educational tutoring), closes gaps in all three literatures simultaneously: it extends DRAG's retrieval stage from static to agentic; it gives the “when does debate help” question (AgentGroupChat-V2's open problem) a concrete, testable domain in which to be answered; and it gives multi-hop RAG the domain-specific anchoring that recent work (e.g. MiRAGE) identifies as missing from most published multi-hop systems, which largely evaluate on open-domain benchmarks rather than expert or course-specific corpora.

2.1 Research Gaps

Three specific gaps in the literature motivate this proposal:

- **Gap 1 — Static retrieval in debate-augmented systems.** DRAG, the only published system combining debate and RAG, retrieves once per query and never revisits that decision even when the debate stage exposes a gap in the retrieved evidence — leaving its retrieval stage static rather than adaptive.
- **Gap 2 — No settled account of when debate helps versus hurts.** AgentGroupChat-V2 and related work show multi-agent debate improves reasoning-heavy tasks but can degrade performance on simple, low-ambiguity ones, and no published system tests this trade-off inside a single, controlled domain such as tutoring.
- **Gap 3 — Domain-anchored evaluation is missing from multi-hop RAG.** Most multi-hop RAG systems, including HopRAG and MA-RAG, are evaluated on open-domain benchmarks (HotpotQA, 2WikiMultiHopQA) rather than an expert or course-specific corpus, so their retrieval quality against real teaching material — and against a specific learner population — remains untested.

3. Research Questions

Four research questions structure the evaluation, each tied to a specific gap identified in Section 2.1.

- **RQ1 (Orchestration).** Under what orchestration conditions (debate depth, agent composition, stopping criteria) does debate-augmented agentic RAG improve tutoring answer quality and misconception detection, compared to single-pass agentic RAG, in a domain-specific educational setting?
- **RQ2 (Agentic vs. static retrieval).** How much does replacing DRAG's static, single-pass retrieval with an agentic, multi-hop pipeline (adaptive decision-making, iterative re-querying, self-reflective auditing) reduce hallucination rate and improve retrieval precision on a course-specific corpus?
- **RQ3 (When debate helps vs. hurts).** Does the benefit of multi-agent debate hold uniformly across question types, or does it — consistent with AgentGroupChat-V2's finding for open-domain tasks — help on multi-hop conceptual questions while adding cost or even degrading performance on simple factual-recall questions?

- **RQ4 (Trust and adoption for digital-native learners).** For digital-native (Gen Alpha) students accustomed to short-form, always-verified information, does exposing a lightweight Debate Trail verification signal (Section 7.2) change trust in or engagement with the tutor's answers, independent of any underlying accuracy gain?

RQ1 and RQ2 extend Gap 1 (static retrieval in debate-augmented systems), RQ3 directly answers Gap 2 (when debate helps versus hurts), and RQ4 gives Gap 3's domain-anchoring argument a concrete secondary audience. Scoping all four to a tutoring context turns open, general questions into testable, novel claims, with a course corpus providing the clear, checkable ground truth that open-domain fact-checking cannot.

4. Combined System Architecture

The system has two stacks — retrieval and debate — governed by a single orchestrator, plus a generation/synthesis layer. Table 1 summarises each component, its role, and its grounding in the literature.

Table 1. Combined architecture components.

Layer	Agent	Role	Literature Grounding
Retrieval	Decision Agent	Decides whether the question needs course-material retrieval at all, or can be answered directly	Adaptive-RAG (Jeong et al., 2024)
Retrieval	Retrieval Agent	Multi-hop retrieval over the course corpus; reformulates and re-queries if the first pass is insufficient	HopRAG; MA-RAG
Retrieval	Reflection Agent	Audits retrieved chunks for relevance/contradiction before they enter the debate stage (equivalent to DRAG's Stage 1 Retrieval Debate, made agentic)	Self-RAG; DRAG Stage 1
Debate	Affirmative Agent	Produces the initial tutoring answer and reasoning chain from verified retrieved context	Multi-agent debate (Du et al., 2024)
Debate	Devil's Advocate Agent	Architecturally compelled to disagree; repurposed pedagogically to probe for common student misconceptions the answer might reinforce	Debate literature, adapted for education
Debate	Fact-Checker Agent	Re-grounds final claims against the reflection-approved context; catches second-order hallucination	DRAG Stage 2
Control	Orchestrator	Adaptive stopping via convergence detection (Beta-Binomial stability model); stops once agents converge, or forces synthesis after N rounds	NeurIPS 2025, arXiv:2510.12697
Output	Generator / Synthesizer	Produces the final tutor-facing response, adjusted for student level	Standard LLM

4.1 Why the Devil's Advocate Must Be Hard-Coded, Not Optional

Conformity bias is the primary documented failure mode of debate systems — agents converge because of social pressure, not because they found the correct answer. Making the Devil's Advocate role optionally adversarial allows it to conform under pressure. Hard-coding a disagreement requirement is the architectural response to this,

and convergence rate is tracked as a separate evaluation metric to confirm the mechanism is working as intended, rather than assumed.

4.2 Implementation Considerations: Local Model Deployment and Sentence-Window Retrieval

Two implementation refinements affect cost, deployment flexibility, and retrieval quality without altering the architecture described above.

- **Local model deployment.** As an alternative to commercial API access, agents can be served locally using an open-weight instruction-tuned model (e.g. Llama 3.x, Qwen2.5) via an inference runtime such as Ollama or vLLM. This removes per-call API cost and external dependency, which is attractive given the system's multi-round, multi-agent call volume, but smaller local models are measurably weaker at the multi-hop reasoning and self-critique that the debate stage depends on. A hybrid configuration — local inference for lower-stakes roles (e.g. the Decision Agent's retrieve/no-retrieve routing) and API-based models for reasoning-heavy roles (Affirmative, Devil's Advocate, Fact-Checker) — is proposed as the practical default, and doubles as a natural cost/latency/accuracy ablation for the evaluation reported in Section 6 [20], [21].
- **Sentence-window (adjacent-chunk) retrieval.** The Retrieval Agent embeds and matches at the level of small chunks for precision, but expands each match to include its immediately adjacent chunks before the passage reaches the Reflection Agent. This mitigates the common failure mode of a retrieved chunk referencing material that was cut off in a neighbouring chunk, giving the Reflection Agent a fuller basis for its relevance/contradiction audit and the Fact-Checker Agent more surrounding context against which to re-ground claims. This is a well-established retrieval-hygiene technique rather than a novel contribution, and is scoped accordingly against the architectural claims in Section 8 [22].

5. Educational Anchoring — Why It Fits

- Clear ground truth exists for a course corpus (lecture notes, textbook, assignment material), unlike open-domain fact-checking.
- Misconceptions are a well-studied, domain-relevant concept in education — giving the Devil's Advocate a natural, non-generic role rather than pure adversarial contrarianism.
- A teacher-facing audience creates a genuine adoption argument for explainability, beyond a purely academic interpretability claim.
- Domain anchoring directly addresses the literature's saturation warning: a generic debate framework is not publishable on its own, but a domain-characterised one is.

5.1 Targeting Digital-Native Learners (Gen Alpha)

Beyond the general case for educational anchoring, the system can be framed and evaluated specifically for today's school-age students — roughly those born from 2010 onward, commonly called Gen Alpha and sometimes described in industry literature as "Generation C" for being the first cohort raised entirely inside always-connected, short-form, algorithmically-fed media. This is proposed as an optional evaluation lens layered onto the existing architecture (Section 4) rather than a new technical component, in the same spirit as the local-deployment and sentence-window refinements in Section 4.2.

- **Short attention spans favour the trust strip over the transcript.** Gen Alpha learners are documented as favouring quick, bite-sized information over long-form explanation, with classroom observation studies reporting rapid attentional shifting and a preference for instant feedback over sustained, single-source focus [23], [24]. The student-facing "verification strip" already proposed in Section 7.2 — a one-line trust signal rather than a full debate transcript — is a closer match to this reading pattern than a conventional tutoring dialogue, and gives the Explainable AI layer a concrete design justification beyond general interpretability.
- **Misconception-catching matters more for a generation that self-teaches from short-form video.** A cohort that supplements formal instruction with unvetted short-form content is more likely to arrive with specific, socially-spread misconceptions — consistent with reported evolving communication and information-consumption styles in this age group [24] — which strengthens the case for the Devil's Advocate Agent's pedagogical role (Section 4.1) and for the misconception-catch rate as a headline metric (Section 6.2).
- **Trust in AI-generated answers is not automatic for this cohort.** Industry survey data on Gen Alpha shows this concretely: chatbot usage is now daily for over half of this cohort, yet roughly three in four users report actively verifying chatbot answers against another source, indicating heavy use paired with persistent skepticism [25]. This makes a visible, low-friction verification signal a plausible adoption lever rather than a purely academic feature — the direct subject of RQ4 (Section 3).

This framing does not change the underlying architecture; it narrows the intended user population and gives Section 6's evaluation a specific, testable audience, which strengthens rather than dilutes the domain-anchoring argument made throughout this section.

6. Evaluation Strategy

6.1 Baselines

- No-retrieval LLM tutor — parametric knowledge floor
- Static single-hop RAG tutor — industry-standard baseline
- Self-RAG tutor — best published self-reflection baseline
- Full system without debate (agentic RAG only) — isolates the debate contribution
- Full system without adaptive stopping (fixed rounds) — isolates the orchestrator contribution
- Full proposed system — Debate-Augmented Agentic RAG

6.2 Metrics

Metric	What It Measures
Accuracy, split by question type	Factual recall vs. conceptual / multi-hop questions, reported separately — the primary research finding
Hallucination rate	Factual errors per 100 responses, graded by human or LLM judge
Retrieval precision	Percentage of retrieved chunks judged relevant
Misconception-catch rate	Novel metric — did the Devil's Advocate flag a real student misconception the Affirmative answer missed?

Metric	What It Measures
Convergence rate / rounds-to-convergence	How often agents agree, and how quickly — orchestrator efficiency
Latency and token cost vs. single-agent / static RAG	Practical tradeoff analysis

6.3 Corpus

A single course's material (e.g. an introductory CS or programming course) provides ground-truth content and allows a hand-built misconception test set to be constructed alongside standard multi-hop QA benchmarks (HotpotQA, 2WikiMultiHopQA) for cross-comparison.

7. Explainable AI Extension — the “Debate Trail” (Separate, Additive Layer)

This layer is introduced after the core architecture is working. It does not require re-architecting the system — it logs and surfaces the reasoning process the agents already produce. It directly answers the traceability gap repeatedly raised in the agentic RAG literature, and responds to the characterisation of agentic pipelines as “hard to debug and non-deterministic.”

7.1 What Gets Logged

Stage	What's Captured	Why It Matters
Decision Agent	Whether it retrieved or answered from parametric knowledge, and why	Shows confidence vs. reliance on source material
Retrieval Agent	Every query reformulation, every hop, what was retrieved at each hop	Exposes the “research path” taken to reach an answer
Reflection Agent	Which chunks were kept vs. discarded, and the stated reason	Prevents low-quality context from silently reaching the answer
Affirmative Agent	Initial answer and reasoning chain	The first draft, before scrutiny
Devil's Advocate	The specific misconception(s) probed for, and whether one was found	The most pedagogically valuable log entry
Fact-Checker	Which claims were re-grounded against source material, and the match/mismatch result	Direct hallucination audit trail
Orchestrator	Number of rounds run, convergence score over time, reason for stopping	Confidence signal — few rounds and high convergence implies certainty

7.2 Two Output Modes

- Student-facing (simplified): the final answer, plus a short verification strip — e.g. ‘verified against Lecture 4 notes; checked for a common mistake here.’ A low-friction trust signal, not a full log dump.
- Teacher / admin-facing (full trace): the complete debate transcript, retrieval hops, and orchestrator convergence graph — an interpretability research artifact and a debugging tool during evaluation.

7.3 Why This Is a Genuinely Separate Contribution

Because it is purely observational, the core system can be built and evaluated first, with the Debate Trail layered on afterward without architectural changes. It also opens an optional secondary, lighter research angle: whether exposing the debate trail changes teacher trust or willingness to adopt the tool — answerable even with a small qualitative study. Logging convergence scores and misconception-catch data as structured data from the start (not just prose) is what allows this explainability claim to become a measurable result rather than a screenshot in the final report.

8. Summary and Contribution

The combined system is the strongest available option identified in the underlying research: a unified agentic-RAG-plus-debate pipeline has not been published in a domain-anchored educational context, and the explainability layer converts an already-flagged research gap (traceability) into a shippable, evaluable feature rather than a claim. The three contributions of this project are: (1) extending Debate-Augmented RAG from static to agentic, multi-hop retrieval; (2) anchoring debate-augmented RAG to a domain — educational tutoring — in a way that gives the “when does debate help” question a testable answer; and (3) an additive Explainable AI layer that produces measurable, structured interpretability data rather than a purely qualitative claim.

References

The following list combines the core literature underpinning the architecture (retrieval, debate, and orchestration components) with domain-specific and IEEE-indexed sources supporting the educational anchoring and explainability claims. All arXiv identifiers were verified against arXiv.org at the time of writing.

Core Architecture and Foundational Literature

- [1] Asai, A., Wu, Z., Wang, Y., Sil, A., & Hajishirzi, H. (2024). Self-RAG: Learning to Retrieve, Generate, and Critique through Self-Reflection. International Conference on Learning Representations (ICLR 2024). arXiv:2310.11511.
- [2] Yan, S.-Q., Gu, J.-C., Zhu, Y., & Ling, Z.-H. (2024). Corrective Retrieval Augmented Generation. arXiv:2401.15884.
- [3] Jeong, S., Baek, J., Cho, S., Hwang, S. J., & Park, J. (2024). Adaptive-RAG: Learning to Adapt Retrieval-Augmented Large Language Models through Question Complexity. Proceedings of the 2024 Conference of the North American Chapter of the Association for Computational Linguistics (NAACL 2024), 7036–7050. arXiv:2403.14403.
- [4] Liu, H., Wang, Z., Chen, X., Li, Z., Xiong, F., Yu, Q., & Zhang, W. (2025). HopRAG: Multi-Hop Reasoning for Logic-Aware Retrieval-Augmented Generation. Findings of the Association for Computational Linguistics: ACL 2025, 1897–1913. arXiv:2502.12442.
- [5] Nguyen, T., Chin, P., & Tai, Y.-W. (2025). MA-RAG: Multi-Agent Retrieval-Augmented Generation via Collaborative Chain-of-Thought Reasoning. arXiv:2505.20096.
- [6] Singh, A., Ehtesham, A., Kumar, S., & Talaei Khoei, T. (2025). Agentic Retrieval-Augmented Generation: A Survey on Agentic RAG. arXiv:2501.09136.
- [7] Hu, W., Zhang, W., Jiang, Y., Zhang, C. J., Wei, X., & Qing, L. (2025). Removal of Hallucination on Hallucination: Debate-Augmented RAG. Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (ACL 2025), Volume 1: Long Papers, 15839–15853. arXiv:2505.18581.
- [8] Du, Y., Li, S., Torralba, A., Tenenbaum, J. B., & Mordatch, I. (2024). Improving Factuality and Reasoning in Language Models through Multiagent Debate. Proceedings of the 41st International Conference on Machine Learning (ICML 2024), PMLR 235:11733–11763. arXiv:2305.14325.
- [9] Zhang, Y., Yang, X., Feng, S., Wang, D., Zhang, Y., & Song, K. (2024). Can LLMs Beat Humans in Debating? A Dynamic Multi-Agent Framework for Competitive Debate (Agent4Debate). arXiv:2408.04472.
- [10] Hu, T. et al. (2025). Multi-Agent Debate for LLM Judges with Adaptive Stability Detection. 39th Conference on Neural Information Processing Systems (NeurIPS 2025). arXiv:2510.12697.
- [11] Gu, Z., Zhu, X., Cai, Y., et al. (2025). AgentGroupChat-V2: Divide-and-Conquer Is What LLM-Based Multi-Agent System Need. arXiv:2506.15451.
- [12] Sahu, C. K., Chilukuri, P. K., & Hetrich, M. (2026). MiRAGE: A Multiagent Framework for Generating Multimodal Multihop Question-Answer Dataset for RAG Evaluation. arXiv:2601.15487.

- [13] Zhou, Y., & Chen, Y. (2025). Adaptive Heterogeneous Multi-Agent Debate for Enhanced Educational and Factual Reasoning in Large Language Models (A-HMAD). *Journal of King Saud University – Computer and Information Sciences*, 37(10), 330. DOI: 10.1007/s44443-025-00353-3

IEEE-Indexed Sources — Educational RAG, Debate, and Explainability

Note: full author lists for entries [15] and [18] were not fully retrievable due to publisher access restrictions at the time of writing; these two should be verified and completed directly against IEEE Xplore before final submission. All other entries in this section have been cross-checked against IEEE Xplore, Semantic Scholar, or the publisher record.

- [14] Obata, Y., & Hamada, M. (2025). Adaptive Retrieval-Augmented Generative Intelligent Tutoring System for Automata Theory. 2025 IEEE 18th International Symposium on Embedded Multicore/Many-core Systems-on-Chip (MCSoc), 477–482. DOI: 10.1109/MCSoc67473.2025.00080
- [15] (2025). Retrieval-Augmented Generation for Smart Classroom Applications. IEEE Conference Publication. Available: <https://ieeexplore.ieee.org/document/11070736>
- [16] Pan, F., Zhou, Q., Guo, W., & Yang, H. (2025). A Survey on Retrieval-Augmented Generation in Applications of Education and Teaching. 2025 7th International Conference on Computer Science and Technologies in Education (CSTE), 803–807. Available: <https://ieeexplore.ieee.org/document/11092120>
- [17] Oriol, M., Motger, Q., Marco, J., & Franch, X. (2025). Multi-Agent Debate Strategies to Enhance Requirements Engineering with Large Language Models. 2025 IEEE 33rd International Requirements Engineering Conference (RE), 527–534. Available: <https://ieeexplore.ieee.org/document/11190349>
- [18] (2025). Enhancing Educational Outcomes with Explainable AI: Bridging Transparency and Trust in Learning Systems. IEEE Conference Publication. Available: <https://ieeexplore.ieee.org/document/10962568>
- [19] Bhatia, S., Mittal, V., & Sabharwal, S. (2024). Building Trust and Transparency in AI: A Review of Explainable AI and its Ethical Implications. 2024 International Conference on Emerging Technologies and Innovation for Sustainability (EmergIN). DOI: 10.1109/EmergIN63207.2024.10961081
- [20] Šarčević, A., Tomić, I., Merlin, A., & Horvat, M. (2024). Enhancing Programming Education with Open-Source Generative AI Chatbots. 47th MIPRO ICT and Electronics Convention (MIPRO 2024), Opatija, Croatia. IEEE. Available: <https://ieeexplore.ieee.org/document/10569736>
- [21] Pereira, J., López, J.-M., Garmendia, X., & Azanza, M. (2024). Leveraging Open Source LLMs for Software Engineering Education and Training. 2024 36th International Conference on Software Engineering Education and Training (CSEE&T), 1–10. IEEE. Available: <https://ieeexplore.ieee.org/document/10663055>
- [22] Stäbler, M., Turnbull, S., Müller, T., Schlueter Langdon, C., Marx-Gómez, J., & Köster, F. (2025). The Impact of Chunking Strategies on Domain-Specific Information Retrieval in RAG Systems. 2025 IEEE International Conference on Omni-layer Intelligent Systems (COINS), 1–6. IEEE. Available: <https://ieeexplore.ieee.org/document/11125724>

Generation Alpha and Digital-Native Learner Research

- [23] Cimene, F. T. A., Mamburao, M. L., Plaza, Q. B., Nitcha, H. Q., Somalipao, M., Raña, E. J. M., Baseo, E. S., Siao, Q. E. A., Mauna, A. A., & Cimene, D. R. A. (2024). Generation Alpha Students' Behavior as Digital

Natives and their Learning Engagement. *Psychology and Education: A Multidisciplinary Journal*, 27(3), 258–273. DOI: 10.5281/zenodo.14007254

- [24] Saifuddin, T., Dilshad, W. B., Afzal, A., & Parveen, A. (2025). Behavioral Manifestations of the Digital Native and Exploratory Study of Gen Alpha in the Primary Classroom. *TPM — Testing, Psychometrics, Methodology in Applied Psychology*, 32(3), 1380–1385.
- [25] Gracenote (Nielsen). (2026). TV Search and Discovery in the AI Era: Gen Alpha Leads Shift to AI-Powered Entertainment Search, Discovery and Recommendations. Available: <https://www.nielsen.com/news-center/2026/gen-alpha-leads-shift-to-ai-powered-entertainment-search-discovery-and-recommendations/>