



Plugins

Media Data Provider

Media Data Provider

Media player data transfer between iCUE and HTML widgets: currently playing track information and playback controls.

Overview

- **Module name:** widgetbuilder.mediadataprovider
- **Plugin name:** Media
- **Version:** 1.0

Manifest entry:

```
"required_plugins": [  
  "widgetbuilder.mediadataprovider:Media:1.0"  
]
```

Properties

Property	Type	Description
songName	string	Current song name
artist	string	Current artist name

Methods

getSongName(requestId)

Gets the current song name asynchronously.

Parameter	Type	Description
<code>requestId</code>	<code>int</code>	Request ID for correlation

Response: `string`

`getArtist(requestId)`

Gets the current artist name asynchronously.

Parameter	Type	Description
<code>requestId</code>	<code>int</code>	Request ID for correlation

Response: `string`

`triggerPlayPause()`

Toggles play/pause state.

`triggerNextTrack()`

Skips to the next track.

`triggerPreviousTrack()`

Returns to the previous track.

Signals

`asyncResponse(requestId, value)`

Emitted when an async method completes.

Parameter	Type	Description
<code>requestId</code>	<code>int</code>	Original request ID
<code>value</code>	<code>var</code>	Response value

SimpleMediaApiWrapper

Promise-based wrapper for the Media plugin. Converts the callback-based Qt async API into Promises.

Important: Use Local Wrapper Files

Copy `common/plugins/` from the documentation bundle into your widget folder and include wrappers via local `<script src>` paths.

Do not reference iCUE installation paths (for example `../common/plugins/...`) in third-party widgets.

Initialization

```
const api = new SimpleMediaApiWrapper(window.plugins.Mediadataprovider);
```

Parameter	Type	Default	Description
<code>plugin</code>	<code>object</code>	-	Plugin instance (<code>window.plugins.Mediadataprovider</code>)
<code>timeoutMs</code>	<code>number</code>	<code>5000</code>	Request timeout (ms)

Methods

`getSongName()`

Returns `Promise<string>` with the current song name.

`getArtist()`

Returns `Promise<string>` with the current artist name.

Required local files

```
<script src="common/plugins/IcueWidgetApiWrapper.js"></script>
<script src="common/plugins/SimpleMediaApiWrapper.js"></script>
```

Example

`manifest.json`

```
"required_plugins": [
  "widgetbuilder.mediadataprovider:Media:1.0"
]
```

`index.html`

```
// After including IcueWidgetApiWrapper and SimpleMediaApiWrapper in <head>:
const mediaApi = new SimpleMediaApiWrapper(window.plugins.Mediadataprovider);

async function displayCurrentTrack() {
  const [songName, artist] = await Promise.all([
    mediaApi.getSongName(),
    mediaApi.getArtist(),
  ]);
  console.log(`Now playing: ${songName} by ${artist}`);
}

// Playback controls (synchronous – call directly on the plugin)
window.plugins.Mediadataprovider.triggerPlayPause();
window.plugins.Mediadataprovider.triggerNextTrack();
window.plugins.Mediadataprovider.triggerPreviousTrack();
```