

[References](#)[Controls](#)[color](#)

color

Color picker control.

Attributes

Attribute	Type	Description	Support JS expressions
<code>data-default</code>	<code>string</code>	Initial color (hex)	☒

Output Value

`string` - Hex color value (e.g., `"#FFFFFF"`)

Example

```
<meta name="x-icue-property" content="textColor"
      data-label="tr('Text Color')"
      data-type="color"
      data-default="'#FFFFFF'">
```

Usage in JavaScript

```
console.log(textColor); // "#FFFFFF"
element.style.color = textColor;
```

Complete Widget Example

Manifest:

```
{
  "author": "Corsair Team",
  "id": "com.corsair.colordemo",
  "name": "Color Demo",
  "description": "Color Demo",
  "version": "1.0.0",
  "preview_icon": "icon.png",
  "min_framework_version": "1.0.0",
  "os": [
    {
      "platform": "windows"
    },
    {
      "platform": "mac"
    }
  ],
  "supported_devices": [
    {
      "type": "dashboard_lcd",
      "features": ["sensor-screen"]
    },
    {
      "type": "pump_lcd"
    },
    {
      "type": "keyboard_lcd"
    }
  ]
}
```

HTML:

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <title>'Color Demo'</title>
  <link rel="icon" type="image/svg+xml" href="resources/icon.svg">

  <meta name="x-icue-property" content="textColor"
        data-label="'Text Color'" data-type="color" data-default="'#e94560'">

  <script type="application/json" id="x-icue-groups">
    [{"title": "'Settings'", "properties": ["textColor"]}]
```

```
</script>
</head>
<body style="margin:0;height:100vh;display:flex;align-items:center;justify-
content:center;background:#1a1a2e;font-family:sans-serif;">
  <div id="demo" style="font-size:48px;">Hello</div>
  <script>
    icueEvents = { "onDataUpdated": update, "onICUEInitialized": update };
    function update() { document.getElementById("demo").style.color = textColor;
  }
    if (iCUE_initialized) update();
  </script>
</body>
</html>
```

For the example to work, you also need to add icon.svg