

[References](#)[Controls](#)[combobox](#)

combobox

Dropdown selection control.

Attributes

Attribute	Type	Description	Support JS expressions
<code>data-default</code>	<code>string</code>	Initial selected key	
<code>data-values</code>	<code>string[]</code> <code>object</code> <code>array<{key, value}></code>	Available options	

Output Value

`string` - Selected key value

Example

Simple array format

```
<meta name="x-icue-property" content="fruit"
  data-label="tr('Fruit')"
  data-type="combobox"
  data-default="'apple'"
  data-values="['apple', 'banana', 'orange']">
```

Key-value array format

```
<meta name="x-icue-property" content="position"
      data-label="tr('Position')"
      data-type="combobox"
      data-default="'left'"
      data-values="[{ 'key': 'left', 'value': tr('Left') },
                    { 'key': 'center', 'value': tr('Center') }, { 'key': 'right', 'value': tr('Right') } ]">
```

Usage in JavaScript

```
console.log(fruit);    // "banana"
console.log(position); // "left"
```

Complete Widget Example

Manifest:

```
{
  "author": "Corsair Team",
  "id": "com.corsair.comboboxdemo",
  "name": "Combobox Demo",
  "description": "Combobox Demo",
  "version": "1.0.0",
  "preview_icon": "icon.png",
  "min_framework_version": "1.0.0",
  "os": [
    {
      "platform": "windows"
    },
    {
      "platform": "mac"
    }
  ],
  "supported_devices": [
    {
      "type": "dashboard_lcd",
      "features": ["sensor-screen"]
    },
    {
```

```

    "type": "pump_lcd"
  },
  {
    "type": "keyboard_lcd"
  }
]
}

```

HTML:

```

<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <title>'Combobox Demo'</title>
  <link rel="icon" type="image/svg+xml" href="resources/icon.svg">

  <meta name="x-icue-property" content="fruit"
        data-label="'Fruit'" data-type="combobox"
        data-default="'apple'" data-values="['apple', 'banana', 'orange']">

  <script type="application/json" id="x-icue-groups">
    [{"title": "'Settings'", "properties": ["fruit"]}]]
  </script>
</head>
<body style="margin:0;height:100vh;display:flex;align-items:center;justify-
content:center;background:#1a1a2e;color:#fff;font-family:sans-serif;">
  <div id="demo" style="font-size:48px;">apple</div>
  <script>
    icueEvents = { "onDataUpdated": update, "onICUEInitialized": update };
    function update() { document.getElementById("demo").textContent = fruit; }
    if (icUE_initialized) update();
  </script>
</body>
</html>

```

For the example to work, you also need to add icon.svg