

[References](#)[Controls](#)[slider](#)

slider

Numeric slider control.

Attributes

Attribute	Type	Description	Support JS expressions
<code>data-default</code>	<code>number</code>	Initial value	✓
<code>data-min</code>	<code>number</code>	Minimum value	✓
<code>data-max</code>	<code>number</code>	Maximum value	✓
<code>data-step</code>	<code>number</code>	Step increment	✓
<code>data-unit-label</code>	<code>string</code>	Unit label (e.g., <code>"%"</code>)	✓

Output Value

`number` - Current slider value

Example

```
<meta name="x-icue-property" content="opacity"
      data-label="tr('Opacity')"
      data-type="slider"
      data-default="100"
      data-min="0"
      data-max="100"
      data-step="1"
```

```
data-unit-label="'%'">
```

Usage in JavaScript

```
console.log(opacity); // 75  
element.style.opacity = opacity / 100;
```

Complete Widget Example

Manifest:

```
{  
  "author": "Corsair Team",  
  "id": "com.corsair.sliderdemo",  
  "name": "Slider Demo",  
  "description": "Slider Demo",  
  "version": "1.0.0",  
  "preview_icon": "icon.png",  
  "min_framework_version": "1.0.0",  
  "os": [  
    {  
      "platform": "windows"  
    },  
    {  
      "platform": "mac"  
    }  
  ],  
  "supported_devices": [  
    {  
      "type": "dashboard_lcd",  
      "features": ["sensor-screen"]  
    },  
    {  
      "type": "pump_lcd"  
    },  
    {  
      "type": "keyboard_lcd"  
    }  
  ]  
}
```

HTML:

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <title>'Slider Demo'</title>
  <link rel="icon" type="image/svg+xml" href="resources/icon.svg">

  <meta name="x-icue-property" content="opacity"
        data-label="'Opacity'" data-type="slider"
        data-default="100" data-min="0" data-max="100" data-step="1" data-unit-
label="'%'">

  <script type="application/json" id="x-icue-groups">
    [{"title": "'Settings'", "properties": ["opacity"]}]]
  </script>
</head>
<body style="margin:0;height:100vh;display:flex;align-items:center;justify-
content:center;background:#1a1a2e;color:#fff;font-family:sans-serif;">
  <div id="demo" style="font-size:48px;">100%</div>
  <script>
    icueEvents = { "onDataUpdated": update, "onICUEInitialized": update };
    function update() { document.getElementById("demo").textContent = opacity +
"%"; }
    if (iCUE_initialized) update();
  </script>
</body>
</html>
```

For the example to work, you also need to add icon.svg