



tab-buttons

Tab-style button group for selecting one option.

Attributes

Attribute	Type	Description	Support JS expressions
<code>data-default</code>	<code>string</code>	Initial selected key	
<code>data-values</code>	<code>string[]</code> <code>array<{key, value}></code>	Available options	

Output Value

`string` - Selected key value

Example

```
<meta name="x-icue-property" content="alignment"
      data-label="tr('Alignment')"
      data-type="tab-buttons"
      data-default="'center'"
      data-values="[{ 'key': 'left', 'value': tr('Left') },
                    { 'key': 'center', 'value': tr('Center') }, { 'key': 'right', 'value': tr('Right') } ]">
```

Usage in JavaScript

```
console.log(alignment); // "center"
```

Complete Widget Example

Manifest:

```
{
  "author": "Corsair Team",
  "id": "com.corsair.tabbuttonsdemo",
  "name": "Tab Buttons Demo",
  "description": "Tab Buttons Demo",
  "version": "1.0.0",
  "preview_icon": "icon.png",
  "min_framework_version": "1.0.0",
  "os": [
    {
      "platform": "windows"
    },
    {
      "platform": "mac"
    }
  ],
  "supported_devices": [
    {
      "type": "dashboard_lcd",
      "features": ["sensor-screen"]
    },
    {
      "type": "pump_lcd"
    },
    {
      "type": "keyboard_lcd"
    }
  ]
}
```

HTML:

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
```

```
<title>'Tab Buttons Demo'</title>
<link rel="icon" type="image/svg+xml" href="resources/icon.svg">

<meta name="x-icue-property" content="alignment"
      data-label="'Alignment'" data-type="tab-buttons"
      data-default="'center'"
      data-values="[{ 'key': 'left', 'value': 'Left' },
{ 'key': 'center', 'value': 'Center' }, { 'key': 'right', 'value': 'Right' } ]">

<script type="application/json" id="x-icue-groups">
[{"title": "'Settings'", "properties": ["alignment"]} ]
</script>
</head>
<body style="margin:0;height:100vh;display:flex;align-
items:center;background:#1a1a2e;color:#fff;font-family:sans-serif;">
  <div id="demo" style="width:100%;font-size:48px;">Hello</div>
  <script>
    icueEvents = { "onDataUpdated": update, "onICUEInitialized": update };
    function update() { document.getElementById("demo").style.textAlign =
alignment; }
    if (iCUE_initialized) update();
  </script>
</body>
</html>
```

For the example to work, you also need to add icon.svg