Typed versus pooled festival covariates in foundation and local forecasting models: matched controls, calendar corrections and unstable orderings

Integrated research draft for professor review, version 7. Not submitted or submission-ready. Version 7 adds registered daily adaptations of Ziel's holiday-as-Sunday and replacing designs for the local models (Sections 3–5, Tables A6–A9) and the Singapore metadata-check outcome to version 6; all version 6 tables are unchanged.

Binay Verma. College/department: _____. Corresponding-author email: _____.

Abstract

Sparse events create a familiar trade-off between separate response identities and statistical sharing. Covariate-informed foundation models add sensitivity to channel allocation and encoding. We study this conditional forecasting problem using two pinned foundation models and four local variants, retaining calendar, zero-channel, typed, pooled and weekday-placebo controls. The main analysis uses 528 complete festival-window cases and 216 seasonal ordinary cases from three Indian states and two historical years. A source-driven correction changes one named festival date, restores its complete window and weekday-matched placebo, and separates feature changes from case-composition changes. Closest-method daily calendar encodings, established response comparators and a controlled simulation supplement this analysis. An NYC replication, committed before its evaluation records were acquired, adds two later holiday occurrences from a separate ridership lineage; an England/Wales electricity study examines a different source and an explicit observation-delay sensitivity. Typed-minus-pooled event MASE spans -0.03971 to 0.05564 in the aligned Indian panel and -0.34441 to 0.15136 in NYC. These are complete registered contrast ranges, not selected improvements or sampling intervals. The preferred representation is not stable: within India the typed-minus-pooled sign is opposite between the two event years in 19 of 36 model/representation/lead cells (one more is an exact tie), and opposite between India and NYC in 11 of 36 cells (3 tie), including all 6 TimesFM-3 cells. Registered adaptations of Ziel's holiday-as-Sunday (hSun) and replacing (Rph, RpH) dummy designs lower local-model event MASE relative to calendar in all 12 Indian local model/lead cells for each design, but in NYC hSun raises it in 12 of 12 cells and pooled replacing in 9 of 12. Source revisions, sparse event years, unmatched adaptation policies, model exposure, unresolved Indian reuse terms and absent independent human review limit generalisation. The evidence documents where the ordering holds and where it reverses; it does not introduce a new architecture or establish causal event effects.

Keywords: event representation; pooling; foundation models; calendar provenance; electricity; temporal evaluation.

1. Question, contribution and closest work

When does sharing an event response across sparse named families help, and does that answer survive the model interface, ordinary-day costs and a new source? Pooling, event regressors,

partial pooling and calendar encodings are established ideas. A useful contribution must show conditions and failure modes beyond adding models to a benchmark.

Kreusel et al. [1] directly examine calendar encodings in Chronos-2 and TimesFM-3. Alipour et al. [2] learn impact-driven event representations from residual responses. Indian moving-holiday regression [3], covariate-uncertainty evaluation [4] and sample/proxy leakage analysis [5] are close antecedents. The typed-versus-pooled choice itself is established in load forecasting: Ziel [9] compared one shared holiday dummy, grouped dummies and a separate dummy for each holiday for German load, and reported that many additional per-holiday dummies did not seem to improve on one additional dummy, with univariate results mixed by holiday type; his multivariate comparison nevertheless tests other models against a replacing design with one dummy per holiday (M-RpH) as the best model forecast. Arora and Taylor [10] treat special days with rule-based seasonal ARMA models. What is examined here is how that choice behaves through foundation-model covariate channels under a fixed channel budget with zero and placebo controls. Daily adaptations of Ziel's holiday-as-Sunday and replacing designs are also run for the local models (Sections 3–5). We compare simple representations under logged information and channel contracts rather than claim to invent them. The proposed contribution is a conditional empirical qualification with complete controls, source-driven corrections and separate-source evidence. Whether it is sufficiently distinct and general for International Journal of Forecasting remains an external scientific judgment.

The primary manuscript tables now use the document-aligned, recentered panel. Original forecasts, the original-ledger manuscript, the flag-only correction, failed attempts and negative findings remain available. A calendar repair is justified by its source, regardless of its forecast score. It is not permission to select the better historical version.

2. Data, dates and forecast information

2.1 Indian supplied electricity and named calendars

The target is daily energy met/supplied in GWh for Delhi, Karnataka and Maharashtra. It is not latent unconstrained demand, household consumption or hourly peak load. The later GRID-INDIA/POSOCO compilation is kept separate from an earlier corrected source. Outcomes through 28 October 2026 have been inspected; new historical method choices are exploratory. Historical revisions, exact release availability and correlated pretraining proxies remain unresolved. Weight dates alone do not establish contamination-free evaluation [5–7].

Five families are Holi, Dussehra, Ganesh Chaturthi, Ugadi/Gudi Padwa and Diwali, with declared state scopes and subsidiary anchors. Twelve retained annual documents support an internal all-58 named-date review: 54 declared-family matches, two explicit shared-national-main exceptions, one Karnataka 2025 mismatch and one Maharashtra 2022 Gudi Padwa evidence gap. The last means the retained one-page schedule does not corroborate the name/date; it is not proof that 2 April is wrong. Visible notification dates are not certified first-publication histories, and amendment chains and human sign-off remain incomplete. Office closure does not establish statewide electricity response.

The Karnataka notification labels Vijayadasami on 1 October 2025 and Gandhi Jayanthi on 2 October. The original ledger used 2 October for Dussehra. A separately registered flag-only

correction holds cases and old placebos fixed. A further registered recentering replaces only three old 5 October target/lead cases with 28 September, yielding the complete 28 September–4 October window, and moves the corresponding +35-day placebo from 6 to 5 November. No error selects these dates. Both original-feature and aligned-feature forecasts are compared on the identical corrected cohort. Case-composition changes under original features are reported separately.

The resulting 528 event-window cases are 176 state/target-date combinations at leads 1, 7 and 14 across 24 family/state/year groups in 2024–2025. They cover 75 distinct target dates and 10 family/year clusters; the clusters, not rows, are the effective event units. Nearby days, states and leads are correlated, not independent event replications. The 216 ordinary cases are a bounded seasonal sample: the first eligible rotating weekday per month/state/year, excluding registered windows. This is not exhaustive daily deployment evaluation.

2.2 NYC: a separately registered holiday replication

The canonical MTA daily ridership/traffic dataset, identifier sayj-mze2, provides Subway and Bus reported estimated counts. A fixed query returned 2,780 records and 1,390 complete daily labels per mode, 1 January 2023–21 October 2026. Counts are converted to million estimated rides, not GWh or unique travellers. The two modes are related series in one city and one source lineage; no deprecated-view splice or Staten Island addition is made. Actual API mode type is TEXT, although the attached dictionary says NUMERIC; the discrepancy is retained.

The protocol was committed (e7d9423, 20:23:38 UTC on 30 October 2026) before these new evaluation records were acquired (20:24:51 UTC). The public push time of that commit has not been independently verified. Five calendar families retain the Indian study's five-channel budget. The 84 event cases cover complete ±3-day windows around Yom Kippur on 21 September and Columbus Day on 12 October 2026, two modes and three decision leads. The 42 ordinary cases balance weekdays and exclude all registered September–October NYC DOT observance windows. The calendar PDFs have matching archive digests in pre-year captures. They document parking observances, not MTA service closures or complete amendments. These target dates follow both actual model-weight uploads, but correlated proxy exposure is not ruled out.

A fixed seven-day observation buffer maps decision leads 1/7/14 to actual model steps 8/14/21. The intervening labels are unobserved, unscored bridge dates. This sensitivity accommodates uncertain update timing without pretending to reconstruct first releases. The current source is revised; the study is retrospective despite registration before target acquisition. Two occurrences cannot establish broad new-geography or annual generalisation.

2.3 England/Wales: source and delay, not holiday confirmation

NESO transmission demand supplies an independent electricity lineage. Daily GWh integrate complete actual half-hourly MW averages, including 46/48/50-period clock changes; forecast flags and incomplete days are excluded. Sixteen ordinary targets, 15–30 September 2026, are compared under ideal availability and 21 additional days of observation delay. Decision leads 1/7/14 become actual steps 22/28/35 in the delayed case. The archived estimates can be revised and published in arrears. This is a fixed lag sensitivity, not a first-vintage reconstruction, and it contains no target holiday. It cannot replace the NYC holiday replication.

2.4 Scoring and dependence

Each origin is the first unseen model date. Target date equals origin plus model step minus one. Scales are fixed pre-year 730-calendar-day mean absolute weekly differences, using positive recorded labels; imputed labels are never scored. Indian event summaries average target errors within state/year/family, states within year, years within family, then families equally. NYC uses the analogous related-mode hierarchy. Ordinary samples and NESO have their declared equal-date/series rules. MAE units remain source-specific. MASE levels across datasets are not direct measures of common task difficulty.

We retain both years, every family, all registered pairwise contrasts and leave-family-out composition tables. We do not use daily-row significance tests or precise annual bootstrap claims from two years. New families, widths, penalties or models are not chosen using evaluated errors.

3. Models and representations

Chronos-2 and TimesFM-3 use pinned code/weights, 730 prior target days, fixed seeds, two CPU threads, logged batching and no task fine-tuning. Actual weight bytes and input bytes are checked. Future-target perturbation and solo/batch checks accompany every registered lane; native quantiles and crossings are retained. TimesFM's weight terms include academic noncommercial restrictions. A model release date does not resolve all historical/proxy exposure.

The four local variants are rich Ridge, stable float32 LightGBM, a separately reported minimum-leaf-2 sensitivity, and fixed SARIMAX. Ridge/trees have 27 past-only history features and the same calendar/event covariates; parameters come from pre-evaluation chronological validation with purged future labels and are shared across arms. Monthly local refits differ from frozen foundation inference. Their lag features can draw on observations preceding the 730 labelled training-origin window. Thus total raw-history access and adaptation policies are not identical; model rankings do not identify an architecture-only effect. SARIMAX retains its declared seasonal order, fit/update policy and logged convergence retries. Original and leaf-2 tree budgets are never merged into a chosen winner.

Eight main arms retain 13 ordinary weekday/annual-harmonic channels: calendar, calendar plus five zeros, typed day, pooled day, typed window, pooled window, and typed day/window placebos. Pooled information occupies one channel padded by four zeros; typed information uses five named channels. Windows are ±3-day unions, including subsidiary dates. Fixed seeded weekday shifts avoid the registered true windows, but are bounded active controls, not a randomisation distribution or proof of semantic neutrality. Equal dimensions do not imply equal information, and zero padding is not assumed inert.

Three further local-model arms adapt Ziel's German load designs [9] to daily festival anchors. hSun treats every family anchor day as a Sunday (weekday one-hot replaced by the Sunday one-hot) with no festival indicator, plus five zeros. Rph adds the pooled day flag and sets all seven weekday dummies to zero on flagged days; RpH does the same with the five typed day flags (Ziel's Eq. 11). Each has 18 channels. They were committed with their protocols and analysis code before any of their forecasts existed (local commits a8975c9, 5e1e4dc and add10e1, published later), but on cases whose other arms had already been inspected, so they are

exploratory. The hSun protocol first called that arm the replacing variant; a dated note corrected the label before any of its metrics were computed. The same runs recompute the calendar, typed-day and pooled-day arms: they reproduce the stored forecasts within 1.1e-13 GWh in India and exactly in NYC, and the stored balanced MASE within 1e-12. Foundation-model versions of these designs were not run.

Ten pure daily encodings include history-only, a zero channel, ordinal weekday/H, one-hot weekday/H, cyclic weekday/H and five context-mean target encodings. H means any declared named-family anchor, not every public holiday. The hourly paper's hour feature is omitted. Means use only the 730-day input context, with fixed global-context fallback for absent categories; support and future fallback are logged. The unchanged 13-channel calendar reference is added by exact forecast reuse. Channel and information differences are explicit, so a pure encoding versus calendar contrast is not an isolated coding effect. Document-aligned pure encodings use the same corrected cases and ledger as the main analysis.

Eight direct daily comparators include conditional means and no-response/typed/pooled/fixed-partial residual profiles. The latter use a last-four-recorded-same-weekday baseline, a declared triangular ±3-day shape and fixed penalty 2. They are daily adaptations, not an exact replication of Alipour's residual tensors, learned 16-dimensional contrastive representations or past-occurrence prototypes. The primary paper's incomplete implementation details and the lack of a comparable account-level panel remain reproduction gaps.

A separately registered explanatory diagnostic measures recorded support and past family residual heterogeneity within each exact 730-day pre-origin context. Its baseline uses four preceding recorded same-weekday labels outside all named ±3-day windows, with no residual until four exist. Family residual means are scaled by the fixed pre-year weekly scale; their population RMS dispersion requires at least two supported families. Prior-year and current-year support days are separated, and undefined moderators propagate to their cell without dropping forecast errors. Associations round cell variables to eight decimals to define numerical ties. These are observational proxies, not model-learned or causal effects.

4. Matched Indian evidence

Tables 1–2 display the prespecified next-day comparison; Figure 1 includes all six variants, both representations and all three leads. Every zero/placebo arm remains in the supplement. Original four-year Chronos seven-channel Diwali deterioration is preserved as a different cohort/definition, not erased by later results.

Table 1. Document-aligned, recentered Indian festival windows: lead-1 MASE.

Model	Calendar	Typed day	Pooled day	Typed window	Pooled window
Rich Ridge	0.57699	0.45317	0.46093	0.57914	0.60838
SARIMAX	0.57301	0.42533	0.45345	0.57787	0.57511
Stable LightGBM	0.69865	0.69483	0.66110	0.70168	0.71233

Model	Calendar	Typed day	Pooled day	Typed window	Pooled window
Tree leaf minimum 2	0.68582	0.64952	0.60469	0.69028	0.70001
Chronos-2	0.53767	0.52009	0.51752	0.53720	0.53268
TimesFM-3	0.55148	0.48005	0.42459	0.55540	0.55131

Table 2. The matched Indian seasonal ordinary sample: lead-1 MASE.

Model	Calendar	Typed day	Pooled day	Typed window	Pooled window
Rich Ridge	0.28458	0.27908	0.28363	0.28887	0.28709
SARIMAX	0.23073	0.22949	0.22910	0.22995	0.23155
Stable LightGBM	0.39366	0.39545	0.38932	0.39507	0.39604
Tree leaf minimum 2	0.39178	0.37852	0.36518	0.38876	0.37951
Chronos-2	0.24924	0.26482	0.26567	0.26108	0.26287
TimesFM-3	0.26547	0.26931	0.26685	0.26196	0.25877




Figure 1. Typed minus pooled MASE on the same document-aligned Indian cases. Both signs, all variants and leads are retained.

The full event contrast range is -0.03971 to 0.05564; it describes registered cells rather than a selected gain. Same-case aligned-feature changes at lead 1 range from -0.00119 to 0.00836. Separately, replacing the three date/lead cases under original features changes the aggregate by -0.00251 to 0.00171. These are different estimands; an old/new macro-score difference must not be attributed entirely to corrected festival features.

Table A4 splits the lead-1 contrasts by event year and family. Across all 36 model/representation/lead cells, the 2024 and 2025 contrasts have opposite signs in 19, with 1 further exact tie, and leaving out one family flips the balanced sign in 17. A few orderings persist: SARIMAX day flags at lead 1 favour separate identities in both years and under every leave-one-family-out subset, and TimesFM-3 day flags at lead 1 favour pooling in 9 of 10 family/year clusters. This descriptive split was registered before it was computed, but it uses previously inspected forecasts; the persistent orderings are expectations for future confirmation, not established effects.

Table 3. Matched Indian festival windows: every registered pure encoding and calendar reference, lead-1 MASE.

Encoding	Chronos-2	TimesFM-3
history	0.54769	0.55366
zero1	0.55892	0.55616
ordinal	0.51574	0.42608
onehot	0.51171	0.43188
cyclic	0.51636	0.45004
te_weekday	0.56433	0.55172
te_sunday	0.51563	0.42528
te_holiday	0.52400	0.39840
te_joint	0.53781	0.44470
te_separate	0.52832	0.41227
calendar	0.53767	0.55148

Table 3 gives every registered pure encoding at the same lead, without selecting a recommended encoding. Complete lead-7/14, ordinary-day, sparse-support and all-pair tables accompany it. Learned category means are past-only summaries of this dataset, not newly discovered holidays or learned causal event effects.

Tables A6–A7 give the Ziel adaptations for the four local models. In India each design lowers event MASE relative to calendar in all 12 local model/lead cells. Relative to the additive flags it carries, Rph is lower than pooled day in 11 of 12 cells and RpH lower than typed day in 12 of 12, but the difference keeps its sign in both years and under every leave-one-family-out subset in only 3 and 4 cells. hSun differs from pooled day by less than 0.005 MASE in 8 of 12 cells; the clear exception is Stable LightGBM, whose lead-1 hSun MASE is 0.06832 below pooled day in both years and every leave-one-family-out subset. Replacing rarely reverses the local typed-versus-pooled ordering: RpH minus Rph has the same sign as typed minus pooled day in 11 of 12 cells; the exception is SARIMAX at lead 7, where the additive difference is only 0.000005.

5. Cross-source checks and pooling conditions

Table 4. NYC event windows: decision lead 1, actual model step 8, MASE.

Model	Calendar	Typed day	Pooled day	Typed window	Pooled window
Rich Ridge	0.99718	1.00451	1.16887	1.19074	1.31328
SARIMAX	0.99947	0.79417	1.04067	1.15250	1.40939
Stable LightGBM	0.91940	0.91940	0.91940	0.91940	1.08484
Tree leaf minimum 2	0.84819	0.84610	0.87819	0.88083	1.02851
Chronos-2	0.93276	0.86384	0.76003	0.93928	0.92961
TimesFM-3	0.88394	0.75636	0.79143	0.86121	0.91833




Figure 2. NYC typed minus pooled MASE. Columns are decision leads 1/7/14, corresponding to actual model steps 8/14/21 under the observation buffer.

NYC's complete event contrast range is -0.34441 to 0.15136. Its local checkpoint already supplied a counterexample to universal pooling gains: SARIMAX typed-day event MASE improves on calendar while pooled-day worsens it, whereas pooling helps the ordinary sample. The full table and Figure 2 now retain both foundation models and every registered contrast. The ordinary table is in Appendix A. Two parking-observance occurrences and two related modes support a bounded robustness check, not universal mechanism identification or a pooled cross-country treatment effect. Comparing signs cell by cell, India and NYC agree in 22 of 36 typed-minus-pooled cells, are opposite in 11 and tie in 3 (Stable LightGBM day flags give identical NYC forecasts); TimesFM-3 favours pooling in India and separate identities in NYC in all 6 of its cells. Within NYC, 36 of 144 family/mode/step cells favour pooling, 96 favour separate identities and 12 tie.

Tables A8–A9 repeat the Ziel adaptations on NYC. There hSun raises event MASE relative to calendar in 12 of 12 local model/step cells, Rph in 9 and RpH in 6; Rph is lower than pooled day in 8 of 12 cells, while RpH is higher than typed day in 9. In these ridership series, encoding an observance as a Sunday raised errors, unlike for the Indian festival days. RpH minus Rph has the same sign as typed minus pooled day in 8 of 12 NYC cells, the opposite sign in 1 and ties in 3

(Stable LightGBM gives identical typed and pooled forecasts). Under replacing, India and NYC agree in sign in 8 of 12 local model/lead cells, are opposite in 1 and tie in 3.

Table 5. NESO calendar models at decision lead 1: ideal model step 1 versus lag-21 model step 22, MASE.

Model	Ideal	Lag 21
Rich Ridge	0.48703	0.50152
SARIMAX	0.48080	0.46981
Stable LightGBM	0.53385	0.46448
Tree leaf minimum 2	0.55685	0.47201
Chronos-2	0.53605	0.59170
TimesFM-3	0.45629	0.38886

The NESO comparison keeps ideal and delayed information separate, including all leads and controls. Delay need not monotonically worsen realised error on a small serial sample. It changes the available information and forecast step, not only a calendar label. These ordinary dates supply no additional festival occurrences.

The prespecified simulation has 16 combinations of event frequency, effect heterogeneity, date-error bound and noise, each with 32 seeds: 512 datasets and 2,560 method cells. Five families share a known triangular shape and an exactly removed baseline; noise is stationary AR(1) with coefficient 0.5. No-event, pooled OLS, typed OLS, fixed partial pooling and the unavailable true-effect oracle are all retained. Homogeneous versus heterogeneous effects illustrate the familiar pooling trade-off under that generator. They do not explain foundation-model internals or constitute new real-world replication.




Figure 3. Synthetic pooling conditions. Intervals quantify Monte Carlo precision over generator seeds, not significance over Indian or NYC events.

The past-support diagnostic reuses all 6,336 typed/pooled case contrasts, producing 864 family/state/year/lead cells and 1,728 descriptive association records across all variants, representations, leads, moderators and fixed scopes. Table A3 reports the prespecified next-day day-representation support-ratio and response-heterogeneity Spearman diagnostics; both

years, all leads and leave-family-out results remain in the supplement. We do not pool models as independent observations or infer a mechanism from a correlation. State/family/year composition and earlier responses from the same event episode can confound these associations. Current-year past responses are legitimate available information, not evidence of forecasting a wholly unseen episode.

6. Native uncertainty and reproducibility

Both foundations are compared on unchanged common quantiles 0.1–0.9. Empirical 80% coverage accompanies scaled width, mean marginal pinball and one-interval WIS: (0.5 × median absolute error + 0.1 × 80% interval score)/1.5. Native crossings are retained. Any invalid lower/upper endpoint makes the associated interval aggregate undefined rather than silently dropping cases. Native interval quality and point MASE are different criteria. Means hide dispersion across event clusters: at lead 1, family/year coverage falls below 0.80 in 85 of 100 foundation-model cluster/arm cells (Table A5); for TimesFM-3 calendar it ranges from 0.357 to 0.786. This cohort has 0 common-grid crossing pairs and 0 invalid interval endpoints.

Table 6. Unmodified native Indian festival-window intervals at lead 1. Undefined interval cells retain invalid endpoints.

Model	Arm	Coverage 80%	Scaled width	Scaled WIS80
Chronos-2	Calendar	0.70714	1.44736	0.36718
Chronos-2	Typed day	0.73466	1.44335	0.35160
Chronos-2	Pooled day	0.72619	1.45710	0.34982
Chronos-2	Pooled window	0.73228	1.48578	0.36511
Chronos-2	Typed window	0.72381	1.45537	0.36526
TimesFM-3	Calendar	0.65926	1.21333	0.38483
TimesFM-3	Typed day	0.70238	1.23353	0.32158
TimesFM-3	Pooled day	0.70741	1.16836	0.27890
TimesFM-3	Pooled window	0.63651	1.19181	0.38615
TimesFM-3	Typed window	0.64735	1.21759	0.38944

Separate audits reconstruct raw source transformations, primary dates, cohorts, weekly scales, actual inputs, local fit/query arrays, label purging, unchanged-forecast reuse and scalar/hierarchical metrics. NYC additionally reruns all 72 past-only validation fits from independently constructed matrices using the same numerical model libraries; maximum validation-MAE difference is zero. Complete clean-environment reruns of all 5,952 direct-comparator forecasts and 2,560 simulation cells are byte-identical. A complete isolated-environment NYC rerun also reproduces all 4,032 local forecasts as byte-identical prediction files and all 72 validation MAEs exactly, including the declared SciPy 1.18.1 versus 1.17.0

package-drift sensitivity. These are internal software checks on one machine, not independent human review or independent foundation reimplementation.

Earlier numerical failures remain material. A float64 tree reproduction failed before a separately named float32 revision. In the stricter scalar review, 135 forecasts agree within tolerance, but 15 of 45 Delhi lead-1 near-zero feature entries differ after float32 conversion. That discrepancy is not removed by later tests. Failed calendar preflight, interrupted report generation and output-directory-only recovery are retained with their original source and result hashes. Two later integration failures also remain visible: the final aligned encoder omitted three registered H-independent arms, and the MTA output writer required a foreign scenario field. Versioned adapters repaired the dispatch/schema without changing cases, numerical features, model settings, metrics or tolerances; closed forecasts were retained byte-for-byte.

The historical daily CQR study [8] improves some coverage at the cost of wider intervals and some worse longer-lead proper scores. Its cohort differs from festival-feature distributions; it is not presented as their calibration. The original 30 October future freeze contains TimesFM history/calendar, Ridge, the original float64 tree and naive forecasts, with no Chronos or festival-feature arms. Its later interval annex repeats the same TimesFM episode with actual later issuance. Both remain immutable and unscored until the registered collection date. They do not directly confirm the main typed-versus-pooled hypothesis. A separate manual rolling plan is not activated and has issued no forecasts.

A new, separately timed Chronos history/calendar competitor completed at 2026-10-30T23:44:07.261024+00:00, with 84 stored forecasts and 66 eligible full 1–11 November cases. Its observed pre-outcome public receipt and separate input/India-day audit are retained. It uses the same stale source/context as the older episode but a later actual issuance; the paired comparison will reuse the original first actual vintage. It fills the missing Chronos competitor, not the prospective festival-feature gap or an independent episode.

7. Limits, interpretation and submission gates

The evidence is conditional on source, event definition, representation, horizon and adaptation policy. It cannot establish a new architecture, a causal holiday effect, contamination-free historical testing or a universal best model. India has two main event years; NYC contributes two occurrences from one city; NESO contributes no holiday targets. A drafted Singapore replication was not registered because its metadata check did not pass: the EMA history start and whether the series is covered by the Singapore Open Data Licence could not be verified, and no demand data were acquired. Weather, supply constraints, transit conditions, coincident observances, source revisions and calendar amendments remain alternative explanations. Local total-history access and fitting policies differ from foundation inference. Row counts and additional models do not create independent events.

The named-date correction demonstrates why checking whether a date is a holiday is weaker than checking which festival the document names. Annual-as-issued alignment is still not final amendment certification. Maharashtra 2022 evidence, shared-main exceptions, first-publication histories and independent human review remain open. Generic encodings, sparse pooling and pooled-versus-separate holiday dummies [9] have close prior work; Ziel's holiday-

as-Sunday and replacing designs are now compared for the local models only, and their advantage over calendar in India does not carry over to NYC; an exact runnable impact-driven comparison or a clearly justified alternative still needs resolution before a novelty claim is defensible.

Indian source-reuse permission is pending after the author manually emailed the curator. Public access and GitHub publication do not imply a grant. The MTA attached Overview explicitly states no data-use limitations, supporting the attributed minimal filtered snapshot; it does not name a standard licence or authorise Indian data. NESO has custom terms whose full body could not be retrieved; raw and complete derived archives remain outside Git. Any journal data-sharing restriction needs an editor-acceptable explanation. No independent reviewer, professor approval, first-vintage reconstruction or future outcome is inferred.

The immediate scientific next step is a genuinely future-issued feature comparison or repeated untouched events with a verified dated calendar and explicit availability/issuance guards, together with external review of the current evidence. It must have a new protocol, actual completion timestamp and pre-outcome public freeze. Current retrieval failures are not grounds to guess 2026 regional dates or silently modify the old future episode. Journal fit, current author instructions, declarations and data/code arrangements require verification; no acceptance or quartile claim follows from these experiments.

Data, code and author statements

Completed code, protocols, predictions, failures and audit artifacts are retained at https://github.com/Binay-verma/tsaf_project . New rows are distinguished from exact reused forecasts and composed views; no grand total is treated as independent evidence. Local environments and model weights/caches are excluded. The GRID-INDIA/POSOCO compilation curated by Robbie Andrew, whose reuse terms are unresolved, is currently present in the public repository (data/external/POSOCO_data.csv), as are derived files containing its values; its sharing status awaits the curator's reply. The Hunt and Bloomfield and SASEA sources are CC BY 4.0. NESO raw archives are outside Git. This draft is a reproducible review document, not a submission or permission certification.

Author: Binay Verma. Affiliation and corresponding email remain blank at the author's request. Funding, conflicts and any real coauthor contributions await factual confirmation. Binay Verma is not the independent reviewer. No outreach or journal submission is made by this build.

References

[1] Kreusel et al. (2026). On the Encoding of Calendar Features in Covariate-Informed Time Series Foundation Models. arXiv:2610.13676v1. https://arxiv.org/abs/2610.13676

[2] Alipour et al. Impact-driven event covariates for time-series foundation models. Primary page and linked paper have unresolved venue/name metadata; see the retained primary-method audit. https://www.amazon.science/publications/impact-driven-event-covariates-for-time-series-foundation-models

[3] Sanyal, Mitra, McElroy and Roy (2017). Holiday Effects in Indian Manufacturing Series. Census RRS2017-04. https://www.census.gov/library/working-papers/2017/adrm/rrs2017-04.html

[4] Kaljevic, Arzola and Zhang (2026). Benchmarking Time Series Foundation Models for Load Forecasting Under Covariate Uncertainty. arXiv:2610.07232v1. https://arxiv.org/abs/2610.07232

[5] Meyer et al. Rethinking Evaluation in the Era of Time Series Foundation Models: (Un)known Information Leakage Challenges. arXiv:2510.13654v3. https://arxiv.org/abs/2510.13654

[6] Ansari et al. (2025). Chronos-2: From Univariate to Universal Forecasting. arXiv:2510.15821v1. https://arxiv.org/abs/2510.15821

[7] Jain and Sen (2026). TimesFM-3: A zero-shot foundation model for multivariate forecasting. Official model announcement. https://research.google/blog/timesfm-3-a-zero-shot-foundation-model-for-multivariate-forecasting/

[8] Romano, Patterson and Candès (2019). Conformalized Quantile Regression. arXiv:1905.03222v1. https://arxiv.org/abs/1905.03222

[9] Ziel (2018). Modeling public holidays in load forecasting: a German case study. Journal of Modern Power Systems and Clean Energy 6(2), 191–207. https://doi.org/10.1007/s40565-018-0385-5

[10] Arora and Taylor (2018). Rule-based autoregressive moving average models for forecasting load on special days: A case study for France. European Journal of Operational Research 266(1), 259–268. https://doi.org/10.1016/j.ejor.2017.08.056

Appendix A. Complete companion comparisons

Table A1. NYC ordinary sample: decision lead 1, actual model step 8, MASE.

Model	Calendar	Typed day	Pooled day	Typed window	Pooled window
Rich Ridge	0.93022	0.82514	0.74570	0.82214	0.69602
SARIMAX	0.69848	0.57159	0.53110	0.61851	0.54580
Stable LightGBM	0.83653	0.83653	0.83653	0.83653	0.75887
Tree leaf minimum 2	0.76625	0.75037	0.71580	0.72767	0.71070
Chronos-2	0.32126	0.35468	0.37401	0.31593	0.40822
TimesFM-3	0.36890	0.40051	0.39322	0.33823	0.35082

Table A2. Fixed response-profile comparators on the original Indian case ledger. This is a separate, unchanged sensitivity.

Method	Lead 1	Lead 7	Lead 14
response_none	1.05617	1.05617	1.12777
response_partial	0.99059	1.04974	1.08356
response_pooled	1.04499	1.06250	1.11693
response_typed	1.02429	1.11325	1.11001

Table A3. Prespecified day-representation, lead-1 Spearman diagnostics. Positive forecast contrasts favour pooling; n counts available family/state/year cells, not independent replications. Undefined means insufficient variation or support.

Model	Support rho	Support n	Response rho	Response n
Rich Ridge	0.05912	24	0.15478	24
SARIMAX	0.46684	24	0.12087	24
Stable LightGBM	0.30970	24	0.01451	24
Tree leaf minimum 2	0.37794	24	0.08000	24
Chronos-2	-0.04204	24	0.17391	24
TimesFM-3	0.10992	24	-0.02174	24

Table A4. Indian typed-minus-pooled MASE at lead 1 by event year and family. Positive favours pooling. Clusters are family/year groups; they share states, weather and source vintage and are not independent replications. LOFO: leave-one-family-out balanced contrast. Exact ties are not counted in the cluster column.

Model	Rep.	Balanced	2024	2025	Pooled / typed clusters	LOFO range
Rich Ridge	day	-0.00776	-0.01727	0.00175	3 / 7	-0.01819 to -0.00060
Rich Ridge	window	-0.02924	-0.04483	-0.01365	4 / 6	-0.04266 to -0.01290
SARIMAX	day	-0.02812	-0.03562	-0.02063	4 / 6	-0.04526 to -0.00690
SARIMAX	window	0.00276	0.00899	-0.00347	4 / 6	-0.00285 to 0.00699
Stable LightGBM	day	0.03374	0.00000	0.06747	4 / 1	0.02864 to 0.04316
Stable LightGBM	window	-0.01065	-0.02319	0.00190	4 / 6	-0.01804 to -0.00069

Model	Rep.	Balanced	2024	2025	Pooled / typed clusters	LOFO range
Tree leaf minimum 2	day	0.04483	0.02723	0.06242	7 / 3	0.03075 to 0.07359
Tree leaf minimum 2	window	-0.00973	-0.01785	-0.00161	6 / 4	-0.01763 to 0.00141
Chronos-2	day	0.00257	-0.00069	0.00583	8 / 2	-0.00191 to 0.01638
Chronos-2	window	0.00452	0.00740	0.00163	6 / 4	0.00082 to 0.00828
TimesFM-3	day	0.05546	0.06834	0.04257	9 / 1	0.04781 to 0.06439
TimesFM-3	window	0.00409	0.00895	-0.00078	8 / 2	0.00227 to 0.00627

Table A5. Native 80% coverage across the ten Indian family/year clusters at lead 1 (unmodified intervals).

Model	Arm	Minimum	Maximum	Clusters below 0.80
Chronos-2	Calendar	0.429	0.857	8 of 10
Chronos-2	Typed day	0.500	0.857	8 of 10
Chronos-2	Pooled day	0.357	0.929	7 of 10
Chronos-2	Typed window	0.500	0.929	8 of 10
Chronos-2	Pooled window	0.429	0.929	8 of 10
TimesFM-3	Calendar	0.357	0.786	10 of 10
TimesFM-3	Typed day	0.500	0.841	9 of 10
TimesFM-3	Pooled day	0.500	0.926	7 of 10
TimesFM-3	Typed window	0.357	0.786	10 of 10
TimesFM-3	Pooled window	0.357	0.786	10 of 10

All leads of Tables A4–A5 and the NYC cells are in the supplement files reanalysis_*.csv.

Table A6. Ziel adaptations on the document-aligned Indian festival windows: local-model lead-1 MASE. The first three columns are recomputed and equal Table 1.

Model	Calendar	Typed day	Pooled day	hSun	Rph	RpH
Rich Ridge	0.57699	0.45317	0.46093	0.46375	0.44589	0.43854
SARIMAX	0.57301	0.42533	0.45345	0.45329	0.43439	0.41492
Stable LightGBM	0.69865	0.69483	0.66110	0.59277	0.64334	0.66625
Tree leaf minimum 2	0.68582	0.64952	0.60469	0.59895	0.59529	0.62115

Table A7. Indian lead-1 contrasts for the Ziel adaptations. Negative favours the first arm. Label: consistent = same sign in both years and every leave-one-family-out subset; negligible = absolute value below 0.005; otherwise unstable (registered rule).

Model	Contrast	Balanced	2024	2025	LOFO range	Label
Rich Ridge	hSun – pooled day	0.00281	0.00109	0.00454	-0.01393 to 0.02915	negligible
Rich Ridge	Rph – pooled day	-0.01504	-0.01297	-0.01712	-0.01786 to -0.01059	consistent
Rich Ridge	RpH – typed day	-0.01463	0.01235	-0.04161	-0.02383 to -0.00173	unstable
Rich Ridge	RpH – Rph	-0.00735	0.00804	-0.02274	-0.02726 to 0.00756	unstable
SARIMAX	hSun – pooled day	-0.00016	0.02551	-0.02582	-0.01257 to 0.02889	negligible
SARIMAX	Rph – pooled day	-0.01905	0.01441	-0.05252	-0.02450 to -0.00273	unstable
SARIMAX	RpH – typed day	-0.01041	0.02030	-0.04112	-0.02160 to 0.00749	unstable
SARIMAX	RpH – Rph	-0.01948	-0.02973	-0.00922	-0.03008 to 0.00193	unstable
Stable LightGBM	hSun – pooled day	-0.06832	-0.09185	-0.04480	-0.07478 to -0.05970	consistent
Stable LightGBM	Rph – pooled day	-0.01775	-0.00914	-0.02637	-0.02282 to -0.00821	consistent
Stable LightGBM	RpH – typed day	-0.02858	-0.00914	-0.04803	-0.03655 to -0.01424	consistent
Stable LightGBM	RpH – Rph	0.02290	0.00000	0.04581	0.01638 to 0.03713	unstable
Tree leaf minimum 2	hSun – pooled day	-0.00574	0.01585	-0.02733	-0.02179 to 0.00874	unstable

Model	Contrast	Balanced	2024	2025	LOFO range	Label
Tree leaf minimum 2	Rph – pooled day	-0.00940	0.01465	-0.03345	-0.01458 to -0.00420	unstable
Tree leaf minimum 2	RpH – typed day	-0.02837	-0.00887	-0.04787	-0.03504 to -0.02112	consistent
Tree leaf minimum 2	RpH – Rph	0.02586	0.00372	0.04800	0.00871 to 0.05995	consistent

Table A8. Ziel adaptations on NYC event windows: decision lead 1 (model step 8), local-model MASE. The first three columns are recomputed and equal Table 4.

Model	Calendar	Typed day	Pooled day	hSun	Rph	RpH
Rich Ridge	0.99718	1.00451	1.16887	1.09958	1.25617	1.03266
SARIMAX	0.99947	0.79417	1.04067	1.31300	1.02060	0.87342
Stable LightGBM	0.91940	0.91940	0.91940	0.97497	0.94489	0.94489
Tree leaf minimum 2	0.84819	0.84610	0.87819	0.97599	0.86605	0.91324

Table A9. NYC decision-lead-1 contrasts for the Ziel adaptations. Negative favours the first arm. Label as in Table A7, with the two modes in place of the two years.

Model	Contrast	Balanced	Bus	Subway	LOFO range	Label
Rich Ridge	hSun – pooled day	-0.06929	-0.16887	0.03029	-0.10211 to -0.03647	unstable
Rich Ridge	Rph – pooled day	0.08730	0.06703	0.10757	0.06802 to 0.10658	consistent
Rich Ridge	RpH – typed day	0.02816	-0.04323	0.09955	0.01199 to 0.04432	unstable
Rich Ridge	RpH – Rph	-0.22351	-0.25205	-0.19496	-0.32138 to -0.12563	consistent
SARIMAX	hSun – pooled day	0.27233	0.29639	0.24827	0.26394 to 0.28072	consistent
SARIMAX	Rph – pooled day	-0.02007	0.00345	-0.04358	-0.02622 to -0.01391	unstable
SARIMAX	RpH – typed day	0.07925	0.08910	0.06940	0.00484 to 0.15365	consistent

Model	Contrast	Balanced	Bus	Subway	LOFO range	Label
SARIMAX	RpH – Rph	-0.14719	-0.14985	-0.14452	-0.21144 to -0.08293	consistent
Stable LightGBM	hSun – pooled day	0.05557	0.05085	0.06030	-0.18779 to 0.29894	unstable
Stable LightGBM	Rph – pooled day	0.02549	0.06735	-0.01636	-0.03794 to 0.08893	unstable
Stable LightGBM	RpH – typed day	0.02549	0.06735	-0.01636	-0.03794 to 0.08893	unstable
Stable LightGBM	RpH – Rph	0.00000	0.00000	0.00000	0.00000 to 0.00000	negligible
Tree leaf minimum 2	hSun – pooled day	0.09779	0.03509	0.16049	-0.03651 to 0.23210	unstable
Tree leaf minimum 2	Rph – pooled day	-0.01214	-0.01049	-0.01380	-0.01631 to -0.00797	consistent
Tree leaf minimum 2	RpH – typed day	0.06714	0.09603	0.03825	0.05458 to 0.07970	consistent
Tree leaf minimum 2	RpH – Rph	0.04719	0.03239	0.06198	-0.08911 to 0.18349	unstable

All leads, both cohorts and every registered contrast of Tables A6–A9 are in the supplement files ziel_*.csv.

The supplementary source tables retain all leads, both cohorts, both feature views, every control and every registered pair. Figure and table values are copied from audited aggregates; the build manifest records exact source hashes. The companion audit compares every DOCX table cell with its exported CSV. PDF rendering and visual review are separate presentation checks, not independent scientific review.