

```
<HTML>
  <HEAD>
    <!-- Insert only HEAD tags. This is a comment. -->
    <TITLE> Welcome to first page1</TITLE>
  </HEAD>
  <BODY>
    <!-- Insert only BODY tags. -->
    <h1> Hello World </H1>
    <!-- Rest of page goes here.
    This is the multiple line comment. -->
  </BODY>
</HTML>
```

```
<HTML>
<HEAD>
  <TITLE>Document Headings</TITLE>
</HEAD>
<BODY>
Samples of the six heading types:
<H1>Level-1 (H1)</H1>
<H2 align="right">Level-2 (H2)</H2>
<H3><i>Level-3 (H3)</i></H3>
<H4 align="center">Level-4 (H4)</H4>
<H5><b>Level-5 (H5)</b></H5>
<H6><u>Level-6 (H6)</U></H6>
</BODY>
</HTML>
```

```
<html>
<head>
<title>Non-standard Margin Attributes</title>
</head>
<body leftmargin="100" topmargin="50" marginwidth="100"
marginheight="20">

<p>The values we've set for the four margin attributes
result in left and right margins that are 100 pixels wide,
and top and bottom margins that are 50 pixels high.</p>
</body>
</html>
```

```

<!DOCTYPE html>
<HTML>
<BODY bgcolor="yellow" background="" text="white" topmargin="30" leftmargin="100" link="red"
alink="green" vlink="black">
<a href="https://www.vit.ac.in">click link</a>

<P name="p1" align="justify">Here is <br><big><big>s</big></big>ome Here is sometext Here
is some text Here is some text Here is some text Here is some text Here is some text Here is
some text Here is some text Here is some text Here is some text Here is some text Here is
some text Here is some text Here is some text Here is some textHere is some text Here is
some text Here is some text Here is some text
text Here is some text Here is some text Here is some text Here is some text Here is some
text Here is some text Here is some textHere is some text Here is some text Here is som
<small><small>e</small></small>
</P>
<br>
<P name="p2" align="center"> Centered text Centered text Centered text Centered textCentered
text Centered textCentered textCentered textCentered textCentered textCentered textCentered
textCentered textCentered textCentered textCentered textCentered textCentered textCentered!
<br> textCentered textCentered textCentered text</P>

<P name="p3" align="right"> Right-justified text Right-justified text Right-justified text
Right-justified text Right-justified text Right-justified text Right-justified text
Right-justified text Right-justified text Right-justified text Right-justified text
Right-justified text Right-justified text Right-justified text Right-justified text
</p>

<hr width="100" align="right"><br>
<hr size="30%"><br>

<FONT COLOR="aqua" SIZE="4" FACE="Arial">
This is the text of line one </FONT><br>

<FONT COLOR="#0000FF" SIZE="7" FACE="Times New Roman">
This is the text of line one </FONT>

<p> We've made this word three times <big>bigger</big> by nesting it inside three sets of
big tags.</p>
<p>
<font size="5">We've made this word three times
<small><small>smaller</small></small> by
nesting it inside three sets of small tags.</font>
</p>
<hr> Use
<hr align=right width=25 > Them
<hr align=center width=25> center line
<hr align=center size=15 width=30> size lin
</BODY></HTML>

```

```
<html>
<head>
<title>Physical Styles</title>
</head>
<body>
<p><b>Bold</b> <br>
<i>Italic</i> <br>
<u>Underline</u> <br>
<s>Strikethrough</s> <br>
<tt>Teletype</tt>
</p>
<p>Superscript: a<sup>2</sup> x b<sup>2</sup> = c<sup>2</sup>
sup></p>
<p>Subscript: H<sub>2</sub>O</p>
<EM>Emphasized Text</EM><BR>
<TT>Teletype (Monospaced)</TT><BR>
<CODE>Computer Code Text</CODE><BR>
<STRIKE>Strike Through</STRIKE><BR>
<B><I>Bold Italic</I></B><BR>
abcdef<DEL>Delete</DEL>fhkfjdkhfdhgf<BR>
gfhgfhgfh<INS>Insert</INS>gfhfghgf<BR>
<p>My favorite color is <del>blue</del> <ins>red</ins>!</p>

</body>
</html>
```

```
<html>
<head>
<title>Logical Styles</title>
</head>
<body bgcolor="#ffffff" background="" leftmargin="100" topmargin="50" marginwidth="100"
marginheight="50">
&copy;,&reg;,&amp;,&yen;,&pound;,&trade;,&cent;,&euro;,&lt;,&gt;,&apos;,&quot;,&frac12;

<br>
<p>
<em>E&nbsp;mp&nbsp;phasis</em> looks <i>italic</i>. <br>
<strong>Strong</strong> looks <b>bold</b>. <br>
<code>Code</code> looks like <tt>teletype</tt>. <br>
<samp>Sample</samp> looks like <tt>teletype</tt> too. <br>
<kbd>Keyboard</kbd> also looks like <tt>teletype</tt>. <br>
<var>x + y=z</var> looks <i>italic</i>. <br>
<dfn>Definition</dfn> also looks <i>italic</i>. <br>
<cite>Cite</cite> is another logical style that looks<br>
<ACRONYM TITLE="Java Development Kit">JDK Acronym</ACRONYM>
<abbr TITLE="Java Development Kit">JDK Acronym</abbr>
<address>
Written by Jon Doe.<br>
Visit us at:<br>
Example.com
<br>Box 564, Disneyland<br>
USA</address>
<pre>
Text in a pre element is displayed in a fixed-width
font, and it preserves
both      spaces and
line breaks
</pre>
Text in a pre element
is displayed in a fixed-width
font, and it preserves
both      spaces and
line breaks

</p>
<p>The following is a quote from www.poets.org:</p>
  <blockquote><blockquote><p align=justify>Edgar Allan Poe was born in
  Boston, Massachusetts, on January 19, 1809. Poe's father and
  mother, both professional actors, died before the poet was
  three and John and Frances Allan raised him as a foster
  child in Richmond, Virginia. John Allan, a prosperous
  tobacco exporter, sent Poe to the best boarding schools and
  later to the University of Virginia, where Poe excelled
  academically.</p></blockquote></blockquote>

</body>
</html>
```