



Cloud Storage with LakeFlow Connect  
Standard Connectors

LECTURE

# Working with the Rescued Data Column




© Databricks 2025. All rights reserved. Apache, Apache Spark, Spark, the Spark Logo, Apache Iceberg, Iceberg, and the Apache Iceberg logo are trademarks of the [Apache Software Foundation](https://www.apache.org/).

In data ingestion, the rescued data column (`_rescued_data`) captures mismatched or unparseable fields as JSON—preserving non-conforming input values in your Lakehouse tables instead of dropping them.

# Working with the Rescued Data Column

## Rescuing Malformed Rows on Ingestion

`read_files()`, `spark.read` or **Auto Loader** provides a **rescued data column** if the raw data does not match the schema




© Databricks 2025. All rights reserved. Apache, Apache Spark, Spark, the Spark Logo, Apache Iceberg, Iceberg, and the Apache Iceberg logo are trademarks of the [Apache Software Foundation](#).

During data ingestion there are times when the input data doesn't match with the schema in your table. Ingestion techniques like `read_files()`, `spark.read` or **Auto Loader** provide a rescued data column during ingestion. The rescued data column ensures that columns that don't match with the schema are rescued instead of being dropped.

# Working with the Rescued Data Column

## Rescued Data Column Example



© Databricks 2025. All rights reserved. Apache, Apache Spark, Spark, the Spark Logo, Apache Iceberg, Iceberg, and the Apache Iceberg logo are trademarks of the [Apache Software Foundation](https://www.apache.org/).

For example, suppose your cloud storage location contains a set of raw files (these could be CSV, TXT, JSON, or other formats) and it contains a users and cost column.

When ingesting this data, the users column must be read into the table as a STRING, and the cost column must be read as a BIGINT.

In the first row of data, the value "Peter" will be read into the users column of the bronze table correctly. However, since the cost column contains a string like \$100, it does not match the expected BIGINT type. As a result, this value will not be inserted into the cost column. Instead, it will be captured in the **\_rescued\_data** column, stored as a JSON-formatted string.

In the second row, both values are valid: the value "zebi" is a STRING, and 300 is a BIGINT. Therefore, this row will be read into the bronze table without issues, and the **\_rescued\_data** column will remain empty for that row.



© Databricks 2025. All rights reserved. Apache, Apache Spark, Spark, the Spark Logo, Apache Iceberg, Iceberg, and the Apache Iceberg logo are trademarks of the [Apache Software Foundation](https://www.apache.org/).

Thank you for completing this lesson and continuing your journey to develop your skills with us.