

Biniam Abebe - 04/27/2024

Hands-on Assignment


Complete the following two sections on Supervised Machine Learning:

- CART
- k-Nearest Neighbors

CART and k-Nearest Neighbors

Part 1: CART

Supervised Machine Learning CART



STEP 1: Import Libraries

- import pandas and numpy libraries
- import scatter_matrix from pandas.plotting
- import DecisionTreeRegressor from sklearn.tree
- import tree from sklearn
- import train_test_split, KFold, and cross_val_score from sklearn.model_selection
- import matplotlib
- import seaborn
- import pyplot from matplotlib

In []:

```

#Add your code here
#Import Libraries
# Import Python Libraries: NumPy and Pandas
import pandas as pd
import numpy as np
# Import Libraries & modules for data visualization
from pandas.plotting import scatter_matrix
import matplotlib.pyplot as plt
import seaborn as sns
# Import scit-Learn module for the algorithm/model: DecisionTreeRegressor and tree to plo
from sklearn.tree import DecisionTreeRegressor
from sklearn import tree
# Import scikit-Learn module to split the dataset into train/ test sub-datasets
from sklearn.model_selection import train_test_split
# Import scikit-Learn module for K-fold cross-validation - algorithm/model evaluation & v
from sklearn.model_selection import KFold
from sklearn.model_selection import cross_val_score

# filter warnings
import warnings
warnings.filterwarnings("ignore")

```

WORKFLOW: DATA SET

STEP 2: Read data description and Load the Data

- Read the description of the dataset listed below
- Dataset is provided in the module and assignment. It is called housing_boston.csv.
- Load the data into Pandas dataframe called df
- View the first five rows of the dataframe

Description of Boston Housing Dataset

We will investigate the Boston House Price dataset as you did with the linear regression homework. Each record in the database describes a Boston suburb or town. The data was drawn from the Boston Standard Metropolitan Statistical Area (SMSA) in 1970. The attributes are defined as follows:

- CRIM: This is the per capita crime rate by town
- ZN: This is the proportion of residential land zoned for lots larger than 25,000 sq. ft.
- INDUS: This is the proportion of non-retail business acres per town.
- CHAS: This is the Charles River dummy variable (this is equal to 1 if tract bounds river; 0 otherwise)
- NOX: This is the concentration of the nitric oxide (parts per 10 million)
- RM: This is the average number of rooms per dwelling
- AGE: This is the proportion of owner-occupied units built prior to 1940
- DIS: This is the weighted distances to five Boston employment centers
- RAD: This is the index of accessibility to radial highways
- TAX: This is the full-value property-tax rate per 10,000 dollars

- PTRATIO: This is the pupil-teacher ratio by town
- AA: This is calculated as $1000(AA - 0.63)^2$, where AA is the proportion of people of African American descent by town
- LSTAT: This is the percentage lower status of the population
- MEDV: This is the median value of owner-occupied homes in \$1000s

Note: For this assignment, we use a subset of the original dataset.

- CRIM: per capita crime rate by town
- INDUS: proportion of non-retail business acres per town
- TAX: full-value property-tax rate per 10,000 dollars
- MEDV: Median value of owner-occupied homes in 1000 dollars.

```
In [ ]: #Add Your Code Here
# Specify location of the dataset.
housingfile = 'housing_boston.csv'
```

```
In [ ]: #Add Your Code Here
# Load the data into a Pandas DataFrame
df = pd.read_csv(housingfile, header=None)
```

```
In [ ]: #Add Your Code Here
# Specify the fields with their names
names = ['CRIM', 'ZN', 'INDUS', 'CHAS', 'NOX', 'RM', 'AGE', 'DIS', 'RAD',
'TAX', 'PTRATIO', 'AA', 'LSTAT', 'MEDV']
```

```
In [ ]: #Add Your Code Here
# Load the data into a Pandas DataFrame
df = pd.read_csv(housingfile, names=names)
# Look at the first 5 rows of data
df.head()
```

```
Out[ ]:   CRIM  ZN  INDUS  CHAS  NOX   RM  AGE   DIS  RAD  TAX  PTRATIO   AA  LSTAT  MEDV
0  0.00632  18.0    2.31    0  0.538  6.575  65.2  4.0900    1   296    15.3  396.90    4.98    24.0
1  0.02731   0.0    7.07    0  0.469  6.421  78.9  4.9671    2   242    17.8  396.90    9.14    21.6
2  0.02729   0.0    7.07    0  0.469  7.185  61.1  4.9671    2   242    17.8  392.83    4.03    34.7
3  0.03237   0.0    2.18    0  0.458  6.998  45.8  6.0622    3   222    18.7  394.63    2.94    33.4
4  0.06905   0.0    2.18    0  0.458  7.147  54.2  6.0622    3   222    18.7  396.90    5.33    36.2
```

WORKFLOW: Clean and Preprocess the Dataset

STEP 3: Clean the data

- Find and Mark Missing Values

- If there are no missing data points, then proceed to Step 4.

```
In [ ]: #Add Your Code Here
df.isnull().sum()
```

```
Out[ ]: CRIM      0
ZN         0
INDUS      0
CHAS       0
NOX        0
RM         0
AGE        0
DIS        0
RAD        0
TAX        0
PTRATIO    0
AA         0
LSTAT      0
MEDV       0
dtype: int64
```

```
In [ ]: #Add Your Code Here
# Now Let's say we want to decrease the number of variables in our heatmap.
# We would use the following code.
# Remember how to make a subset. Try using different variables.
df2= df[['CRIM', 'INDUS', 'TAX', 'MEDV']]
# We will use df2 for the rest of the calculations.
```

```
In [ ]: #Add Your Code Here
df2.head()
```

```
Out[ ]:   CRIM  INDUS  TAX  MEDV
0  0.00632    2.31  296   24.0
1  0.02731    7.07  242   21.6
2  0.02729    7.07  242   34.7
3  0.03237    2.18  222   33.4
4  0.06905    2.18  222   36.2
```

STEP 4: Performing the Exploratory Data Analysis (EDA)

- Print a count of the number of rows (observations) and columns (variables)
- Print the data types of all variables
- Print a summary statistics of the data

```
In [ ]: #Add Your Code Here
print(df2.shape)
```

```
(452, 4)
```

In []:

```
#Add Your Code Here
print(df2.dtypes)
```

```
CRIM      float64
INDUS     float64
TAX       int64
MEDV      float64
dtype: object
```

In []:

```
#Add Your Code Here
# Obtain the summary statistics of the data
print(df2.describe())
```





	CRIM	INDUS	TAX	MEDV
count	452.000000	452.000000	452.000000	452.000000
mean	1.420825	10.304889	377.442478	23.750442
std	2.495894	6.797103	151.327573	8.808602
min	0.006320	0.460000	187.000000	6.300000
25%	0.069875	4.930000	276.750000	18.500000
50%	0.191030	8.140000	307.000000	21.950000
75%	1.211460	18.100000	411.000000	26.600000
max	9.966540	27.740000	711.000000	50.000000

STEP 4A: Create Histograms

- Create histograms for each variable from the dataframe df with a figure size of 14 x 12
- Plot the histograms

In []:


```
#Add Your Code Here
# Plot histogram for each variable. I encourage you to work with the
# histogram. Remember what you did in the previous homework.
df2.hist(edgecolor= 'black',figsize=(14,12))
plt.show()
```



STEP 4B: Create Scatter Plots

In []:

```
#Add Your Code Here
# Create scatter plot matrix
scatter_matrix(df2, alpha=0.8, figsize=(15, 15))
plt.show()
```




STEP 4C: Join Plots with Seaborn

IMPORTANT NOTE: You can find more information on joint plots here


<http://seaborn.pydata.org/generated/seaborn.jointplot.html>

```
In [ ]: #Add Your Code Here
sns.jointplot(data=df2, x="CRIM", y="MEDV", kind="reg")
```

```
Out[ ]: <seaborn.axisgrid.JointGrid at 0x1f3c79bb0d0>
```




```
In [ ]: #Add Your Code Here
sns.jointplot(x = 'CRIM', y = 'MEDV', data = df2, kind = 'kde', height = 5,
joint_kws={'color': 'green'})
plt.show()
```



```
In [ ]: #Add Your Code Here
#Join plot with TAX and MEDV
sns.jointplot(x = 'TAX', y = 'MEDV', data = df2, kind = 'hex', height = 5,
```




```
joint_kws={'color':'purple'})
plt.show()
```



In []:

```
#Add Your Code Here
# Join plot with TAX and MEDV
sns.jointplot(x = 'INDUS', y = 'MEDV', data = df2, kind = 'hist', height = 5,
joint_kws={'color':'orange'}, binwidth=(3,5), cbar=True)
plt.show()
```




In []:

```
#Add Your Code Here
# Now we will combine the join plots
g = sns.PairGrid(df2, height= 10)
g.map_upper(sns.histplot, bins= 20, binwidth=3, cbar=True)
```

```
g.map_lower(sns.kdeplot, fill=True, cbar=True)
g.map_diag(sns.histplot, kde=True, cbar=True)
```

Out[]: <seaborn.axisgrid.PairGrid at 0x1f3c8231040>



WORKFLOW: DATA SPLIT

STEP 5: Separate the Dataset into Input & Output NumPy Arrays

- Store the dataframe d2 values into a NumPy array
- Separate the array into input and output components by slicing

In []:

```
#Add Your Code Here
# Store the dataframe values into a numPy array
array = df2.values
```

```
# Separate the array into input and output components by slicing (you used this in your P
# For X (input)[:,3] --> ALL the rows and columns from 0 up to 3
X = array[:, 0:3]
# For Y (output)[:,3] --> ALL the rows in the last column (MEDV)
Y = array[:,3]
```

STEP 6: Split into Input/Output Array into Training/Testing Datasets

- Split the dataset into training at 67% and test at 33% with the seed = 7

```
In [ ]: #Add Your Code Here
# Split the dataset --> training sub-dataset: 67%, and test sub-dataset:33%
test_size = 0.33
# Selection of records to include in which sub-dataset must be done randomly -use the for
seed = 7
# Split the dataset (both input & output) into training/testing datasets
X_train, X_test, Y_train, Y_test= train_test_split(X,Y, test_size=test_size,random_state=
```

WORKFLOW: TRAIN MODEL

STEP 7: Build and Train the Model


- Assign DecisionTreeRegressor to the model
- Train the model
- Print output

```
In [ ]: #Add Your Code Here
# Build the model
model = DecisionTreeRegressor(random_state=seed)
```

```
In [ ]: #Add Your Code Here
# Train the model using the training sub-dataset
model.fit(X_train,Y_train)
# Non-Linear --> NO coefficients and the intercept
DecisionTreeRegressor (criterion='mse', max_depth=None, max_features=None,
                        max_leaf_nodes=None, min_impurity_decrease=0.0, min_samples_split=
min_weight_fraction_leaf=0.0, random_state=seed, splitter='best')
```

```
Out[ ]: DecisionTreeRegressor(min_samples_split=100, random_state=7)
```

```
In [ ]: #Add Your Code Here
#Plot tree
tree.plot_tree(model, feature_names=X_train, class_names=Y_train, filled =
True, fontsize=10)
plt.show()
```



WORKFLOW: SCORE MODEL

STEP 8: Calculate R-Squared

- Calculate the R-Squared
- Print the score

**** Note:** The higher the R-squared, the better (0 – 100%). Depending on the model, the best models score above 83%. The R-squared value tells us how well the independent variables predict the dependent variable, which is very low. Think about how you could increase the R-squared. What variables would you use?

In []:

```
#Add Your Code Here
R_squared = model.score(X_test, Y_test)
print('R-Squared = ', R_squared)
```

R-Squared = -0.04775035045890075

Step 9: Prediction

- Execute model prediction
- We have now trained the model. Let's use the trained model to predict the "Median value of owner-occupied homes in 1000 dollars" (MEDV).

We are using the following predictors for the 1st prediction:

- CRIM: per capita crime rate by town: 12
- INDUS: proportion of non-retail business acres per town: 10
- TAX: full-value property-tax rate per \$10,000: 450

Notes: So, the model predicts that the median value of owner-occupied homes in 1000 dollars in the above suburb should be around \$12,600.

We are using the following predictors for the 2nd prediction:

- CRIM: per capita crime rate by town: 2
- INDUS: proportion of non-retail business acres per town: 30
- TAX: full-value property-tax rate per \$10,000: 50

Notes: So, the model predicts that the median value of owner-occupied homes in 1000 dollars in the above suburb should be around \$15,700.

```
In [ ]: #Add Your Code Here
        model.predict([[12,10,450]])
```

```
Out[ ]: array([12.6])
```

```
In [ ]: #Add Your Code Here
        model.predict([[2,30,50]])
```

```
Out[ ]: array([7.])
```

WORKFLOW: EVALUATE MODELS

Step 10: Train & Score Model 2 Using K-Fold Cross Validation Data Split

- Specify the k-size to 10
- Fix the random seed to 7
- Split the entire data set
- Obtain score
- Train the model and run K-fold cross-validation
- Print results

```
In [ ]: #Add Your Code Here
        # Evaluate the algorithm
        # Specify the K-size
        num_folds = 10
        # Fix the random seed
        # must use the same seed value so that the same subsets can be obtained
        # for each time the process is repeated
        seed = 7
        # Split the whole data set into folds
        kfold= KFold(n_splits=num_folds, random_state=seed, shuffle=True)
        scoring = 'neg_mean_squared_error'
```

```
In [ ]: #Add Your Code Here
        # Train the model and run K-fold cross-validation to validate/evaluate the model

        results = cross_val_score(model, X, Y, cv=kfold, scoring=scoring)
        # Print out the evaluation results
        # Result: the average of all the results obtained from the k-fold cross validation
        print("Average of all results from the K-fold Cross Validation, using negative mean squar
```

Average of all results from the K-fold Cross Validation, using negative mean squared error: -76.82251835748792

Notes: After we train, we evaluate. We are using K-fold to determine if the model is acceptable. We pass the whole set since the system will divide it for us. This value would traditionally be a positive value but scikit reports this value as a negative value. If you want a positive number, you may calculate the square root of the Negative Mean Squared Error value.

Part 2: k-Nearest Neighbors (kNN)

Supervised Machine Learning k-Nearest Neighbors (kNN)

- Let's begin Part 2 using the same Supervised Learning Workflow used in part 1.

STEP 1: Import Libraries

- import pandas and numpy libraries
- import scatter_matrix from pandas.plotting
- import matplotlib
- import seaborn
- import pyplot from matplotlib
- import KNeighborsClassifier from sklearn.neighbors
- import train_test_split, KFold, and cross_val_score from sklearn.model_selection
- import classification_report from sklearn.metrics

In []:

```
#Add Your Code Here
# Import Python Libraries: NumPy and Pandas
import pandas as pd
import numpy as np
# Import Libraries & modules for data visualization
from pandas.plotting import scatter_matrix
from matplotlib import pyplot
# Import scikit-Learn module for the algorithm/model: Nearest Neighbors
from sklearn.neighbors import KNeighborsClassifier
```

In []:

```
#Add Your Code Here
# Import scikit-Learn module to split the dataset into train/ test sub-datasets
from sklearn.model_selection import train_test_split
# Import scikit-Learn module for K-fold cross-validation - algorithm/model evaluation & v
from sklearn.model_selection import KFold
from sklearn.model_selection import cross_val_score
# Import scikit-Learn module classification report to later use for information about how
from sklearn.metrics import classification_report
```

WORKFLOW: DATA SET

STEP 2: Read data description and Load the Data

- Read the description of the dataset listed below
- Dataset is provided in the module and assignment. It is called iris.csv.
- Load the data into Pandas dataframe called df
- View the first five rows of the dataframe

Description Iris Dataset

Data Set: iris.csv

Title: Iris Plants Database Updated Sept 21 by C. Blake -Added discrepancy information Sources:

- Creator: RA_ Fisher
- Donor: Michael Marshall (MARSHALL%PLU@io.arc.nasa.gov)
- Date: 1988

Relevant Information: This is perhaps the best-known database to be found in the pattern recognition literature. Fisher's paper is a classic in the field and is referenced frequently to this day. (See Duda & Hart, for example)

The data set contains 3 classes of 50 instances each, where each class refers to a type of iris plant.

Predicted attribute: class of Iris plant

Number of Instances: 150 (50 in each of three classes)

Number of predictors: 4 numeric

Predictive attributes and the class attribute information:

- sepal length in cm
- sepal width in cm
- petal length in cm
- petal width in cm

class:

**Iris Versicolor****Iris Setosa****Iris Virginica**

```
In [ ]: #Add Your Code Here
        # Specify location of the dataset
        filename = 'iris.csv'
```

```
In [ ]: #Add Your Code Here
        # Load the data into a Pandas DataFrame
        df = pd.read_csv(filename)
```

WORKFLOW: Clean and Preprocess the Dataset

STEP 3: Clean the data

- Find and Mark Missing Values
- If there are no missing data points, then proceed to Step 4.

```
In [ ]: #Add Your Code Here
        # mark zero values as missing or NaN
        df[['SepalLengthCm', 'SepalWidthCm', 'PetalLengthCm', 'PetalWidthCm']] \
        = df[['SepalLengthCm', 'SepalWidthCm', 'PetalLengthCm', 'PetalWidthCm']] \
        .replace(0, np.NaN)
        # count the number of NaN values in each column
        print (df.isnull().sum())
```

```
Id          0
SepalLengthCm  0
SepalWidthCm  0
PetalLengthCm  0
PetalWidthCm  0
Species      0
dtype: int64
```

STEP 4: Performing the Exploratory Data Analysis (EDA)

- Print a count of the number of rows (observations) and columns (variables)
- Print the data types of all variables
- Print the first five records

- Print a summary statistics of the data
- Print the number of records in each class

In []:

```
#Add Your Code Here
# get the dimensions or shape of the dataset
# i.e. number of records / rows X number of variables / columns
print(df.shape)
```

(150, 6)

In []:

```
#Add Your Code Here
#get the data types of all the variables / attributes in the data set
print(df.dtypes)
```

```
Id                int64
SepalLengthCm     float64
SepalWidthCm      float64
PetalLengthCm     float64
PetalWidthCm      float64
Species           object
dtype: object
```

In []:

```
#Add Your Code Here
#return the first five records / rows of the data set
print(df.head(5))
```

	Id	SepalLengthCm	SepalWidthCm	PetalLengthCm	PetalWidthCm	Species
0	1	5.1	3.5	1.4	0.2	Iris-setosa
1	2	4.9	3.0	1.4	0.2	Iris-setosa
2	3	4.7	3.2	1.3	0.2	Iris-setosa
3	4	4.6	3.1	1.5	0.2	Iris-setosa
4	5	5.0	3.6	1.4	0.2	Iris-setosa

In []:

```
#Add Your Code Here
#return the summary statistics of the numeric variables / attributes in the data set
print(df.describe())
```

	Id	SepalLengthCm	SepalWidthCm	PetalLengthCm	PetalWidthCm
count	150.000000	150.000000	150.000000	150.000000	150.000000
mean	75.500000	5.843333	3.054000	3.758667	1.198667
std	43.445368	0.828066	0.433594	1.764420	0.763161
min	1.000000	4.300000	2.000000	1.000000	0.100000
25%	38.250000	5.100000	2.800000	1.600000	0.300000
50%	75.500000	5.800000	3.000000	4.350000	1.300000
75%	112.750000	6.400000	3.300000	5.100000	1.800000
max	150.000000	7.900000	4.400000	6.900000	2.500000

In []:

```
#Add Your Code Here
#class distribution i.e. how many records are in each class
print(df.groupby('Species').size())
```


```
Species
Iris-setosa      50
Iris-versicolor  50
Iris-virginica   50
dtype: int64
```

STEP 4A: Create Histograms

- Create histograms from the dataframe df that is black with a figure size of 12 x 8
- Plot the histograms

In []:

```
#Add Your Code Here
#plot histogram of each numeric variable / attribute in the data set
df.hist(figsize=(12, 8))
pyplot.show()
```




Step 4B: Density plots

- Create density plots from the dataframe df

In []:

```
#Add Your Code Here
# generate density plots of each numeric variable / attribute in the data set
df.plot(kind='density', subplots=True, layout=(3, 3), sharex=False,
legend=True, fontsize=1,
figsize=(12, 16))
pyplot.show()
```




Step 4C: Create Boxplots

- Create Boxplots

In []:

```
#Add Your Code Here
# generate box plots of each numeric variable / attribute in the data set
df.plot(kind='box', subplots=True, layout=(3,3), sharex=False,
figsize=(12,8))
pyplot.show()
```




Step 4C: Create Scatter plots

- Create Scatter plots

In []:

```
#Add Your Code Here  
# generate scatter plot matrix of each numeric variable / attribute in the data set  
scatter_matrix(df, alpha=0.8, figsize=(15, 15))  
pyplot.show()
```



WORKFLOW: DATA SPLIT

STEP 5: Separate the Dataset into Input & Output NumPy Arrays

- Store the dataframe values into a NumPy array

In []:

```
#Add Your Code Here
# store dataframe values into a numpy array
array = df.values
# separate array into input and output by slicing
# for X(input)[:, 1:5] --> all the rows, columns from 1 - 4 (5 - 1)
# these are the independent variables or predictors
X = array[:,1:5]
# for Y(input)[:, 5] --> all the rows, column 5
# this is the value we are trying to predict
Y = array[:,5]
```

STEP 6: Split into Input/Output Array into Training/Testing Datasets

- Split the dataset into training at 67% and test at 33% with the seed = 7

```
In [ ]: #Add Your Code Here
# split the dataset --> training sub-dataset: 67%; test sub-dataset: 33%
test_size = 0.33
#selection of records to include in each data sub-dataset must be done randomly
seed = 7
```

```
In [ ]: #Add Your Code Here
#split the dataset (input and output) into training / test datasets
X_train, X_test, Y_train, Y_test = train_test_split(X, Y, test_size=test_size, random_state
```

WORKFLOW: TRAIN MODEL

STEP 7: Build and Train the Model

- Assign kNN to the model
- Train the model
- Print the classification report

```
In [ ]: #Add Your Code Here
#build the model
model = KNeighborsClassifier()
# train the model using the training sub-dataset
model.fit(X_train, Y_train)
```

```
Out[ ]: KNeighborsClassifier()
```

```
In [ ]: #Add Your Code Here
#print the classification report
predicted = model.predict(X_test)
report = classification_report(Y_test, predicted)
print("Classification Report: ", "\n", "\n", report)
```

Classification Report:

	precision	recall	f1-score	support
Iris-setosa	1.00	1.00	1.00	14
Iris-versicolor	0.85	0.94	0.89	18
Iris-virginica	0.94	0.83	0.88	18
accuracy			0.92	50
macro avg	0.93	0.93	0.93	50
weighted avg	0.92	0.92	0.92	50

```
In [ ]: #Add Your Code Here
#score the accuracy leve
result = model.score(X_test, Y_test)
#print out the results
print(("Accuracy: %.3f%%" % (result*100.0))
```

Accuracy: 92.000%

WORKFLOW: SCORE MODEL 1

STEP 8: Score the Accuracy of the Model

- Calculate accuracy score
- Print the score

```
In [ ]: #Add Your Code Here
#score the accuracy leve
result = model.score(X_test, Y_test)
#print out the results
print(("Accuracy: %.3f%%" % (result*100.0))
```

Accuracy: 92.000%

Step 9: Prediction

- Execute model prediction

Note: We have now trained the model and using that trained model to predict the type of flower we have with the listed values for each variable.

```
In [ ]: #Add Your Code Here
model.predict([[5.3, 3.0, 4.5, 1.5]])
```

```
Out[ ]: array(['Iris-versicolor'], dtype=object)
```

WORKFLOW: EVALUATE MODELS

Step 10: Train & Score Model 2 Using K-Fold Cross Validation Data Split

- Specify the k-size to 10
- Fix the random seed to 7
- Split the entire data set
- Obtain the accuracy level
- Train the model and run K-fold cross-validation
- Print results

```
In [ ]: #Add Your Code Here
# evaluate the algorithm
# specify the number of time of repeated splitting, in this case 10 folds
n_splits = 10
```

```
In [ ]: #Add Your Code Here
# fix the random seed
# must use the same seed value so that the same subsets can be obtained
# for each time the process is repeated
seed = 7
```

```
In [ ]: #Add Your Code Here
# split the whole dataset into folds
kfold = KFold(n_splits, random_state=seed, shuffle=True)
```

```
In [ ]: #Add Your Code Here
# we can use the accuracy level to evaluate the model / algorithm
scoring = 'accuracy'
```

```
In [ ]: #Add Your Code Here
# train the model and run K-fold cross validation to validate / evaluate the model
results = cross_val_score(model, X, Y, cv=kfold, scoring=scoring)
```

```
In [ ]: #Add Your Code Here
# print the evaluation results
# result: the average of all the results obtained from the K-fold cross validation
print("Accuracy: %.3f (%.3f)" % (results.mean(), results.std()))
```

Accuracy: 0.953 (0.052)

```
In [ ]: #Compare this outcome to last week's Supervised Logistic Regression exercise and assess w
#last week Accuracy was : 0.967 (0.054) and this week Accuracy: 0.953 (0.052)
print("""Based on the accuracy scores provided, last week's Supervised Logistic Regressio
It has a higher accuracy score of 0.967 compared to this week's accuracy score of 0
```

Based on the accuracy scores provided, last week's Supervised Logistic Regression model is superior. It has a higher accuracy score of 0.967 compared to this week's accuracy score of 0.953.

GREAT JOB! YOU ARE DONE.