

MODULE END ASSIGNMENT

E-COMMERCE CHURN ANALYSIS

PREPARED BY:

AMRA ABDUL HAMEED

Problem Statement:

In the realm of e-commerce, businesses face the challenge of understanding customer churn patterns to ensure customer satisfaction and sustained profitability. This project aims to delve into the dynamics of customer churn within an e-commerce domain, utilizing historical transactional data to uncover underlying patterns and drivers of churn. By analyzing customer attributes such as tenure, preferred payment modes, satisfaction scores, and purchase behavior, the project seeks to investigate and understand the dynamics of customer attrition and their propensity to churn. The ultimate objective is to equip e-commerce enterprises with actionable insights to implement targeted retention strategies and mitigate churn, thereby fostering long-term customer relationships and ensuring business viability in a competitive landscape.

DATABASE:

```
DROP DATABASE IF EXISTS ecomm;
```

```
CREATE DATABASE ecomm;
```

```
USE ecomm;
```

```
CREATE TABLE customer_churn(  
    CustomerID          INT PRIMARY KEY,  
    Churn                BIT,  
    Tenure               INT,  
    PreferredLoginDevice VARCHAR(20),  
    CityTier             INT,  
    WarehouseToHome     INT,  
    PreferredPaymentMode VARCHAR(20),  
    Gender               ENUM('Male','Female'),  
    HourSpendOnApp       INT,  
    NumberOfDeviceRegistered INT,  
    PreferredOrderCat    VARCHAR(20),  
    SatisfactionScore    INT,  
    MaritalStatus        VARCHAR(10),  
    NumberOfAddress      INT,  
    Complain             BIT,  
    OrderAmountHikeFromlastYear INT,  
    CouponUsed           INT,  
    OrderCount           INT,  
    DaySinceLastOrder    INT,  
    CashbackAmount       INT  
);
```

And then 5630 rows of data is added.

```
5658      (55630,0,8,'Mobile Phone',1,15,'Credit Card','Male',3,2,'Laptop & Accessory',3,'Married',4,0,13,2,2,3,169);
5659
5660 • SELECT * FROM customer_churn;
```

	CustomerID	Churn	Tenure	PreferredLoginDevice	CityTier	WarehouseToHome	PreferredPaymentMode	Gender	HourSpendOnApp	NumberOfDeviceRegistered	PreferredC
▶	50001	1	4	Mobile Phone	3	6	Debit Card	Female	3	3	Laptop & A
	50002	1	NULL	Phone	1	8	UPI	Male	3	4	Mobile
	50003	1	NULL	Phone	1	30	Debit Card	Male	2	4	Mobile
	50004	1	0	Phone	3	15	Debit Card	Male	2	4	Laptop & A
	50005	1	0	Phone	1	12	CC	Male	NULL	3	Mobile
	50006	1	0	Computer	1	22	Debit Card	Female	3	5	Mobile Phoi
	50007	1	NULL	Phone	3	11	Cash on Deliverv	Male	2	3	Laptop & A

```
5661
5662 • SELECT COUNT(*) AS Total_Customers
5663 FROM customer_churn;
```

	Total_Customers
▶	5630

DATA CLEANING:

1. Handling Missing Values and Outliers:

➤ Impute mean for the following columns, and round off to the nearest integer if required: WarehouseToHome, HourSpendOnApp, OrderAmountHikeFromlastYear, DaySinceLastOrder.

➤ Impute mode for the following columns: Tenure, CouponUsed, OrderCount.

➤ Handle outliers in the 'WarehouseToHome' column by deleting rows where the values are greater than 100.

First lets find all the missing values.

```

3 • SELECT
4     COUNT(*) AS Total_Rows,
5     SUM(WarehouseToHome IS NULL) AS Missing_WarehouseToHome,
6     SUM(HourSpendOnApp IS NULL) AS Missing_HourSpendOnApp,
7     SUM(OrderAmountHikeFromLastYear IS NULL) AS Missing_OrderAmountHike,
8     SUM(DaySinceLastOrder IS NULL) AS Missing_DaySinceLastOrder,
9     SUM(Tenure IS NULL) AS Missing_Tenure,
10    SUM(CouponUsed IS NULL) AS Missing_CouponUsed,
11    SUM(OrderCount IS NULL) AS Missing_OrderCount
12 FROM customer_churn;

```

	Total_Rows	Missing_WarehouseToHome	Missing_HourSpendOnApp	Missing_OrderAmountHike	Missing_DaySinceLastOrder	Missing_Tenure	Missing_CouponUsed	Missing_OrderCo
▶	5628	251	255	265	307	264	256	258

Now, Remove WarehouseToHome outliers

```

3 • SELECT *
4 FROM customer_churn
5 WHERE WarehouseToHome > 100;

```

	CustomerID	Churn	Tenure	PreferredLoginDevice	CityTier	WarehouseToHome	PreferredPaymentMode	Gender	HourSpendOnApp	NumberOfDeviceRegistered	PreferredOrder
▶	51310	0	25	Computer	3	126	Debit Card	Male	2	3	Mobile
▶	54125	0	26	Computer	3	127	Debit Card	Male	3	4	Mobile Phone
•	NULL	NULL	NULL	NULL	NULL	NULL	NULL	NULL	NULL	NULL	NULL

```

DELETE FROM customer_churn
WHERE WarehouseToHome > 100;

```

Output will be

3 22 19:47:26 DELETE FROM customer_churn WHERE WarehouseToHome > 100 2 row(s) affected 0.031 sec

The following columns need mean imputation:

- WarehouseToHome
- HourSpendOnApp
- OrderAmountHikeFromlastYear
- DaySinceLastOrder


```

42 • UPDATE customer_churn
43   SET HourSpendOnApp = (
44       SELECT avg_value
45       FROM (
46           SELECT ROUND(AVG(HourSpendOnApp)) AS avg_value
47           FROM customer_churn
48       ) AS temp
49   )
50   WHERE HourSpendOnApp IS NULL;

```

```

51
52 • UPDATE customer_churn
53   SET OrderAmountHikeFromlastYear = (
54       SELECT avg_value
55       FROM (
56           SELECT ROUND(AVG(OrderAmountHikeFromlastYear)) AS avg_value
57           FROM customer_churn
58       ) AS temp
59   )
60   WHERE OrderAmountHikeFromlastYear IS NULL;

```

```

61
62 • UPDATE customer_churn
63   SET DaySinceLastOrder = (
64       SELECT avg_value
65       FROM (
66           SELECT ROUND(AVG(DaySinceLastOrder)) AS avg_value
67           FROM customer_churn
68       ) AS temp
69   )
70   WHERE DaySinceLastOrder IS NULL;

```

Now lets do mode imputation on the following columns.

- Tenure

```

71
72 • SELECT Tenure, COUNT(*) AS Frequency
73 FROM customer_churn
74 WHERE Tenure IS NOT NULL
75 GROUP BY Tenure
76 ORDER BY Frequency DESC
77 LIMIT 1;

```

	Tenure	Frequency
▶ 1	1	690

- CouponUsed

```

78
79 • SELECT CouponUsed, COUNT(*) AS Frequency
80 FROM customer_churn
81 WHERE CouponUsed IS NOT NULL
82 GROUP BY CouponUsed
83 ORDER BY Frequency DESC
84 LIMIT 1;

```

	CouponUsed	Frequency
▶ 1	1	2104

- OrderCount

```

85
86 • SELECT OrderCount, COUNT(*) AS Frequency
87 FROM customer_churn
88 WHERE OrderCount IS NOT NULL
89 GROUP BY OrderCount
90 ORDER BY Frequency DESC
91 LIMIT 1;

```

	OrderCount	Frequency
▶ 2	2	2024

For this dataset, the modes are:

- **Tenure = 1**
- **CouponUsed = 1**
- **OrderCount = 2**

Now lets update each one .

```
92
93 • UPDATE customer_churn
94   SET Tenure = 1
95   WHERE Tenure IS NULL;

Output

96 • UPDATE customer_churn
97   SET CouponUsed = 1
98   WHERE CouponUsed IS NULL;

99 • UPDATE customer_churn
100  SET OrderCount = 2
101  WHERE OrderCount IS NULL;
```

Now lets check the missing values.

```
102
103 • SELECT
104   SUM(Tenure IS NULL) AS Missing_Tenure,
105   SUM(WarehouseToHome IS NULL) AS Missing_WarehouseToHome,
106   SUM(HourSpendOnApp IS NULL) AS Missing_HourSpendOnApp,
107   SUM(OrderAmountHikeFromLastYear IS NULL) AS Missing_OrderAmountHike,
108   SUM(CouponUsed IS NULL) AS Missing_CouponUsed,
109   SUM(OrderCount IS NULL) AS Missing_OrderCount,
110   SUM(DaySinceLastOrder IS NULL) AS Missing_DaySinceLastOrder
111 FROM customer_churn;
```

Missing_Tenure	Missing_WarehouseToHome	Missing_HourSpendOnApp	Missing_OrderAmountHike	Missing_CouponUsed	Missing_OrderCount	Missing_DaySinceLastOrder
0	0	0	0	0	0	0

All done.

Dealing with Inconsistencies:

- Replace occurrences of "Phone" in the 'PreferredLoginDevice' column and

"Mobile" in the 'PreferredOrderCat' column with "Mobile Phone" to ensure uniformity.

➤ Standardize payment mode values: Replace "COD" with "Cash on Delivery" and "CC" with "Credit Card" in the PreferredPaymentMode column.

Preferred login device is set to mobile phone from phone here,

```
--
113 • UPDATE customer_churn
114     SET PreferredLoginDevice = 'Mobile Phone'
115     WHERE PreferredLoginDevice = 'Phone';
```

Output				
Action Output				
#	Time	Action	Message	
✓ 34	19:59:31	SELECT OrderCount, COUNT(*) AS Frequency FROM customer_churn WHERE OrderCount IS NOT NULL G...	1 row(s) returned	
✓ 35	20:00:12	UPDATE customer_churn SET Tenure = 1 WHERE Tenure IS NULL	264 row(s) affected	
✓ 36	20:00:57	UPDATE customer_churn SET CouponUsed = 1 WHERE CouponUsed IS NULL	256 row(s) affected	
✓ 37	20:01:25	UPDATE customer_churn SET OrderCount = 2 WHERE OrderCount IS NULL	258 row(s) affected	
✓ 38	20:02:14	SELECT SUM(Tenure IS NULL) AS Missing_Tenure, SUM(WarehouseToHome IS NULL) AS Missing_W...	1 row(s) returned	
✓ 39	20:03:28	UPDATE customer_churn SET PreferredLoginDevice = 'Mobile Phone' WHERE PreferredLoginDevice = 'Phone'	1231 row(s) affected	

Preferred login device is set to mobile phone from mobile here,

```
--
17 • UPDATE customer_churn
18     SET PreferredOrderCat = 'Mobile Phone'
19     WHERE PreferredOrderCat = 'Mobile';
```

Output				
Action Output				
#	Time	Action	Message	

Preferred payment mode is set to cash on delivery from cod;

```
121 • UPDATE customer_churn
122     SET PreferredPaymentMode = 'Cash on Delivery'
123     WHERE PreferredPaymentMode = 'COD';
```

Preferred payment mode is set to credit card from cc;

```

5 • UPDATE customer_churn
5   SET PreferredPaymentMode = 'Credit Card'
7   WHERE PreferredPaymentMode = 'CC';

```

Now lets check.

```

129 • SELECT PreferredPaymentMode, COUNT(*) AS Customer_Count
130   FROM customer_churn
131  GROUP BY PreferredPaymentMode;

```

Result Grid		Filter Rows:	Export:	Wrap Cell Content:
	PreferredPaymentMode	Customer_Count		
▶	Debit Card	2312		
	UPI	414		
	Credit Card	1774		
	Cash on Delivery	514		
	E wallet	614		

Data Transformation:

Column Renaming:

- Rename the column "PreferedOrderCat" to "PreferredOrderCat".
- Rename the column "HourSpendOnApp" to "HoursSpentOnApp".

```

1 • USE ecomm;
2
3 • ALTER TABLE customer_churn
4   RENAME COLUMN PreferedOrderCat TO PreferredOrderCat;
5
6 • ALTER TABLE customer_churn
7   RENAME COLUMN HourSpendOnApp TO HoursSpentOnApp;

```

Creating New Columns:

- Create a new column named 'ComplaintReceived' with values "Yes" if the corresponding value in the 'Complain' is 1, and "No" otherwise.

```

9 • ALTER TABLE customer_churn
10   ADD COLUMN ComplaintReceived VARCHAR(3);
11
12 • UPDATE customer_churn
13   SET ComplaintReceived =
14     CASE
15       WHEN Complain = 1 THEN 'Yes'
16       ELSE 'No'
17     END;
18

```

```

18
19 • SELECT ComplaintReceived, COUNT(*) AS Customer_Count
20   FROM customer_churn
21  GROUP BY ComplaintReceived;

```

Result Grid	Filter Rows:	Export:	Wrap Cell Content:
ComplaintReceived	Customer_Count		
Yes	1604		
No	4024		

➤ Create a new column named 'ChurnStatus'. Set its value to “Churned” if the corresponding value in the 'Churn' column is 1, else assign “Active”.

```

23 • ALTER TABLE customer_churn
24   ADD COLUMN ChurnStatus VARCHAR(10);
25
26 • UPDATE customer_churn
27   SET ChurnStatus =
28     CASE
29       WHEN Churn = 1 THEN 'Churned'
30       ELSE 'Active'
31     END;

```

```

33 • SELECT ChurnStatus, COUNT(*) AS Customer_Count
34 FROM customer_churn
35 GROUP BY ChurnStatus;

```

Result Grid	Filter Rows:	Export:	Wrap Cell Content:
ChurnStatus	Customer_Count		
Churned	948		
Active	4680		

Column Dropping:

- Drop the columns "Churn" and "Complain" from the table.

```

36
37 • ALTER TABLE customer_churn
38 DROP COLUMN Churn,
39 DROP COLUMN Complain;

```

Output

Data Exploration and Analysis:

- Retrieve the count of churned and active customers from the dataset.

```

3 • SELECT
4     ChurnStatus,
5     COUNT(*) AS Customer_Count
6 FROM customer_churn
7 GROUP BY ChurnStatus;

```

Result Grid	Filter Rows:	Export:	Wrap Cell Content:
ChurnStatus	Customer_Count		
Churned	948		
Active	4680		

- Display the average tenure and total cashback amount of customers who

churned.

```
9 • SELECT
10     ROUND(AVG(Tenure), 2) AS Average_Tenure,
11     SUM(CashbackAmount) AS Total_Cashback
12 FROM customer_churn
13 WHERE ChurnStatus = 'Churned';
```

Result Grid | | Filter Rows: | Export: | Wrap Cell Content:

	Average_Tenure	Total_Cashback
▶	3.18	152030

➤ Determine the percentage of churned customers who complained.

```
15 • SELECT
16     ROUND(
17         100.0 * SUM(ComplaintReceived = 'Yes') / COUNT(*),
18         2
19     ) AS Complaint_Percentage
20 FROM customer_churn
21 WHERE ChurnStatus = 'Churned';
```

Result Grid | | Filter Rows: | Export: | Wrap Cell Content:

	Complaint_Percentage
▶	53.59

➤ Identify the city tier with the highest number of churned customers whose preferred order category is Laptop & Accessory.

```

23 • SELECT
24     CityTier,
25     COUNT(*) AS Customer_Count
26 FROM customer_churn
27 WHERE ChurnStatus = 'Churned'
28     AND PreferredOrderCat = 'Laptop & Accessory'
29 GROUP BY CityTier
30 ORDER BY Customer_Count DESC;

```

Result Grid	Filter Rows:	Export:	Wrap Cell Content:
	CityTier	Customer_Count	
▶	3	150	
	1	60	

➤ Identify the most preferred payment mode among active customers.

```

32 • SELECT
33     PreferredPaymentMode,
34     COUNT(*) AS Customer_Count
35 FROM customer_churn
36 WHERE ChurnStatus = 'Active'
37 GROUP BY PreferredPaymentMode
38 ORDER BY Customer_Count DESC;

```

Result Grid	Filter Rows:	Export:	Wrap Cell Co
	PreferredPaymentMode	Customer_Count	
▶	Debit Card	1956	
	Credit Card	1522	
	E wallet	474	
	Cash on Delivery	386	
	UPI	342	

➤ Calculate the total order amount hike from last year for customers who are single and prefer mobile phones for ordering.

```

39
40 • SELECT
41     SUM(OrderAmountHikeFromlastYear) AS Total_OrderAmount_Hike
42 FROM customer_churn
43 WHERE MaritalStatus = 'Single'
44     AND PreferredOrderCat = 'Mobile Phone';

```

Result Grid |  Filter Rows: | Export:  | Wrap Cell Content: 

	Total_OrderAmount_Hike
▶	12177

➤ Find the average number of devices registered among customers who used UPI as their preferred payment mode.

```

45
46 • SELECT
47     ROUND(AVG(NumberOfDeviceRegistered), 2) AS Average_Devices
48 FROM customer_churn
49 WHERE PreferredPaymentMode = 'UPI';

```

Result Grid |  Filter Rows: | Export:  | Wrap Cell Content: 

	Average_Devices
▶	3.72

➤ Determine the city tier with the highest number of customers.

```

51 • SELECT
52     CityTier,
53     COUNT(*) AS Customer_Count
54 FROM customer_churn
55 GROUP BY CityTier
56 ORDER BY Customer_Count DESC;

```

Result Grid | Filter Rows: | Export: | W

	CityTier	Customer_Count
▶	1	3666
	3	1720
	2	242

➤ Identify the gender that utilized the highest number of coupons.

```

57
58 • SELECT
59     Gender,
60     SUM(CouponUsed) AS Total_Coupons
61 FROM customer_churn
62 GROUP BY Gender
63 ORDER BY Total_Coupons DESC;

```

Result Grid | Filter Rows: | Export: | Wrap Cell Content:

	Gender	Total_Coupons
▶	Male	5629
	Female	4034

➤ List the number of customers and the maximum hours spent on the app in each preferred order category.

```

65 • SELECT
66     PreferredOrderCat,
67     COUNT(*) AS Customer_Count,
68     MAX(HoursSpentOnApp) AS Maximum_Hours_Spent
69 FROM customer_churn
70 GROUP BY PreferredOrderCat
71 ORDER BY PreferredOrderCat;

```

Result Grid	Filter Rows:	Export:	Wrap Cell Content:
PreferredOrderCat	Customer_Count	Maximum_Hours_Spent	
Fashion	826	5	
Grocery	410	4	
Laptop & Accessory	2050	5	
Mobile Phone	2078	5	
Others	264	4	

➤ Calculate the total order count for customers who prefer using credit cards and have the maximum satisfaction score.

```

73 • SELECT
74     SUM(OrderCount) AS Total_Order_Count
75 FROM customer_churn
76 WHERE PreferredPaymentMode = 'Credit Card'
77 AND SatisfactionScore = (
78     SELECT MAX(SatisfactionScore)
79     FROM customer_churn
80 );

```

Result Grid	Filter Rows:	Export:	Wrap Cell C
Total_Order_Count			
1122			

➤ What is the average satisfaction score of customers who have complained?

```

82 • SELECT
83     ROUND(AVG(SatisfactionScore), 2) AS Average_Satisfaction_Score
84 FROM customer_churn
85 WHERE ComplaintReceived = 'Yes';

```

Result Grid | Filter Rows: | Export: | Wrap Cell Content:

	Average_Satisfaction_Score
▶	3.00

➤ List the preferred order category among customers who used more than 5 coupons.

```

86
87 • SELECT
88     PreferredOrderCat,
89     COUNT(*) AS Customer_Count
90 FROM customer_churn
91 WHERE CouponUsed > 5
92 GROUP BY PreferredOrderCat
93 ORDER BY Customer_Count DESC;

```

Result Grid | Filter Rows: | Export: | Wrap Cell Content:

	PreferredOrderCat	Customer_Count
▶	Laptop & Accessory	99
	Fashion	89
	Mobile Phone	45
	Grocery	42
	Others	28

Result 13 x

➤ List the top 3 preferred order categories with the highest average cashback amount.

```

95 • SELECT
96     PreferredOrderCat,
97     ROUND(AVG(CashbackAmount), 2) AS Average_Cashback
98 FROM customer_churn
99 GROUP BY PreferredOrderCat
100 ORDER BY Average_Cashback DESC
101 LIMIT 3;

```

Result Grid | Filter Rows: | Export: | Wrap Cell Content: | Fetch rows:

	PreferredOrderCat	Average_Cashback
▶	Others	304.45
	Grocery	266.24
	Fashion	210.40

➤ Find the preferred payment modes of customers whose average tenure is 10 months and have placed more than 500 orders.

```

102
103 • SELECT
104     PreferredPaymentMode,
105     Tenure,
106     OrderCount
107 FROM customer_churn
108 WHERE Tenure = 10
109     AND OrderCount > 500;

```

Result Grid | Filter Rows: | Export: | Wrap Cell Content: | Fetch rows:

	PreferredPaymentMode	Tenure	OrderCount
--	----------------------	--------	------------

It returns no records. Because the dataset's `OrderCount` does not reach 500.

➤ Categorize customers based on their distance from the warehouse to home such as 'Very Close Distance' for distances ≤ 5 km, 'Close Distance' for ≤ 10 km, 'Moderate Distance' for ≤ 15 km, and 'Far Distance' for > 15 km. Then, display the churn status breakdown for each distance category.

```

110
111 • ALTER TABLE customer_churn
112     ADD COLUMN DistanceCategory VARCHAR(30);
113 • UPDATE customer_churn
114     SET DistanceCategory =
115     CASE
116         WHEN WarehouseToHome <= 5 THEN 'Very Close Distance'
117         WHEN WarehouseToHome <= 10 THEN 'Close Distance'
118         WHEN WarehouseToHome <= 15 THEN 'Moderate Distance'
119         ELSE 'Far Distance'
120     END;

```

```

122 • SELECT
123     DistanceCategory,
124     ChurnStatus,
125     COUNT(*) AS Customer_Count
126 FROM customer_churn
127 GROUP BY DistanceCategory, ChurnStatus
128 ORDER BY
129     CASE DistanceCategory
130         WHEN 'Very Close Distance' THEN 1
131         WHEN 'Close Distance' THEN 2
132         WHEN 'Moderate Distance' THEN 3
133         WHEN 'Far Distance' THEN 4
134     END,
135     ChurnStatus;

```

Result Grid | Filter Rows: | Export: | Wrap Cell Content: [IA](#)

	DistanceCategory	ChurnStatus	Customer_Count
▶	Very Close Distance	Active	7
	Very Close Distance	Churned	1
	Close Distance	Active	1696
	Close Distance	Churned	265
	Moderate Distance	Active	1106
	Moderate Distance	Churned	184
	Far Distance	Active	1871
	Far Distance	Churned	498

Result 16 x

Output :

➤ List the customer's order details who are married, live in City Tier-1, and their order counts are more than the average number of orders placed by all

customers.

The overall average order count is :

```
137 • SELECT
138     AVG(OrderCount) AS Average_Order_Count
139 FROM customer_churn;
```

Result Grid

Average_Order_Count
2.9623

```
141 • SELECT *
142 FROM customer_churn
143 WHERE MaritalStatus = 'Married'
144 AND CityTier = 1
145 AND OrderCount > 2.9623
146     SELECT AVG(OrderCount)
147 FROM customer_churn
148 ;
```

Result Grid

CustomerID	Tenure	PreferredLoginDevice	CityTier	WarehouseToHome	PreferredPaymentMode	Gender	HoursSpentOnApp	NumberOfDeviceRegistered	PreferredOrderCat
50049	3	Computer	1	15	Credit Card	Male	3	3	Laptop & Accessory
50119	13	Mobile Phone	1	30	Cash on Delivery	Male	3	3	Laptop & Accessory
50132	15	Mobile Phone	1	16	Credit Card	Female	2	4	Mobile Phone
50133	13	Mobile Phone	1	8	Credit Card	Male	2	3	Others
50152	2	Mobile Phone	1	28	Debit Card	Female	3	2	Fashion
50180	12	Mobile Phone	1	6	Credit Card	Male	2	2	Fashion
50187	18	Computer	1	13	Debit Card	Male	3	3	Fashion

customer_churn 18 x

Output

Action Output

There are 576 records that satisfy all three conditions.

➤ a) Create a 'customer_returns' table in the 'ecomm' database and insert the following data:

ReturnID CustomerID ReturnDate RefundAmount

```
1001 50022 2023-01-01 2130
1002 50316 2023-01-23 2000
1003 51099 2023-02-14 2290
1004 52321 2023-03-08 2510
1005 52928 2023-03-20 3000
1006 53749 2023-04-17 1740
1007 54206 2023-04-21 3250
1008 54838 2023-04-30 1990
```

```

151 ● CREATE TABLE customer_returns (
152     ReturnID INT PRIMARY KEY,
153     CustomerID INT,
154     ReturnDate DATE,
155     RefundAmount INT,
156     FOREIGN KEY (CustomerID)
157         REFERENCES customer_churn(CustomerID)
158 );
159 ● INSERT INTO customer_returns
160     (ReturnID, CustomerID, ReturnDate, RefundAmount)
161     VALUES
162     (1001, 50022, '2023-01-01', 2130),
163     (1002, 50316, '2023-01-23', 2000),
164     (1003, 51099, '2023-02-14', 2290),
165     (1004, 52321, '2023-03-08', 2510),
166     (1005, 52928, '2023-03-20', 3000),
167     (1006, 53749, '2023-04-17', 1740),
168     (1007, 54206, '2023-04-21', 3250),
169     (1008, 54838, '2023-04-30', 1990);

```

b) Display the return details along with the customer details of those who have churned and have made complaints.

```

171 • SELECT
172     r.ReturnID,
173     r.CustomerID,
174     r.ReturnDate,
175     r.RefundAmount,
176     c.ChurnStatus,
177     c.ComplaintReceived,
178     c.Tenure,
179     c.PreferredLoginDevice,
180     c.CityTier,
181     c.WarehouseToHome,
182     c.PreferredPaymentMode,
183     c.Gender,
184     c.HoursSpentOnApp,
185     c.NumberOfDeviceRegistered,
186     c.PreferredOrderCat,
187     c.SatisfactionScore,
188     c.MaritalStatus,
189     c.NumberOfAddress,
190     c.OrderAmountHikeFromlastYear,
191     c.CouponUsed,
192     c.OrderCount,
193     c.DaySinceLastOrder,
194     c.CashbackAmount
195 FROM customer_returns r
196 JOIN customer_churn c
197     ON r.CustomerID = c.CustomerID
198 WHERE c.ChurnStatus = 'Churned'
199     AND c.ComplaintReceived = 'Yes';

```

Output

Result Grid											
Filter Rows:											
Export: Wrap Cell Content:											
ReturnID	CustomerID	ReturnDate	RefundAmount	ChurnStatus	ComplaintReceived	Tenure	PreferredLoginDevice	CityTier	WarehouseToHome	PreferredPaymentMode	Gender
1002	50316	2023-01-23	2000	Churned	Yes	0	Computer	2	29	UPI	Female
1004	52321	2023-03-08	2510	Churned	Yes	18	Mobile Phone	3	19	E wallet	Male
1006	53749	2023-04-17	1740	Churned	Yes	1	Mobile Phone	3	31	Credit Card	Female