```
- module AJupiter -
 1 [
    Model checking the Jupiter protocol presented by Attiya and others.
 5 EXTENDS OT, TLC
 6 |
 7
    CONSTANTS
                        the set of client replicas
         Client.
 8
         Server.
 9
                        the (unique) server replica
         InitState,
                        the initial state of each replica
10
         Priority
                        Priority[c]: the priority value of client c \in Client
11
12
        Cop
                   \setminus * Cop[c]: operations issued by the client c \in Client
    ASSUME
14
         \land InitState \in List
15
         \land Priority \in [Client \rightarrow PosInt]
16
      \land Cop \in [Client \rightarrow Seq(Op)]
17
    Generate operations for AJupiter clients.
    Note: Remember to overvide the definition of PosInt.
    FIXME: PosInt \Rightarrow MaxPos; MaxPr determined by the size of Client.
    OpToIssue \stackrel{\Delta}{=} \{opset \in SUBSET \ Op : \}
26
                              \forall op1, op2 \in opset:
27
                                  (op1.type = "Ins" \land op2.type = "Ins") \Rightarrow op1.ch \neq op2.ch
28
    VARIABLES
        For model checking:
                 \setminus * cop[c]: operations issued by the client c \in Client
34
                     a set of operations for clients to issue
35
         cop,
        For the client replicas:
         cbuf,
40
                     cbuf[c]: buffer (of operations) at the client c \in Client
41
         crec,
                     crec[c]: the number of new messages have been received by the client c \in Client
42
                             since the last time a message was sent
         cstate,
                    cstate[c]: state (the list content) of the client c \in Client
43
        For the server replica:
         sbuf,
                     sbuf[c]: buffer (of operations) at the Server, one per client c \in Client
48
                     srec[c]: the number of new messages have been ..., one per client c \in Client
49
         srec,
         sstate,
                     sstate: state (the list content) of the server Server
50
        For communication between the Server and the Clients:
         cincoming,
                          cincoming[c]: incoming channel at the client c \in Client
55
         sincoming
                          incoming channel at the Server
56
    comm \stackrel{\triangle}{=} INSTANCE \ CSComm
59 F
```

```
cVars \triangleq \langle cop, cbuf, crec, cstate \rangle
       sVars \stackrel{\triangle}{=} \langle sbuf, srec, sstate \rangle
         FIXME: subscript error (Don't know why yet!)
      \begin{array}{l} vars \ \stackrel{\Delta}{=} \ cVars \circ sVars \circ \langle cincoming, \, sincoming \rangle \\ jVars \ \stackrel{\Delta}{=} \ \langle cbuf, \, crec, \, cstate, \, sbuf, \, srec, \, sstate, \, cincoming, \, sincoming \rangle \end{array}
                                                                                                                            all variables
      vars \triangleq \langle cop, cbuf, crec, cstate, sbuf, srec, sstate, cincoming, sincoming \rangle
                                                                                                                                  all variables
 66
       TypeOK \stackrel{\triangle}{=}
 67
           \land \ cop \in \ [\mathit{Client} \rightarrow \mathit{Seq}(\mathit{Op})]
 68
              \land cop \in \text{SUBSET } Op
 69
            For the client replicas:
              \land cbuf \in [Client \rightarrow Seq(Op \cup \{Nop\})]
 73
             \land crec \in [Client \rightarrow Nat]
 74
              \land cstate \in [Client \rightarrow List]
 75
            For the server replica:
              \land sbuf \in [Client \rightarrow Seq(Op \cup \{Nop\})]
 79
             \land srec \in [Client \rightarrow Nat]
 80
              \land \ sstate \in \mathit{List}
 81
             For communication between the server and the clients:
              \land comm! TypeOK
 85
 86 |
       The Init predicate.
      Init \triangleq
 90
            \land \mathit{cop} = \mathit{Cop}
 91
              \land cop \in OpToIssue
 92
            For the client replicas:
              \land cbuf = [c \in Client \mapsto \langle \rangle]
 96
              \land crec = [c \in Client \mapsto 0]
 97
              \land cstate = [c \in Client \mapsto InitState]
 98
            For the server replica:
              \land \mathit{sbuf} = [\mathit{c} \in \mathit{Client} \mapsto \langle \rangle]
102
             \land \mathit{srec} = [c \in \mathit{Client} \mapsto 0]
103
              \land \, sstate = \mathit{InitState}
104
             For communication between the server and the clients:
              \land comm!Init
108
109 |
       LegalizeOp(op, c) \triangleq
110
             LET len \stackrel{\triangle}{=} Len(cstate[c])
111
                    CASE op.type = "Del" \rightarrow
112
                              IF len = 0 THEN Nop else [op \ EXCEPT !.pos = Min(@, len)]
113
                      op.type = "Ins" \rightarrow
114
115
                              [op except !.pos = Min(@, len + 1), !.pr = Priority[c]]
       Client c \in Client issues an operation op.
```

```
Do(c) \triangleq
119
          \land cop[c] \neq \langle \rangle
120
           \land cop \neq \{\}
121
           \wedge LET o \stackrel{\triangle}{=} CHOOSE x \in cop: TRUE
122
                  op \stackrel{\Delta}{=} \textit{LegalizeOp}(o, c) preprocess an illegal operation
123
                    \vee \wedge op = Nop
124
                          \wedge cop' = cop \setminus \{o\}
                                                      consume one operation
125
                          \land UNCHANGED jVars
126
                       \lor \land op \neq Nop
127
                        \land PrintT(c \circ ": Do" \circ ToString(op))
128
                          \land cstate' = [cstate \ EXCEPT \ ![c] = Apply(op, @)]
129
                          \wedge cbuf' = [cbuf \ EXCEPT \ ![c] = Append(@, op)]
130
                          \land crec' = [crec \ EXCEPT \ ![c] = 0]
131
                          \land comm! CSend([c \mapsto c, ack \mapsto crec[c], op \mapsto op])
132
                          \wedge cop' = cop \setminus \{o\}
                                                       consume one operation
133
134
                          \land Unchanged sVars
         \land cop' = [cop \ EXCEPT \ ![c] = Tail(@)] \setminus * consume one operation
135
      Client c \in Client receives a message from the Server.
      Rev(c) \triangleq
140
             \land comm! CRev(c)
141
             \land crec' = [crec \ EXCEPT \ ![c] = @ + 1]
142
             \wedge \text{ LET } m \stackrel{\triangle}{=} Head(cincoming[c])
143
                      cBuf \triangleq cbuf[c] the buffer at client c \in Client

cShiftedBuf \triangleq SubSeq(cBuf, m.ack + 1, Len(cBuf)) buffer shifted
144
145
                      xop \stackrel{\triangle}{=} XformOpOps(m.op, cShiftedBuf) transform op vs. shifted buffer
146
                       xcBuf \stackrel{\Delta}{=} XformOpsOp(cShiftedBuf, m.op) transform shifted buffer vs. op
147
                       \wedge cbuf' = [cbuf \ EXCEPT \ ![c] = xcBuf]
148
                        \land cstate' = [cstate \ EXCEPT \ ![c] = Apply(xop, @)]
                                                                                              apply the transformed operation xop
149
             \land UNCHANGED \langle sbuf, srec, sstate, cop \rangle
                                                                       NOTE: sVars \circ \langle cop \rangle is wrong!
150
151 |
      The Server receives a message.
      SRev \triangleq
155
            \land comm!SRev
156
           \wedge LET m \stackrel{\triangle}{=} Head(sincoming) the message to handle with
157
                     c \triangleq m.c
                                                      the client c \in Client that sends this message
158
                     cBuf \triangleq sbuf[c]
                                                      the buffer at the Server for client c \in Client
159
                     cShiftedBuf \stackrel{\Delta}{=} SubSeq(cBuf, m.ack + 1, Len(cBuf)) buffer shifted
160
                     xop \stackrel{\triangle}{=} XformOpOps(m.op, cShiftedBuf) transform op vs. shifted buffer
161
                      xcBuf \stackrel{\Delta}{=} XformOpsOp(cShiftedBuf, m.op) transform shifted buffer vs. op
162
                      \land srec' = [cl \in Client \mapsto
163
               IN
164
                                           THEN srec[cl] + 1 receive one more operation from client c \in Client
165
166
                                           ELSE 0 reset srec for other clients than c \in Client
                       \wedge sbuf' = [cl \in Client \mapsto
167
```

```
If cl = c
168
                                       THEN xcBuf transformed buffer for client c \in Client
169
                                       ELSE Append(sbuf[cl], xop)] store transformed xop into other clients' bufs
170
                    \land sstate' = Apply(xop, sstate) apply the transformed operation
171
172
                    \land comm! SSend(c, srec, xop)
           \land unchanged \mathit{cVars}
173
174
     The next-state relation.
     Next \triangleq
178
          \lor \exists c \in Client : Do(c) \lor Rev(c)
179
          \vee SRev
180
     The Spec.
184 Spec \stackrel{\triangle}{=} Init \wedge \Box [Next]_{vars} \wedge WF_{vars}(Next)
     The safety properties to check: Eventual Convergence (EC), Quiescent Consistency (QC), Strong
     Eventual Convergence (SEC), Weak List Specification, (WLSpec), and Strong List Specification,
     (SLSpec).
     Eventual Consistency (EC)
     Quiescent Consistency (QC)
     QConvergence \triangleq \forall c \in Client : cstate[c] = sstate
     QC \stackrel{\Delta}{=} comm! Empty Channel \Rightarrow QConvergence
203 THEOREM Spec \Rightarrow \Box QC
     Strong Eventual Consistency (SEC)
     Weak List Consistency (WLSpec)
     Strong List Consistency (SLSpec)
216 └
      \ * Modification History
      \ * Last modified Sun Jul 08 11:30:24 CST 2018 by hengxin
      \ * Created Sat Jun 23 17:14:18 CST 2018 by hengxin
```