

```

1  |----- MODULE XJupiterExtended -----|
   | XJupiter extended with serial views. This is used to show that XJupiter implements CJupiter. |
6  | EXTENDS XJupiter |
7  |-----|
8  | VARIABLES |
   | Simulating the behavior of propagating original operations in CJupiter. |
12 |   cincomingCJ,   cincoming for CJupiter which contains original operations |
13 |                   instead of transformed ones in XJupiter |
14 |   sincomingCJ,   (not used) |
   | For edge ordering in CSS. |
18 |   serial,   serial[r]: the serial view of replica r ∈ Replica about the server |
19 |   cincomingSerial, cincomingSerial[c]: the serial view received by client c ∈ Client |
20 |                   from the Server |
21 |   sincomingSerial (not used) |
23 | commCJVars ≜ ⟨cincomingCJ, sincomingCJ⟩ |
24 | serialVars   ≜ ⟨serial, cincomingSerial, sincomingSerial⟩ |
25 | varsEx ≜ ⟨commCJVars, serialVars, vars⟩ |
26 |-----|
27 | commCJ ≜ INSTANCE CSComm WITH Msg ← Seq(Cop), |
28 |                   cincoming ← cincomingCJ, sincoming ← sincomingCJ |
29 | commSerial ≜ INSTANCE CSComm WITH Msg ← Seq(Oid), |
30 |                   cincoming ← cincomingSerial, sincoming ← sincomingSerial |
31 |-----|
32 | TypeOKEx ≜ |
33 |   ∧ TypeOK |
34 |   ∧ commCJ! TypeOK |
35 |   ∧ serial ∈ [Replica → Seq(Oid)] |
36 |   ∧ commSerial! TypeOK |
37 |-----|
38 | InitEx ≜ |
39 |   ∧ Init |
40 |   ∧ commCJ! Init |
41 |   ∧ serial = [r ∈ Replica ↦ ⟨⟩] |
42 |   ∧ commSerial! Init |
43 |-----|
44 | DoEx(c) ≜ |
45 |   ∧ Do(c) |
46 |   ∧ UNCHANGED ⟨commCJVars, serialVars⟩ |
48 | RevEx(c) ≜ |
49 |   ∧ Rev(c) |
50 |   ∧ commCJ! CRev(c) |
51 |   ∧ commSerial! CRev(c) |
52 |   ∧ serial' = [serial EXCEPT ![c] = Head(cincomingSerial[c])] |

```

```

53       $\wedge$  UNCHANGED  $\langle s2ssVars \rangle$ 

55   $SRevEx \triangleq$ 
56       $\wedge$   $SRev$ 
57       $\wedge$  LET  $cop \triangleq Head(sincoming)$ 
58           $c \triangleq cop.oid.c$ 
59          IN  $\wedge commCJ!SSendSame(c, cop)$ 
60               $\wedge serial' = [serial \text{ EXCEPT } ![Server] = Append(@, cop.oid)]$ 
61               $\wedge commSerial!SSendSame(c, serial'[Server])$ 
62       $\wedge$  UNCHANGED  $\langle sincomingCJ, sincomingSerial \rangle$ 
63  ───────────────────────────────────────────────────────────────────────────────────┘
64   $NextEx \triangleq$ 
65       $\vee \exists c \in Client : DoEx(c) \vee RevEx(c)$ 
66       $\vee SRevEx$ 

68   $SpecEx \triangleq InitEx \wedge \Box[NextEx]_{varsEx}$ 
69       $\wedge \text{WF}_{varsEx}(SRevEx \vee \exists c \in Client : RevEx(c))$ 
70  ───────────────────────────────────────────────────────────────────────────────────┘

  \ * Modification History
  \ * Last modified Wed Nov 07 12:38:23 CST 2018 by hengxin
  \ * Created Tue Oct 30 20:32:27 CST 2018 by hengxin

```