

```

1 |----- MODULE XJupiterExtended -----|
  |XJupiter extended with Cop with the sctx field.
5 |----- EXTENDS Integers, OT, TLCUtils, AdditionalFunctionOperators, AdditionalSequenceOperators -----|
6 |-----|
7 |CONSTANTS
8   |Client,      | the set of client replicas
9   |Server,      | the (unique) server replica
10  |Char,         | set of characters allowed
11  |InitState    | the initial state of each replica

13 |Replica  $\triangleq$  Client  $\cup$  {Server}

15 |List  $\triangleq$  Seq(Char  $\cup$  Range(InitState)) | all possible lists/strings
16 |MaxLen  $\triangleq$  Cardinality(Char) + Len(InitState) | the max length of lists in any states;
17 |   We assume that all inserted elements are unique.

19 |ClientNum  $\triangleq$  Cardinality(Client)
20 |Priority  $\triangleq$  CHOOSE  $f \in [Client \rightarrow 1 \dots ClientNum] : Injective(f)$ 

22 |   direction flags
23 |Local  $\triangleq$  0
24 |Remote  $\triangleq$  1

25 |-----|
26 |ASSUME
27 |    $\wedge Range(InitState) \cap Char = \{\}$  | due to the uniqueness requirement
28 |    $\wedge Priority \in [Client \rightarrow 1 \dots ClientNum]$ 

29 |-----|
  |The set of all operations. Note: The positions are indexed from 1.
34 |Rd  $\triangleq$  [type : { "Rd" }]
35 |Del  $\triangleq$  [type : { "Del" }, pos : 1 .. MaxLen]
36 |Ins  $\triangleq$  [type : { "Ins" }, pos : 1 .. (MaxLen + 1), ch : Char, pr : 1 .. ClientNum] | pr: priority

38 |Op  $\triangleq$  Ins  $\cup$  Del

39 |-----|
  |Cop: operation of type Op with context
43 |Oid  $\triangleq$  [c : Client, seq : Nat] | operation identifier
  |Cop with the sctx field (the extended part)
47 |Cop  $\triangleq$  [op : Op  $\cup$  {Nop}, oid : Oid, ctx : SUBSET Oid, sctx : SUBSET Oid]

  |OT of two operations of type Cop.
52 |COT(lcop, rcop)  $\triangleq$  [lcop EXCEPT !.op = Xform(lcop.op, rcop.op), !.ctx = @  $\cup$  {rcop.oid}]

53 |-----|
54 |VARIABLES
  |For the client replicas:
58 |   cseq,      | cseq[c]: local sequence number at client c  $\in$  Client

```

For the server replica (the extended part):

62 *soids*, the set of operations the *Server* has executed

The 2D state spaces (*ss*, for short). Each client maintains one 2D state space. The server maintains *n* 2D state spaces, one for each client.

68 *css*, *css*[*c*]: the 2D state space at client  $c \in Client$

69 *ccur*, *ccur*[*c*]: the current node of *css*[*c*]

70 *sss*, *sss*[*c*]: the 2D state space maintained by the *Server* for client  $c \in Client$

71 *scur*, *scur*[*c*]: the current node of *sss*[*c*]

For all replicas

75 *state*, *state*[*r*]: state (the list content) of replica  $r \in Replica$

For communication between the *Server* and the Clients:

79 *cincoming*, *cincoming*[*c*]: incoming channel at the client  $c \in Client$

80 *sincoming*, *sincoming* channel at the *Server*

For model checking:

84 *chins* a set of chars to insert

---

85

86  $comm \triangleq \text{INSTANCE } CComm \text{ WITH } Msg \leftarrow Cop$

---

87

88  $eVars \triangleq \langle chins \rangle$  variables for the environment

89  $cVars \triangleq \langle cseq \rangle$  variables for the clients

90  $sVars \triangleq \langle soids \rangle$  variables for the *Server*

91  $cssVars \triangleq \langle css, ccur \rangle$  variables for 2D state spaces at clients

92  $sssVars \triangleq \langle sss, scur \rangle$  variables for 2D state spaces at the *Server*

93  $commVars \triangleq \langle cincoming, sincoming \rangle$  variables for communication

94  $vars \triangleq \langle eVars, cVars, sVars, commVars, cssVars, sssVars, state \rangle$  all variables

---

95

A 2D state space is a directed graph with labeled edges. It is represented by a record with node field and edge field. Each node is characterized by its context, a set of operations. Each edge is labeled with an operation and a direction flag indicating whether this edge is LOCAL or REMOTE. For clarity, we denote edges by records instead of tuples.

104  $IsSS(G) \triangleq$

105  $\wedge G = [node \mapsto G.node, edge \mapsto G.edge]$

106  $\wedge G.node \subseteq (\text{SUBSET } Oid)$

107  $\wedge G.edge \subseteq [from : G.node, to : G.node, cop : Cop, lr : \{Local, Remote\}]$

109  $TypeOK \triangleq$

For the client replicas:

113  $\wedge cseq \in [Client \rightarrow Nat]$

For the 2D state spaces:

117  $\wedge \forall c \in Client : IsSS(css[c]) \wedge IsSS(sss[c])$

118  $\wedge ccur \in [Client \rightarrow \text{SUBSET } Oid]$

119  $\wedge scur \in [Client \rightarrow \text{SUBSET } Oid]$

120  $\wedge state \in [Replica \rightarrow List]$

For communication between the server and the clients:

```

124     $\wedge comm!TypeOK$ 
      For model checking:
128     $\wedge chins \subseteq Char$ 
129  |-----|
      The Init predicate.
133  Init  $\triangleq$ 
      For the client replicas:
137     $\wedge cseq = [c \in Client \mapsto 0]$ 
      For the Server replica (the extended part):
141     $\wedge soids = \{\}$ 
      For the 2D state spaces:
145     $\wedge css = [c \in Client \mapsto [node \mapsto \{\{\}\}, edge \mapsto \{\}]]$ 
146     $\wedge ccur = [c \in Client \mapsto \{\}]$ 
147     $\wedge sss = [c \in Client \mapsto [node \mapsto \{\{\}\}, edge \mapsto \{\}]]$ 
148     $\wedge scur = [c \in Client \mapsto \{\}]$ 
      For all replicas:
152     $\wedge state = [r \in Replica \mapsto InitState]$ 
      For communication between the server and the clients:
156     $\wedge comm!Init$ 
      For model checking:
160     $\wedge chins = Char$ 
161  |-----|
      Locate the node in the 2D state space ss which matches the context ctx of cop.
165  Locate(cop, ss)  $\triangleq$  CHOOSE  $n \in (ss.node) : n = cop.ctx$ 

xForm: iteratively transform cop with a path through the 2D state space ss at some client,
following the edges with the direction flag d.
172  xForm(cop, ss, cur, d)  $\triangleq$ 
173    LET  $u \triangleq Locate(cop, ss)$ 
174     $v \triangleq u \cup \{cop.oid\}$ 
175    RECURSIVE xFormHelper( $-, -, -, -$ )
176    'h' stands for "helper"; xss: eXtra ss created during transformation
177    xFormHelper(uh, vh, coph, xss)  $\triangleq$ 
178    IF uh = cur
179    THEN xss
180    ELSE LET  $e \triangleq$  CHOOSE  $e \in ss.edge : e.from = uh \wedge e.lr = d$ 
181     $uprime \triangleq e.to$ 
182     $copprime \triangleq e.cop$ 
183     $coph2copprime \triangleq COT(coph, copprime)$ 
184     $copprime2coph \triangleq COT(copprime, coph)$ 
185     $vprime \triangleq vh \cup \{copprime.oid\}$ 
186    IN xFormHelper(uprime, vprime, coph2copprime,
187    [xss EXCEPT  $!.node = @ \circ \langle vprime \rangle$ ],

```

188 the order of recording edges here is important  
189 so that the last one is labeled with the final transformed operation  
190  $!.edge = @ \circ \langle [from \mapsto vh, to \mapsto vprime, cop \mapsto copprime2coph, lr \mapsto$   
191  $[from \mapsto uprime, to \mapsto vprime, cop \mapsto coph2copprime,$   
192 IN  $xFormHelper(u, v, cop, [node \mapsto \langle v \rangle,$   
193  $edge \mapsto \langle [from \mapsto u, to \mapsto v, cop \mapsto cop, lr \mapsto 1 - d] \rangle]$   
194  $\vdash$  Client  $c \in Client$  perform operation  $cop$  guided by the direction flag  $d$ .

198  $ClientPerform(cop, c, d) \triangleq$   
199 LET  $xss \triangleq xForm(cop, css[c], ccur[c], d)$   
200  $xn \triangleq xss.node$   
201  $xe \triangleq xss.edge$   
202  $xcur \triangleq Last(xn)$   
203  $xcop \triangleq Last(xe).cop$   
204 IN  $\wedge css' = [css \text{ EXCEPT } ![c].node = @ \cup Range(xn),$   
205  $![c].edge = @ \cup Range(xe)]$   
206  $\wedge ccur' = [ccur \text{ EXCEPT } ![c] = xcur]$   
207  $\wedge state' = [state \text{ EXCEPT } ![c] = Apply(xcop.op, @)]$

Client  $c \in Client$  issues an operation  $op$ .

211  $DoOp(c, op) \triangleq$   $op$ : the raw operation generated by the client  $c \in Client$   
212  $\wedge cseq' = [cseq \text{ EXCEPT } ![c] = @ + 1]$   
213  $op$  with the  $sctx$  field (the extended part)  
214  $\wedge \text{LET } cop \triangleq [op \mapsto op, oid \mapsto [c \mapsto c, seq \mapsto cseq'[c]], ctx \mapsto ccur[c], sctx \mapsto \{\}]$   
215 IN  $\wedge ClientPerform(cop, c, Remote)$   
216  $\wedge comm!CSend(cop)$

218  $DoIns(c) \triangleq$   
219  $\exists ins \in Ins :$   
220  $\wedge ins.pos \in 1 \dots (Len(state[c]) + 1)$   
221  $\wedge ins.ch \in chins$   
222  $\wedge ins.pr = Priority[c]$   
223  $\wedge chins' = chins \setminus \{ins.ch\}$  We assume that all inserted elements are unique.  
224  $\wedge DoOp(c, ins)$   
225  $\wedge \text{UNCHANGED } \langle sVars, sssVars \rangle$

227  $DoDel(c) \triangleq$   
228  $\exists del \in Del :$   
229  $\wedge del.pos \in 1 \dots Len(state[c])$   
230  $\wedge DoOp(c, del)$   
231  $\wedge \text{UNCHANGED } \langle sVars, sssVars, eVars \rangle$

233  $Do(c) \triangleq$   
234  $\vee DoIns(c)$   
235  $\vee DoDel(c)$

Client  $c \in Client$  receives a message from the *Server*.

```

239  $Rev(c) \triangleq$ 
240    $\wedge comm!CRev(c)$ 
241    $\wedge LET\ cop \triangleq Head(cincoming[c])$  the received (transformed) operation
242      $IN\ ClientPerform(cop, c, Local)$ 
243    $\wedge UNCHANGED \langle eVars, cVars, sVars, sssVars \rangle$ 
244 |-----|
245 | The Server performs operation cop.
246 |
247  $ServerPerform(cop) \triangleq$ 
248    $LET\ c \triangleq cop.oid.c$ 
249    $xss \triangleq xForm(cop, sss[c], scur[c], Remote)$ 
250    $xn \triangleq xss.node$ 
251    $xe \triangleq xss.edge$ 
252    $xcur \triangleq Last(xn)$ 
253    $xcop \triangleq Last(xe).cop$ 
254    $IN\ \wedge sss' = [cl \in Client \mapsto$ 
255      $IF\ cl = c$ 
256        $THEN\ [sss[cl] EXCEPT\ !.node = @ \cup Range(xn),$ 
257          $!.edge = @ \cup Range(xe)]$ 
258        $ELSE\ LET\ scurcl \triangleq scur[cl]$ 
259          $scurclprime \triangleq scurcl \cup \{cop.oid\}$ 
260          $IN\ [sss[cl] EXCEPT\ !.node = @ \cup \{scurclprime\},$ 
261            $!.edge = @ \cup \{[from \mapsto scurcl, to \mapsto scurclprime,$ 
262              $cop \mapsto xcop, lr \mapsto Remote]\}]$ 
263          $]$ 
264      $\wedge scur' = [cl \in Client \mapsto$ 
265        $IF\ cl = c\ THEN\ xcur\ ELSE\ scur[cl] \cup \{cop.oid\}]$ 
266      $\wedge state' = [state EXCEPT\ ![Server] = Apply(xcop.op, @)]$ 
267      $\wedge comm!SSendSame(c, xcop)$  broadcast the transformed operation
268 |-----|
269 | The Server receives a message.
270 |
271  $SRev \triangleq$ 
272    $\wedge comm!SRev$ 
273    $\wedge LET\ cop \triangleq [Head(sincoming) EXCEPT\ !.sctx = soids]$ 
274     cop with the sctx field (the extended part)
275    $IN\ \wedge soids' = soids \cup \{cop.oid\}$ 
276      $\wedge ServerPerform(cop)$ 
277    $\wedge UNCHANGED \langle eVars, cVars, cssVars \rangle$ 
278 |-----|
279 | The next-state relation.
280 |
281  $Next \triangleq$ 
282    $\vee \exists c \in Client : Do(c) \vee Rev(c)$ 
283    $\vee SRev$ 
284 |-----|
285 | The Spec. (TODO: Check the fairness condition.)
286 |
287  $Spec \triangleq Init \wedge \Box[Next]_{vars} \wedge WF_{vars}(Next)$ 
288 |-----|
289
290

```

\\* Modification History  
\\* *Last* modified *Wed Oct 31 17:26:33 CST 2018* by *hengxin*  
\\* Created *Tue Oct 30 20:32:27 CST 2018* by *hengxin*