```
- module OT -
EXTENDS Naturals, Sequences
CONSTANTS
    CH,
    POS,
    PR,
             for test only
    LOP.
    LOPS,
                 for test only
    ROP for test only
OP \stackrel{\triangle}{=} [type : \{ \text{"ins"}, \text{"del"} \}, pos : POS, ch : CH, pr : PR]
NOP \stackrel{\triangle}{=} CHOOSE \ v : v \notin OP
X form II(lins, rins) \stackrel{\triangle}{=} the left insertion transformed against the right insertion
    IF lins.pos < rins.pos
     THEN lins
     ELSE IF lins.pos > rins.pos
         THEN [lins EXCEPT !.pos = @ + 1]
          ELSE IF lins.ch = rins.ch
              THEN NOP
              ELSE IF lins.pr > rins.pr
                   THEN [lins EXCEPT !.pos = @ + 1]
                   ELSE lins
X form ID(ins, del) \stackrel{\Delta}{=}  the left insertion transformed against the right deletion
    IF ins.pos < del.pos
     THEN ins
     ELSE [ins EXCEPT !.pos = @-1]
XformDI(del, ins) \stackrel{\Delta}{=} the first deletion transformed against the right insertion
    If del.pos < ins.pos
     THEN del
     ELSE [del \ EXCEPT \ !.pos = @ + 1]
XformDD(ldel, rdel) \stackrel{\triangle}{=} the first deletion transformed against the right deletion
    If ldel.pos < rdel.pos
     THEN ldel
     ELSE IF ldel.pos > rdel.pos
          THEN [ldel \ EXCEPT \ !.pos = @ -1]
          ELSE NOP
Xform(lop, rop) \stackrel{\Delta}{=} the left operation is transformed against the right operation
    CASE lop.type = \text{``ins''} \land rop.type = \text{``ins''} \rightarrow XformII(lop, rop)
    \square lop.type = "ins" \land rop.type = "del" \rightarrow XformID(lop, rop)
    \square lop.type = "del" \land rop.type = "ins" \rightarrow XformDI(lop, rop)
    \square lop.type = "del" \land rop.type = "del" <math>\rightarrow XformDD(lop, rop)
```