Annotation Pipelines

There are a few robust and well designed microbial genome annotation pipelines that you can use to analyze your genome sequences. Each has its own benefits and drawbacks, and these may dictate which pipeline you end up using.

- RAST
- PROKKA
- PATRIC
- NCBI PGAP

Creating an assembled genome to annotate

The same approach that we have talked about in other modules was used to generate a test dataset, namely, downloading fastq data from SRA and then assembling the data with spades. To summarize, these are the commands that were used.

I downloaded the reads from ERS012013, which is part of Kat Holt's *Klebsiella* dataset (Project ID PRJEB2111), and assembled them using spades.

Statistic	Value
Number of sequences	4271
Total length	8,716,579
Shortest contig	56
Longest contig	86,652
N50	11,152
N75	28,825
	,

In all the cases below we use the scaffolds.fasta output from spades for subsequent analysis.

Example annotation using RAST

Start at the RAST website and from Your Jobs choose Upload a new Job. This opens up the file chooser page, and at the file chooser

select your scaffolds.fasta file. After that file is uploaded, you are presented with a summary of the contigs. Note that RAST may split some of the scaffolds that spades generated, and thus you may have slightly more contigs and slightly shorter sequence size, as shown here. The split happens on runs of N bases that




Figure 1: file chooser

spades inserts where it can estimate gaps between contigs based on sequence overlap.

Contig statistics

Statistic	As uploaded	After splitting into scaffolds
Sequence size	8716579	8654096
Number of contigs	4271	6027
GC content (%)	57.1	57.1
Shortest contig size	56	6
Median sequence size	571	374
Mean sequence size	2040.9	1435.9
Longest contig size	86652	86652
N50 value	11152	10463
L50 value	176	185

Figure 2: RAST summary statistics

The bottom of this page asks for information about the organism you have sequenced. If you enter the taxid, as shown here, the form should populate with information from NCBI.

There a series of questions about the annotation pipeline. Two recommended options are to build metabolic models and fix frameshifts, especially if you have a draft genome. Fixing frameshifts is controversial because some genomes (notably *Salmonella enterica serovar Typhi*) have a large number of frameshifts that are an evolutionary trait!

Note: at this stage you can also choose to customize some of the options for the RAST pipeline.

Genome information	tion:		
Taxonomy ID:	573	Fill in form based on NCBI taxonomy-ID.	
Taxonomy	Bacteria; Proteobacteria; Gammaproteobacteria;		
string:	Enterobacterales; Enterobacteriaceae; Klebsiella		
		//	
Domain:	 Bacteria Archaea 	Virus	
Genus:	Klebsiella		
Species:	pneumoniae		
Strain:			
Genetic Code:	11 (Archaea, most B	acteria, most Virii, and some Mitochondria)	
	4 (Mycoplasmaea, S_i Mitochondria)	oiroplasmaea, Ureoplasmaea, and Fungal	
Use this data and go to step 3			

Figure 3: RAST Job Information




Figure 4: RAST Pipeline

Example annotation using PROKKA

Note: The PROKKA GiutHub Site contains many other recipes and advances options for annotating the scaffolds.fasta file using PROKKA.

Example submission using PATRIC

To annotate the contigs using PATRIC, I first go to the PATRIC website and log in. If you don't have an account you will need to create one.

Create a new workspace called Klebsiella by clicking on the Workspaces menu and going to your home directory, and then clicking on the



Then use the p3 commands to submit the scaffolds.fasta file for annotation as a genome. You will need to follow these installation instructions to install the p3 commands, and at the moment they do not provide a CentOS version so it they are not included on the AWS instance.

Once you have installed p3, you will need to login:

p3-login

and provide the same credentials that you use for the website.

For the command, we need to provide several variables:

```
Varial Definition
      the
contigsource
file
      of
      the
      con-
      tigs
      (prob-
      a-
      bly
      scaf-
      folds.fasta
      from
      spades
      output)
```

Variab Definition

-n the

name

we

want

to

use

for

our

genome

Variab Definition

-t the

NCBI

Tax-

on-

omy

ID.

For

Kleb-

siella

pneu-

mo-

•

niae

this is

573.

This

is

used

to

en-

sure

that the

cor-

rect

pa-

ram-

e-

 ters

are used

for

the

an-

no-

ta-

tion

processes.

Vari	alDefinition
-d	the
	do-
	main
	(Bac-
	te-
	ria,
	Ar-
	chaea,
	Eu-
	karya,
	or
	Virus)

Then we provide the workspace and the file name to call it in the workspace.

p3-submit-genome-annotation --contigs-file scaffolds.fasta -n "Klebsiella pneumoniae NT21146