

Problem Set 08 Discussion

28 October 2025

Kayla Wilhoit

String Manipulation

- `str_replace_all()`
 - By itself – acts on a data frame, column, or vector and creates a new vector
 - Needs to be assigned to something

```
Gasch$Sample <- str_replace_all(Gasch$Sample, "[Hh]eat\\. [Ss]hock", "Heat.shock")
```

```
str_replace_all(gaschdata, pattern = "Heat.Shock|heat.shock", replacement = "Heat.shock")
```

```
pattern = c("heat\\.shock" = "Heat\\.shock", "Heat\\.Shock" = "Heat\\.shock"))
```

- `mutate()` plus `str_replace`
 - Acts on a data frame to create a new column

```
mutate(exp_cond = str_replace(  
  exp_cond,  
  regex("^(heat\\.shock|Heat\\.Shock)"),  
  "Heat.shock"))
```

```
mutate(sample = str_replace_all(sample,  
  pattern = '[hH]eat\\. [sS]hock',  
  replacement = "Heat\\.shock"))
```

Strings continued

- temp.shift column options

```
shift.pattern <- c("Heat.shock", "\\dC\\.to\\.\\.\\.d", "\\d\\.to\\.\\.\\.d", "\\d\\.to\\.\\.\\.dC")
```

```
str_detect(sample, "Heat\\.shock|\\.to\\.\\.|X33C\\.vs\\.\\.\\.30C")
```

```
str_detect(data$sample, "(Heat.shock)|\\.to\\.\\.")
```

- relocate – moving columns

```
relocate(sample, condition)
```