

# Problem Set 15 Discussion

27 Jan 2026

Kayla Wilhoit

# wget -i

- ``man wget`` can be more helpful than ``wget --help!``
- The `-i` flag lets you pass a file containing a list of specific filenames to wget, instead of a whole directory or running one command at a time

Note: You could also create this type of file manually in the VS Code text editor by copying and pasting from a source (less reproducible)

```
{bash}
touch urls.txt
echo https://raw.githubusercontent.com/nytimes/covid-19-data/refs/heads/master/rolling-averages/us-counties-2020.csv > urls.txt
echo https://raw.githubusercontent.com/nytimes/covid-19-data/refs/heads/master/rolling-averages/us-counties-2021.csv >> urls.txt
echo https://raw.githubusercontent.com/nytimes/covid-19-data/refs/heads/master/rolling-averages/us-counties-2022.csv >> urls.txt
echo https://raw.githubusercontent.com/nytimes/covid-19-data/refs/heads/master/rolling-averages/us-counties-2023.csv >> urls.txt
# check that they are all there
cat urls.txt

# run wget to download files
wget -i urls.txt
```

# Problem 5.f

```
{bash}  
cat us-states.csv | sed 's/date/year,month,day/' > us-states-expanded.csv
```

```
cat df | cut -f1 -d"," | awk -F'-' '{print $1"," $2"," $3","}' | grep -v "date" > date-split.csv
```

```
cat us-states.csv | sed -E 's/([0-9]{2})-([0-9]{2})-([0-9]{2})/\1,\2,\3/g' > sedstates.csv
```