




waag society

institute for art, science and technology

BioHack Academy Sterile Hood Design



Working sterile





Sterile hoods




Public Domain



Rudolph Simon - CC-BY-SA 3.0



José Eugenio Gómez Rodríguez - CC-BY-SA 2.0




Public Domain




Components

- Pre filter
- Fan
- HEPA Filter
- Minimal air flow of 0.5 m / second






Horizontal vs Vertical airflow







BioHack Academy 1 Design





BioHack Academy 2 Design





HEPA filter

- Fellowes office air filter
- 0.3 micron pores
- 99.97% filtering
- H14 class
 - EN1822 standard





Blower

- Calculate the airflow
- Needed:
 - $0.41 \times 0.32 \times 0.5 =$
 - 0.0656
 - cubic meter / second
- 236.16
- cubic meter / hour
- We choose 250 cubic meter / hour


$$1 \text{ CFM} = 1,6990 \text{ m}^3/\text{h}$$



IKEA



Test results





Schedule Monday / Tuesday

- Monday Morning:
 - 10:00 Sketchup instructions
 - 13:30 FabLab tour and demonstration
- Tuesday:
 - 10:00 Production and assembly of SterileHood



**some
rights
reserved**

These slides are published by Waag
Society under CC-BY-SA 4.0 license