

Package ‘ascct’

February 14, 2024

Type Package

Title Accelerated Sufficient Condition Conjunction Algorithm Based on Contingency Table

Version 1.0

Date 2024-02-11

Author Wei Xu

Maintainer Wei Xu <eric.wxu@hotmail.com>

Description Pkg{ascct} is a package to perform the Accelerated Sufficient Condition Conjunction Algorithm Based on Contingency Table.

License GPL (>= 2)

Encoding UTF-8

LinkingTo Rcpp

Imports Rcpp,plyr,purrr,stringr,admisc,dplyr

RoxygenNote 7.1.0

NeedsCompilation yes

ExperimentalWindowsRuntime ucrt

Archs x64

R topics documented:

ascct-package	2
ascct	2
ascctonepattern	3
bocorrection	4
chi2test	5
generatecombineall	6
samplescount	7
Index	8

ascct-package	<i>Accelerated Sufficient Condition Conjunction Algorithm Based on Contingency Table</i>
---------------	--

Description

Pkgascct is a package to perform the Accelerated Sufficient Condition Conjunction Algorithm Based on Contingency Table.

Author(s)

Author:

Wei Xu

Maintainer:

Wei Xu <eric.wxu@hotmail.com>

References

Baumgartner, Michael.(2009). Inferring Causal Complexity. Sociological Methods & Research. 38. 10.1177/0049124109339369.

ascct	<i>Accelerated Sufficient Condition Conjunction Algorithm Based on Contingency Table</i>
-------	--

Description

This function completes the calculation of ascct analysis.

Usage

```
ascct(sccsamples,mvsccsamples,maxnumofconditions,consistencythreshold,coveragethreshold)
```

Arguments

sccsamples	Dataset.
mvsccsamples	Dataset with multivalue coding.
maxnumofconditions	Maximum order of combinations.
consistencythreshold	Threadhold of consistency.
coveragethreshold	Threadhold of coverage.

Value

The ascct solution.

Value

A numeric value of pvalue in the pearsons chisquared by bonferroni correction..

References

Benjamini, Y. and D. Yekutieli (2001). The control of the false discovery rate in multiple testing under dependency. The Annals of Statistics. 29: 1165-1188.

Examples

```
library(purrr)
library(plyr)
library(stringr)
mvscsamples<-data.frame(
  V1=c(1,2,1,1,1,1,1,1,1,3,1,1,1,3,3,1,3,1,1,1,1,1,1,2,1,1,1,3,1,1,1,1,1,1,1),
  V2=c(1,3,1,1,1,2,1,1,1,1,1,1,1,1,1,1,1,1,1,2,1,1,1,1,1,1,3,1,1,1,2,1,3,1,1,3,1),
  V3=c(1,1,1,1,3,1,1,1,2,1,3,1,1,1,1,3,1,1,1,1,1,1,1,1,1,2,1,1,1,1,1,1,3,1,3,1),
  V4=c(2,1,3,1,1,1,1,1,1,1,1,1,1,1,1,1,1,1,2,1,1,1,1,1,1,2,1,1,1,1,1,1,1,1,1),
  V5=c(1,1,2,1,1,1,1,1,1,3,1,1,2,1,1,1,1,1,1,1,3,1,1,1,1,1,1,1,1,1,1,1,3,1,1,2,1,3),
  V6=c(1,1,1,1,1,1,1,1,1,1,1,1,1,1,1,1,1,1,2,2,2,2,2,2,2,2,2,2,2,2,2,2,2,2,2,2,2)
)
screencom<-c(3,4)
pvalue<-chi2test(screencom,mvscsamples)
numofsnps<-ncol(mvscsamples)-1
pvaluewithbc<-bocorrection(screencom,pvalue,numofsnps)
```

chi2test

Chisquaretest for the Pattern in the Source Data

Description

This function tests whether the pattern is related to the depend variable in the source dataset by Pearson's Chi-squared test.

Usage

```
chi2test(pattern,mvscsamples)
```

Arguments

pattern	the pathogenic pattern,for example,"[2,3]" denotes the mutation of the sceond and the third snp.
mvscsamples	the data of samples.

Value

A numeric value of pvalue in the Pearsons Chi-squared test.

References

Haviland MG. Yates's correction for continuity and the analysis of 2 x 2 contingency tables. Stat Med. 1990 Apr;9(4):363-7; discussion 369-83. doi: 10.1002/sim.4780090403. PMID: 2362976.

Examples

```
library(purrr)
library(plyr)
library(stringr)
mvscsamples<-data.frame(
  V1=c(1,2,1,1,1,1,1,1,1,3,1,1,1,3,3,1,3,1,1,1,1,1,1,2,1,1,1,3,1,1,1,1,1,1,1,1),
  V2=c(1,3,1,1,1,2,1,1,1,1,1,1,1,1,1,1,1,1,1,2,1,1,1,1,1,3,1,1,1,2,1,3,1,1,3,1),
  V3=c(1,1,1,1,3,1,1,1,2,1,3,1,1,1,1,3,1,1,1,1,1,1,1,1,2,1,1,1,1,1,1,1,3,1,3,1),
  V4=c(2,1,3,1,1,1,1,1,1,1,1,1,1,1,1,1,1,1,1,2,1,1,1,1,1,2,1,1,1,1,1,1,1,1,1,1),
  V5=c(1,1,2,1,1,1,1,1,1,1,1,2,1,1,1,1,1,1,1,2,1,1,1,1,1,1,1,1,1,1,1,1,1,1,1,2)
)
pattern<-c(2,3)
pvalue<-chi2test(pattern,mvscsamples)
```

generatecombineall	<i>Generate all the combinations less than or equal to the max order</i>
--------------------	--

Description

This function generates all the combinations less than or equal to the max order.

Usage

```
generatecombineall(conditionalvarvec,maxorder)
```

Arguments

conditionalvarvec
the vector of the conditional variables.

maxorder
the maximum order specified.

Value

A list of the combinations.

References

Lockwood, Elise, Gibson, Bryan R..Combinatorial tasks and outcome listing: Examining productive listing among undergraduate students[J].Educational Studies in Mathematics.2016,91(2).

Examples

```
library(purrr)
library(plyr)
library(stringr)
conditionalvarvec<-c(1:8)
maxorder=3
allcombinations<-generatecombineall(conditionalvarvec,maxorder)
```

samplescount

Generate a contingency table for the Source Data

Description

This function generate a contingency table for the source data.

Usage

```
samplescount(pattern,mvscsamples)
```

Arguments

pattern The condition combination.
mvscsamples Dataset.

Value

A contingency table for the source data as matrix.

References

Gravetter, F. J., & Wallnau, L. B. (2010). Essentials of Statistics for the Behavioral Sciences (PSY 200 (300) Quantitative Methods in Psychology). Boston: Cengage Learning.

Examples

```
library(purrr)
library(plyr)
library(stringr)
mvscsamples<-data.frame(
  V1=c(1,2,1,1,1,1,1,1,1,3,1,1,1,3,3,1,3,1,1,1,1,1,1,1,2,1,1,1,3,1,1,1,1,1,1,1,1),
  V2=c(1,3,1,1,1,1,2,1,1,1,1,1,1,1,1,1,1,1,1,1,1,2,1,1,1,1,1,1,3,1,1,1,2,1,3,1,1,3,1),
  V3=c(1,1,1,1,3,1,1,1,2,1,3,1,1,1,1,3,1,1,1,1,1,1,1,1,1,1,2,1,1,1,1,1,1,1,3,1,3,1),
  V4=c(2,1,3,1,1,1,1,1,1,1,1,1,1,1,1,1,1,1,1,2,1,1,1,1,1,1,2,1,1,1,1,1,1,1,1,1,1,1),
  V5=c(1,1,2,1,1,1,1,1,1,1,3,1,1,2,1,1,1,1,1,1,1,3,1,1,1,1,1,1,1,1,1,1,1,1,3,1,1,2,1,3),
  V6=c(1,1,1,1,1,1,1,1,1,1,1,1,1,1,1,1,1,1,1,1,1,2,2,2,2,2,2,2,2,2,2,2,2,2,2,2,2,2,2,2)
)
pattern<-c(2,3)
contingencytable<-samplescount(pattern,mvscsamples)
```

Index

ascct, [2](#)
ascct-package, [2](#)
ascctonepattern, [3](#)

bocorrection, [4](#)

chi2test, [5](#)

generatecombineall, [6](#)

samplescount, [7](#)