

SUPPORTING INFORMATION TOWARDS  
**HIGH ASYMMETRIC LONGITUDINAL FIELD ION MOBILITY  
SPECTROMETRY (HALF-IMS) DEVICE FOR LOW POWER  
MOBILE CHEMICAL SEPARATION AND DETECTION**

Yuriy Zrodnikov<sup>1,§</sup>, Maneeshin Y. Rajapakse<sup>1</sup>, Daniel J. Peirano<sup>1,†</sup>, Alexander A. Aksenov<sup>1,‡</sup>, Nicholas J. Kenyon<sup>2,3,4</sup> and Cristina E. Davis<sup>1,\*</sup>

<sup>1</sup> Department of Mechanical and Aerospace Engineering, University of California Davis, Davis, CA 95616, USA.

<sup>2</sup> Department of Internal Medicine, 4150 V Street, Suite 3400, University of California, Davis, Sacramento, CA 95817, USA.

<sup>3</sup> Center for Comparative Respiratory Biology and Medicine, University of California, Davis, CA 95616, USA.

<sup>4</sup> VA Northern California Health Care System, 10535 Hospital Way, Mather, CA 95655, USA.

§ presently at Intel Corporation, Inc.

† presently at Google, Inc.


‡ presently at University of California, San Diego

---

ABSTRACT of Supporting Information: Supporting information covers the circuitry schematics of the HALF-IMS device and the automated control of testing setup of HALF-IMS using LABVIEW

---

Voltage input amplification:



Current measurement:




Figure S-1: Circuitry schematics for upper and lower HALF-IMS planes.




Figure S-2: Automated control of testing setup using LABVIEW