

# Applied Genome Research

## *De novo* transcriptome assembly

205048 & 205049

Boas Pucker



(<https://github.com/trinityrnaseq/trinityrnaseq/wiki>)

Generates initial  
assembly of  
dominant isoforms

Constructs graph of  
common sequences  
and unique  
sequences of  
different isoforms

Resolves graph and  
reports separate isoforms  
(final assembly)

# Assembly requires trimming of reads

- Why is trimming required?
  - Removal of adapters to avoid artificial joins
- Start trimmomatic in SE mode on the RNA-Seq read sets!

# Running Trinity


```
$ Trinity \  
--normalize_reads \  
--seqType fq \  
--max_memory 20G \  
--single <INPUT>.fastq \  
--CPU 6 \  
--output <OUTPUT_DIRECTORY>
```

# Trinity on cluster

```
1  #!/bin/bash
2  echo "Trinity \
3  --normalize_reads \
4  --seqType fq \
5  --max_memory 10G \
6  --left 1_1P.fastq,2_1P.fastq \
7  --right 1_2P.fastq,2_2P.fastq \
8  --CPU 4 \
9  --output <SOME_DIRECTORY>" \
10 | qsub \
11 -cwd \
12 -N iGEM_trin \
13 -l vf=10G -l arch=lx-amd64 -l idle=1 \
14 -P fair_share \
15 -pe multislots 20 \
16 -o output.txt \
17 -e error.txt
```

# Components of Trinity

Illumina reads





Contigs





Contig clusters





de Bruijn graphs



Reconstructed isoforms



# General analysis concept




<https://doi.org/10.3389/fmolb.2018.00062>

# Best practice workflow

- 1) Generate resource report:  
trinityrnaseq-Trinity-v2.4.0/trinity-plugins/COLLECTL/examine\_resource\_usage\_profiling.pl collect
- 2) Check assembly for full length transcripts => BLASTx vs. nr
- 3) Analyze tophit coverage
- 4) Check integrated hits via bowtie mapping against assembly
- 5) Calculate Nx stats e.g. Ex90N50 (N50 is not useful)
- 6) Run BUSCO to check assembly completeness
- 7) Run Interproscan to assign GO terms




# Assembly evaluation – Nx for continuity quantification




Contigs are sorted by decreasing size.

Contigs sum up to  
50% of total  
assembly size

# Assembly evaluation – Ex90N50




Sorting contigs by expression and selecting all sequences that account for 90% of all expression



Contigs sum up to 50% of selected assembly fraction

# Saturation of assembly size



# BUSCO

- “quantitative measures for the assessment of genome assembly, gene set, and transcriptome completeness, based on evolutionarily-informed expectations of gene content from near-universal single-copy orthologs ”
- <https://busco.ezlab.org/>
- Applications: assembly completeness assessment, estimation of heterozygosity, optimization of gene prediction, identification of paralogs, ...

# Gene Ontology (GO) terms

- <http://geneontology.org/>
- Computational representation of biological knowledge
- Over 40k biological concepts
- Used for automatic annotation of predicted genes
- GO enrichment analyses (e.g. in RNA-Seq studies)

# Construct GFF3

- One feature/entry in GFF3 file is created per sequence in FASTA file
- Length of sequences is used to determine start/end
- Running number is used to generate unique IDs


# EXERCISE

- 1) Run 'contig\_stats.py' on Trinity.fasta!
- 2) Use STAR to map all WT and 3xmyb reads to assembly!
- 3) Construct reference file for read counting via 'fasta2gff.py'!
- 4) Use featureCounts to get expression values! (feature type = mRNA)
- 5) Construct heatmap via 'construct\_heatmap.py'! (see tips)

# Construct Heatmap

Add your own file paths and file names!

```
if __name__ == '__main__':  
    candidate_gene_file = "<ADD_YOUR_PATH>/candidate_seqs.txt" #file with up to 5 selected contigs/unigenes  
    data_files = [ { 'id': "WT", "file": "<YOUR_FILE_NAME_WT>.count_table" },  
                   { 'id': "mut", "file": "<YOUR_FILE_NAME_MUT>.count_table" }  
                  ]  
    cutoff = 0 #minimal cumulative expression of gene in all tissues combined  
    prefix = "<YOUR_OUTPUT_DIRECTORY>"
```

A large red arrow points down to the placeholder "<ADD\_YOUR\_PATH>". Two red arrows point left to the placeholders "<YOUR\_FILE\_NAME\_WT>" and "<YOUR\_FILE\_NAME\_MUT>". A red arrow points up to the placeholder "<YOUR\_OUTPUT\_DIRECTORY>".

Run script like always: `python construct_heatmap.py`



# EXERCISE

- Identify MYB11, MYB12, and MYB111 via BLAST!
- Is there expression different between samples?