

# Somatic SNV Calling

Andy Lynch

CRUK CI

July 2016

# Outline

---

This morning's session:

- **An example processing pipeline**
- **Some calling tools**
- **How well should you expect a tool to perform?**
- **Some special cases**


# Somatic SNV calling

---


An example processing pipeline

# A processing pipeline


---




# A processing pipeline




# A processing pipeline



# A processing pipeline




# A processing pipeline





# A processing pipeline



# Somatic SNV calling

---

SNV-calling tools

# The SNV caller is not the only concern

---

We use CaVEMan here.

Caveat – full details of CaVEMan are not explicitly reported anywhere, and I am not going to go through the code (java). So all a bit of a black box

- **Seems to have a sensible Bayesian model**
- **Considers base quality, read position, lane, and read orientation**
- **Can make use of copy number profiles**
- **Associated filters**

One could argue that any sensible caller would do the job. The secret is in the filtering.

# Other tools

---

## Several tools worth considering:

The detail of

- **MuTect2** – Combines a good quality caller with haplotype reassembly. Built in filters and the ability to take in a panel of normal samples. Can also return indels.
- **VarScan2 (Koboldt 2012)** – Uses a basic statistical test rather than a full Bayesian model, but will probably be followed by filtering anyway. A portable java program.
- **Strelka (Saunders 2012)** – A hierarchical model of allele frequencies. Also returns indels.
- **SMuFin (Moncunill 2014)** – A reference free variant caller with high specificity.

# Somatic SNV calling

---

Anticipated performance

# How well should we expect a tool to perform?

Precision/recall is a function of the biology, the sample/data quality, and the calling method.

■ When you see a tool promising a particular precision/recall, how will it perform for you?


■ The precision and recall are averaged over many SNVs and typically over many samples (although not in this illustration)

■ The two things affecting precision and recall are the ability to deal with artefacts, and the genuine power of the study

■ Typically we have the power to detect SNVs that are present in two or more copies in every cell, but those in one copy, or sub-clonal, are more often missed

■ A sample with relatively more of these recent events will have lower recall/precision

■ A sample with generally low power will have lower recall/precision



# Somatic SNV calling

---

Some special cases

# What if you have multiple tumour samples

## Exploring heterogeneity

Datasets that are more than Tumour-Normal are increasingly common. What can be done for variant calling in them?

Theoretically, we can draw strength from related samples to improve our sensitivity.

Still require a filtering regime afterwards.

- **VarScan2 (Koboldt 2012)** offers the ability to call over multiple samples, but doesn't appear to make the best use of structure in those calls

- **FreeBayes (Garrisson 2012)** can be applied to this task, but the set-up is not optimized for this scenario

- **Platypus (Rimmer 2014)** can be applied to this task. Although it is primarily a germline caller, it does a good job

- **multiSNV (Josephidou 2015)** was designed specifically for the task. It works particularly well in combination with Platypus



# What if you have RNA-seq data?

## Things get trickier.

We need to stop worrying about recall – there will be a lot missed, and splicing activity and post-transcriptional modifications will introduce artefacts that require new filters.

Nevertheless, there are data to be interrogated...

- **Tophat (Kim et al. 2013) + Isaac (Raczy 2013) variant caller.** Isaac not specifically designed for RNA-seq.

- **MAP-RSeq (Kalari et al. 2014).** Tophat + GATK-based approach. Large suite of tools – not a nimble solution.

- **RNASEQR (Chen et al. 2011).** A Bowtie-based approach that takes several passes at the alignment to remove splice-site driven artefacts. Low precision?

- **SNPiR (Piskol et al. 2013).** More expensive aligner to address the problems. Not really designed for somatic variants. See also SNVQ.

- **GLMVC (Sheng et al. 2016).** Specifically for somatic. Addresses cycle bias, but this could be filtered later.

# What if you have no matched normal

Obvious strategies:

- **Treat the sample as if it were a normal sample in which you were calling variants. Cellularity allowing, it is probable that somatic events will look like germline heterogeneous SNPs.**

- **Use a relative's, or ethnically-matched, normal sample and run as a T:N pair.**

Either approach will lead to an excess of a couple of million calls, so filtering is required

- **dbSNP**

- **Cellularity-driven distinctions in allele-fraction may help**

These should reduce the numbers substantially, but there will still be an excess

# What if you have cell-lines

Generally won't have matched normal or cellularity


Recently in this situation with OAC cell lines

Clearly too many variants being called

Exonic regions give a feel for the overall performance


A

Detected variants in each cell line (absolute Values)



B

Coding sequence variant mean distribution (non UTR)



Contino et al. 2016

# References

- Alioto T. S. et al. (2015). A comprehensive assessment of somatic mutation detection in cancer using whole-genome sequencing. *Nature Communications*, 6, 10001.
- Kim D. et al. (2013). TopHat2: accurate alignment of transcriptomes in the presence of insertions, deletions and gene fusions. *Genome Biology*, 14(4), R36.
- Raczy C. et al. (2013). Isaac: Ultra-fast whole genome secondary analysis on Illumina sequencing platforms. *Bioinformatics*, btt314.
- Kalari K. R. et al. (2014). MAP-RSeq: Mayo Analysis Pipeline for RNA sequencing. *BMC Bioinformatics*, 15(1), 224.
- Chen L. Y. et al. (2012). RNASEQR-a streamlined and accurate RNA-seq sequence analysis program. *Nucleic Acids Research*, 40(6), 1–12.
- Piskol R. et al. (2013). Reliable identification of genomic variants from RNA-seq data. *American Journal of Human Genetics*, 93(4), 641–651.
- Sheng Q. et al. (2016). Practicability of detecting somatic point mutation from RNA high throughput sequencing data. *Genomics*, 107(5), 163–169.
- Contino G. et al. (2016). Whole-genome sequencing of nine esophageal adenocarcinoma cell lines, 1336(633974), 1–8.
- Koboldt D. C. et al. (2012). VarScan 2: Somatic mutation and copy number alteration discovery in cancer by exome sequencing. *Genome Research*, 22(3), 568–576

# References

- Saunders C. T. et al. (2012). Strelka: accurate somatic small-variant calling from sequenced tumor-normal sample pairs. *Bioinformatics* (Oxford, England), 28(14), 1811–7.
- Moncunill V et al. (2014). Comprehensive characterization of complex structural variations in cancer by directly comparing genome sequence reads. *Nature Biotechnology*, 32(11), 1106–1112.
- Garrison E, Marth G. Haplotype-based variant detection from short-read sequencing. *arXiv preprint arXiv:1207.3907 [q-bio.GN]* 2012
- Rimmer A. et al. (2014). Integrating mapping-, assembly- and haplotype-based approaches for calling variants in clinical sequencing applications. *Nature Genetics*, 46(8), 912–918.
- Josephidou M. et al. (2015). multiSNV: a probabilistic approach for improving detection of somatic point mutations from multiple related tumour samples. *Nucleic Acids Research*, 1–9.