

UNIL | Université de Lausanne




Swiss Institute of Bioinformatics

```
ENSMUSG00000023051, ENSMUSG00000040629, ENSMUSG00000058398, ENSMUSG00000025235, ENSMUSG00000048118,
ENSMUSG00000026567, ENSMUSG00000047014, ENSMUSG00000005506, ENSMUSG00000016758, ENSMUSG00000050799,
ENSMUSG00000026790, ENSMUSG00000062300, ENSMUSG00000001157, ENSMUSG00000048003, ENSMUSG00000040850,
ENSMUSG00000028614, ENSMUSG00000047003, ENSMUSG00000029707, ENSMUSG00000036478, ENSMUSG00000028962,
ENSMUSG00000060499, ENSMUSG00000063889, ENSMUSG00000062438, ENSMUSG00000040841, ENSMUSG00000053729,
ENSMUSG00000045179, ENSMUSG00000003549, ENSMUSG00000007907, ENSMUSG00000051306, ENSMUSG00000049470,
ENSMUSG00000026650, ENSMUSG00000024352, ENSMUSG00000024116, ENSMUSG00000063415, ENSMUSG00000072479,
ENSMUSG00000036211, ENSMUSG00000038994, ENSMUSG00000016626, ENSMUSG00000035246, ENSMUSG00000026360,
ENSMUSG00000029516, ENSMUSG00000060794, ENSMUSG00000028427, ENSMUSG00000028426, ENSMUSG00000068037,
ENSMUSG00000072663, ENSMUSG00000017767, ENSMUSG00000032921, ENSMUSG00000037017, ENSMUSG00000051965,
ENSMUSG00000038227, ENSMUSG0000005672, ENSMUSG00000003131, ENSMUSG00000028410, ENSMUSG00000028894,
ENSMUSG00000006527, ENSMUSG00000072770, ENSMUSG00000024176, ENSMUSG00000026234, ENSMUSG00000049539,
ENSMUSG00000051617, ENSMUSG00000040891, ENSMUSG00000096769, ENSMUSG00000037001, ENSMUSG00000039781,
ENSMUSG00000038210, ENSMUSG00000051977, ENSMUSG00000019834, ENSMUSG00000023070, ENSMUSG00000027794,
ENSMUSG00000026463, ENSMUSG00000040407, ENSMUSG00000027793, ENSMUSG00000028760, ENSMUSG0000002015,
ENSMUSG00000027433, ENSMUSG00000071470, ENSMUSG00000005883, ENSMUSG00000006731, ENSMUSG00000071359,
ENSMUSG00000030968, ENSMUSG00000031931, ENSMUSG00000005893, ENSMUSG00000002384, ENSMUSG0000000085,
ENSMUSG00000027660, ENSMUSG00000024392, ENSMUSG00000025482, ENSMUSG00000063972, ENSMUSG00000029848,
ENSMUSG00000090083, ENSMUSG00000075706, ENSMUSG00000096620, ENSMUSG00000014361, ENSMUSG00000038797,
ENSMUSG00000031922, ENSMUSG00000011349, ENSMUSG00000036529, ENSMUSG00000056131, ENSMUSG00000038709,
ENSMUSG00000020063, ENSMUSG00000020064, ENSMUSG00000032280, ENSMUSG00000049721, ENSMUSG00000081218,
ENSMUSG00000048516, ENSMUSG00000021038, ENSMUSG00000027938, ENSMUSG00000050957, ENSMUSG00000024426,
ENSMUSG00000068117, ENSMUSG00000047654, ENSMUSG00000069565, ENSMUSG00000027939, ENSMUSG00000035431,
ENSMUSG00000092118, ENSMUSG00000043050, ENSMUSG00000034579, ENSMUSG00000033487, ENSMUSG00000033486,
ENSMUSG00000031065, ENSMUSG00000021264, ENSMUSG00000083628, ENSMUSG00000020059, ENSMUSG00000024778,
ENSMUSG00000043289, ENSMUSG00000002768, ENSMUSG0000001558, ENSMUSG00000058328, ENSMUSG00000038932,
ENSMUSG00000037716, ENSMUSG00000056155, ENSMUSG00000021499, ENSMUSG00000074704, ENSMUSG00000025977,
ENSMUSG00000010592, ENSMUSG00000032498, ENSMUSG00000020390, ENSMUSG00000020150, ENSMUSG00000024990,
ENSMUSG00000071788, ENSMUSG00000021007, ENSMUSG00000046532, ENSMUSG0000000567, ENSMUSG00000050623,
ENSMUSG00000040828, ENSMUSG00000040829, ENSMUSG00000056215, ENSMUSG00000023010, ENSMUSG0000002799,
ENSMUSG0000001225, ENSMUSG00000041912, ENSMUSG00000023015, ENSMUSG00000027855, ENSMUSG00000024107,
ENSMUSG00000056223, ENSMUSG00000032076, ENSMUSG00000059970, ENSMUSG00000023000, ENSMUSG00000002324,
ENSMUSG00000020096, ENSMUSG00000020097, ENSMUSG00000079681, ENSMUSG00000049932, ENSMUSG00000027722,
ENSMUSG00000028938, ENSMUSG00000036551, ENSMUSG00000070999, ENSMUSG00000059625, ENSMUSG00000032187,
ENSMUSG00000033031, ENSMUSG00000022021, ENSMUSG00000048731, ENSMUSG00000079470, ENSMUSG00000044288,
ENSMUSG00000024207, ENSMUSG00000045378, ENSMUSG00000027719, ENSMUSG00000037992, ENSMUSG00000036545,
ENSMUSG00000013787, ENSMUSG00000035578, ENSMUSG00000037514, ENSMUSG00000020193, ENSMUSG00000021040,
ENSMUSG0000000365, ENSMUSG00000082639, ENSMUSG00000024430, ENSMUSG0000003873, ENSMUSG00000060985,
ENSMUSG00000025407, ENSMUSG00000014767, ENSMUSG00000071748, ENSMUSG00000037625, ENSMUSG00000094727,
ENSMUSG00000029155, ENSMUSG00000028063, ...
```

How to characterize gene lists?

Functional categories enriched among these genes

- Gene Ontology enrichment test
- GSEA
- Pathways analysis
- **-** . . .



Gene Ontology enrichment test

For each functional category:

	Gene list Other genes		
Annotaated	n ₁	n ₃	
Not annotaated	n_2	n ₄	

Fisher / Hypergeometric test

```
• Bioconductor: topGO, GOstats, goseq,...
```


How to characterize gene lists?

Functional categories enriched among these genes?

- Gene Ontology enrichment test
- GSEA
- Pathways analyses
- **-** . . .



- Gene expression atlases
- TopAnat






Quick reminder:

- Only "normal" samples: no tumors, no mutants, no treatments
- RNA-seq, microarray, EST, in situ hybridization data from 17 animal species
- Manual mapping to Uberon ontology of anatomy and development

Uberon anatomical ontology





Quick reminder:

- Only "normal" samples: no tumors, no mutants, no treatments
- RNA-seq, microarray, EST, in situ hybridization data from 17 animal species
- Manual mapping to Uberon ontology of anatomy and development
- Data reprocessed as presence/absence calls

Gene Ontology enrichment test

For each functional category:

	Gene list Other genes		
Annotated	n_1	n ₃	
Not annotaated	n ₂	n ₄	

Fisher / Hypergeometric test

TopAnat test


For each anatomical structure:

	Gene list Other genes		
Expressed	n ₁	n ₃	
Not expressed	n ₂	n ₄	

Fisher / Hypergeometric test

Implementation

- Based on topGO package
- Extension of topGOdata class
 - Accommodate Uberon Ontology
 - Use custom gene mapping



http://bgee.org/?page=top_anat

BgeeDB

http://www.bioconductor.org/packages/BgeeDB/

 Komljenovic*, Roux*, Robinson-Rechavi and Bastian (2016) BgeeDB, an R package for retrieval of curated expression datasets and for gene list expression localization enrichment tests. F1000Research, 5:2748



BgeeDB use case

TopAnat test:

- **Foreground**: 150 Ensembl genes with *phenotype* related to pectoral fin, retrieved from ZFIN database
- Background: 3,136 Ensembl genes with an annotated phenotype in ZFIN



```
Emacs@julien.home
> library(biomaRt)
# zebrafish data in Ensembl 85 (stable link)
> ensembl <- useMart("ENSEMBL MART ENSEMBL",</pre>
                    dataset="drerio gene ensembl",
                     host="jul2016.archive.ensembl.org")
# get the mapping of Ensembl genes to phenotypes
> genesToPhenotypes <- getBM(filters=c("phenotype source"),</pre>
                            value=c("ZFIN"),
                             attributes=c("ensembl gene id",
                                   "phenotype description"),
                            mart=ensembl)
# select phenotypes related to pectoral fin
> myPhenotypes <- grep("pectoral fin",</pre>
            unique (genesToPhenotypes$phenotype description),
            value=T)
# select the genes annotated to select phenotypes
> myGenes <- unique(genesToPhenotypes$ensembl gene id[</p>
 genesToPhenotypes$phenotype description %in% myPhenotypes])
```

..\$ ENSDARG0000000002: chr [1:11] "UBERON:0000019" "UBERON:0000468" ## ..\$ ENSDARG0000000018: chr [1:28] "UBERON:0000019" "UBERON:0000080" ... ## \$ organ.relationships:List of 12587 ## ..\$ AEO:0000013 : chr "UBERON:0000479" ## ..\$ AEO:0000127 : chr "UBERON:0005423" ## ..\$ AEO:0000173 : chr [1:2] "UBERON:0002416" "UBERON:0000020" ## \$ organ.names : 'data.frame': 12588 obs. of 2 variables: ## ..\$ ID : chr [1:12588] "AEO:0001009" "AEO:0001010" "AEO:0001013" "CL:0000005" ... ## ..\$ NAME: chr [1:12588] "proliferating neuroepithelium" "differentiating neuroepithelium" "neuronal column" "fibroblast neural crest derived" ... ## \$ bgee.object :Reference class 'Bgee' [package "BgeeDB"] with 13 fields



```
# Prepare the TopAnat object
> myTopAnatDataObject <- topAnat(myTopAnatData, geneList)</pre>
 Launch the enrichment test using topGO algorithms
> results <- runTest(myTopAnatDataObject,</pre>
                      statistic='Fisher',
                      algorithm='weight')
# Retrieve anatomical structures enriched (FDR=1%)
> tableOver <- makeTable(myTopAnatData,</pre>
                          myTopAnatDataObject,
                          results,
                          cutoff=0.01)
```

Organ name	Enrichment fold	P-value	FDR
pectoral appendage field	12.7	4.00E-10	7.14E-08
pectoral appendage cartilage tissue	10.7	2.41E-08	3.58E-06
ceratohyal cartilage	7.6	4.76E-08	6.06E-06
median fin fold	7.1	7.17E-12	2.13E-09
fin bone	6.5	4.29E-06	0.000478091
bone of free limb or fin	6.1	7.95E-05	0.004168941
irregular bone	6.0	8.17E-06	0.000659745
dorsal hyoid arch skeleton	5.9	0.000107699	0.004817668
paired limb/fin bud	5.7	1.62E-22	1.45E-19
endochondral bone	5.4	7.11E-06	0.000633841
dermal bone	4.8	8.89E-06	0.000659745
mouth	4.4	0.000101104	0.004817668
pharyngeal epithelium	4.0	4.89E-06	0.000483901
hypoblast (generic)	3.6	1.12E-05	0.000713807
pectoral fin	3.4	1.04E-18	4.62E-16
germ ring	3.2	3.95E-05	0.002344194
skin epidermis	3.0	6.22E-05	0.003463408
ear vesicle	2.7	3.14E-10	6.98E-08
endoderm	2.7	0.000108141	0.004817668
pharyngeal arch	2.4	1.08E-05	0.000713807
cranium	2.2	0.000129452	0.005492447
immature eye	1.8	0.000190297	0.007707016

Conclusions

- TopAnat is a new way to make biological sense of gene lists
- Gene annotation entirely experimental!
- BgeeDB is a versatile way of running TopAnat analyses

Add BgeeDB to your toolbox!

Thanks!

http://www.bioconductor.org/packages/BgeeDB/

 Komljenovic*, Roux*, Robinson-Rechavi and Bastian (2016) BgeeDB, an R package for retrieval of curated expression datasets and for gene list expression localization enrichment tests. F1000Research, 5:2748



