

REFERENCE BASELINE / NO CLIENT-SPECIFIC DATA


Veoveo UAF 1.3 / SysML 1.6 Reference Architecture

Veoveo is an organization-owned MCP platform for governed capabilities, durable work, artifacts, recordings, analytical decision support, and autonomous agents. This architecture describes the complete scoped software structure and connects it to enterprise capabilities, operational mission threads, services, security controls, deployment configurations, requirements, and repository evidence.

Version 0.1.0 Revision 2026-07-14 Source commit 64a5977aeb57 48 software resources 33 interfaces 18 requirements

Document control

Title	Veoveo UAF 1.3 / SysML 1.6 Reference Architecture
Architecture identity	VV-MODEL-001
Purpose	Generic reference architecture for formal client review and model exchange.
Scope	All 26 Rust workspace packages, the React console, Python SDK and server template, internal Python/C++ executors, deployment and verification components, and external runtime resources in the canonical architecture.
Exclusions	Source-code modules within a component, transient permission/init jobs, test fixtures, customer-specific configuration, personnel structure, facilities, and classified mission content.
Handling	Reference baseline with no client-specific data. Apply contract, export-control, CUI, distribution, and classification markings before client release.
Authority	The repository implementation and executable verification remain product evidence. The model organizes and traces that evidence; it does not replace tests.



Architecture method and conformance posture

UAF 1.3 governs the enterprise and mission architecture. SysML 1.6 supplies detailed software blocks, requirement semantics, connectivity, and lifecycle behavior beneath it. Stable identifiers preserve traceability across diagrams, catalogs, XMI, repository evidence, and future client overlays.

Model-exchange posture. The included XMI applies the official OMG UAF 1.3 and SysML 1.6 profile URIs and carries the semantic elements and trace relationships used by this report. The release validates XML structure, identifiers, references, catalog coverage, and rendered outputs. Vendor-specific diagram notation and profile OCL validation require import into a UAF 1.3-capable modeling tool; the package does not claim a vendor-native project or tool-certified UAF conformance.

Trace rule

Requirement -> Capability -> Operational Activity -> Service -> Software Resource -> Actual Resource -> Verification Evidence

Baseline invariants


SurrealDB is the sole platform coordination authority. Provider completion is webhook-only. The gateway preserves the complete MCP surface where it fits. Artifacts, recordings, tasks, agents, policy decisions, and audit evidence retain canonical typed identities. Compose and Helm instantiate the same service graph.

Selected formal layers

Layer	Question answered	Veoveo model elements
Strategic	Which enterprise abilities and outcomes matter?	VV-CAP-*
Operational	Which logical activities and mission threads produce the outcome?	VV-OPA-*
Services	Which implementation-independent offers support the activities?	VV-SVC-*
Resources	Which software, interfaces, data, and runtimes realize the services?	VV-CMP-* and VV-IF-*
Actual Resources	Which connected or offline fielded configuration is present?	VV-AR-*
Requirements and evidence	Which claims constrain the architecture and where are they verified?	VV-REQ-* and repository evidence


Architecture view map

Shows how strategic, operational, service, resource, actual-resource, security, standards, and evidence concerns remain one traceable model.




Enterprise context

Defines the installation boundary, external performers, organization-owned dependencies, and principal exchanges.




Capability map

Defines the abilities Veoveo contributes to logistics, defense, analytics, autonomy, governance, and deployment.




Operational mission thread

Follows a representative governed observe-analyze-decide-act thread and the evidence created along it.




Service structure

Separates implementation-independent services from their realizing software resources.




Software resource structure

Enumerates all 48 scoped first-party, packaged, and external software resources.



Software resource connectivity

Shows runtime protocols, trust transitions, private authorities, and specialized execution boundaries.



Deployment configurations

Compares the four fieldable connected/offline Compose/Helm configurations and their invariant service graph.

Deployment configurations

VV-VIEW-07
UAF 1.3 / SysML 1.6 | v0.1.0

VV-AR-001
Compose connected
Single host. External OIDC; RustFS or S3; private HTTP; loopback ports

Gateway + console

Hosted MCP domains

Artifact plane

Recording plane

SurrealDB authority

Telemetry + audit

Form-specific controls
Compose secrets, volumes, Caddy

VV-AR-002
Compose offline
Single isolated host. Offline OIDC discovery; RustFS; mTLS option; imported images

Gateway + console

Hosted MCP domains

Artifact plane

Recording plane

SurrealDB authority

Telemetry + audit

Form-specific controls
Offline image import and local trust

VV-AR-003
Helm connected
Kubernetes. External OIDC/S3; Ingress; default-deny NetworkPolicy; mesh mTLS

Gateway + console

Hosted MCP domains

Artifact plane

Recording plane

SurrealDB authority

Telemetry + audit

Form-specific controls
Kubernetes Secrets, PVCs, Ingress

VV-AR-004
Helm offline
Isolated Kubernetes. Imported images; existing Secrets; offline values; retained evidence

Gateway + console

Hosted MCP domains

Artifact plane

Recording plane

SurrealDB authority

Telemetry + audit

Form-specific controls
Offline Helm values and image policy


Deployment invariant: one enterprise installation owns identity mapping, policy, persistence, artifacts, recordings, telemetry, secrets, ingress, and lifecycle.

Veoveo reference baseline - no client-specific data

Revision 2026-07-14 | VV-VIEW-07

Security and trust

Locates identity transitions, trust zones, protected assets, and the controls that preserve policy context.




Requirements traceability

Connects formal requirements to UAF capabilities, operational activities, services, resources, and repository evidence.

Requirements traceability						
						VV-VIEW-09
						UAF 1.3 / SysML 1.6 v0.1.0
Requirement	Requirement statement	Capability	Activity	Service	Principal resources	Verification evidence
VV-REQ-001	Each installation shall remain organization-owned and shall not depend on a Veevo vendor control plane, hosted service, or canonical domain name.	VV-CAP-008	VV-OPA-010	VV-SVC-009	VV-CMP-035, VV-CMP-036, VV-CMP-037, VV-CMP-048	README.md; docs/ARCHITECTURE_DECISIONS.md; testing/smoke/tests/offline_contract.rs
VV-REQ-002	Hosted domains shall use the complete MCP protocol surface where it fits, including resources, templates, prompts, completions, tasks, subscriptions, notifications, structured content, and URI identities.	VV-CAP-001	VV-OPA-002	VV-SVC-001	VV-CMP-001, VV-CMP-011, VV-CMP-012, VV-CMP-016, VV-CMP-017, VV-CMP-019, VV-CMP-020, VV-CMP-022, VV-CMP-023, VV-CMP-025	configs/gateway/local.json; testing/mcp-conformance; testing/smoke
VV-REQ-003	Every externally reachable MCP or administrative operation shall pass through profile selection, policy evaluation, and audit at the gateway.	VV-CAP-001	VV-OPA-001	VV-SVC-001	VV-CMP-001, VV-CMP-008, VV-CMP-011	platform/gateway/tests; testing/smoke gateway scenarios
VV-REQ-004	Provider job completion shall be accepted only from a signed provider webhook and shall never poll provider status.	VV-CAP-002	VV-OPA-003	VV-SVC-003	VV-CMP-019, VV-CMP-009, VV-CMP-004, VV-CMP-043	servers/media-mcp tests; testing/smoke webhook-only media scenarios; docs/TECH_DESIGN.md
VV-REQ-005	Long-running operations shall use one durable task authority with explicit idempotency, leases, recovery class, cancellation, results, retention, and ordered event delivery.	VV-CAP-002	VV-OPA-003	VV-SVC-003	VV-CMP-008, VV-CMP-009, VV-CMP-012, VV-CMP-038	platform/task-runtime tests; mcp/task-extension tests; testing/smoke
VV-REQ-006	Artifact occurrences and bytes shall remain tenant-isolated and shall enforce labels, grants, release state, retention, and bounded sharing.	VV-CAP-003	VV-OPA-004	VV-SVC-004	VV-CMP-004, VV-CMP-014, VV-CMP-016, VV-CMP-039	platform/artifacts tests; servers/artifact-mcp tests; testing/smoke artifact scenarios
VV-REQ-007	World and sensor producers shall push typed Resur streams into a private durable recording boundary that preserves crash-discorable evidence.	VV-CAP-004	VV-OPA-005	VV-SVC-005	VV-CMP-005, VV-CMP-015, VV-CMP-023, VV-CMP-047	platform/recordings/hub tests; testing/smoke hub scenario; docs/RECORDINGS.md
VV-REQ-008	Perception shall run locally over authorized recorded data with bounded GPU execution and shall publish governed derived results.	VV-CAP-006	VV-OPA-007	VV-SVC-012	VV-CMP-022, VV-CMP-032, VV-CMP-044, VV-CMP-004, VV-CMP-005	servers/perception-mcp tests and GPU smoke; servers/perception-mcp/DESIGN.md
VV-REQ-009	Autonomous agents shall persist wakes, episodes, task descriptors, retries, results, and retention pins across process restart.	VV-CAP-007	VV-OPA-008	VV-SVC-007	VV-CMP-006, VV-CMP-007, VV-CMP-008, VV-CMP-009	agents/kernel tests; agents/runtime tests; testing/smoke agent-kernel scenario
VV-REQ-010	Browser JavaScript shall never receive the gateway bearer and every unsafe console request shall enforce CSRF.	VV-CAP-009	VV-OPA-009	VV-SVC-008	VV-CMP-002, VV-CMP-003, VV-CMP-001	apps/console/bff tests; console build checks; testing/smoke console scenarios
VV-REQ-011	An offline installation shall verify all transferred files and images and shall not require network access during loading or operation of provider-independent capabilities.	VV-CAP-010	VV-OPA-010	VV-SVC-009	VV-CMP-037, VV-CMP-035, VV-CMP-036, VV-CMP-048	deploy/offline; testing/smoke/tests/offline_contract.rs
VV-REQ-012	Compose and Helm shall instantiate the same canonical service graph while retaining form-specific controls for storage, ingress, network policy, and mTLS.	VV-CAP-010	VV-OPA-010	VV-SVC-009	VV-CMP-035, VV-CMP-036, VV-CMP-048	testing/smoke deployment contract tests; deploy/helm/veevo/values.schema.json
VV-REQ-013	Analytical users shall retain arbitrary DuckDB SQL within owner-accepted workspaces bounded by engine, filesystem, process, resource, and network controls.	VV-CAP-005	VV-OPA-006	VV-SVC-006	VV-CMP-018, VV-CMP-010, VV-CMP-045, VV-CMP-004	servers/duckdb-mcp tests; testing/smoke DuckDB scenarios; servers/duckdb-mcp/DESIGN.md
VV-REQ-014	The platform shall support governed map acquisition, release activation, restrictions, geotesty, routing, reachable areas, and logistics matrices through stable map identities.	VV-CAP-011	VV-OPA-006	VV-SVC-011	VV-CMP-020, VV-CMP-031, VV-CMP-046, VV-CMP-004, VV-CMP-038	servers/map-mcp tests; servers/map-mcp/DESIGN.md; gateway catalog validation
VV-REQ-015	Known platform and domain contracts shall use typed structs, enums, identifiers, and schemas; raw JSON shall remain confined to genuinely opaque provider boundaries.	VV-CAP-012	VV-OPA-002	VV-SVC-001	VV-CMP-011, VV-CMP-030, VV-CMP-001, VV-CMP-HOSTED	cargo test workspace; Python type and test suite; gateway configuration schema validation
VV-REQ-016	Only the gateway shall sign short-lived internal identity assertions and hosted services shall validate the key identifier, audience, tenant, principal, labels, scopes, and expiry.	VV-CAP-008	VV-OPA-001	VV-SVC-002	VV-CMP-001, VV-CMP-011, VV-CMP-030, VV-CMP-HOSTED	platform/gateway authentication tests; Python SDK tests; testing/smoke
VV-REQ-017	SumedB shall remain the sole platform coordination authority; transactional outbox replay shall remain authoritative over best-effort live delivery.	VV-CAP-008	VV-OPA-003	VV-SVC-003	VV-CMP-008, VV-CMP-009, VV-CMP-038	platform/store tests; platform/task-runtime tests; docs/TECH_DESIGN.md
VV-REQ-018	New hosted servers shall compose through shared contracts and the gateway catalog without leaking server-specific behavior into generic gateway modules.	VV-CAP-012	VV-OPA-002	VV-SVC-001	VV-CMP-001, VV-CMP-011, VV-CMP-012, VV-CMP-030, VV-CMP-025	templates/python-mcp tests; gateway catalog validation; testing/mcp-conformance
Veevo reference baseline - no client-specific data						
						Revision 2026-07-14 VV-VIEW-09

Durable task lifecycle

Defines the durable state transitions and the webhook-only provider completion branch.



Software component catalog

The catalog includes every buildable first-party component and every external runtime that participates in the stated architecture. Deployment aliases and external operational actors appear in the interface model but are not counted as software resources.

ID	Component	Category	Implementation	Deployment	Responsibility	Authority
VV-CMP-001	MCP gateway	Core deployable	Rust	one or more replicas	Aggregates policy-scoped MCP profiles; terminates OAuth; evaluates policy; records audit; issues short-lived internal identity; proxies hosted-server administration and governed artifact downloads.	SurrealDB control revisions and security records
VV-CMP-002	Console BFF	Core deployable	Rust	one or more replicas	Owns the browser security boundary, PKCE login, encrypted HttpOnly sessions, CSRF enforcement, installation projections, and explicit administrative workflows.	Encrypted browser session cookie only
VV-CMP-003	Operations console web application	Core application	React and TypeScript	static assets served by Console BFF	Presents health, tasks, artifacts, agents, recordings, MCP topology, policy, audit, and installation state without receiving gateway bearer tokens.	No authoritative state
VV-CMP-004	Artifact service	Core deployable	Rust	one or more replicas	Enforces tenant, label, grant, release, retention, share-link, and write-capability policy for governed artifact occurrences and bytes.	SurrealDB artifact identity and authorization records; object store bytes
VV-CMP-005	Recording Hub	Core deployable	Rust	single private spooler per recording volume	Accepts push-based Rerun log streams, writes crash-decodable RRD segments, verifies frozen segments, and catalogs governed recordings.	RRD segment files and SurrealDB recording catalog
VV-CMP-006	Agent kernel	Core agent component	Rust	operator-launched agent process	Runs bounded autonomous episodes with MCP tools, elicitation, memory, replay, budgets, recording, and detach/resume behavior.	SurrealDB-backed runtime descriptors; RRD episode evidence
VV-CMP-007	Agent runtime	Core library	Rust	linked into agent processes	Persists agents, wakes, episodes, watcher leases, retry schedules, task descriptors, results, and retention pins across process restart.	SurrealDB agent records and outbox
VV-CMP-008	Platform store	Core library	Rust	linked into platform services	Owns typed persistence records, ordered migrations, stable identities, transactional outbox, changefeed replay, and platform-store access.	SurrealDB 3.2.0
VV-CMP-009	Durable task runtime	Core library	Rust	linked into durable workers	Owns UUIDv7 task creation, idempotency, leases, claims, progress, elicited input, cancellation, terminal results, retention, recovery, and outbox transitions.	SurrealDB task and provider-job records
VV-CMP-010	DuckDB runtime	Core library	Rust	linked into analytical components	Provides owner-scoped DuckDB workspace construction and locked analytical execution primitives.	Owner-scoped DuckDB workspace files
VV-CMP-011	Shared MCP contract	Core library	Rust	linked into gateway clients and servers	Defines typed cross-service identities, gateway configuration, policy vocabulary, artifacts, coordinates, storage, tasks, subscriptions, usage, and URI conventions.	No authoritative state
VV-CMP-012	Final MCP task extension	Core library	Rust	linked into gateway clients and durable servers	Implements discovery, task-required invocation, get, update, cancel, list, notifications, and SSE subscription projection over the shared runtime.	Shared task runtime only

ID	Component	Category	Implementation	Deployment	Responsibility	Authority
VV-CMP-013	MCP stdio bridge	Core deployable	Rust	one bridge process for the Rerun viewer server	Projects a child stdio MCP server onto bounded Streamable HTTP while preserving the registered gateway identity.	No authoritative state
VV-CMP-014	Artifact client	Core library	Rust	linked into domain servers	Provides the typed native client for artifact metadata, capabilities, upload, download, grants, release, and sharing operations.	Artifact service only
VV-CMP-015	RRD library	Core library	Rust	linked into recording query and agent components	Provides typed Rerun/RRD read, merge, query, and recording utility behavior shared by the platform.	RRD segment files
VV-CMP-016	Artifact MCP server	Hosted MCP server	Rust	replicated hosted service	Exposes governed artifact discovery, metadata, grants, release states, share links, subscriptions, prompts, and completions through canonical artifact URIs.	Artifact service and platform store
VV-CMP-017	Frames MCP server	Hosted MCP server	Rust	replicated hosted service	Converts WGS84, ECEF, ENU, and NED frames; derives local frames; persists coordinate operations; and executes durable batches.	SurrealDB frame and coordinate-operation records
VV-CMP-018	DuckDB MCP server	Hosted MCP server	Rust	single persistent owner-workspace service	Executes arbitrary query, execute, ingest, and export SQL inside bounded owner-scoped workspaces with governed inputs and outputs.	Owner-scoped DuckDB files; SurrealDB task metadata
VV-CMP-019	Media MCP server	Hosted MCP server	Rust	replicated hosted service	Provides provider-neutral media model discovery, schemas, generation tasks, webhook-only provider completion, usage reconciliation, and governed output artifacts.	SurrealDB provider jobs events usage and tasks; artifact plane outputs
VV-CMP-020	Map MCP server	Hosted MCP server	Rust	single persistent map catalog service	Governs map sources and releases; performs geodesy, CRS transformation, location inspection, restrictions, reachable areas, routing, and logistics matrices.	SurrealDB map governance records; DuckDB catalog; map release files
VV-CMP-021	Optimization MCP server	Hosted MCP server	Rust	replicated hosted service	Builds deterministic planning options, records durable task state, and publishes typed plan artifacts.	SurrealDB task metadata; artifact plane plan outputs
VV-CMP-022	Perception MCP server	Hosted MCP server	Rust	GPU-backed hosted service	Authorizes recorded sensor data, extracts bounded clips, runs local detection and tracking, and publishes typed results plus derived RRD annotations.	SurrealDB analyses and tasks; artifact plane outputs
VV-CMP-023	Recording MCP server	Hosted MCP server	Rust	replicated read projection with shared recording volume	Applies tenant and label authorization to recording discovery, query, sealing, subscriptions, prompts, and artifact publication.	Recording Hub RRD files and SurrealDB catalog
VV-CMP-024	Timeseries MCP server	Hosted MCP server	Rust	replicated hosted service	Runs typed forecasting as durable work and publishes structured forecast artifacts and RRD output.	SurrealDB task metadata; artifact and RRD outputs
VV-CMP-025	Datasheet MCP server	Hosted MCP server	Python	replicated hosted service and canonical Python template	Demonstrates the Python platform contract through dataset preview, column statistics, task-based profiling, prompts, completions, resources, and notifications.	SurrealDB task metadata; artifact plane reports
VV-CMP-026	Chart MCP packaged service	Hosted MCP server	Node.js and flint-chart-mcp	replicated hosted service	Packages the pinned chart MCP implementation and exposes chart compilation, validation, rendering, view creation, resources, and prompts through the gateway.	Server-owned chart resources

ID	Component	Category	Implementation	Deployment	Responsibility	Authority
VV-CMP-027	Rerun viewer MCP child	Hosted MCP server	Rerun viewer MCP process	child process behind the stdio bridge	Provides the Rerun viewer's MCP tool surface under the registered rerun server identity.	Rerun viewer process state
VV-CMP-028	SUMO MCP server	Showcase component	Rust	optional showcase service	Owens serialized TraCI access, exposes typed traffic reads and actuation, runs durable generation and optimization tasks, and pushes world state to Recording Hub.	SUMO live state; SurrealDB tasks; RRD recordings
VV-CMP-029	SUMO simulator and LuST world	Showcase component	SUMO 1.27.1	optional showcase container	Runs the pinned LuST traffic scenario and exposes private TraCI control to the SUMO MCP owner.	SUMO live simulation state
VV-CMP-030	Python hosted-server SDK	Development component	Python	installed into Python hosted servers	Provides typed identity, pagination, internal authentication, telemetry, artifact, deployment, task-runtime, and final task-extension support.	Platform services only
VV-CMP-031	Map data acquisition helper	Internal execution component	Python	subprocess in the Map MCP container	Normalizes authoritative OSM, GTFS, maritime, aviation, and authority datasets into bounded acquisition products.	Map acquisition scratch and release files
VV-CMP-032	Perception DeepStream runner	Internal execution component	C++	one subprocess per perception task	Executes the bounded GStreamer and DeepStream pipeline and returns typed detections and tracks to the owning server.	No durable authority
VV-CMP-033	MCP conformance client	Verification component	Rust	test and operator process	Exercises typed external MCP surfaces and configuration against real or fake services.	Test evidence only
VV-CMP-034	Rust smoke harness	Verification component	Rust	test and CI process	Owens multi-process and container lifecycle, readiness, timeouts, cleanup, typed calls, assertions, and deployment contract verification.	Test evidence only
VV-CMP-035	Docker Compose deployment definition	Deployment component	YAML and container images	connected or offline single-host installation	Instantiates the canonical single-host service graph with loopback development ports, private internal networks, volumes, bootstrap, and edge routing.	Installation configuration
VV-CMP-036	Helm deployment chart	Deployment component	Helm and Kubernetes YAML	connected or offline Kubernetes installation	Instantiates the service graph with existing secrets, network policy, persistent storage, optional service-mesh mTLS, and ingress controls.	Installation configuration
VV-CMP-037	Offline bundle builder and loader	Deployment component	Shell dispatch plus verified manifests	connected build host and isolated target host	Builds and verifies digest-pinned images, configuration schemas, checksums, SPDX SBOMs, Compose and Helm material without requiring target-network access.	Bundle manifest and retained verification evidence
VV-CMP-038	SurrealDB platform database	External platform runtime	SurrealDB 3.2.0	required single RocksDB-backed node	Provides the sole durable coordination store for identity, control, policy, tasks, artifacts, recordings, agents, audit, and outbox state.	Canonical platform coordination state
VV-CMP-039	S3-compatible object store	External platform runtime	RustFS or installation-owned S3-compatible service	required object store	Stores governed artifact bytes while the Artifact service owns identity and authorization.	Artifact blob bytes
VV-CMP-040	Installation edge and ingress	External platform runtime	Caddy or Kubernetes ingress controller	one installation ingress	Terminates installation ingress and exposes only console, gateway, public share redemption, and required provider plumbing routes.	Ingress routing and TLS configuration

ID	Component	Category	Implementation	Deployment	Responsibility	Authority
VV-CMP-041	Enterprise identity provider	External enterprise service	OIDC provider	installation-owned external dependency	Authenticates users and clients and supplies issuer, JWKS, claims, authorization, and token endpoints to the gateway trust configuration.	Enterprise identity records
VV-CMP-042	OpenTelemetry collector and SIEM export	External platform runtime	OpenTelemetry Collector 0.155.0 and optional SIEM	one or more collectors	Receives logs, traces, metrics, and audit-compatible telemetry and forwards installation-approved signals.	Telemetry pipeline state
VV-CMP-043	Media generation provider	External domain service	provider-neutral HTTPS API	optional connected dependency	Accepts media jobs, delivers signed terminal webhooks, and provides output bytes only to the bounded server-side completion path.	Provider job state
VV-CMP-044	NVIDIA DeepStream and TensorRT runtime	External execution runtime	DeepStream 9 and TensorRT	required for production perception	Decodes H.264, executes site-approved TensorRT engines, and emits native detection and tracking metadata without starting a Triton service.	Mounted model engines and transient GPU state
VV-CMP-045	DuckDB and Spatial runtime	External execution runtime	DuckDB 1.5.4 and pinned Spatial extension	embedded and container-local	Provides arbitrary analytical SQL, spatial functions, bounded owner workspaces, spill, ingest, and export execution.	Owner-scoped analytical workspace files
VV-CMP-046	Map processing and routing toolchain	External execution runtime	Valhalla 3.8.2 GDAL 3.11.4 and GTFS Validator 8.0.1	container-local subprocesses	Builds and serves routing tiles, transforms geospatial data, and validates transit datasets under the Map MCP owner.	Map release and routing tile files
VV-CMP-047	Rerun data model and transport	External execution runtime	Rerun 0.34.x libraries and proxy protocol	embedded and private service boundary	Carries typed world logs, persists RRD segments, supports queries, and renders recording evidence.	RRD files where persisted
VV-CMP-048	Container execution environment	External platform runtime	Docker Engine or Kubernetes	installation substrate	Runs isolated service images, networks, volumes, secrets, resource limits, GPUs, and deployment health controls.	Container and orchestration state

Interface and protocol catalog

Interfaces describe canonical ownership, protocol, identity transition, data exchanged, and recovery behavior. Convenience projections do not create alternate authorities.

ID	Interface	Source	Target	Protocol / contract	Identity and policy	Availability / recovery
VV-IF-001	External MCP profile access	VV-EXT-MCP-CLIENT	VV-CMP-001	HTTPS; MCP Streamable HTTP; JSON-RPC	Gateway OAuth access token bound to profile and protected resource; per-method and target-aware policy	Gateway replicas are stateless over durable control and runtime state
VV-IF-002	Browser console access	VV-EXT-BROWSER	VV-CMP-002	HTTPS; HTML; same-origin JSON	Encrypted HttpOnly SameSite session plus CSRF on unsafe requests	Browser never receives gateway bearer; BFF replicas use encrypted cookie state
VV-IF-003	Console static application	VV-CMP-002	VV-CMP-003	HTTPS static assets	CSP, frame denial, MIME sniff prevention, and same-origin referrer policy	Immutable build assets
VV-IF-004	Console to gateway administration	VV-CMP-002	VV-CMP-001	HTTPS; typed gateway admin and artifact routes	BFF-held OAuth token; gateway policy and audit	BFF refresh rotation uses durable gateway token family state
VV-IF-005	Enterprise identity federation	VV-CMP-001	VV-CMP-041	OIDC discovery; OAuth 2.0; JWKS HTTPS	Issuer, key, claim, tenant, client, scope, and protected-resource validation	Unknown issuers or keys fail closed
VV-IF-006	Gateway OAuth service	VV-EXT-OAUTH-CLIENT	VV-CMP-001	OAuth authorization code with PKCE; client credentials; client assertions; ID-JAG	Authorization server policy; rotating refresh families; replay detection	Durable compare-and-swap rotation and bounded duplicate delivery
VV-IF-007	Gateway hosted-server MCP	VV-CMP-001	VV-CMP-HOSTED	Private HTTP; MCP Streamable HTTP	Short-lived Ed25519 internal assertion with audience, principal, tenant, labels, and scopes	Gateway reconnects per request/session; server state is durable where required
VV-IF-008	Gateway hosted-server administration	VV-CMP-001	VV-CMP-HOSTED	Private typed HTTP under canonical server admin mount	AdminRead or AdminWrite policy, audit, and short-lived internal assertion	Owning server uses the same domain state as its MCP surface
VV-IF-009	Platform persistence	VV-CMP-PLATFORM	VV-CMP-038	SurrealDB WebSocket at database scope	Dedicated runtime credentials; tenant-aware typed APIs	Transactional outbox is authoritative; LIVE is a latency path only
VV-IF-010	Installation bootstrap	VV-CMP-001	VV-CMP-038	SurrealDB WebSocket at root scope	Separate bootstrap credentials	Runs to completion before long-lived services
VV-IF-011	Task protocol projection	VV-CMP-HOSTED	VV-CMP-012	MCP final task extension and SSE	Same principal and policy context as tool invocation	Projects the shared task runtime without a second task store
VV-IF-012	Task persistence	VV-CMP-009	VV-CMP-008	Typed Rust API and transactional outbox	Task owner includes tenant, principal, profile, server, and operation	Resume
VV-IF-013	Domain artifact operations	VV-CMP-HOSTED	VV-CMP-004	Private typed HTTP through artifact client or Python SDK	Forwarded internal identity or task-bound write capability	Idempotent capability redemption and durable artifact records
VV-IF-014	Artifact byte storage	VV-CMP-004	VV-CMP-039	S3-compatible API	Installation object-store credentials; service-only access	Tenant-derived storage keys and content integrity hashes
VV-IF-015	Authorized artifact download	VV-EXT-AUTHORIZED-USER	VV-CMP-001	HTTPS /artifacts/{profile}/{artifact_id}/download	Gateway policy and audit; service-side authorization	No domain-specific byte route
VV-IF-016	Public artifact redemption	VV-EXT-LINK-HOLDER	VV-CMP-004	HTTPS /s/{token}	Random read-only bearer; hash-only storage; expiry, limit, release state, revocation	Edge logging suppresses bearer path
VV-IF-017	Recording ingest	VV-EXT-PRODUCER	VV-CMP-005	Private Rerun gRPC proxy	Installation-private boundary and configured recording owner	Push-only ingest; fsynced crash-decodable segment rotation

ID	Interface	Source	Target	Protocol / contract	Identity and policy	Availability / recovery
VV-IF-018	Recording query	VV-CMP-023	VV-CMP-005	Read-only RRD files plus SurrealDB catalog	Tenant and data-label authorization before physical segment resolution	Logical recordings may span restart siblings
VV-IF-019	Perception source read	VV-CMP-022	VV-CMP-005	Read-only RRD files or explicitly bounded recent proxy	Canonical recording URI authorization; classification and labels propagate	Durable reads use frozen or sealed segments; recent proxy is interrupted-indeterminate
VV-IF-020	Perception runner	VV-CMP-022	VV-CMP-032	Bounded typed JSON subprocess contract	Site-approved mounted configuration and task-level filesystem boundary	One process per task with timeout and cancellation
VV-IF-021	DeepStream execution	VV-CMP-032	VV-CMP-044	GStreamer, CUDA, NVDEC, TensorRT, NVIDIA metadata	Mounted approved engine and coherent host-driver libraries	No CPU inference fallback and no Triton server process
VV-IF-022	Media provider submission	VV-CMP-019	VV-CMP-043	Provider HTTPS API	Provider credential held only by media server	Submission binding commits before task detaches
VV-IF-023	Media terminal webhook	VV-CMP-043	VV-CMP-019	Signed HTTPS webhook	Provider signature and unique event validation	Webhook-only completion; missing delivery is operational failure
VV-IF-024	Analytical execution	VV-CMP-018	VV-CMP-045	Embedded DuckDB API and arbitrary SQL	Owner-derived workspace and locked engine settings	Read work may resume; uncertain mutation is never replayed
VV-IF-025	Map acquisition helper	VV-CMP-020	VV-CMP-031	Typed JSON subprocess contract and filesystem exchange	Registered source policy, bounded paths, network controls	Acquisition tasks persist durable state and immutable release identities
VV-IF-026	Map routing toolchain	VV-CMP-020	VV-CMP-046	Local process and HTTP APIs	Container-local endpoints and governed active release	Active release dependencies are recorded with route products
VV-IF-027	Rerun viewer bridge	VV-CMP-013	VV-CMP-027	MCP stdio child to Streamable HTTP parent	Gateway profile controls the external HTTP projection	Bridge process owns child lifecycle
VV-IF-028	World recording publication	VV-CMP-028	VV-CMP-005	Private Rerun gRPC	Internal recording identity	Recording Hub never polls SUMO
VV-IF-029	SUMO control	VV-CMP-028	VV-CMP-029	Private TraCI TCP	Single serialized owner; not published to host	Uncertain mutating batch execution is interrupted-indeterminate
VV-IF-030	Telemetry export	VV-CMP-PLATFORM	VV-CMP-042	OTLP gRPC or HTTP	Installation-selected exporter and SIEM credentials	Telemetry excludes tokens
VV-IF-031	Deployment control	VV-CMP-035	VV-CMP-048	Docker Compose and OCI runtime APIs	Installation operator credentials and secret files	Compose is the canonical local and single-host form
VV-IF-032	Kubernetes deployment control	VV-CMP-036	VV-CMP-048	Helm and Kubernetes APIs	Installation operator RBAC and existing Secrets	Helm preserves the same service graph and explicit singleton resources
VV-IF-033	Offline transfer	VV-CMP-037	VV-CMP-048	Verified tar and OCI image archives	SHA-256 checksums, resolved identities, SPDX SBOMs	Loader performs no network operation

Requirements traceability catalog

Requirements are modeled as SysML 1.6 requirements and linked through UAF concepts to software resources and executable repository evidence.

ID	Requirement	Capability	Activity	Service	Resources	Evidence
VV-REQ-001	Each installation shall remain organization-owned and shall not depend on a Veoveo vendor control plane, hosted service, or canonical domain name.	VV-CAP-008	VV-OPA-010	VV-SVC-009	VV-CMP-035, VV-CMP-036, VV-CMP-037, VV-CMP-048	README.md; docs/ARCHITECTURE_DECISIONS.md; testing/smoke/tests/offline_contract.rs
VV-REQ-002	Hosted domains shall use the complete MCP protocol surface where it fits, including resources, templates, prompts, completions, tasks, subscriptions, notifications, structured content, and URI identities.	VV-CAP-001	VV-OPA-002	VV-SVC-001	VV-CMP-001, VV-CMP-011, VV-CMP-012, VV-CMP-016, VV-CMP-017, VV-CMP-019, VV-CMP-020, VV-CMP-022, VV-CMP-023, VV-CMP-025	configs/gateway.local.json; testing/mcp-conformance; testing/smoke
VV-REQ-003	Every externally reachable MCP or administrative operation shall pass through profile selection, policy evaluation, and audit at the gateway.	VV-CAP-001	VV-OPA-001	VV-SVC-001	VV-CMP-001, VV-CMP-008, VV-CMP-011	platform/gateway/tests; testing/smoke gateway scenarios
VV-REQ-004	Provider job completion shall be accepted only from a signed provider webhook and shall never poll provider status.	VV-CAP-002	VV-OPA-003	VV-SVC-003	VV-CMP-019, VV-CMP-009, VV-CMP-004, VV-CMP-043	servers/media-mcp tests; testing/smoke webhook-only media scenarios; docs/TECH_DESIGN.md
VV-REQ-005	Long-running operations shall use one durable task authority with explicit idempotency, leases, recovery class, cancellation, results, retention, and ordered event delivery.	VV-CAP-002	VV-OPA-003	VV-SVC-003	VV-CMP-008, VV-CMP-009, VV-CMP-012, VV-CMP-038	platform/task-runtime tests; mcp/task-extension tests; testing/smoke
VV-REQ-006	Artifact occurrences and bytes shall remain tenant-isolated and shall enforce labels, grants, release state, retention, and bounded sharing.	VV-CAP-003	VV-OPA-004	VV-SVC-004	VV-CMP-004, VV-CMP-014, VV-CMP-016, VV-CMP-039	platform/artifacts tests; servers/artifact-mcp tests; testing/smoke artifact scenarios
VV-REQ-007	World and sensor producers shall push typed Rerun streams into a private durable recording boundary that preserves crash-decodable evidence.	VV-CAP-004	VV-OPA-005	VV-SVC-005	VV-CMP-005, VV-CMP-015, VV-CMP-023, VV-CMP-047	platform/recordings/hub tests; testing/smoke hub scenario; docs/RECORDINGS.md
VV-REQ-008	Perception shall run locally over authorized recorded data with bounded GPU execution and shall publish governed derived results.	VV-CAP-006	VV-OPA-007	VV-SVC-012	VV-CMP-022, VV-CMP-032, VV-CMP-044, VV-CMP-004, VV-CMP-005	servers/perception-mcp tests and GPU smoke; servers/perception-mcp/DESIGN.md
VV-REQ-009	Autonomous agents shall persist wakes, episodes, task descriptors, retries, results, and retention pins across process restart.	VV-CAP-007	VV-OPA-008	VV-SVC-007	VV-CMP-006, VV-CMP-007, VV-CMP-008, VV-CMP-009	agents/kernel tests; agents/runtime tests; testing/smoke agent-kernel scenario
VV-REQ-010	Browser JavaScript shall never receive the gateway bearer and every unsafe console request shall enforce CSRF.	VV-CAP-009	VV-OPA-009	VV-SVC-008	VV-CMP-002, VV-CMP-003, VV-CMP-001	apps/console/bff tests; console build checks; testing/smoke console scenarios
VV-REQ-011	An offline installation shall verify all transferred files and images and shall not require network access during loading or operation of provider-independent capabilities.	VV-CAP-010	VV-OPA-010	VV-SVC-009	VV-CMP-037, VV-CMP-035, VV-CMP-036, VV-CMP-048	deploy/offline; testing/smoke/tests/offline_contract.rs
VV-REQ-012	Compose and Helm shall instantiate the same canonical service graph while retaining form-specific controls for storage, ingress, network policy, and mTLS.	VV-CAP-010	VV-OPA-010	VV-SVC-009	VV-CMP-035, VV-CMP-036, VV-CMP-048	testing/smoke deployment contract tests; deploy/helm/veoveo/values.schema.json

ID	Requirement	Capability	Activity	Service	Resources	Evidence
VV-REQ-013	Analytical users shall retain arbitrary DuckDB SQL within owner-scoped workspaces bounded by engine, filesystem, process, resource, and network controls.	VV-CAP-005	VV-OPA-006	VV-SVC-006	VV-CMP-018, VV-CMP-010, VV-CMP-045, VV-CMP-004	servers/duckdb-mcp tests; testing/smoke DuckDB scenarios; servers/duckdb-mcp/DESIGN.md
VV-REQ-014	The platform shall support governed map acquisition, release activation, restrictions, geodesy, routing, reachable areas, and logistics matrices through stable map identities.	VV-CAP-011	VV-OPA-006	VV-SVC-011	VV-CMP-020, VV-CMP-031, VV-CMP-046, VV-CMP-004, VV-CMP-038	servers/map-mcp tests; servers/map-mcp/DESIGN.md; gateway catalog validation
VV-REQ-015	Known platform and domain contracts shall use typed structs, enums, identifiers, and schemas; raw JSON shall remain confined to genuinely opaque provider boundaries.	VV-CAP-012	VV-OPA-002	VV-SVC-001	VV-CMP-011, VV-CMP-030, VV-CMP-001, VV-CMP-HOSTED	cargo test workspace; Python type and test suite; gateway configuration schema validation
VV-REQ-016	Only the gateway shall sign short-lived internal identity assertions and hosted services shall validate the key identifier, audience, tenant, principal, labels, scopes, and expiry.	VV-CAP-008	VV-OPA-001	VV-SVC-002	VV-CMP-001, VV-CMP-011, VV-CMP-030, VV-CMP-HOSTED	platform/gateway authentication tests; Python SDK tests; testing/smoke
VV-REQ-017	SurrealDB shall remain the sole platform coordination authority; transactional outbox replay shall remain authoritative over best-effort live delivery.	VV-CAP-008	VV-OPA-003	VV-SVC-003	VV-CMP-008, VV-CMP-009, VV-CMP-038	platform/store tests; platform/task-runtime tests; docs/TECH_DESIGN.md
VV-REQ-018	New hosted servers shall compose through shared contracts and the gateway catalog without leaking server-specific behavior into generic gateway modules.	VV-CAP-012	VV-OPA-002	VV-SVC-001	VV-CMP-001, VV-CMP-011, VV-CMP-012, VV-CMP-030, VV-CMP-025	templates/python-mcp tests; gateway catalog validation; testing/mcp-conformance

Model glossary

Term	Definition	Formal mapping
Actual Resource	A fielded or instantiated resource configuration. In this baseline it represents a connected or offline Compose or Helm installation.	UAF ActualResource
Artifact	A governed occurrence with a canonical artifact URI, metadata, authorization, retention, release state, and separately stored bytes.	UAF ResourceArtifact and OperationalInformation
Capability	An enterprise ability realized through operational activities, services, resources, people, and constraints.	UAF Capability
Compatibility helper	An explicitly registered narrow projection for a client that cannot use a richer MCP surface; it reuses canonical typed models, policy, audit, tasks, artifacts, and URIs.	Derived service projection
Completion	An MCP protocol capability that helps complete identifiers or arguments; it is distinct from provider job completion.	MCP service function
Control plane	The typed identity, server, profile, policy, OAuth, and gateway revision state that governs an installation.	UAF Architecture Management and Security information
Data label	A classification or handling label enforced with tenant and grant policy before access is allowed.	UAF Security constraint
Durable task	A long-running operation whose identity, owner, transitions, recovery, result, and events survive process restart.	SysML state machine subject and UAF Function
Gateway profile	A protected MCP resource that selects servers, capabilities, scopes, clients, and policy rules for a client population.	UAF ServiceArchitecture
Hosted MCP server	A deployable domain owner registered in the gateway catalog and projected through one or more profiles.	UAF Software and ResourceService
Internal assertion	A short-lived Ed25519 JWT signed only by the gateway for a specific hosted-service audience.	UAF Security control mechanism
MCP resource	Addressable domain state with a canonical URI, optionally produced from a template and optionally subscribable.	UAF ResourceInformation or OperationalInformation
Mission thread	An ordered operational scenario that traces mission need through activities, services, resources, information, and evidence.	UAF Operational sequence and process
Operational Activity	A logical process independent of its implementing software or deployment.	UAF OperationalActivity
Outbox	An ordered event record committed in the same transaction as domain state and replayed from a durable consumer cursor.	UAF ResourceInformation
Provider completion	The transition of an external provider job from submitted to terminal state. Veoveo accepts it only from a signed webhook.	UAF Operational event and SysML state transition
Recording	A governed logical Rerun recording composed of one or more crash-decodable RRD segments and a SurrealDB catalog identity.	UAF ResourceArtifact and ResourceInformation
Recovery class	The declared restart semantics of a durable operation: Resume, WebhookWait, or InterruptedIndeterminate.	SysML state-machine constraint
Resource	A concrete software, data, infrastructure, personnel, or facility element that realizes services and operational activities.	UAF Resource domain
Resource URI	A typed URI owned by one domain and preserved across gateway aggregation, tasks, artifacts, and links.	UAF ResourceInformation identity
Service	An implementation-independent capability offered across an interface to support operational activities.	UAF Service
Software component	A first-party or external executable, library, application, package, deployment definition, or runtime included in the architecture scope.	UAF Software and SysML Block
System	A resource performer that composes software and infrastructure into an operationally useful whole.	UAF System and SysML Block
Tenant	An installation-local isolation boundary carried through identity, tasks, artifacts, recordings, policy, audit, and persistence.	UAF Organization/security boundary
Transactional authority	The store whose committed record decides system state after restart or concurrency. For platform coordination this is SurrealDB.	UAF ResourceInformation source of truth
View	A presentation of selected model elements that addresses named stakeholder concerns without becoming a separate source of truth.	SysML View and UAF View specification
Viewpoint	The conventions, concerns, stakeholders, and model kinds used to construct a view.	SysML Viewpoint and UAF viewpoint/aspect
Webhook wait	A durable recovery state entered only after provider submission and provider-job binding commit; completion awaits a signed webhook.	SysML state

Normative and implementation references

- [OMG Unified Architecture Framework 1.3](#), including the DMM, UAFML, traceability appendix, sample problem, enterprise architecture guide, and normative machine-readable profile.
- [OMG Systems Modeling Language 1.6](#).
- [Veoveo README](#), [architecture decisions](#), [technical design](#), and [code map](#).
- [Veoveo model exchange XML](#), [model manifest](#), and [import guidance](#).