acc. to Safe Work Australia - Code of Practice

Aluminum acetate, basic hydrate ≥98 %, pure

article number: 1HE9 date of compilation: 2021-02-17 Version: GHS 2.0 en Revision: 2024-03-02

Replaces version of: 2021-02-17

Version: (GHS 1)

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

Product identifier 1.1

Identification of the substance **Aluminum acetate, basic hydrate** ≥98 %, pure

Article number 1HE9

CAS number 142-03-0

Relevant identified uses of the substance or mixture and uses advised against 1.2

> Laboratory and analytical use Laboratory chemical

Uses advised against: Do not use for private purposes (household).

Food, drink and animal feedingstuffs.

Details of the supplier of the safety data sheet 1.3

Carl Roth GmbH + Co. KG Schoemperlenstr. 3-5 D-76185 Karlsruhe Germany

Relevant identified uses:

Telephone:+49 (0) 721 - 56 06 0 **Telefax:** +49 (0) 721 - 56 06 149 e-mail: sicherheit@carlroth.de Website: www.carlroth.de

sheet:

e-mail (competent person): sicherheit@carlroth.de

1.4 **Emergency telephone number**

Name	Street	Postal code/city	Telephone	Website
NSW Poisons Information Centre Childrens Hospital	Hawkesbury Road	2145 West- mead, NSW	131126	

SECTION 2: Hazards identification

Classification of the substance or mixture

Classification acc. to GHS

Section	Hazard class	Cat- egory	Hazard class and category	Hazard statement
3.3	Serious eye damage/eye irritation	1	Eye Dam. 1	H318

For full text of abbreviations: see SECTION 16

2.2 **Label elements**

Labelling

Signal word	Danger
-------------	--------

Page 1 / 14 Australia (en)

acc. to Safe Work Australia - Code of Practice

Aluminum acetate, basic hydrate ≥98 %, pure

article number: 1HE9



Pictograms

GHS05



Hazard statements

H318 Causes serious eye damage

Precautionary statements

Precautionary statements - prevention

P280 Wear eye protection/face protection

Precautionary statements - response

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing

P310 Immediately call a POISON CENTER or doctor/physician

2.3 Other hazards

Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB.

Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of \geq 0,1%.

SECTION 3: Composition/information on ingredients

3.1 Substances

Name of substance Aluminum acetate, basic hydrate

Molecular formula $C_4H_7AlO_5$ Molar mass $162.1 \, ^g/_{mol}$ CAS No 142-03-0

SECTION 4: First aid measures

4.1 Description of first aid measures



General notes

Take off contaminated clothing.

Following inhalation

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.

Following skin contact

Rinse skin with water/shower. In all cases of doubt, or when symptoms persist, seek medical advice.

Australia (en) Page 2 / 14

acc. to Safe Work Australia - Code of Practice

Aluminum acetate, basic hydrate ≥98 %, pure

article number: 1HE9



Following eye contact

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Following ingestion

Rinse mouth. Call a doctor if you feel unwell.

4.2 Most important symptoms and effects, both acute and delayed

Risk of blindness, Risk of serious damage to eyes

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Firefighting measures

5.1 Extinguishing media



Suitable extinguishing media

co-ordinate firefighting measures to the fire surroundings! water, foam, dry extinguishing powder, ABC-powder

Unsuitable extinguishing media

water jet

5.2 Special hazards arising from the substance or mixture

Combustible.

Hazardous combustion products

In case of fire may be liberated: Carbon monoxide (CO), Carbon dioxide (CO₂)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures



For non-emergency personnel

Wearing of suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. Do not breathe dust.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. If substance has entered a water course or sewer, inform the responsible authority.


6.3 Methods and material for containment and cleaning up

Australia (en) Page 3 / 14

acc. to Safe Work Australia - Code of Practice

Aluminum acetate, basic hydrate ≥98 %, pure

article number: 1HE9



Covering of drains. Take up mechanically.

Advice on how to clean up a spill

Take up mechanically. Control of dust.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 **Precautions for safe handling**

Avoid dust formation.

Measures to prevent fire as well as aerosol and dust generation

Removal of dust deposits.

Advice on general occupational hygiene

Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs.

Conditions for safe storage, including any incompatibilities 7.2

Store in a dry place.

Incompatible substances or mixtures

Observe hints for combined storage.

Consideration of other advice:

Ventilation requirements

Use local and general ventilation.

Specific designs for storage rooms or vessels

Recommended storage temperature: 15 - 25 °C

7.3 Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1 **Control parameters**

National limit values

Occupational exposure limit values (Workplace Exposure Limits)

Coun	Name of agent	CAS No	Identifi- er	TWA [mg/ m³]	STEL [mg/ m³]	Ceil- ing-C [mg/ m³]	Nota- tion	Source
AU	nuisance dusts		WES	10			i	WES

Notation

Ceiling value is a limit value above which exposure should not occur Inhalable fraction Ceiling-C

Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)
Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 **STEL**

TWA hours time-weighted average (unless otherwise specified)

Page 4 / 14 Australia (en)



acc. to Safe Work Australia - Code of Practice

Aluminum acetate, basic hydrate ≥98 %, pure

article number: 1HE9



Human health values

Relevant DNELs and other threshold levels					
Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time	
DNEL	17.8 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects	
DNEL	36 mg/kg bw/ day	human, dermal	worker (industry)	chronic - systemic effects	

Environmental values

Relevant	Relevant PNECs and other threshold levels				
End- point	Threshold level	Organism	Environmental com- partment	Exposure time	
PNEC	0.86 ^{µg} / _l	aquatic organisms	freshwater	short-term (single instance)	
PNEC	0.086 ^{µg} / _l	aquatic organisms	marine water	short-term (single instance)	
PNEC	90,000 ^{µg} / _l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)	
PNEC	3.51 ^{µg} / _{kg}	aquatic organisms	freshwater sediment	short-term (single instance)	
PNEC	0.35 ^{µg} / _{kg}	aquatic organisms	marine sediment	short-term (single instance)	
PNEC	0.2 ^{µg} / _{kg}	terrestrial organisms	soil	short-term (single instance)	

8.2 Exposure controls

Individual protection measures (personal protective equipment)

Eye/face protection





Use safety goggle with side protection.

Skin protection





hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The times are approximate values from measurements at 22 °C and permanent contact. Increased temperatures due to heated substances, body heat etc. and a reduction of the effective layer thickness by stretching can lead to a considerable reduction of the breakthrough time. If in doubt, contact manufacturer. At an approx. 1.5 times larger / smaller layer thickness, the respective breakthrough time is doubled / halved. The data apply only to the pure substance. When transferred to substance mixtures, they may only be considered as a guide.

type of material

NBR (Nitrile rubber)

Australia (en) Page 5 / 14

acc. to Safe Work Australia - Code of Practice

Aluminum acetate, basic hydrate ≥98 %, pure

article number: 1HE9



>0,11 mm

breakthrough times of the glove material

>480 minutes (permeation: level 6)

other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended

Respiratory protection





Respiratory protection necessary at: Dust formation. Particulate filter device (EN 143). P1 (filters at least 80 % of airborne particles, colour code: White).

Environmental exposure controls

Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state solid
Form powder
Colour white

Odour characteristic

Melting point/freezing point not determined

Boiling point or initial boiling point and boiling not determined

range

Flammability this material is combustible, but will not ignite

readily

Lower and upper explosion limit not determined

Flash point not applicable

Auto-ignition temperature 384 °C (ECHA)

Decomposition temperature 280 – 440 °C (ECHA)

pH (value) 4.8 (20 °C)
Kinematic viscosity not relevant

Solubility(ies)

Water solubility 0.013 ^g/_l at 20 °C (ECHA)

Partition coefficient

Partition coefficient n-octanol/water (log value): -0.63 (25 °C) (ECHA)

Australia (en) Page 6 / 14



acc. to Safe Work Australia - Code of Practice

Aluminum acetate, basic hydrate ≥98 %, pure

article number: 1HE9

Vapour pressure <0 Pa at 20 °C

Density and/or relative density

Density 1.43 ^g/_{cm³} at 20 °C

Relative vapour density Information on this property is not available.

Particle characteristics No data available.

Other safety parameters

Oxidising properties none

9.2 Other information

Information with regard to physical hazard hazard classes acc. to GHS

classes: (physical hazards): not relevant

Other safety characteristics: There is no additional information.

SECTION 10: Stability and reactivity

10.1 Reactivity

The product in the delivered form is not dust explosion capable; the enrichment of fine dust however leads to the danger of dust explosion.

10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

10.3 Possibility of hazardous reactions

Violent reaction with: strong oxidiser

10.4 Conditions to avoid

Keep away from heat. Decompostion takes place from temperatures above: 280 – 440 °C.

10.5 Incompatible materials

There is no additional information.

10.6 Hazardous decomposition products

Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Classification acc. to GHS

Acute toxicity

Shall not be classified as acutely toxic.

GHS of the United Nations, annex 4. May be harmful if swallowed.

Australia (en) Page 7 / 14



acc. to Safe Work Australia - Code of Practice



article number: 1HE9



Acute toxicity					
Exposure route	Endpoint	Value	Species	Method	Source
oral	LD50	>2,000 ^{mg} / _{kg}	rat		ECHA

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

Symptoms related to the physical, chemical and toxicological characteristics

If swallowed

Data are not available.

• If in eyes

Causes serious eye damage, risk of blindness

• If inhaled

Data are not available.

• If on skin

Data are not available.

Other information

This information is based upon the present state of our knowledge.

11.2 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of \geq 0,1%.

Australia (en) Page 8 / 14

acc. to Safe Work Australia - Code of Practice

Aluminum acetate, basic hydrate ≥98 %, pure

article number: 1HE9



SECTION 12: Ecological information

12.1 Toxicity

Very toxic to aquatic life.

Aquatic toxicity (acute)

Endpoint	Value	Species	Source	Exposure time
LC50	>1.46 ^{mg} / _l	fish	ECHA	96 h
EC50	>0.96 ^{mg} / _l	aquatic invertebrates	ECHA	48 h
ErC50	1.02 ^{mg} / _l	algae	ECHA	72 h

Aquatic toxicity (chronic)

Endpoint	Value	Species	Source	Exposure time
EC50	>1,000 ^{mg} / _l	microorganisms	ECHA	3 h

12.2 Persistence and degradability

Theoretical Oxygen Demand: 0.6416 ^{mg}/_{mg} Theoretical Carbon Dioxide: 1.086 ^{mg}/_{mg}

12.3 Bioaccumulative potential

Does not significantly accumulate in organisms.

n-octanol/water (log KOW)	-0.63 (25 °C) (ECHA)
---------------------------	----------------------

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of \geq 0,1%.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods



This material and its container must be disposed of as hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.

Sewage disposal-relevant information

Do not empty into drains.

Australia (en) Page 9 / 14

acc. to Safe Work Australia - Code of Practice

Aluminum acetate, basic hydrate ≥98 %, pure

article number: 1HE9



Waste treatment of containers/packagings

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used. Handle contaminated packages in the same way as the substance itself. Completely emptied packages can be recycled.

13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions. Non-contaminated packages may be recycled.

SECTION 14: Transport information

14.1	HIN	num	her
14. 1	UIV	HUHIII	ncı

UN 3077
IMDG-Code UN 3077
ICAO-TI UN 3077

14.2 UN proper shipping name

UN RTDG ENVIRONMENTALLY HAZARDOUS SUBSTANCE,

SOLID, N.O.S.

IMDG-Code ENVIRONMENTALLY HAZARDOUS SUBSTANCE,

SOLID, N.O.S.

ICAO-TI Environmentally hazardous substance, solid,

n.o.s.

Technical name Aluminum acetate, basic hydrate

14.3 Transport hazard class(es)

UN RTDG 9
IMDG-Code 9
ICAO-TI 9

14.4 Packing group

UN RTDG III
IMDG-Code III
ICAO-TI III

14.5 Environmental hazards hazardous to the aquatic environment

14.6 Special precautions for user

There is no additional information.

14.7 Transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

14.8 Information for each of the UN Model Regulations

Australia (en) Page 10 / 14

acc. to Safe Work Australia - Code of Practice

Aluminum acetate, basic hydrate ≥98 %, pure

article number: 1HE9

Transport informationNational regulationsAdditional information(UN RTDG)

UN number 3077 Class 9

Environmental hazards Yes

Hazardous to the aquatic environment

Packing group III

Danger label(s) 9
Fish and tree

Special provisions (SP) 274, 331, 335, 375

UN RTDĞ

Excepted quantities (EQ) E1

UN RTDG

Limited quantities (LQ) 5 kg

UN RTDG

Emergency Action Code 2Z

International Maritime Dangerous Goods Code (IMDG) - Additional information

Proper shipping name ENVIRONMENTALLY HAZARDOUS SUBSTANCE,

SOLID, N.O.S.

Particulars in the shipper's declaration UN3077, ENVIRONMENTALLY HAZARDOUS SUB-

STANCE, SOLID, N.O.S., (Aluminum acetate, basic

hydrate), 9, III

Marine pollutant yes (hazardous to the aquatic environment), (Aluminum acet-

ate, basic hydrate)

Danger label(s) 9, "Fish and tree"

Special provisions (SP) 274, 335, 966, 967, 969

Excepted quantities (EQ) E1
Limited quantities (LQ) 5 kg
EmS F-A, S-F

Stowage category A

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Proper shipping name Environmentally hazardous substance, solid,

n.o.s.

Particulars in the shipper's declaration UN3077, Environmentally hazardous substance,

solid, n.o.s., (Aluminum acetate, basic hydrate), 9,

Ш

Environmental hazards yes (hazardous to the aquatic environment)

Danger label(s) 9, "Fish and tree"

Australia (en) Page 11 / 14



acc. to Safe Work Australia - Code of Practice

Aluminum acetate, basic hydrate ≥98 %, pure

article number: 1HE9



Special provisions (SP) A97, A158, A179, A197, A215

Excepted quantities (EQ) Limited quantities (LQ) 30 kg

SECTION 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture There is no additional information.

National regulations(Australia)

Australian Inventory of Chemical Substances(AICS)

Substance is listed.

Other information

Directive 94/33/EC on the protection of young people at work. Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

National inventories

Country	Inventory	Status
AU	AIIC	substance is listed
CA	DSL	substance is listed
CN	IECSC	substance is listed
EU	ECSI	substance is listed
EU	REACH Reg.	substance is listed
JP	CSCL-ENCS	substance is listed
KR	KECI	substance is listed
MX	INSQ	substance is listed
NZ	NZIoC	substance is listed
TW	TCSI	substance is listed
US	TSCA	substance is listed (ACTIVE)
VN	NCI	substance is listed

Legend

AIIC CSCL-ENCS

Australian Inventory of Industrial Chemicals List of Existing and New Chemical Substances (CSCL-ENCS) Domestic Substances List (DSL)

DSL ECSI

EC Substance Inventory (EINECS, ELINCS, NLP)
Inventory of Existing Chemical Substances Produced or Imported in China
National Inventory of Chemical Substances **IECSC**

KECI Korea Existing Chemicals Inventory
NCI National Chemical Inventory
NZIOC New Zealand Inventory of Chemicals
REACH Reg. REACH registered substances

Taiwan Chemical Substance Inventory **Toxic Substance Control Act**

15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this substance.

Page 12 / 14 Australia (en)



acc. to Safe Work Australia - Code of Practice

Aluminum acetate, basic hydrate ≥98 %, pure

article number: 1HE9



SECTION 16: Other information

Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety- relev- ant
1.1	EC number: 205-518-2		yes
2.3		Endocrine disrupting properties: Does not contain an endocrine disruptor (ED) at a concentration of ≥ 0,1%.	yes
14.7	Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.		yes
14.8		Emergency Action Code: 2Z	yes
14.8		Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.	yes
14.8		Particulars in the shipper's declaration: UN3077, ENVIRONMENTALLY HAZARDOUS SUB- STANCE, SOLID, N.O.S., (Aluminum acetate, ba- sic hydrate), 9, III	yes
14.8		Proper shipping name: Environmentally hazardous substance, solid, n.o.s.	yes
14.8		Particulars in the shipper's declaration: UN3077, Environmentally hazardous substance, solid, n.o.s., (Aluminum acetate, basic hydrate), 9, III	yes
14.8	Special provisions (SP): A97, A158, A179, A197	Special provisions (SP): A97, A158, A179, A197, A215	yes
15.1		Other information: Directive 94/33/EC on the protection of young people at work. Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.	yes
15.1		National inventories: change in the listing (table)	yes

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations	
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)	
Ceiling-C	Ceiling value	
DGR	Dangerous Goods Regulations (see IATA/DGR)	
DNEL	Derived No-Effect Level	
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval	
ED	Endocrine disruptor	
EINECS	European Inventory of Existing Commercial Chemical Substances	

Australia (en) Page 13 / 14

acc. to Safe Work Australia - Code of Practice

Aluminum acetate, basic hydrate ≥98 %, pure

article number: 1HE9



Abbr.	Descriptions of used abbreviations	
ELINCS	European List of Notified Chemical Substances	
EmS	Emergency Schedule	
ErC50	≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control	
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations	
IATA	International Air Transport Association	
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)	
ICAO	International Civil Aviation Organization	
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air	
IMDG	International Maritime Dangerous Goods Code	
IMDG-Code	International Maritime Dangerous Goods Code	
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval	
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval	
NLP	No-Longer Polymer	
PBT	Persistent, Bioaccumulative and Toxic	
PNEC	Predicted No-Effect Concentration	
STEL	Short-term exposure limit	
TWA	Time-weighted average	
UN RTDG	UN Recommendations on the Transport of Dangerous Good	
vPvB	Very Persistent and very Bioaccumulative	
WES	Safe Work Australia: Workplace exposure standards for airborne contaminants	

Key literature references and sources for data

Safe Work Australia's Code of Practice for Labelling of Workplace Hazardous Chemicals (under WHS Regulations).

UN Recommendations on the Transport of Dangerous Good. International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H318	Causes serious eye damage.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

Australia (en) Page 14 / 14