

1

Outline

- Containers vs. Virtual machines
- What is Docker ?
- What problems does Docker solve ?
- Docker architecture fundamentals
- Installing and Configuring the Docker Service
- Running your first container

2

Containers vs. Virtual machines

3

The IT Landscape is Changing

- **Movement in the cloud**
  - Migrate workloads to cloud
  - Portability across environments
  - Want to avoid cloud vendor lock-in
- **Applications are transforming**
  - From Monoliths to Microservices
- **Continuous Integration and Delivery**
  - Collaboration between Devs and IT Ops
  - Continious Quality Control



4

Application Deployment

- **Hypervisor-based Virtualization**
  - **One physical server can contain multiple applications**
  - **Each application runs in a virtual machine (VM)**



5

Benefits & Limitations of VMs

- **Benefits of VMs**
  - **Better resource pooling**
    - One physical machine divided into multiple virtual machines
  - **Easier to scale**
  - **VMs in the cloud**
    - Rapid elasticity
    - Pay as you go model
- **Limitations of VMs**
  - **Each VM stills requires**
    - CPU allocation/Storage/RAM
    - An entire guest operating system
  - **The more VMs you run, the more resources you need**
  - **Guest OS means wasted resources**
  - **Application portability not guaranteed**

6

Containers vs. VMs



Containers are isolated, but share OS kernel and, where appropriate, bins/libraries

...result is significantly faster deployment, much less overhead, easier migration, faster restart



7

Containers vs. VMs

- **Container advantages**



8

Containers vs VMs

- **Software application are moving to Micro-services**

- **Developer issues**
  - Minor code changes require full re-compileand re-test
  - Application becomes single point of failure
  - Application is difficult to scale
- **Microservices**: Break application into separate operations
- **12-Factor Apps**: Make the app independently scalable, stateless, highly available by design

- **Container's aim is to facilitate the execution of microservices**

9

What is Docker ?

10

What is Docker ?

- Docker is a platform for managing the delivery of distributed applications in lightweight, portable, self sufficient containers
- Containers are an abstraction of capabilities built into the Linux kernel

What is Docker ?

- OS-level Isolation
  - Isolation at individual kernel subsystem level (e.g. filesystem, process table, etc)
  - User-level process (LXC, libcontainer)
  - orchestrates these subsystems to create a container
- Why?
  - **Process isolation**
  - **Reproducible environment**
  - **Enables management at scale**



Docker history

- **Docker was born in 2013**
  - Docker is based on Linux LXC Containers
- **Containing processes is not a new phenomenon**
  - Chroot has been added to Version 7 Unix Bell Labs in 1979
  - Jails has been added to FreeBSD in 2000
  - Zones introduced in Sun's Solaris 19 in 2004



13

Docker growth



14

Who is Behind Docker?

- Docker is open source software, developed and maintained by a community
- Originally created as part of a PaaS offering, provided by dotCloud Inc.
- Project governed by the Docker Governance and Advisory Board (DGAB)

Everything at Google Runs in Containers !

[https://www.infoq.com/news/2014/06/everything-google-containers/]

15

What problems does Docker solve ?

16

Docker tackles these problems

- **Isolation**
  - Complete loose coupling between workloads
- **Consistency/Cohesion**
  - Each app is packaged along with its dependencies
  - No more “It works on my machine”
- **Speed/Scalability**
  - Faster than VMs
  - Portability

17

The Dependency matrix



18

The matrix from Hell

	Development VM	QA Server	Single Prod Server	Onsite Cluster	Public Cloud	Contributor's laptop	Customer Servers
Static website	?	?	?	?	?	?	?
Web frontend	?	?	?	?	?	?	?
Background workers	?	?	?	?	?	?	?
User DB	?	?	?	?	?	?	?
Analytics DB	?	?	?	?	?	?	?
Queue	?	?	?	?	?	?	?

19

The parallel with shipping industry



20

Intermodal shipping containers

21

A shipping container system for applications



22

Eliminate the matrix from hell



23

Container Fits Well with DevOps Lifecycle

- **Docker is a shipping container for Code !**
  - No more “Works on my machine”



24

Docker Use Cases

Standardized, reproduceable development environments

Microservices aids delivery of faster, better quality software

Incorporation into continuous integration and continuous delivery workflows

Safe experimentation with software components and versions

25

Docker architecture fundamentals

26

Docker Architecture……

- **It is an open source implementation of the LXC (Linux Containers) used for packaging an application and its needed dependencies into a container that can be deployed and replaced easily.**



- **The containerization in Docker is achieved via:**
  - Resource isolation (**cgroups**),
  - Kernel **namespaces** (isolating the application's view of the OS, process trees, etc) and,
  - A union-capable file system (such as aufs – mounting multiple directories into one that appears to contain their combined contents).

27

Linux Namespaces

- **A Namespace in Linux is a kernel mechanism for isolating a process or processes from specific system-related resources**



28

Control Groups

- CGroups are a kernel capability for allocating and controlling access to system resources
- Resource control is provided by a number of cgroup sub-systems or controllers
- Ordered hierarchically, with processes belonging to one cgroup fo



The Docker Engine

- Docker Engine allows you to develop, assemble, ship, and run applications using the following components:
  - Docker Daemon: A persistent background process that manages Docker images, containers, networks, and storage volumes.
  - Docker Engine REST API: An API used by applications to interact with the Docker daemon; it can be accessed by an HTTP client.
  - Docker CLI: A command line interface client for interacting with the Docker daemon.



- Rkt (Rocket)
- Mesos

31

Docker Concepts

Image
The basis of a Docker container. The content at rest.

Container
The image when it is 'running.' The standard unit for app service

Engine
The software that executes commands for containers. Networking and volumes are part of Engine. Can be clustered together.

Registry
Stores, distributes and manages Docker images

32

Docker Client, Host and Registry



33

Docker containers & images



34

Installing and Configuring the Docker Service

35

Installing Docker

- **Installing Docker on an existing Linux machine (Physical or VM)**
  - The recommended method is to install the packages supplied by Docker Inc.
    - add Docker Inc.'s package repositories to your system configuration
    - install the Docker Engine
  - Detailed installation instructions (distro by distro) are available on: https://docs.docker.com/engine/installation/
- **Installing Docker on MacOS or Windows**
  - On **Windows 10 Pro, Enterprise, and Education**, you can use Docker Desktop for Windows:
    - https://docs.docker.com/docker-for-windows/install/
  - On older versions of Windows, you can use the Docker Toolbox:
    - https://docs.docker.com/toolbox/toolbox_install_windows/
  - On Windows Server 2016, you can also install the native engine:
    - https://docs.docker.com/install/windows/docker-ee/
  - On macOS, the recommended method is to use Docker Desktop for Mac:
    - https://docs.docker.com/docker-for-mac/install/

36

Docker Desktop

- **Special Docker edition available for Mac and Windows**
- **Integrates well with the host OS:**
  - installed like normal user applications on the host
  - provides user-friendly GUI to edit Docker configuration and settings
- **Only support running one Docker VM at a time ...**
  - ... but we can use docker-machine, the Docker Toolbox, VirtualBox, etc. to get a cluster.

37

Docker Desktop Internals

- **Leverages the host OS virtualization subsystem**
  - (e.g. the Hypervisor API on macOS)
- **Under the hood, runs a tiny VM (transparent to our daily use)**
- **Accesses network resources like normal applications (and therefore, plays better with enterprise VPNs and firewalls)**
- **Supports filesystem sharing through volumes**

38

Testing Docker installation

- Run the following command:

```
$ docker version
Client: Docker Engine - Community
 Version:           19.03.8
 API version:       1.40
 Go version:        go1.12.17
 Git commit:        afacb8b
 Built:             Wed Mar 11 01:23:10 2020
 OS/Arch:           windows/amd64
 Experimental:      false

Server: Docker Engine - Community
 Engine:
  Version:          19.03.8
  API version:      1.40 (minimum version 1.12)
  Go version:       go1.12.17
  Git commit:       afacb8b
  Built:            Wed Mar 11 01:29:16 2020
  OS/Arch:          linux/amd64
  Experimental:     false
 containerd:
  Version:          v1.2.13
  GitCommit:        7ad184331fa3e55e52b890ea95e65ba581ae3429
 runc:
  Version:          1.0.0-rc10
  GitCommit:        dc9208a3303feef5b3839f4323d9beb36df0a9dd
 docker-init:
  Version:          0.18.0
  GitCommit:        fec3683
```


39

Running your first container

40

Hello World

- **In your Docker environment, just run the following command:**

```
$ docker run hello-world

Hello from Docker!
This message shows that your installation appears to be
working correctly
…
```

  - This command will download the hello-world Docker image from the Dockerhub, if not present already, and run it

41

Running Linux Alpine Container

- **Start a Linux Alpine container using the following command**

```
$ docker run alpine echo hello world
hello world
```

  - If your Docker install is brand new, you will also see a few extra lines, corresponding to the download of the alpine image.

- **Let's run Alpine in interactive mode:**

```
$ docker run -it alpine
/#
```

  - This is a brand new container.
    - It runs a bare-bones, no-frills alpine system. **-it** is shorthand for **-i -t**.
    - **-i** tells Docker to connect us to the container's stdin.
    - **-t** tells Docker that we want a pseudo-terminal.
  - Run several Unix command in the terminal like **`date`**, **`pwd`**, **`whoami`**
  - Close the terminal by typing the **`exit`** command.

42