


Lecture 14: Red-Black Trees

Perfect Balance
and Efficiency



1

Wholeness Statement

A red-black tree is an implementation of a (2, 4) tree that is optimized for space utilization. The insert and delete operations are also optimized to avoid backtracking; the operations are performed locally yet maintain balance and order in the whole. *Science of Consciousness*: Nature operates in accord with the law of least action while maintaining balance and order in the whole. Contact with the source of thought brings that order and balance out into our daily life.

2


Outline and Reading

- ◆ From (2,4) trees to red-black trees
- ◆ Red-black tree
 - Definition
 - Height
 - Insertion
 - ◆ restructuring
 - ◆ recoloring
 - Deletion
 - ◆ restructuring
 - ◆ recoloring
 - ◆ adjustment

3

From (2,4) to Red-Black Trees


- ◆ A red-black tree is a representation of a (2,4) tree by means of a binary tree whose nodes are colored **red** or **black**
- ◆ In comparison with its associated (2,4) tree, a red-black tree has
 - same logarithmic time performance
 - simpler implementation with a single node type



4

Red-Black Tree

- ◆ A red-black tree can also be defined as a binary search tree that satisfies the following properties:
 - **Root Property**: the root is black
 - **External Property**: every leaf is black
 - **Internal Property**: the children of a red node are black
 - **Depth Property**: all the leaves have the same black depth



5

Height of a Red-Black Tree

- ◆ **Theorem**: A red-black tree storing n items has height $O(\log n)$
- Proof:
 - The height of a red-black tree is at most twice the height of its associated (2,4) tree, which is $O(\log n)$
- ◆ The search algorithm for a red-black tree is the same as that for a binary search tree
- ◆ By the above theorem, searching in a red-black tree takes $O(\log n)$ time

6

Main Point

1. A red-black tree is an implementation of a (2, 4) tree in which each (2, 4) node is converted into a small binary tree. That is, a red-black tree is a reflection of a corresponding (2, 4) tree.

Science of Consciousness: Our individual consciousness is the reflection of pure consciousness based on the purity and activity of our physiology and nervous system.


7

Red-Black Tree Insertion

8

Recall Binary Tree Insertion

- ◆ If k is in the tree, replace the element associated with k , and return the previous element associated with k
- ◆ If k is not in the tree, then a search for k will find a leaf where the item is to be inserted by operation $\text{insert}(k, o)$
- ◆ Let w be the leaf reached by the search
- ◆ Insert k at node w and expand w into an internal node
- ◆ Example: insert 5




Binary Search Trees

9

Insertion

- ◆ To perform operation $\text{insert}(k, o)$, we execute the insertion algorithm for binary search trees and color the newly inserted node z **red** unless it is the root. We preserve the root, external, and depth properties.
 - If the parent v of z is black, we preserve the internal property and we are done...
 - ...else (v is red) we have a **double red** (i.e., a violation of the internal property), which requires a reorganization of the tree
- ◆ For example, the insertion of 4 causes a double red:




10

Remedying a Double Red

- ◆ Consider a double red with child z and parent v , and let w be the sibling of v

Case 1: z 's uncle w is black


- The double red is an incorrect replacement of a 4-node
- **Restructuring:** we change the 4-node representation



11


Case 2: z 's uncle w is red

- The double red corresponds to an overflow
- **Recoloring:** we perform the equivalent of a **split**



Case 1: Restructuring

- ◆ A restructuring remedies a child-parent double red when the parent red node has a black sibling
- ◆ It is equivalent to restoring the correct replacement of a 4-node
- ◆ The internal property is restored and the other properties are preserved




12

11

12

Restructuring (cont.)

- There are four restructuring configurations depending on whether the double red nodes are left or right children




13

13

Case 2: Recoloring

- A recoloring remedies a child-parent double red when the parent red node has a red sibling
- The parent v and its sibling w become black and the grandparent u becomes red, unless it is the root
- It is equivalent to performing a split on a 5-node
- The double red violation may propagate to the grandparent u



14

14

Example:

- Insert the following into an initially empty red-black tree in this order:
(16, 5, 22, 45, 2, 10, 18, 30, 50, 12, 1)

15

15

Analysis of Insertion

Algorithm *insertItem(k, o)*

- Search for key k to locate the insertion node z
- Add the new item (k, o) at node z and color z red
- while *isDoubleRed*(z) do
if *isBlack*(*sibling*(*parent*(z)))
 $z \leftarrow \text{restructure}(z)$
 return
else { *sibling*(*parent*(z)) is red }
 $z \leftarrow \text{recolor}(z)$

- Recall that a red-black tree has $O(\log n)$ height
- Step 1 takes $O(?)$ time
- Step 2 takes $O(?)$ time
- Step 3 takes $O(?)$ time
- Thus, an insertion in a red-black tree takes $O(?)$ time

16

16

Analysis of Insertion

Algorithm *insertItem(k, o)*

- Search for key k to locate the insertion node z
- Add the new item (k, o) at node z and color z red
- while *isDoubleRed*(z) do
if *isBlack*(*sibling*(*parent*(z)))
 $z \leftarrow \text{restructure}(z)$
 return
else { *sibling*(*parent*(z)) is red }
 $z \leftarrow \text{splitRecolor}(z)$

- Recall that a red-black tree has $O(\log n)$ height
- Step 1 takes $O(\log n)$ time because we visit $O(\log n)$ nodes
- Step 2 takes $O(1)$ time
- Step 3 takes $O(\log n)$ time because we perform
 - $O(\log n)$ recolorings, each taking $O(1)$ time, and
 - at most one restructuring taking $O(1)$ time
- Thus, an insertion in a red-black tree takes $O(\log n)$ time

17

17

Analysis of Insertion

Algorithm *isDoubleRed(z)*

- ```

if isRoot(z) then
 setColor(z , BLACK)
 return False
else
 return isRed(parent(z))

```

### Algorithm *splitRecolor(z)*

- ```

 $pz \leftarrow \text{parent}(z)$ 
setColor( $pz$ , BLACK)
setColor(sibling( $pz$ ), BLACK)
 $gpz \leftarrow \text{parent}(pz)$ 
setColor( $gpz$ , RED)
return  $gpz$ 
    
```

18

18

Analysis of Insertion

```

Algorithm restructure(gpz, pz, z)
  setColor(gpz, RED)
  if isLeft(z) then
    if isLeft(pz) then
      rotateRight(pz)
      setColor(pz, BLACK)
    else
      rotateRight(z)
      rotateLeft(pz)
      setColor(z, BLACK)
  else { z is a right child }
    if isLeft(pz) then
      rotateLeft(z)
      rotateRight(pz)
      setColor(z, BLACK)
    else
      rotateLeft(pz)
      rotateLeft(z)
      setColor(z, BLACK)


```

19

Recall

Binary Tree Deletion

- ◆ To perform operation **remove**(*k*), first search for key *k*
- ◆ Assume key *k* is in the tree, and let *v* be the node storing *k*
- ◆ Two cases:
 - Node *v* has a leaf child *w*
 - Node *v* has no leaf child
- ◆ If node *v* has a leaf child *w*, we remove *v* and *w* from the tree with operation **remove**(*v*)
- ◆ Example: remove 4




Binary Search Trees

20

Deletion (Case 2)


- ◆ We consider the case where the key *k* to be removed is stored at a node *v* whose children are both internal
 - we find the internal node *w* that precedes *v* in an in-order traversal
 - we copy *key(w)* into node *v*
 - we remove node *w* and its right child *z* (which must be a leaf) by means of operation **remove**(*w*)
- ◆ Example: remove 8



21

Deletion (Case 2)

- ◆ We consider the case where the key *k* to be removed is stored at a node *v* whose children are both internal
 - we find the internal node *w* that precedes *v* in an in-order traversal
 - we copy *key(w)* into node *v*
 - we remove node *w* and its right child *z* (which must be a leaf) by means of operation **remove**(*w*)
- ◆ Example: remove 8




22

Red-Black Tree Deletion

23

Deletion


- ◆ To perform operation **remove**(*k*), first execute the deletion algorithm for binary search trees
 - If node to be removed, *u*, does not have an external child, find next internal node by in-order traversal, called *v*, and move key at *v* to *u*, then remove *v*.
 - Thus, every removal occurs at an internal node with an external child.



24

Deletion

- ◆ Let v be the internal node removed, w the external node removed, and r the sibling of v
 - If either v or r was red, we color r black and we are done
 - Else (v and r were both black), so we color r **double black** (a fictitious color), which is a violation of the internal property requiring a reorganization of the tree (denotes underflow)
- ◆ For example, the deletion of 8 causes a double black:



25

25


Remedying a Double Black

- ◆ The algorithm for remedying a double black node r with sibling y considers three cases
 - Case 1: y is black and has a red child z
 - Case 2: y is black and its children are both black
 - Case 3: y is red

26

26


Case 1a – sibling y is black and has a red child z



27

27


Case 1b – sibling y is black and has a red child z



28

28


Case 2 – sibling y is black and its children are both black



29

29

Case 3 – sibling y is red



30

30


Remedying a Double Black

- The algorithm for remedying a double black node r with sibling y considers three cases
 - Case 1:** y is black and has a red child
 - Perform a **restructuring**, equivalent to a **transfer**, and we are done
 - Case 2:** y is black and its children are both black
 - Perform a **recoloring**, equivalent to a **fusion**, which may propagate the double black violation up to parent
 - Case 3:** y is red
 - We perform an **adjustment**, equivalent to choosing a different representation of a 3-node, after which either Case 1 or Case 2 applies
- Deletion in a red-black tree takes $O(\log n)$ time

31

Restructuring (as Single Rotations)


Single Rotations:



32

Restructuring (as Double Rotations)

double rotations:



33

Analysis of Deletion (abstract)

Algorithm **deleteItem(k, o)**

- Search for key k , then locate the deletion node v and external child w . Let $y = \text{sibling}(v)$.
- Let $r = \text{sibling}(w)$. Remove node v (removes v and w). If r is black (external) then color r double black else r was red so color r black and we're done.
- while **isDoubleBlack(r)**
 - if **isRed(y)**
 - $y \leftarrow \text{adjustment}(y)$
 - if **hasRedChild(y)**
 - $r \leftarrow \text{restructure}(r)$
 - return
 - else { $\text{sibling}(r)$ has no red child}
 - $r \leftarrow \text{fusionRecolor}(r)$

- Recall that a red-black tree has $O(\log n)$ height
- Step 1 takes $O(\log n)$ time because we visit $O(\log n)$ nodes
- Step 2 takes $O(1)$ time
- Step 3 takes $O(\log n)$ time because we perform
 - $O(\log n)$ recolorings, each taking $O(1)$ time, and
 - at most two restructurings taking $O(1)$ time each
- Thus, an deletion in a red-black tree takes $O(\log n)$ time

34

Analysis of Deletion (details)

Algorithm **removeDoubleBlack(y, r)**
 Input r is the double black node, y is r 's sibling
 if **isDoubleBlack(r)** then
 if **isRed(y)** then (Case 3: when y , the sibling of r , is red)
 $y \leftarrow \text{adjustment}(y)$
 $py \leftarrow \text{parent}(y)$
 $z \leftarrow \text{redChildOf}(y)$
 if **isBlack(z)** then (Case 1: when y has no red child)
 $r \leftarrow \text{fusionRecolor}(y, py, r)$
 if **isRoot(r)** then
 setColor(r , BLACK)
 else
 $y \leftarrow \text{sibling}(r)$
 removeDoubleBlack(y, r) // recursive call
 else (Case 2: y has a red child, so we do a transfer)
 restructure(py, y, z)
 setColor($\text{parent}(py)$, color(py))
 setColor(py , BLACK)
 setColor($\text{sibling}(py)$, BLACK)
 setColor(r , BLACK)

35

Analysis of Deletion (details)

Algorithm **fusionRecolor(y, p, r)**

Input r and y are siblings, p is their parent
 setColor(y , RED)
 if **isRed(p)** then
 setColor(p , BLACK)
 else
 setColor(p , DOUBLE_BLACK)
 if **isInternal(r)** then
 setColor(r , BLACK)
 return p

36

Red-Black Tree Reorganization

Insertion remedy double red		
Red-black tree action	(2,4) tree action	result
restructuring	correct the 4-node representation	double red removed
recoloring	split	double red removed or propagated up
Deletion remedy double black		
Red-black tree action	(2,4) tree action	result
restructuring	transfer	double black removed
recoloring	fusion	double black removed or propagated up
adjustment	change of 3-node representation	restructuring or recoloring follows

37

37

Main Point

3. A red-black tree is an efficient way to implement an ordered dictionary ADT because it achieves logarithmic worst-case running times for both searching and updating.

Science of Consciousness: The TM technique is a very simple, effortless way to facilitate contact with the field of total knowledge, where the fulfillment of intellectual study is achieved, i.e., one feels at home with everything and everyone.

38

38

Connecting the Parts of Knowledge with the Wholeness of Knowledge

1. A (2, 4) tree offers a simple and effective way of maintaining balance in a dynamic tree structure.
2. A red-black tree offers a refinement of the (2, 4) tree by eliminating data slots and optimizing operations.

39

39

3. **Transcendental Consciousness** is the unbounded field of pure order and balance and is the basis of order and balance in creation.
4. **Impulses within Transcendental Consciousness:** The dynamic natural laws within this unbounded field create and maintain the order and balance in creation.
5. **Wholeness moving within itself:** In Unity Consciousness, the diversity of creation is experienced as waves of intelligence, perfectly orderly fluctuations of one's own self-referral consciousness.

40

40