

AL-RH230

4.0MP POE Network Full Color 2-Way Audio Dome Camera



Model Number	AL-RH230
Camera	
Image Sensor	1/2.8" SONY color CMOS
Min. Illumination	Color: 0.01Lux @F1.2, B/W: 0Lux with IR on
Lens	2.8mm lens
Shutter Time	Auto
IR Distance	30m
Full Color	2 LEDS
White Balance	Auto / Manual
AGC	Auto
WDR	Digital WDR
DNR	2D/3D DNR
BLC	support
HLC	support

Video	
Max. Image Resolution	4MP(2560*1440)@15fps
Frame Rate	Main code stream: 4MP@15fps,3MP@25fps,1080P/720P@30fps Auxiliary stream: D1/VGA/640x352/CIF@25fps
Video Compression	H265+/H265/H264
Video Bit Rate	500Kbps-4000Kbps support self-adjustable as needed
Image Settings	Brightness, Contrast, Saturation, Exposure, Upside Down, Mirror Adjustable
Bit Superposition	Support OSD name, time and date information superposition
Web Access	Internet explorer 6.0 and above (Web Server embedded in device) browser
Audio	
Audio I/O	Yes
Audio Compression	G.711
Network	
Network Interface	1*RJ45 10M/100M Ethernet Port
Networking Protocol	TCP/IP, HTTP,RTSP,DHCP,NTP,UPNP
ONVIF	ONVIF2.6
APP	Support android, IOS
PC	Support
System	
Alarm I/O	Motion detection alarm
Storage	No
Motion Detection	22*18 windows motion detection areas can be setting(sensitivity setting 1-100)
Human Detection	Yes
Video Mask	Support
Action with Alarm	Push to mobile APP
General	
Language Support	CHN(S)/CHN(T)/ENG
POE	IEEE802.3af
Power Supply	DC12V±10% / POE
Power Consumption	Max 5W
Lightning Protection	2KV
Housing	Metal Bullet
Working Temperature	-30 °C to 85 °C
Working Humidity	10%-95% (Non-condensing)