

OE-EC604B — Operating System

Semester VI • 3L:0T:0P • 3 Credits

Module 5 Exam Notes: Deadlocks

CGEC | B.Tech ECE (2023–27) | *Biraj Sarkar*

Contents

1	System Model and Deadlock Characterization	2
1.1	Four Necessary Conditions (Coffman Conditions)	2
1.2	Resource Allocation Graph (RAG)	2
2	Deadlock Handling Strategies	2
2.1	1. Deadlock Prevention	2
2.2	2. Deadlock Avoidance	3
	2.2.1 Banker's Algorithm	3
2.3	3. Deadlock Detection & Recovery	4

1. System Model and Deadlock Characterization

A **deadlock** is a state where a set of processes are blocked because each process is holding a resource and waiting for another resource held by some other process in the set.

1.1 Four Necessary Conditions (Coffman Conditions)

A deadlock situation can arise if and only if all four of the following conditions hold simultaneously in a system: 1. **Mutual Exclusion:** At least one resource must be held in a non-shareable mode (only one process can use it at a time). 2. **Hold and Wait:** A process must be holding at least one resource and waiting to acquire additional resources that are currently being held by other processes. 3. **No Preemption:** Resources cannot be preempted; a resource can be released only voluntarily by the process holding it, after that process has finished its task. 4. **Circular Wait:** A closed loop of processes must exist, where each process waits for a resource held by the next process in the loop. E.g., P_0 waits for R_1 (held by P_1), P_1 waits for R_2 (held by P_2), and P_n waits for R_0 (held by P_0).

1.2 Resource Allocation Graph (RAG)

Deadlocks can be described precisely using a directed graph called a **Resource Allocation Graph (RAG)**:

- **Vertices (V):** Divided into two partitions:
 - Processes $P = \{P_1, P_2, \dots, P_n\}$ (represented by circles).
 - Resource types $R = \{R_1, R_2, \dots, R_m\}$ (represented by rectangles containing dots for instances).
- **Edges (E):**
 - **Request Edge:** Directed edge $P_i \rightarrow R_j$ (process P_i has requested resource R_j).
 - **Assignment Edge:** Directed edge $R_j \rightarrow P_i$ (resource instance in R_j is allocated to process P_i).
- **Theorem:**
 - If the RAG contains no cycles $\rightarrow$ No deadlock.
 - If the RAG contains a cycle $\rightarrow$
 - If single instance per resource type: Deadlock exists (cycle is necessary and sufficient).
 - If multiple instances per resource type: Deadlock *may* exist (cycle is necessary but not sufficient).

2. Deadlock Handling Strategies

Operating systems use three main strategies to handle deadlocks:

2.1 1. Deadlock Prevention

Ensures that the system can never enter a deadlock state by designing the system such that at least one of the four Coffman conditions cannot hold:

- **Prevent Mutual Exclusion:** Make resources shareable (e.g., read-only files). **Drawback:** Some resources (printers, mutexes) are inherently non-shareable.
- **Prevent Hold and Wait:** Require processes to request all resources at once before execution, or release current resources before requesting new ones. **Drawback:** Low resource utilization; starvation.
- **Prevent No Preemption:** If a process holding resources requests another that cannot be immediately allocated, all its current resources are preempted (released). **Drawback:** Overhead of saving/restoring process states.
- **Prevent Circular Wait:** Impose a global ordering on all resource types (e.g., $F(R_j) = i$) and require processes to request resources only in strictly increasing order of enumeration. **Advantage:** Most practical prevention strategy.

2.2 2. Deadlock Avoidance


Requires that the OS has prior knowledge of the maximum resources a process will ever request.

Safe State vs Unsafe State

A state is **safe** if there exists a **safe sequence** $\langle P_1, P_2, \dots, P_n \rangle$ of execution such that, for each P_i , the resources that P_i can still request can be satisfied by the currently available resources plus the resources held by all prior processes P_j (for $j < i$).

- **Relationship:** A safe state is not deadlocked. An unsafe state is not necessarily deadlocked, but it can lead to a deadlock if processes request their maximum limits. Avoidance algorithms keep the system inside a safe state.

Deadlock State Space Partitioning



2.2.1 Banker's Algorithm

Used for systems with multiple instances of resources. Data structures:

- `Available[m]`: Available instances of each resource.
- `Max[n][m]`: Maximum demand of each process.
- `Allocation[n][m]`: Resources currently allocated to each process.
- `Need[n][m]`: Remaining resources a process may request. Note: $\text{Need}[i][j] = \text{Max}[i][j] - \text{Allocation}[i][j]$.

2.3 3. Deadlock Detection & Recovery

If a system does not prevent or avoid deadlocks, a deadlock may occur. The OS must provide:

- A detection algorithm (periodically runs to find cycles or execute safety checks).
- A recovery scheme:
 - **Process Termination:** Abort all deadlocked processes, or abort one-by-one until the cycle is broken.
 - **Resource Preemption:** Preempt resources from some processes, roll back those processes to a safe checkpoint, and restart them.

Quick Revision — Module 5

Deadlocks | OE-EC604B

Banker's Safety Algorithm Equations

Let $Work = Available$ and $Finish[i] = false$ for $i = 0, 1, \dots, n - 1$. Find an index i such that both: 1. $Finish[i] == false$ 2. $Need_i \leq Work$ If such an i exists, update:

$$Work = Work + Allocation_i$$

$$Finish[i] = true$$

Repeat. If $Finish[i] == true$ for all i , the system is in a **Safe State**.

One-Line Definitions

- **Deadlock:** State where processes wait indefinitely for resources held by each other.
- **Mutual Exclusion:** Rule that only one process can hold a resource instance at any time.
- **Hold and Wait:** Process holding resources while requesting more without releasing current ones.
- **Preemption:** Forcible retrieval of allocated resources from a process by the OS.
- **Circular Wait:** Chain of processes where each waits for a resource held by the next.
- **Resource Allocation Graph:** Directed graph showing resource allocations and process requests.
- **Safe Sequence:** Order of process execution that guarantees no deadlock can occur.
- **Ostrich Algorithm:** Deadlock strategy of ignoring the problem (used when deadlocks are rare).

Frequently Asked / Viva Questions

Q1. What are the four necessary conditions for a deadlock to occur?

Mutual Exclusion, Hold and Wait, No Preemption, and Circular Wait (Coffman conditions). All four must hold simultaneously for a deadlock to exist.

Q2. Consider a system with 5 processes (P0 to P4) and 3 resource types (A, B, C):

$$\text{Allocation} = \begin{pmatrix} 0 & 1 & 0 \\ 2 & 0 & 0 \\ 3 & 0 & 2 \\ 2 & 1 & 1 \\ 0 & 0 & 2 \end{pmatrix}, \quad \text{Max} = \begin{pmatrix} 7 & 5 & 3 \\ 3 & 2 & 2 \\ 9 & 0 & 2 \\ 2 & 2 & 2 \\ 4 & 3 & 3 \end{pmatrix}, \quad \text{Available} = \begin{pmatrix} 3 & 3 & 2 \end{pmatrix}$$

Frequently Asked / Viva Questions (contd.)

Is the system in a safe state? Find the safe sequence.

Step 1: Calculate Need matrix (Need = Max – Allocation)

$$\text{Need} = \begin{pmatrix} 7-0 & 5-1 & 3-0 \\ 3-2 & 2-0 & 2-0 \\ 9-3 & 0-0 & 2-2 \\ 2-2 & 2-1 & 2-1 \\ 4-0 & 3-0 & 3-2 \end{pmatrix} = \begin{pmatrix} 7 & 4 & 3 \\ 1 & 2 & 2 \\ 6 & 0 & 0 \\ 0 & 1 & 1 \\ 4 & 3 & 1 \end{pmatrix}$$

Step 2: Initialize Work = (3 3 2)

- **Check P1:** Need₁ (1 2 2) ≤ Work (3 3 2)? Yes. Work → Work + Alloc₁ = (5 3 2).
- **Check P3:** Need₃ (0 1 1) ≤ Work (5 3 2)? Yes. Work → Work + Alloc₃ = (7 4 3).
- **Check P0:** Need₀ (7 4 3) ≤ Work (7 4 3)? Yes. Work → Work + Alloc₀ = (7 5 3).
- **Check P2:** Need₂ (6 0 0) ≤ Work (7 5 3)? Yes. Work → Work + Alloc₂ = (10 5 5).
- **Check P4:** Need₄ (4 3 1) ≤ Work (10 5 5)? Yes. Work → Work + Alloc₄ = (10 5 7).

Result: All processes finished. System is in **safe state** with safe sequence: (P1, P3, P0, P2, P4).

Q3. Differentiate between Deadlock Prevention and Deadlock Avoidance.

Prevention limits system design by enforcing policies that violate one of the 4 Coffman conditions (e.g., resource ordering). Avoidance does not restrict request structures but checks dynamic resource availability and maximum limits to keep the system in a safe state.

Q4. How can the circular wait condition be prevented in operating systems?

By defining a global 1-to-1 enumeration function $F : R \rightarrow \mathbb{N}$ for all resource types. A process can only request resource R_j if $F(R_j) > F(R_i)$, where R_i is any resource currently held by the process.

Q5. What is an unsafe state? Does it always lead to a deadlock?

An unsafe state is a state from which the OS cannot guarantee that all processes can finish their maximum execution. It does **not** always lead to a deadlock; it will only deadlock if processes actually request their maximum declared resources.

Frequently Asked / Viva Questions (contd.)

Q6. Why does a cycle in a Resource Allocation Graph (RAG) not always indicate a deadlock?

If a resource type has multiple instances, a cycle indicates a potential deadlock but not a guaranteed one, as a process outside the cycle might release an instance, breaking the cycle.

Q7. What is the difference between a Resource Allocation Graph and a Wait-For Graph?

A Resource Allocation Graph shows both processes and resources with request/assignment edges. A Wait-For Graph is a simplified version for single-unit resource systems, showing only processes, where edge $P_i \rightarrow P_j$ means P_i waits for P_j to release a resource.

Q8. Explain the recovery methods from deadlock.

1. Process Termination: Abort all deadlocked processes, or abort processes one-by-one until the cycle is broken. 2. Resource Preemption: Take resources from a process, roll it back to a safe checkpoint, and restart it.

Q9. What is the "Ostrich Algorithm" and when is it appropriate to use?

It is the strategy of ignoring deadlocks altogether, assuming they occur rarely. It is used by most general-purpose OS (like Windows/Linux) because deadlock prevention/avoidance adds heavy run-time overhead.

Q10. Why is preemption difficult to implement for some resources?

Because some resources (like printers or files being written) cannot be easily saved and restored mid-operation without corrupting data or output.

Deadlock Handling Trade-offs

Strategy	Run-time Overhead	Resource Utilization	Implementation
Prevention	None (static rules)	Low (strict limits)	Simple
Avoidance	Moderate (safety checks)	Moderate	Complex (needs max demand)
Detection	High (periodic checks)	High (free allocation)	Moderate