

OE-EC704A — Web Technology

Semester VII • 3L:0T:0P • 3 Credits

Module 8 Exam Notes: Java Utility Package (Collections Framework)

CGEC | B.Tech ECE (2023–27) | *Biraj Sarkar*

Contents

1	Java Collections Framework Overview	2
1.1	Core Interfaces	2
2	ArrayList vs. LinkedList	2
3	Accessing and Iterating Collections	3
3.1	The Iterator Interface	3
3.2	The For-Each Statement	3

1. Java Collections Framework Overview

The Collections Framework, declared inside the `java.util` package, provides a unified architecture to store and manipulate a group of objects.

Core Design Benefits

- Reduces programming effort by providing standard data structures.
- Boosts speed and quality via high-performance, optimized implementations.
- Promotes software reuse by offering polymorphic operations.

1.1 Core Interfaces

The framework is structured hierarchically around a set of core interfaces:


- **Collection:** The root interface defining basic operations (size, add, remove, clear).
- **List:** Extends `Collection`. Represents an ordered sequence of elements that can contain duplicates. Supports index-based access.
- **Set:** Extends `Collection`. A collection that cannot contain duplicate elements, modeling mathematical sets.
- **Queue:** Extends `Collection`. Designed to hold elements prior to processing (typically FIFO).

2. ArrayList vs. LinkedList


Metric	ArrayList	LinkedList
Internal Structure	Dynamically resizing array.	Doubly linked list nodes.
Access Time	$O(1)$ random access (index-based).	$O(n)$ search access (sequential traverse).
Insertion/Deletion	$O(n)$ (requires element shifts).	$O(1)$ if pointer is located.
Memory Overhead	Low (only stores elements).	Higher (stores element and prev/next links).

ArrayList vs. LinkedList Memory Layout

ArrayList (Contiguous Memory):



LinkedList (Pointer Links):



3. Accessing and Iterating Collections

Java provides two primary mechanisms to traverse through collection elements:

3.1 The Iterator Interface

An iterator provides sequential access to collection elements. It is retrieved using `iterator()` method on any Collection object.

```
ArrayList<String> list = new ArrayList<>();
list.add("Java");
list.add("HTML");

Iterator<String> itr = list.iterator();
while (itr.hasNext()) {
    String element = itr.next();
    System.out.println(element);
}
```

- **Methods:** `hasNext()` (returns true if more elements exist), `next()` (returns next element), and `remove()` (removes current element safely during iteration).
- **Fail-Fast Behavior:** Iterators on standard collections like `ArrayList` throw a `ConcurrentModificationException` if the collection is structurally modified (add/remove) outside the iterator's own methods during iteration.

3.2 The For-Each Statement

Introduced in Java 5, the enhanced `for` loop (for-each) provides a cleaner syntax to iterate over arrays and collections:

```
for (String element : list) {
    System.out.println(element);
}
```

Internally, the compiler translates this syntax into standard Iterator-based code for objects implementing the `java.lang.Iterable` interface.

Quick Revision — Module 8

Java Utility package - Collections | OE-EC704A

Collection Syntax

Construct	Syntax and Example Usage
ArrayList Declaration	<code>ArrayList<String> list = new ArrayList<String>();</code>
ArrayList Insert	<code>list.add("Java"); list.add(1, "CSS"); // inserts at index 1</code>
LinkedList Declaration	<code>LinkedList<Integer> lList = new LinkedList<>();</code>
Iterator Traversal	<code>Iterator<String> itr = list.iterator(); while(itr.hasNext()) { ... }</code>
For-Each Loop	<code>for (String str : list) { System.out.println(str); }</code>

One-Line Definitions

- **Collections Framework:** Architecture of interfaces and classes for grouping multiple objects.
- **ArrayList:** Resizable-array implementation of the List interface, backing elements contiguously.
- **LinkedList:** Doubly-linked node implementation of the List and Deque interfaces.
- **Iterator:** Object traversal cursor enabling forward traversal and safe element removals.
- **Fail-Fast Iterator:** Iterator throwing exception immediately if collection structure changes during loop.
- **Iterable:** Interface indicating target object can be traversed using enhanced for-each.
- **Generics:** Compiler feature ensuring type-safety in collections (e.g., `ArrayList<String>`).
- **Auto-boxing:** Implicit compiler conversion between primitives and their wrapper classes.

Frequently Asked / Viva Questions

Q1. What is the difference between ArrayList and Vector?

`ArrayList` is non-synchronized, fast, and not thread-safe. `Vector` is synchronized, has thread-safe methods, and carries significant execution overhead.

Q2. Why does a LinkedList consume more memory than an ArrayList?

An `ArrayList` stores elements contiguously inside a backing array. A `LinkedList` wraps each element inside a node object that also holds reference addresses for the previous and next nodes.

Frequently Asked / Viva Questions (contd.)**Q3. What is fail-fast behavior in collections?**

It is a JVM runtime validation that throws a `ConcurrentModificationException` if a collection is modified structurally (elements added or deleted) while an active iterator is traversing it.

Q4. How does ArrayList grow its internal array capacity?

When an element is added and the array is full, `ArrayList` allocates a new array and copies elements. Starting from Java 10, it increases capacity by roughly 50% ($\text{New Capacity} = \text{Old Capacity} + (\text{Old Capacity} \gg 1)$).

Q5. What is the purpose of the Iterable interface?

It is the superinterface of the `Collection` interface. Implementing `Iterable` requires the class to return an `Iterator`, allowing instances to be used in the enhanced for-each loop.

Q6. Can we store primitive data types (like int, char) inside collections?

No, collections only store object references. However, Java handles this automatically using **Autoboxing**, which converts primitives to their wrapper objects (e.g., `int` to `Integer`) when inserted.

Q7. What is the difference between Iterator and ListIterator?

`Iterator` can traverse any `Collection` in a forward direction. `ListIterator` can only traverse `Lists`, but supports bidirectional traversal (forward and backward) and element modifications.

Q8. Which List implementation is preferred for frequent search operations?

`ArrayList` is preferred because it supports $O(1)$ constant time lookup via index-based access, whereas `LinkedList` requires $O(n)$ linear traversal.

Q9. Which List implementation is preferred for frequent insertions at the beginning of the list?

`LinkedList` is preferred. Inserting at the beginning requires only updating two node pointers ($O(1)$), whereas `ArrayList` requires shifting all existing elements, taking $O(n)$ time.

Q10. What is the difference between List and Set interfaces?

A `List` maintains insertion order and can contain duplicate elements. A `Set` is unordered and cannot contain duplicate elements.

ArrayList vs. LinkedList operations complexity

Operation	ArrayList	LinkedList
Get by Index	$O(1)$ constant time.	$O(n)$ linear traversal.
Insert/Delete (Start)	$O(n)$ shift overhead.	$O(1)$ pointer change.
Insert/Delete (End)	$O(1)$ amortized.	$O(1)$ tail reference update.
Memory consumption	Low (consecutive slots).	High (two references per node).